



COMMISSION OF THE EUROPEAN COMMUNITIES

Brussels, 16.10.2001
COM(2001) 587 final

Proposal for a

COUNCIL REGULATION

**amending Regulation (EC) No 1255/96 temporarily suspending the autonomous
common customs tariff duties on certain industrial, agricultural and fishery products**

(presented by the Commission)

EXPLANATORY MEMORANDUM

The Commission, assisted by the Economic Tariff Questions Group, has reviewed all the requests for temporary suspension of autonomous common customs tariff duties presented to it by the Member States, including requests for extending suspensions at present in force.

The attached proposal concerns certain industrial, agricultural and fishery products.

Requests for suspension relating to the above products were examined in the light of the criteria set out in the communication from the Commission concerning autonomous tariff suspensions and quotas (see OJ C 128, 25.4.1998, p. 2).

Following this review, the Commission considers that the suspension of duties is justified for the products listed in the Annex to the attached proposal for a Regulation.

Some products, for which suspension is no longer in the Community's economic interests, have been withdrawn from the annex.

The period of validity of the proposed measure is unspecified, since its purpose is to amend the annex to Council Regulation (EC) No 1255/96, the period of validity of which is itself unspecified.

Proposal for a

COUNCIL REGULATION

amending Regulation (EC) No 1255/96 temporarily suspending the autonomous common customs tariff duties on certain industrial, agricultural and fishery products

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty establishing the European Community, and in particular Article 26 thereof,

Having regard to the proposal from the Commission,

Whereas:

- (1) It is in the interest of the Community to suspend partially or totally the autonomous common customs tariff duties for a number of new products not listed in the Annex to Regulation (EC) No 1255/96¹.
- (2) A number of products which are referred to in the said Regulation should be withdrawn from the list in the Annex because it is no longer in the Community's interest to maintain suspension of autonomous common customs tariff duties or because the description needs to be altered in order to take account of technical product developments and economic trends on the market.
- (3) Accordingly, products whose description needs to be altered should be regarded as new products.
- (4) For ease of comprehension, in view of the large number of amendments coming into force on 1 January 2002, the Annex to Regulation (EC) No 1255/96 should be replaced by a completely new version.

HAS ADOPTED THIS REGULATION:

Article 1

The Regulation (EC) No 1255/96 is amended as follows:

The Annex shall be replaced by the Annex to this Regulation.

¹ OJ L 158, 29.6.1996, p.1. Regulation last amended by Regulation (EC) No 1159/2001 (OJ L 169, 23.6.2001, p.1).

Article 2

This Regulation shall enter into force on the day of its publication in the *Official Journal of the European Communities*.

It shall apply with effect from 1 January 2002.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels, [...]

*For the Council
The President*

ANNEX

CN code & TARIC	Description	Rate of autonomous duty (%)
0001 ex 0302 69 99 10 ex 0303 79 98 10	Sturgeons, fresh, chilled or frozen, for processing (a) (b) (c)	0
0002 ex 0302 69 99 20	Lump fish (<i>Cyclopterus lumpus</i>) with roe, fresh or chilled, for processing (a) (c)	0
0003 ex 0302 69 99 30 ex 0303 79 98 20	Red snapper (<i>Lutjanus purpureus</i>), fresh, chilled or frozen, for processing (a) (d) (c)	0
0004 ex 0302 70 00 11 ex 0302 70 00 31 ex 0302 70 00 41 ex 0302 70 00 91 ex 0303 80 90 10 ex 0303 80 90 19	Hard fish roes, fresh, chilled or frozen (c)	0
0005 ex 0303 11 00 10 ex 0303 19 00 10	Pacific salmon (<i>Oncorhynchus spp.</i>), frozen and headless, for the processing industry for manufacture into pastes or spreads (a) (c)	0
0006 ex 0304 10 98 60 ex 0304 90 97 31	Meat of dogfish of the species <i>Squalus acanthias</i> , fresh, chilled or frozen (c)	6
0007 ex 0305 20 00 11 ex 0305 20 00 18 ex 0305 20 00 20	Hard fish roes, salted or in brine (c)	0
0008 ex 0306 19 90 10 ex 0306 29 90 10	Krill for processing (a) (c)	0
0009 ex 0603 90 00 10 ex 0604 99 90 10	Flowers, flower buds, foliage, leaves and other parts of plants, not further prepared than dried, dyed or bleached, for use in the manufacture of pot pourri of subheading 3307 49 00 (a)	0
0010 ex 0710 21 00 10	Peas in pods, of the species <i>Pisum sativum</i> of the variety <i>Hortense axiphium</i> , frozen, of a thickness not exceeding 6 mm, to be used, in their pods, in the manufacture of prepared meals (a) (d)	0
0011 ex 0711 59 00 11 ex 0711 59 00 91	Mushrooms, excluding mushrooms of the genus <i>Agaricus</i> , provisionally preserved in brine, in sulphur water, or in other preservative solutions, but unsuitable in that state for immediate consumption, for the food-canning industry (a)	0
0012 ex 0712 32 00 11 ex 0712 32 00 21 ex 0712 33 00 11 ex 0712 33 00 21 ex 0712 39 00 11 ex 0712 39 00 21	Mushrooms, excluding mushrooms of the genus <i>Agaricus</i> , dried, whole or in identifiable slices or pieces, for treatment other than simple repacking for retail sale (a) (d)	0
0013 ex 0804 10 00 11 ex 0804 10 00 21	Dates, fresh or dried, not put up for retail sale	0
0014 ex 0810 40 50 10	Fruit of the species <i>Vaccinium macrocarpon</i> , fresh	0
0015 ex 0810 90 95 10	Rose-hips, fresh	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0016	0811 90 50 0811 90 70 ex 0811 90 95 66 ex 0811 90 95 67	Fruit of the genus <i>Vaccinium</i> , uncooked or cooked by steaming or boiling in water, frozen, not containing added sugar or other sweetening matter	0
0017	ex 0811 90 95 40	Rose-hips, uncooked or cooked by steaming or boiling in water, frozen, not containing added sugar or other sweetening matter	0
0018	ex 1511 90 19 10 ex 1511 90 91 10 ex 1513 11 10 10 ex 1513 19 30 10 ex 1513 21 11 10 ex 1513 29 30 10	Palm oil, coconut (copra) oil, palm kernel oil, for the manufacture of: – industrial monocarboxylic fatty acids of subheading 3823 19 10, – mixtures of methyl esters of fatty acids of subheading 3824 90 95, – methyl esters of fatty acids of heading 2915 or 2916 or – stearic acid of subheading 3823 11 00 (a)	0
0019	ex 1518 00 91 10	Soya-bean oil, modified with maleic acid, for the manufacture of cosmetic products (a)	0
0020	ex 1604 11 00 20 ex 1604 20 10 20	Pacific salmon (<i>Oncorhynchus spp.</i>), for the processing industry for manufacture into pastes or spreads (a) (c)	0
0021	ex 1604 30 90 10	Hard fish roes, washed, cleaned of adherent organs and simply salted or in brine, for processing (a) (c)	0
0022	ex 1605 10 00 11 ex 1605 10 00 19	Crabs of the species “King” (<i>Paralithodes camchaticus</i>), “Hanasaki” (<i>Paralithodes brevipes</i>), “Kegani” (<i>Erimacrus isenbecki</i>), “Queen” and “Snow” (<i>Chionoecetes spp.</i>), “Red” (<i>Geryon quinquedens</i>), “Rough stone” (<i>Neolithodes asperrimus</i>), <i>Lithodes antarctica</i> , “Mud” (<i>Scylla serrata</i>), “Blue” (<i>Portunus spp.</i>), simply boiled in water and shelled, whether or not frozen, in immediate packings of a net content of 2 kg or more (c)	0
0023	ex 1605 10 00 92 ex 1605 10 00 94	Crabs of the species <i>Paralomis granulosa</i> (c)	0
0024	ex 2005 90 80 70	Bamboo shots, prepared or preserved, shredded, not put up for retail sale	0
0025	ex 2707 99 11 10	Crude light oils containing by weight: – 10 % or more of vinyltoluenes, – 10 % or more of indene and – 1 % or more but not more than 5 % of naphthalene	0
0026	ex 2805 30 10 10	Alloy of cerium and other rare-earth metals, containing by weight 47 % or more of cerium	0
0027	ex 2805 30 10 20	Alloy of lanthanum and other rare-earth metals, containing by weight 43 % or more of lanthanum	0
0029	ex 2805 30 90 10	Lanthanum of a purity by weight of 99 % or more	0
0030	ex 2811 19 80 10	Sulfamidic acid	0
0031	ex 2811 22 00 10	Silicon dioxide in the form of powder, for use in the manufacture of high performance liquid chromatography columns (HPLC) and sample preparation cartridges (a)	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
	0032	ex 2811 29 90 10 Tellurium dioxide	0
	0033	ex 2812 90 00 10 Nitrogen trifluoride	0
	0034	ex 2818 30 00 10 Aluminium hydroxide oxide in the form of pseudo-boehmite	4
	0035	ex 2819 90 90 10 Dichromium trioxide: – of a specific surface of 37 m ² /g or more (as determined by the BET method), – of a purity by weight of 99,5 % or more calculated on the dry substance, – of a specific gravity of 1,2 g/cm ³ or less, for the manufacture of magnetic chromium dioxide (a)	0
	0036	ex 2820 90 90 10 Manganese (II,III) oxide containing by weight 70 % or more of manganese	0
	0037	ex 2821 10 00 10 Diiron trioxide, in the form of powder, of a purity by weight of 99,2 % or more, for the manufacture of goods of heading No 8504 (a)	0
	0038	ex 2823 00 00 10 Titanium dioxide, of a purity by weight of 99,9 % or more, with an average grain-size of 1,2 µm or more but not exceeding 1,8 µm, for the manufacture of goods of heading No 8532 or 8533 (a)	0
	0039	ex 2825 50 00 10 Copper (I or II) oxide containing by weight 78 % or more of copper and not more than 0,03 % of chloride	0
	0040	ex 2826 90 90 10 Potassium hexafluorophosphate	0
	0041	ex 2827 39 80 10 Copper monochloride of a purity by weight of 96 % or more but not exceeding 99 %	0
	0042	ex 2827 60 00 10 Titanium tetraiodide	0
	0043	ex 2830 10 00 10 Disodium tetrasulfide, containing by weight 38 % or less of sodium calculated on the dry weight	0
	0044	ex 2830 20 00 10 Zinc sulfide containing: – 20,0 mg/kg or less of chloride, – 0,2 mg/kg or less of copper, – 0,5 mg/kg or less of iron and – 1,0 mg/kg or less of lead	0
	0045	ex 2836 91 00 20 Lithium carbonate, containing one or more of the following impurities at the concentrations indicated: – 2 mg/kg or more of arsenic, – 200 mg/kg or more of calcium, – 200 mg/kg or more of chlorides, – 20 mg/kg or more of iron, – 150 mg/kg or more of magnesium, – 20 mg/kg or more of heavy metals, – 300 mg/kg or more of potassium, – 300 mg/kg or more of sodium, – 200 mg/kg or more of sulfates, determined according to the methods specified in the European Pharmacopœia	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0046	ex 2837 19 00 10	Zinc cyanide	0
0047	ex 2837 19 00 20	Copper cyanide	0
0048	ex 2839 90 00 10	Lead silicate hydrate, of a lead content by weight of (84,5 ± 1,5) %, evaluated as lead monoxide, in the form of powder	0
0049	ex 2843 90 90 20	Palladium monoxide	0
0050	ex 2843 90 90 30	Mixture of palladium phthalocyanines	0
0051	2845 10 00	Heavy water (deuterium oxide) (<i>Euratom</i>)	0
0052	2845 90 10	Deuterium and compounds thereof; hydrogen and compounds thereof, enriched in deuterium; mixtures and solutions containing these products (<i>Euratom</i>)	0
0053	ex 2846 10 00 10 ex 3824 90 99 48	Rare-earth concentrate containing by weight 60 % or more but not more than 95 % of rare-earth oxides and not more than 1 % each of zirconium oxide, aluminium oxide or iron oxide, and having a loss on ignition of 5 % or more by weight	0
0055	ex 2848 00 00 10	Phosphine	0
0056	ex 2850 00 20 10	Silane	0
0057	ex 2903 30 80 10	Carbon tetrafluoride (tetrafluoromethane)	0
0058	ex 2903 30 80 20	1,1,1,2,3,3,3-Heptafluoropropane	0
0059	ex 2903 30 80 30	Perfluoroethane	0
0060	ex 2903 30 80 40	1,1-Difluoroethane	0
0061	ex 2903 59 90 10	1,6,7,8,9,14,15,16,17,17,18,18-Dodecachloropentacyclo= [12.2.1.1 ^{6,9} .0 ^{2,13} .0 ^{5,10}]octadeca-7,15-diene, for use in the manufacture of polyamide, polyethylene, synthetic rubber or polystyrene (a)	0
0062	ex 2903 59 90 20	Hexachlorocyclopentadiene	0
0063	ex 2903 69 90 10	Di- or tetrachlorotricyclo[8.2.2.2 ^{4,7}]hexadeca-1(12),4,6,10,13,15-hexaene, mixed isomers	0
0064	ex 2903 69 90 20	1,2-Bis(pentabromophenyl)ethane	0
0065	ex 2903 69 90 40	2,6-Dichlorotoluene, of a purity by weight of 99 % or more and containing: <ul style="list-style-type: none"> - 0,001 mg/kg or less of tetrachlorodibenzodioxines, - 0,001 mg/kg or less of tetrachlorodibenzofurans, - 0,2 mg/kg or less of tetrachlorobiphenyls 	0
0066	ex 2903 69 90 50	1-(Chloromethyl)naphthalene	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0067	ex 2903 69 90 60	α -Chloro(ethyl)toluenes	0
0068	ex 2904 10 00 30	Sodium <i>p</i> -styrenesulfonate	0
0069	ex 2904 20 00 10	Nitromethane	0
0070	ex 2904 20 00 20	Nitroethane	0
0071	ex 2904 20 00 30	1-Nitropropane	0
0072	ex 2904 20 00 40	2-Nitropropane	0
0073	ex 2904 90 20 10	Tosyl chloride	0
0074	ex 2904 90 40 10	Trichloronitromethane, for the manufacture of goods of subheading 3808 20 (a)	0
0075	ex 2904 90 85 10	Quintozene (ISO)	0
0076	ex 2905 19 00 11 ex 3824 90 99 56	Potassium <i>tert</i> -butanolate (potassium <i>tert</i> -butoxide), whether or not in the form of a solution in tetrahydrofuran	0
0077	2905 29 10	Allyl alcohol	0
0079	ex 2905 39 80 10	2-Methylpropane-1,3-diol	0
0078	ex 2905 39 80 20	Hexa-1,5-diene-3,4-diol	0
0080	ex 2905 49 10 10	Ethylidynetrimethanol	0
0081	2906 11 00	Menthol	0
0082	ex 2906 19 00 10	Cyclohex-1,4-ylenedimethanol	0
0083	ex 2906 19 00 20	4,4'-Isopropylidenedicyclohexanol	0
0084	ex 2906 29 00 10	2,2'-(<i>m</i> -Phenylene)dipropan-2-ol	0
0085	ex 2907 21 00 10	Resorcinol	0
0086	ex 2907 29 00 10	Disodium 1,4-dihydroanthracene-9,10-diolate, in the form of an aqueous solution	0
0087	ex 2907 29 00 20	4,4'-(3,3,5-Trimethylcyclohexylidene)diphenol	0
0088	ex 2907 29 00 30	4,4',4''-Ethylidynetriphenol	0
0089	ex 2907 29 00 40	Mixture of isomers of methylenediphenol	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0090	ex 2907 29 00 50	6,6',6''-Tricyclohexyl-4,4',4''-butane-1,1,3-triyltri(<i>m</i> -cresol)	0
0091	ex 2907 29 00 60	4,4'-(1,3-Phenylenediisopropylidene)diphenol	0
0092	ex 2908 20 00 10	Disodium 3-hydroxynaphthalene-2,7-disulfonate	0
0093	ex 2908 20 00 20	Dipotassium 7-hydroxynaphthalene-1,3-disulfonate	0
0094	ex 2908 20 00 30 ex 3824 90 99 74	6-Hydroxynaphthalene-2-sulfonic acid and its salts	0
0095	ex 2908 90 00 10	4-Nitroso- <i>o</i> -cresol	0
0096	ex 2909 19 00 10	1,2-Bis(2-chloroethoxy)ethane	0
0097	ex 2909 30 38 10	Bis(pentabromophenyl) ether	0
0098	ex 2909 30 90 10	4-(<i>p</i> -Tolyloxy)biphenyl	0
0099	ex 2909 30 90 20	1,2-Bis(<i>m</i> -tolylloxy)ethane	0
0100	ex 2909 30 90 30	1,2-Diphenoxyethane	0
0101	ex 2909 44 00 10	2-Hexyloxyethanol	0
0102	ex 2909 49 19 10	1- <i>tert</i> -Butoxypropan-2-ol	0
0103	ex 2909 50 90 10	4-(2-Methoxyethyl)phenol	0
0104	ex 2910 90 00 30	2,3-Epoxypropan-1-ol (glycidol)	0
0105	ex 2910 90 00 40	Perfluoroepoxypropane	0
0106	ex 2910 90 00 60 ex 3824 90 99 59	1,2-Epoxyoctadecane, of a purity by weight of 82 % or more	0
0107	ex 2912 29 00 10	Terephthalaldehyde	0
0108	ex 2912 49 00 10	3-Phenoxybenzaldehyde	0
0109	ex 2914 19 90 10	3,3-Dimethylbutan-2-one	0
0110	2914 21 00	Camphor	0
0111	ex 2914 29 00 10	Estr-4-ene-3,17-dione	0
0112	ex 2914 50 00 30	2'-Hydroxyacetophenone	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0113	ex 2914 50 00 40	4'-Hydroxyacetophenone	0
0114	ex 2914 50 00 50	6'-Methoxy-2'-acetophenone	0
0115	ex 2914 69 90 10	2-Ethylanthraquinone	0
0116	ex 2914 69 90 20	2-Pentylanthraquinone	0
0117	ex 2914 69 90 30	1,4-Dihydroxyanthraquinone	0
0118	ex 2914 69 90 40	2,3-Dihydro-1,4-dihydroxyanthraquinone	0
0119	ex 2914 70 90 10	1-Chloro-3,3-dimethylbutan-2-one	0
0120	ex 2914 70 90 30	4,4'-Dibromobenzil	0
0121	ex 2915 29 00 10	Antimony triacetate	0
0122	ex 2915 39 90 20	5 α -Bromo-6 β -hydroxy-17-oxo-androstan-3 β -yl acetate	0
0123	ex 2915 39 90 30	But-3-ene-1,2-diyl di(acetate)	0
0124	ex 2915 40 00 10	Vinyl chloroacetate	0
0125	ex 2915 90 80 20	Trimethyl orthoacetate	0
0126	ex 2915 90 80 30	2-Ethylbutyric acid	0
0127	ex 2915 90 80 40	Nonanoic acid (pelargonic acid)	0
0128	ex 2916 12 90 10	2- <i>tert</i> -Butyl-6-(3- <i>tert</i> -butyl-2-hydroxy-5-methylbenzyl)-4-methylphenyl acrylate	0
0129	ex 2916 12 90 20	2-Ethoxyethyl acrylate	0
0130	ex 2916 12 90 30	Isobutyl acrylate	0
0131	ex 2916 13 00 10	Hydroxyzinc methacrylate, in the form of powder	0
0132	ex 2916 13 00 20	Zinc dimethacrylate, in the form of powder	0
0133	ex 2916 14 90 10	2,3-Epoxypropyl methacrylate	0
0134	ex 2916 19 80 20	Methyl 3,3-dimethylpent-4-enoate	0
0135	ex 2916 20 00 10	Methyl 3-(2,2-dichlorovinyl)-2,2-dimethylcyclopropanecarboxylate	0
0136	ex 2916 20 00 30	Empenthrin (ISO)	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0137	ex 2916 20 00 40	Cyclohexanecarboxylic acid	0
0138	ex 2916 39 00 10	Methyl 3-chlorobenzoate	0
0139	ex 2916 39 00 20	3,5-Dichlorobenzoyl chloride	3.6
0140	ex 2916 39 00 40	Vinyl 4- <i>tert</i> -butylbenzoate	0
0141	ex 2916 39 00 50	3,5-Dimethylbenzoyl chloride	0
0142	ex 2916 39 00 60	4-Ethylbenzoyl chloride	0
0143	ex 2917 11 00 20	Bis(<i>p</i> -methylbenzyl) oxalate	0
0144	ex 2917 19 90 20	Sodium 1,2-bis(cyclohexyloxycarbonyl)ethanesulfonate	0
0145	ex 2917 19 90 40	Dodecanedioic acid, of a purity by weight of more than 98,5 %	0
0146	ex 2917 19 90 50	Glutaric anhydride	0
0148	ex 2917 20 00 30	1,4,5,6,7,7-Hexachloro-8,9,10-trinorborn-5-ene-2,3-dicarboxylic anhydride	0
0147	ex 2917 20 00 40	3-Methyl-1,2,3,6-tetrahydrophthalic anhydride	0
0149	ex 2917 34 00 10	Diallyl phthalate	0
0150	ex 2917 39 80 10	Dimethyl naphthalene-2,6-dicarboxylate	0
0151	ex 2917 39 80 20	Benzene-1,2,4,5-tetracarboxylic acid (pyromellitic acid)	0
0152	ex 2917 39 80 30	Benzene-1,2:4,5-tetracarboxylic dianhydride (pyromellitic dianhydride)	0
0153	ex 2918 13 00 10	L-(-)-Di- <i>p</i> -toluoyltartaric acid	0
0155	ex 2918 19 80 20	L-Malic acid	0
0156	ex 2918 29 10 10	Monohydroxynaphthoic acids	0
0157	ex 2918 29 50 10	Gallic acid, of a purity by weight of 98,5 % or more calculated on the dry weight (measured by acidimetry)	0
0158	ex 2918 29 90 10	Hexamethylene bis[3-(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)propionate]	0
0159	ex 2918 90 90 10	3,4-Epoxy cyclohexylmethyl 3,4-epoxycyclohexanecarboxylate	0
0160	ex 2918 90 90 20	Methyl 3-methoxyacrylate	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0161	ex 2919 00 90 10	2,2'-Methylenebis(4,6-di- <i>tert</i> -butylphenyl) phosphate, monosodium salt	0
0162	ex 2919 00 90 20	Diammonium salt of tetramyristoylcardiolipin	0
0163	ex 2920 10 00 10	Fenitrothion (ISO)	0
0164	ex 2920 10 00 20	Tolclofos-methyl (ISO)	0
0165	ex 2920 90 10 10	Diethyl sulfate	0
0166	2920 90 30	Trimethyl phosphite	0
0167	ex 2920 90 85 10	<i>O,O'</i> -Dioctadecyl pentaerythritol bis(phosphite)	0
0168	ex 2920 90 85 30	<i>O,O'</i> -Bis(2,4-di- <i>tert</i> -butylphenyl)pentaerythritol bis(phosphite)	0
0169	ex 2921 19 80 10	Triallylamine	0
0170	ex 2921 19 80 20	Ethyl(2-methylallyl)amine	0
0171	ex 2921 19 80 30	Allylamine	0
0172	ex 2921 29 00 10	<i>N,N,N',N'</i> -Tetrabutylhexamethylenediamine	0
0173	ex 2921 29 00 20	Tris[3-(dimethylamino)propyl]amine	0
0174	ex 2921 29 00 30	Bis[3-(dimethylamino)propyl]methylamine	0
0175	ex 2921 30 99 10	Dicyclohexyl(methyl)amine	0
0176	ex 2921 42 10 10	2,6-Dichloro-4-nitroaniline	0
0177	ex 2921 42 10 20	2-Bromo-4,6-dinitroaniline	0
0178	ex 2921 42 10 30	4-Aminobenzene-1,3-disulfonic acid and its salts	0
0179	ex 2921 42 10 40	2-Bromo-6-chloro-4-nitroaniline	0
0180	ex 2921 42 10 50	3-Aminobenzenesulfonic acid	0
0181	ex 2921 43 00 10	5-Amino-2-chlorotoluene-4-sulfonic acid	0
0182	ex 2921 43 00 20	4-Amino-6-chlorotoluene-3-sulfonic acid	0
0183	ex 2921 43 00 30	3-Nitro- <i>p</i> -toluidine	0
0184	ex 2921 44 00 10	Methyldiphenylamine	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0185	ex 2921 45 00 10	3-Aminonaphthalene-1,5-disulfonic acid, monosodium salt	0
0186	ex 2921 45 00 20	2-Aminonaphthalene-1,5-disulfonic acid and its sodium salts	0
0187	ex 2921 45 00 30	2-Aminonaphthalene-1-sulfonic acid	0
0188	ex 2921 45 00 40	1-Naphthylamine	0
0189	ex 2921 49 10 20	Pendimethalin (ISO)	3.5
0190	ex 2921 49 80 10	8-Anilinonaphthalene-1-sulfonic acid	0
0191	ex 2921 59 90 10	Mixture of isomers of 3,5-diethyltoluenediamine	0
0192	ex 2921 59 90 20 ex 3824 90 99 68	4-(4-Aminoanilino)-3-nitrobenzenesulfonic acid	0
0193	ex 2922 19 80 10	4,4-Dimethoxybutylamine	0
0194	ex 2922 19 80 20	2-[2-(Dimethylamino)ethyl(methyl)amino]ethanol	0
0195	ex 2922 19 80 30	<i>N,N,N',N'</i> -Tetramethyl-2,2'-oxybis(ethylamine)	0
0196	ex 2922 19 80 40	2-Amino-2-methylpropanol, for use in the manufacture of goods of subheadings 3004 90 and 3305 30 (a)	0
0197	ex 2922 21 00 10	2-Amino-5-hydroxynaphthalene-1,7-disulfonic acid and its salts, of a purity by weight of 60 % or more	0
0198	ex 2922 21 00 20	4-Hydroxy-7-methylaminonaphthalene-2-sulfonic acid	0
0199	ex 2922 21 00 30	6-Amino-4-hydroxynaphthalene-2-sulfonic acid	0
0200	ex 2922 21 00 40	7-Amino-4-hydroxynaphthalene-2-sulfonic acid	0
0201	ex 2922 22 00 10	Anisidines	0
0202	ex 2922 29 00 10	2-Methyl- <i>N</i> -phenyl- <i>p</i> -anisidine	0
0203	ex 2922 29 00 20	3-Aminophenol	0
0204	ex 2922 29 00 30	4-Amino-5-methoxy-2-methylbenzenesulfonic acid	0
0205	ex 2922 29 00 40	2-Amino-4- <i>tert</i> -pentyl-6-nitrophenol	0
0206	ex 2922 29 00 50	6-Methoxy- <i>m</i> -toluidine	0
0207	ex 2922 29 00 60	3,5-Dichloro-4-(1,1,2,2-tetrafluoroethoxy)aniline	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0208	ex 2922 29 00 70	4-Nitro- <i>o</i> -anisidine	0
0209	ex 2922 29 00 80	3-Diethylaminophenol	0
0211	ex 2922 39 00 10	1-Amino-4-bromo-9,10-dioxoanthracene-2-sulfonic acid and its salts	0
0212	ex 2922 39 00 20	1-Aminoanthraquinone	0
0210	ex 2922 39 00 30	1-Bromo-4-methylaminoanthraquinone	0
0214	ex 2922 49 95 10	Ornithine aspartate (INN)	0
0215	ex 2922 49 95 20	12-Aminododecanoic acid	0
0213	ex 2922 49 95 30	2-(3-Amino-4-chlorobenzoyl)benzoic acid	0
0216	ex 2922 50 00 50	2-(4-Dibutylaminosalicyloyl)benzoic acid	0
0217	ex 2923 90 00 10	Tetramethylammonium hydroxide, in the form of an aqueous solution containing: – (25 ± 0,5) % by weight of tetramethylammonium hydroxide, – 500 mg/kg or less of carbonate, – 200 mg/kg or less of chloride and – 5 mg/kg or less of potassium	0
0218	ex 2923 90 00 30	Tetramethylammonium hydroxide pentahydrate, of a purity by weight of 98 % or more	0
0219	ex 2923 90 00 40	Benzyltrimethyl(octadecyl)ammonium salts, for use in the manufacture of toner for photocopiers (a)	0
0220	ex 2924 19 00 10	2-Acrylamido-2-methylpropanesulfonic acid and its sodium or ammonium salts	0
0221	ex 2924 19 00 20	<i>N,N'</i> -Methylenediacrylamide	0
0222	ex 2924 21 90 10 ex 3824 90 99 62	4,4'-Dihydroxy-7,7'-ureylenedi(naphthalene-2-sulfonic acid) and its sodium salts	0
0224	ex 2924 29 95 10	Alachlor (ISO)	0
0225	ex 2924 29 95 15	Acetochlor (ISO)	0
0226	ex 2924 29 95 20	3'-Amino-4'-methoxyacetanilide	0
0227	ex 2924 29 95 25	3'-Diethylaminoacetanilide	0
0228	ex 2924 29 95 30	Propachlor (ISO)	0
0229	ex 2924 29 95 35	Diethofencarb (ISO)	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0230	ex 2924 29 95 40	7-Acetamido-4-hydroxynaphthalene-2-sulfonic acid and its sodium salts	0
0231	ex 2924 29 95 45	3'-Diethylamino-4'-methoxyacetanilide	0
0232	ex 2924 29 95 50	5-[N-(2-Acetoxyethyl)acetoxycetamido]-N,N'-bis(2,3-diacetoxy= propyl)-2,4,6-triidoisophthalamide	0
0233	ex 2924 29 95 55	4'-Amino-N-methylacetanilide	0
0234	ex 2924 29 95 60	Beflubutamid (ISO)	0
0223	ex 2924 29 95 70	4-Acetamido-2-aminobenzenesulfonic acid	0
0235	ex 2925 11 00 20	Saccharin and its sodium salt	0
0236	ex 2925 19 95 10	N-Phenylmaleimide	0
0237	ex 2925 20 00 10	Dicyclohexylcarbodiimide	0
0239	ex 2926 90 95 10	Methacrylonitrile	0
0238	ex 2926 90 95 20	2-(m-Benzoylphenyl)propiononitrile	0
0240	ex 2926 90 95 30	2-Amino-5-nitrobenzonitrile	0
0241	ex 2926 90 95 40	Chlorothalonil (ISO)	0
0242	ex 2926 90 95 45	2-Cyanoacetamide	0
0243	ex 2926 90 95 50	Alkyl or alkoxyalkyl esters of cyanoacetic acid	0
0244	ex 2926 90 95 60	Cyanoacetic acid in crystalline form	0
0245	ex 2926 90 95 65	Malononitrile	0
0246	ex 2926 90 95 70	Tetrachloroterephthalonitrile	0
0247	ex 2927 00 00 10	2,2'-Dimethyl-2,2'-azodipropionamidine dihydrochloride	0
0248	ex 2927 00 00 20	4-Anilino-2-methoxybenzenediazonium hydrogen sulfate	0
0249	ex 2927 00 00 30 ex 3824 90 99 69	4'-Aminoazobenzene-4-sulfonic acid	0
0250	ex 2927 00 00 40	2-Hydroxynaphthalene-1-diazonium-4-sulfonate	0
0251	ex 2927 00 00 50 ex 3824 90 99 41	2-Hydroxy-6-nitronaphthalene-1-diazonium-4-sulfonate, of a purity by weight of 60 % or more	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0252	ex 2928 00 90 10	3,3'-Bis(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)- <i>N,N'</i> -bipropionamide	0
0253	ex 2928 00 90 20	2,4,6-Trichlorophenylhydrazine	0
0254	ex 2928 00 90 40	<i>O</i> -Ethylhydroxylamine, in the form of an aqueous solution	0
0255	ex 2928 00 90 50	<i>N</i> -Isopropylhydroxylamine, in the form of an aqueous solution	0
0256	ex 2929 10 90 10	Methylenedicyclohexyl diisocyanates	0
0257	ex 2929 10 90 30	3,3'-Dimethylbiphenyl-4,4'-diyl diisocyanate	0
0258	ex 2929 10 90 40	<i>m</i> -Isopropenyl- α,α -dimethylbenzyl isocyanate	0
0259	ex 2929 10 90 50	<i>m</i> -Phenylenediisopropylidene diisocyanate	0
0260	ex 2929 10 90 60	Trimethylhexamethylene diisocyanate, mixed isomers	0
0262	ex 2930 90 70 10	Thiophenol	0
0263	ex 2930 90 70 15	Ethoprophos (ISO)	0
0264	ex 2930 90 70 20	3,3-Dimethyl-1-methylthiobutanone oxime	0
0265	ex 2930 90 70 25	Thiophanate-methyl (ISO)	0
0266	ex 2930 90 70 30	4-(4-Isopropoxyphenylsulfonyl)phenol	0
0267	ex 2930 90 70 40	3,3'-Thiodi(propionic acid)	0
0268	ex 2930 90 70 45	2-[(<i>p</i> -Aminophenyl)sulfonyl]ethyl hydrogen sulfate	0
0269	ex 2930 90 70 50 ex 3824 90 99 51	2-Chlorophenylsulfonyl isocyanate, in the form of a solution in xylene	0
0270	ex 2930 90 70 55 ex 3824 90 99 52	Methyl 2-(isocyanatosulfonyl)methylbenzoate, in the form of a solution in xylene	0
0271	ex 2930 90 70 60	Methyl phenyl sulfide	0
0272	ex 2930 90 70 65	Diiodomethyl <i>p</i> -tolyl sulfone	0
0273	ex 2930 90 70 70 ex 3824 90 99 71	2-Aminophenyl phenyl sulfone, of a purity by weight of 75 % or more	0
0274	ex 2930 90 70 75	4,4'-[Methylenebis(oxyethylenethio)]diphenol	0
0275	ex 2930 90 70 80	Captan (ISO)	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0261	ex 2930 90 70 85	Mesotrione (ISO)	0
0276	2931 00 10	Dimethyl methylphosphonate	0
0277	ex 2931 00 95 05	Butylethylmagnesium, in the form of a solution in heptane	0
0281	ex 2931 00 95 10	2-Diphenylphosphinobenzoic acid	0
0282	ex 2931 00 95 20	Bis(2-chloroethyl) 2-chloroethylphosphonate	0
0283	ex 2931 00 95 25	Sodium phenylphosphinate	0
0284	ex 2931 00 95 30	Bis(2-chloroethyl) vinylphosphonate	0
0285	ex 2931 00 95 35	Sodium tetraphenylborate	0
0286	ex 2931 00 95 40	<i>N</i> -(Phosphonomethyl)iminodiacetic acid	0
0287	ex 2931 00 95 45	Tributylphosphine	0
0288	ex 2931 00 95 50	Bis(2,4,4-trimethylpentyl)phosphinic acid	0
0289	ex 2931 00 95 55	Dimethyl[dimethylsilyldiindenyl]hafnium	0
0290	ex 2931 00 95 60	Trioctylphosphine oxide	0
0291	ex 2931 00 95 65	Triethylborane	0
0278	ex 2931 00 95 70	<i>N,N</i> -Dimethylanilinium tetrakis(pentafluorophenyl)borate	0
0279	ex 2931 00 95 75	{2,7-Di- <i>tert</i> -butyl-9-[(η^5 -cyclopentadienyl)bis(4-triethylsilylphenyl)methyl]-4a,4b,8a,9,9a- η -fluorene}dimethylhafnium, in the form of a solution in hexane	0
0292	ex 2931 00 95 85	Tributyl(tetradecyl)phosphonium chloride, whether or not in the form of an aqueous solution	0
0280	ex 2931 00 95 95	Trichloro(3-chloropropyl)silane	0
0293	ex 2932 11 00 10	Tetrahydrofuran, containing not more than 40 mg per litre in total of tetrahydro-2-methylfuran and tetrahydro-3-methylfuran, for the manufacture of α -4-hydroxybutyl- ω -hydroxypoly(oxytetramethylene) (a)	0
0294	ex 2932 13 00 10	Tetrahydrofurfuryl alcohol	0
0295	ex 2932 19 00 40	Furan of a purity by weight of 99 % or more	0
0296	ex 2932 19 00 50	2,3-Dihydrofuran	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0297	ex 2932 29 80 10	2'-Anilino-6'-[ethyl(isopentyl)amino]-3'-methylspiro[isobenzofuran= -1(3H),9'-xanthen]-3-one	0
0298	ex 2932 29 80 15	13,14,15,16-Tetranorlabdano-12,8 α -lactone	0
0299	ex 2932 29 80 25	2'-(2-Chloroanilino)-6'-dibutylaminospiro[isobenzofuran= -1(3H),9'-xanthen]-3-one	0
0300	ex 2932 29 80 30	2'-Anilino-3'-methyl-6'-methyl(propyl)aminospiro[isobenzofuran= -1(3H),9'-xanthen]-3-one	0
0301	ex 2932 29 80 35	6'-Diethylamino-3'-methyl-2'-(2,4-xylidino)spiro[isobenzofuran= -1(3H),9'-xanthen]-3-one	0
0302	ex 2932 29 80 40	2'-Anilino-6'-(N-ethyl-p-toluidino)-3'-methylspiro[isobenzofuran= -1(3H),9'-xanthen]-3-one	0
0303	ex 2932 29 80 45	2'-Anilino-6'-ethyl(isobutyl)amino-3'-methylspiro[isobenzofuran= -1(3H),9'-xanthen]-3-one	0
0304	ex 2932 29 80 50	2'-Anilino-6'-cyclohexyl(methyl)amino-3'-methylspiro[isobenzofuran= -1(3H),9'-xanthen]-3-one	0
0305	ex 2932 29 80 55	6-Dimethylamino-3,3-bis(4-dimethylaminophenyl)phthalide	0
0307	ex 2932 99 70 10	Bendiocarb (ISO)	0
0308	ex 2932 99 70 20	Androsta-1,4-diene-3,17-dione 17-(2,2-dimethylpropylene) acetal	0
0306	ex 2932 99 70 40	1,3:2,4-Bis-O-(3,4-dimethylbenzylidene)-D-glucitol	0
0309	ex 2933 19 90 10	4,5-Diamino-1-(2-hydroxyethyl)-1H-pyrazole sulfate	0
0310	ex 2933 21 00 10	Hydantoin	0
0311	ex 2933 21 00 20	2-(3-Benzyl-2,5-dioximidazolidin-1-yl)-2'-chloro-5'-(3-dodecylmethylpropionamido)-4,4-dimethyl-3-oxovaleranilide sulfonyl-2-	0
0312	ex 2933 21 00 40	1-[1,3-Bis(hydroxymethyl)-2,5-dioximidazolidin-4-yl]=-1,3-bis(hydroxymethyl)urea	0
0313	ex 2933 29 90 20	Reaction product consisting of the methyl esters of (\pm)-6-(4-isopropyl-4-methyl-5-oxo-2-imidazolin-2-yl)- <i>m</i> -toluic acid and (\pm)-2-(4-isopropyl-4-methyl-5-oxo-2-imidazolin-2-yl)- <i>p</i> -toluic acid (Imazamethabenz-methyl)	4
0314	ex 2933 29 90 40	Triflumizole (ISO)	0
0315	ex 2933 39 99 10	Cloperastine fendizoate (INNM)	0
0316	ex 2933 39 99 15	Pyridine-2,3-dicarboxylic acid	0
0317	ex 2933 39 99 20	5-Methyl-2-pyridylamine	0
0318	ex 2933 39 99 25	Imazethapyr (ISO)	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0319	ex 2933 39 99 30	4,4'-Trimethylenedipiperidine	0
0320	ex 2933 39 99 60	2-Fluoro-6-(trifluoromethyl)pyridine	0
0321	ex 2933 49 10 10	Quinmerac (ISO)	0
0322	ex 2933 49 90 20	5,7-Dichloro-4-(4-fluorophenoxy)quinoline	0
0323	ex 2933 49 90 40	<i>N</i> -Ethyl-5,6,7,8-tetrahydroquinolinium <i>p</i> -toluenesulfonate, in the form of a solution in water	0
0324	ex 2933 49 90 50	Methyl 2-[(<i>S</i>)-3-[(<i>E</i>)-3-[2-(7-chloro-2-quinoly)vinyl]phenyl]-3-hydroxypropyl]-benzoate monohydrate	0
0325	ex 2933 49 90 60	5,6,7,8-Tetrahydroquinoline	0
0326	ex 2933 59 95 10	1-Ethyl-6-fluoro-1,4-dihydro-4-oxo-7-piperazin-1-yl-1,8-naphthyridine-3-carboxylic acid and its salts and esters	0
0327	ex 2933 59 95 20	2,4-Diamino-6-chloropyrimidine	0
0328	ex 2933 59 95 30	Mepaniprim (ISO)	0
0329	ex 2933 59 95 40	Guanine	0
0330	ex 2933 59 95 50	1-Chloromethyl-4-fluoro-1,4-diazoniabicyclo[2.2.2]octane bis(tetrafluoroborate)	0
0332	ex 2933 69 80 10	1,3,5-Tris(4- <i>tert</i> -butyl-3-hydroxy-2,6-dimethylbenzyl)-1,3,5-triazine-2,4,6-(1 <i>H</i> ,3 <i>H</i> ,5 <i>H</i>)-trione	0
0333	ex 2933 69 80 20	1,3,5-Tris[(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)methyl]-1,3,5-triazine-2,4,6-(1 <i>H</i> ,3 <i>H</i> ,5 <i>H</i>)-trione	0
0334	ex 2933 69 80 40	Cyanazine (ISO)	0
0335	ex 2933 69 80 50	1,3,5-Tris(2,3-dibromopropyl)-1,3,5-triazinane-2,4,6-trione	0
0331	ex 2933 69 80 60	Hexazinone (ISO)	0
0336	ex 2933 99 30 10	Azepane, for the manufacture of goods of subheading 3808 30 (a)	0
0337	ex 2933 99 90 10	2-(2 <i>H</i> -Benzotriazol-2-yl)-4,6-di- <i>tert</i> -butylphenol	0
0338	ex 2933 99 90 15	2-(2 <i>H</i> -Benzotriazol-2-yl)-4,6-di- <i>tert</i> -pentylphenol	0
0339	ex 2933 99 90 20	2-(2 <i>H</i> -Benzotriazol-2-yl)-4,6-bis(1-methyl-1-phenylethyl)phenol	0
0340	ex 2933 99 90 25	6,6'-Di-2 <i>H</i> -benzotriazol-2-yl-4,4'-bis(1,1,3,3-tetramethylbutyl)-2,2'-methylenediphenol	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0341	ex 2933 99 90 30	Quizalofop-P-ethyl (ISO)	0
0342	ex 2933 99 90 35	Indoline	0
0343	ex 2933 99 90 45	Maleic hydrazide (ISO)	0
0344	ex 2933 99 90 50	Metconazole (ISO)	3.2
0345	ex 2933 99 90 55	5-Nitroindole	0
0346	ex 2933 99 90 60	1,3-Bis(3-isocyanatomethylphenyl)-1,3-diazetidione-2,4-dione (dimeric 2,4-toluene diisocyanate)	0
0347	ex 2933 99 90 65	Candesartan cilexetil (INNM)	0
0348	ex 2933 99 90 70	6,7-Dihydro-5H-cyclopenta[b]pyridine	0
0349	ex 2934 10 00 10	Hexythiazox (ISO)	0
0350	ex 2934 10 00 20	2-(4-Methylthiazol-5-yl)ethanol	0
0351	ex 2934 20 80 10	4-Chloro-1,3-benzothiazol-2(3H)-one	0
0352	ex 2934 99 90 10	7-Chloro-5-methyl-2H-1,4-benzothiazin-3-(4H)-one	0
0353	ex 2934 99 90 15	Carboxin (ISO)	0
0354	ex 2934 99 90 20	4-[4-(Tridecyl[branched]oxy)phenyl]-1,4-thiazinane 1,1-dioxide	0
0355	ex 2934 99 90 25	Oxycarboxin (ISO)	0
0356	ex 2934 99 90 30	Etridiazole (ISO)	0
0357	ex 2934 99 90 35	Dimethenamide (ISO)	0
0358	ex 2934 99 90 40	2,3,5,6-Tetrahydroxy-1,4-diisobutyl-1,4-dioxo-1,4-diphosphinane	0
0359	ex 2934 99 90 45	Tris(2,3-epoxypropyl)-1,3,5-triazinetrione	0
0360	ex 2934 99 90 50	1-[2-(1,3-Dioxan-2-yl)ethyl]-2-ethylpyridinium bromide	0
0361	ex 2934 99 90 55	Olmesartan medoxomil (INN)	0
0362	ex 2935 00 90 10	Salts of sulfathiazole (INN)	0
0363	ex 2935 00 90 20	Toluenesulfonamides	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0364	ex 2935 00 90 30	Mixture of isomers consisting of <i>N</i> -ethyltoluene-2-sulfonamide and <i>N</i> -ethyltoluene-4-sulfonamide	0
0365	ex 2935 00 90 40	1-(4,6-Dimethoxy-2-pyrimidin-2-yl)-3-(2-ethylsulfonylimidazo[1,2-a]pyridin-3-ylsulfonyl)urea (sulfosulfuron)	0
0366	ex 2935 00 90 50	4,4'-Oxydi(benzenesulfonylhydrazide)	0
0367	ex 2935 00 90 60	5-Amino- <i>N</i> -(2,6-dichloro- <i>m</i> -tolyl)-1 <i>H</i> -1,2,4-triazole-3-sulfonamide	0
0368	ex 2935 00 90 70	Methyl 3-aminosulfonylthiophene-2-carboxylate	0
0369	3201 20 00	Wattle extract	0
0370	ex 3201 90 90 10	Tanning extracts of eucalyptus	3.2
0371	ex 3201 90 90 20	Tanning extracts derived from gambier and myrobalan fruits	0
0372	ex 3204 15 00 10	Dye C.I. Vat Orange 7	0
0373	ex 3204 15 00 20	Dye C.I. Vat Red 15	0
0374	ex 3204 15 00 30	Dye C.I. Vat Red 14	0
0375	ex 3204 15 00 40	Dye C.I. Vat Brown 57	0
0376	ex 3204 17 00 10	Dye C.I. Pigment Yellow 81	0
0377	ex 3204 19 00 10	Nickel bis{4-methoxy-2-[6-(pentafluoroethylthio)benzothiazol-2-ylazo]-(dipropylamino)benzenesulfonate}	0
0378	ex 3204 19 00 20	13-Ethyl-3-[4-(morpholino)phenyl]-3-phenyl-3,13-dihydrobenzo[<i>h</i>]indeno[2,1- <i>f</i>]chromen-13-ol	0
0379	ex 3204 19 00 30	13-Isopropyl-3,3-bis(4-methoxyphenyl)-6,11-dimethyl-3,13-dihydrobenzo[<i>h</i>]indeno[2,1- <i>f</i>]chromen-13-ol	0
0380	ex 3204 19 00 40	Methyl 8'-acetoxy-1,3,3,5,6-pentamethyl-2,3-dihydrospiro[1 <i>H</i> -indole-2,3'-naphtho[2,1- <i>b</i>][1,4]oxazine]-9'-carboxylate	0
0381	ex 3204 19 00 50	Methyl 6-(isobutyryloxy)-2,2-diphenyl-2 <i>H</i> -benzo[<i>h</i>]chromene-5-carboxylate	0
0382	ex 3204 19 00 60	Ethoxycarbonylmethyl 8-methyl-2,2-diphenyl-2 <i>H</i> -benzo[<i>h</i>]chromene-5-carboxylate	0
0383	ex 3204 19 00 70	Dye C.I. Solvent Red 49	0
0385	ex 3206 42 00 10	Lithopone	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0386	ex 3206 49 90 10	Black preparation of iron-oxide pigments, in liquid form, with a maximum particle size not exceeding 20 nanometres and containing by weight 25 % or more of iron evaluated as Fe ₂ O ₃ , for the manufacture of goods of heading No 3304 or 9608 (a)	0
0387	ex 3208 20 10 10	Copolymer of <i>N</i> -vinylcaprolactam, <i>N</i> -vinyl-2-pyrrolidone and dimethylaminoethyl methacrylate, in the form of a solution in ethanol containing by weight 34 % or more but not more than 40 % of copolymer	0
0388	ex 3208 20 10 20 ex 3905 91 00 92	Copolymer of vinylpyrrolidone and dimethylaminoethyl methacrylate, partially quaternized by diethyl sulfate, in the form of a solution in ethanol	0
0389	ex 3208 20 10 30	Solution of diundecyl phthalate and a copolymer of dibutyl maleate and isobutyl methacrylate in a hydrocarbon solvent	0
0392	ex 3208 90 19 10 ex 3911 90 99 35	Copolymer of maleic acid and methyl vinyl ether, monoesterified with ethyl and/or isopropyl and/or butyl groups, in the form of a solution in ethanol, ethanol and butanol, isopropanol or isopropanol and butanol	0
0393	ex 3208 90 19 20	Copolymer of polyurethane and silicone, in the form of a solution in a mixture of butanone, toluene and cyclohexanone, containing by weight 13 % or more but not more than 16 % of copolymer	0
0394	ex 3208 90 19 30	Solution containing: ~ (30 ± 5) % by weight of polyamide resin, ~ (6,5 ± 3,5) % by weight of diazonaphthoquinone, ~ (55 ± 5) % by weight of 1-methyl-2-pyrrolidone, ~ 1 000 µg/kg or less of chloride, ~ 1 000 µg/kg or less of potassium and ~ 1 000 µg/kg or less of iron	0
0390	ex 3208 90 19 40	Polymer of methylsiloxane, in the form of a solution in a mixture of acetone, butanol, ethanol and isopropanol, containing by weight 5 % or more but not more than 11 % of polymer of methylsiloxane	0
0395	ex 3208 90 99 10	Solution based on chemically modified natural polymers, containing two or more of the following dyes: ~ methyl 8'-acetoxy-1,3,3,5,6-pentamethyl-2,3-dihydrospiro[1 <i>H</i> -indole= -2,3'-naphtho[2,1- <i>b</i>][1,4]oxazine]-9'-carboxylate, ~ methyl 6-(isobutyryloxy)-2,2-diphenyl-2 <i>H</i> -benzo[<i>h</i>]chromene= -5-carboxylate, ~ 13-isopropyl-3,3-bis(4-methoxyphenyl)-6,11-dimethyl-3,13-dihydrobenzo= [i>h]indeno[2,1- <i>f</i>]chromen-13-ol, ~ ethoxycarbonylmethyl 8-methyl-2,2-diphenyl-2 <i>H</i> -benzo[<i>h</i>]chromene-5-carboxylate, ~ 13-ethyl-3-[4-(morpholino)phenyl]-3-phenyl-3,13-dihydrobenzo= [i>h]indeno[2,1- <i>f</i>]chromen-13-ol	0
0396	ex 3215 90 80 10	Ink formulation, for use in the manufacture of ink-jet cartridges (a)	0
0397	ex 3215 90 80 20	Heat sensitive ink fixed on a plastic film	0
0398	3301 12 10	Essential oil of orange, not deterpenated	0
0399	ex 3402 90 10 20	Mixture of docusate sodium (INN) and sodium benzoate	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0400	ex 3402 90 10 30	Non-aqueous surface-active preparation, containing: ~ polyethylene glycol alkylphenyl ether, ~ 2,4,7,9-tetramethyldec-5-yne-4,7-diol and ~ phosphoric acid esters	0
0401	ex 3402 90 90 10	Crystalline powder obtained by the reaction of trisodium phosphate with a mixture of sodium hypochlorite and sodium chloride ("chlorinated trisodium phosphate"), containing by weight: ~ 3,5 % or more of available chlorine, measured iodometrically and ~ 17,0 % or more of phosphorus evaluated as P ₂ O ₅	0
0402	ex 3403 99 90 10	Cutting-fluid preparation based on an aqueous solution of synthetic polypeptides	0
0403	ex 3504 00 00 10	Purified antigens obtained from genetically manipulated yeast cells, for the manufacture of detection tests for hepatitis-C (a)	0
0404	ex 3504 00 00 20	Glycoprotein 160 obtained from Human Immunodeficiency Virus, HIV-1 strain	0
0405	ex 3505 10 50 20	<i>O</i> -(2-Hydroxyethyl)-derivative of hydrolysed maize starch	0
0406	ex 3506 91 00 10	Adhesive based on an aqueous dispersion of a mixture of dimerised rosin and a copolymer of ethylene and vinyl acetate (EVA)	0
0407	ex 3506 91 00 20	Heat-activated adhesive based on phenolic resin and rubber, in the form of a film on a release paper, for use in the manufacture of brake pads for the automotive industry (a)	0
0408	ex 3507 90 90 10	Asparaginase	0
0409	ex 3507 90 90 20	Enzymatic preparation based on thermolysine	0
0410	ex 3507 90 90 40	Avian myeloblastosis virus (AMV) reverse transcriptase	0
0411	ex 3507 90 90 50	Lipase	0
0412	ex 3701 30 00 10	Relief printing plate, of a kind used for printing on newsprint, consisting of a metal substrate coated with a photopolymer layer of a thickness of 0,2 mm or more but not exceeding 0,8 mm, not covered with a release film, of a total thickness not exceeding 1 mm	0
0413	ex 3701 99 00 10	Plate of quartz or of glass, covered with a film of chromium and coated with a photosensitive or electron-sensitive resin, for the manufacture of masks for the goods of heading No 8541 or 8542 (a)	0
0414	ex 3702 31 99 10	Colour negative film, for the manufacture of instant-picture film-packs (a)	0
0415	ex 3702 43 00 10 ex 3702 44 00 10	Photographic film, of a nominal width of 459, 669 or 761 mm, composed of several layers, including two polyester films, a carbon layer, an adhesive layer and a layer of a copolymer of styrene with acrylonitrile	0
0416	ex 3703 90 10 10	Paper sheet, coated with silver halide emulsion, for the manufacture of goods of subheading 3701 20 00 (a)	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0417	ex 3707 10 00 10	Photosensitive emulsion for the sensitization of silicon discs (a)	0
0418	ex 3707 90 30 10	Toner, in the form of powder, consisting of a copolymer of styrene and butyl acrylate and magnetite, for use as a developer in the manufacture of cartridges for facsimile machines (a)	0
0419	3805 20 00	Pine oil	1.7
0420	ex 3808 10 90 10	Indoxacarb (ISO) and its (R) isomer, fixed on a support of silicon dioxide	0
0421	ex 3808 20 80 10	Fungicide in the form of a powder, containing by weight 65 % or more but not more than 75 % of hymexazole (ISO), not put up for retail sale	0
0422	ex 3808 20 80 20	Preparation based on diiodomethyl <i>p</i> -tolyl sulfone, not put up for retail sale	0
0423	ex 3808 40 20 10	Preparation containing by weight: ~ 58 % or more but not more than 62 % of 1-bromo-3-chloro-5,5-dimethylhydantoin, ~ 26 % or more but not more than 29 % of 1,3-dichloro-5,5-dimethylhydantoin, ~ 10 % or more but not more than 12 % of 1,3-dichloro-5-ethyl-5-methylhydantoin, for the manufacture of swimming-pool disinfectants (a)	0
0424	ex 3808 40 90 10	1-Dodecylguanidine hydrochloride, in the form of a solution in isopropanol and water, containing by weight 40 % or less of 1-dodecylguanidine hydrochloride	0
0425	ex 3809 91 00 10	Mixture of 5-ethyl-2-methyl-2-oxo-1,3,2λ ⁵ -dioxaphosporan-5-ylmethyl methylmethylphosphonate and bis(5-ethyl-2-methyl-2-oxo-1,3,2λ ⁵ -dioxaphosporan-5-ylmethyl)methylphosphonate	0
0426	ex 3809 92 00 10	Paper anti-fading agent, consisting of a mixture of magnesium trisilicate and monosodium salt of 2,2'-methylenebis(4,6-di- <i>tert</i> -butylphenyl) phosphate	0
0427	ex 3811 21 00 10	Salts of dinonylnaphthalenesulfonic acid, in the form of a solution in mineral oils	0
0428	ex 3811 21 00 20	Additives for lubricating oils, based on complex organic molybdenum compounds, in the form of a solution in mineral oil	0
0431	ex 3812 30 80 10	Tetraaluminium nonamagnesium dicarbonate hexacosahydroxide heptahydrate, coated with a surface-active agent	0
0432	ex 3812 30 80 20	Mixture containing predominantly bis(2,2,6,6-tetramethyl-1-octyloxy-4-piperidyl) sebacate	0
0433	ex 3812 30 80 30	Compound stabilisers containing by weight 15 % or more but not more than 40 % of sodium perchlorate and not more than 70 % of 2-(2-methoxyethoxy)ethanol	0
0434	ex 3812 30 80 40	Dialuminium tetramagnesium monocarbonate dodecahydroxide monohydrate, coated with a surface-active agent	0
0435	ex 3812 30 80 50	Aluminium magnesium zinc hydroxide carbonate hydrate, coated with a surface-active agent	0
0436	ex 3814 00 90 10	Mixture containing by weight 25 % or more but not more than 35 % of dimethyl sulfoxide and 65 % or more but not more than 75 % of monoethanolamine	3

	CN code & TARIC	Description	Rate of autonomous duty (%)
0437	ex 3815 12 00 10	Catalyst, in the form of granules or rings of a diameter of 3 mm or more but not exceeding 10 mm, consisting of silver on an aluminium oxide support and containing by weight 8 % or more but not more than 20 % of silver	0
0438	ex 3815 12 00 20	Catalyst consisting of palladium and rhenium, fixed on a support of active carbon, in the form of powder, containing: ~ 0,5 % or more but not more than 1,5 % by weight of palladium, ~ 3 % or more but not more than 5 % by weight of rhenium and ~ 0,1 mole % or more but not more than 1 mole % of alkaline metals, for use in the manufacture of tetrahydrofuran (a)	0
0439	ex 3815 19 90 10	Catalyst, consisting of chromium trioxide or dichromium trioxide fixed on a support of silicon dioxide, of a pore volume, as determined by the nitrogen absorption method, of 2 cm ³ /g or more	0
0440	ex 3815 19 90 15	Catalyst, in the form of a powder, consisting of a mixture of metal oxides fixed on a support of silicon dioxide, containing by weight 20 % or more but not more than 40 % of molybdenum, bismuth and iron evaluated together, for use in the manufacture of acrylonitrile (a)	0
0441	ex 3815 19 90 20	Catalyst consisting of chromium oxides and titanium dioxide fixed on a support of silicon dioxide, aluminium oxide or aluminium phosphate	0
0442	ex 3815 19 90 30	Catalyst containing titanium tetrachloride supported on magnesium dichloride, for use in the manufacture of polypropylene (a)	0
0443	ex 3815 19 90 40	Catalyst, in the form of spheres of a diameter of 4,2 mm or more but not exceeding 9 mm, consisting of a mixture of metals oxides containing predominantly oxides of molybdenum, vanadium and copper, on a support of silicon dioxide and/or aluminium oxide, for use in the manufacture of acrylic acid (a)	0
0444	ex 3815 19 90 45	Catalyst, consisting predominantly of dichromium copper tetraoxide and copper (II) oxide, containing by weight 38 % or more but not more than 48 % of copper, evaluated as copper (II) oxide, fixed on a support of silicon dioxide, for the hydrogenation of acetophenones (a)	0
0445	ex 3815 19 90 50	Catalyst consisting of organo-metallic compounds of titanium, magnesium and aluminium on a support of silicon dioxide, in the form of a suspension in tetrahydrofuran	0
0446	ex 3815 19 90 55	Catalyst consisting of a mixture of metal oxides containing chromium trioxide, fixed on a support of silicon dioxide	0
0447	ex 3815 19 90 60	Catalyst consisting of dichromium trioxide, fixed on a support of aluminium oxide	0
0448	ex 3815 19 90 65	Catalyst consisting of phosphoric acid chemically bonded to a support of silicon dioxide	0
0449	ex 3815 19 90 70	Catalyst consisting of organo-metallic compounds of aluminium and zirconium, fixed on a support of silicon dioxide	0
0450	ex 3815 19 90 75	Catalyst consisting of organo-metallic compounds of aluminium and chromium, fixed on a support of silicon dioxide	0
0451	ex 3815 19 90 80	Catalyst consisting of organo-metallic compounds of magnesium and titanium, fixed on a support of silicon dioxide, in the form of a suspension in mineral oil	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0452	ex 3815 19 90 85	Catalyst consisting of organo-metallic compounds of aluminium, magnesium and titanium, fixed on a support of silicon dioxide, in the form of powder	0
0453	ex 3815 90 90 15	Catalyst, consisting of a mixture of oxides containing by weight more than 96 % of oxides of molybdenum, vanadium, nickel and antimony, whether or not mixed with porcelain balls, for use in the manufacture of acrylic acid (a)	0
0454	ex 3815 90 90 20	Catalyst, in powder form, consisting of a mixture of titanium trichloride and aluminium chloride, containing by weight: ~ 20 % or more but not more than 30 % of titanium and ~ 55 % or more but not more than 72 % of chlorine	0
0455	ex 3815 90 90 25	Catalyst, consisting of a mixture of oxides containing by weight more than 96 % of oxides of molybdenum, bismuth, nickel, iron and silicon, whether or not mixed with porcelain balls, for use in the manufacture of acrylaldehyde (a)	0
0456	ex 3815 90 90 30	Catalyst, in the form of a powder, containing by weight 82 % or more of copper and of a specific surface of 0,5 m ² /g or more but not exceeding 8 m ² /g	0
0457	ex 3815 90 90 35	Catalyst, in the form of a suspension in oil, consisting of titanium trichloride and aluminium trichloride, containing by weight (on an oil-free basis): ~ 15 % or more but not more than 30 % of titanium and ~ 40 % or more but not more than 72 % of chlorine	0
0458	ex 3815 90 90 40	Catalyst, in the form of rodlets of a length of 5 mm or more but not exceeding 8 mm, consisting of a mixture of metals oxides containing predominantly oxides of iron, molybdenum and bismuth, whether or not containing silicon dioxide as filler, for use in the manufacture of acrylic acid (a)	0
0459	ex 3815 90 90 50	Catalyst containing titanium trichloride, in the form of a suspension in hexane or heptane containing by weight, in the hexane- or heptane-free material, 9 % or more but not more than 30 % of titanium	0
0460	ex 3815 90 90 55	Reaction initiator, consisting of a mixture of <i>N,N,N',N'</i> -tetramethyl-2,2'-oxybis(ethylamine) and dipropylene glycols	0
0461	ex 3815 90 90 60	Catalyst, in the form of rodlets, consisting of an acid aluminosilicate (zeolite): ~ with a mole-ratio of silicon dioxide : dialuminium trioxide of not less than 500 : 1 and ~ containing by weight 0,2 % or more but not more than 0,8 % of platinum	0
0462	ex 3815 90 90 65	Catalyst based on a mordenite zeolite, in the form of granules, for use in the manufacture of mixtures of methylamines containing by weight 50 % or more of dimethylamine (a)	0
0463	ex 3815 90 90 70	Catalyst, consisting of a mixture of (2-hydroxypropyl)trimethylammonium formate and dipropylene glycols	0
0464	ex 3815 90 90 75	Catalyst, consisting of a mixture of 1,4-diazabicyclo[2.2.2]octane, 2-hydroxyethyliminodi(acetic acid) and dibutyltin di(acetate), containing by weight 5 % or more but not more than 10 % of 1,4-diazabicyclo[2.2.2]octane	0
0465	ex 3815 90 90 80	Catalyst consisting predominantly of dinonylnaphthalenedisulfonic acid in the form of a solution in isobutanol	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0466	ex 3815 90 90 81	Catalyst, containing by weight 38 % or more but not more than 48 % of (2-hydroxy-1-methylethyl)trimethylammonium 2-ethylhexanoate	0
0467	ex 3815 90 90 82	Catalyst, containing by weight 35 % or more but not more than 55 % of (2-hydroxy-1-methylethyl)trimethylammonium formate and formic acid	0
0468	ex 3815 90 90 83	Catalyst, in the form of powder, containing aluminium magnesium hydroxide hydrate, rare-earth metals oxides and divanadium pentaoxide	0
0469	ex 3815 90 90 85	Catalyst based on aluminosilicate (zeolite), for the transalkylation of alkylaromatic hydrocarbons or the oligomerization of olefins (a)	0
0470	ex 3823 19 10 91	Mixture of fatty acids containing by weight: ~ 2 % or more but not more than 6 % of hexanoic acid, ~ 53 % or more but not more than 60 % of octanoic acid, ~ 34 % or more but not more than 42 % of decanoic acid and ~ not more than 2 % of dodecanoic acid	0
0471	ex 3824 90 15 10	Acid aluminosilicate (artificial zeolite of the Y type) in the sodium form, containing by weight not more than 11 % of sodium evaluated as sodium oxide, in the form of rodlets	0
0472	ex 3824 90 64 01	Intermediate products of the antibiotics manufacturing process obtained from the fermentation of <i>Micromonospora purpurea</i> , whether or not dried	0
0473	ex 3824 90 64 02	Cholic acid and 3 α ,12 α -dihydroxy-5 β -cholan-24-oic acid (deoxycholic acid), crude	0
0474	ex 3824 90 64 03	Products obtained by the N-ethylation of sisomycin (INN)	0
0475	ex 3824 90 64 04	Intermediate products of the antibiotics manufacturing process obtained from the fermentation of <i>Micromonospora inyoensis</i> , whether or not dried	0
0476	ex 3824 90 64 05	Residues of manufacture containing by weight 40 % or more of 11 β ,17,20,21-tetrahydroxy-6-methylpregna-1,4-dien-3-one 21-acetate	0
0479	ex 3824 90 99 01	Colloidal diantimony pentaoxide	0
0480	ex 3824 90 99 02	Mixture of nitromethane and 1,2-epoxybutane	0
0481	ex 3824 90 99 03	Grains or granules, consisting of a mixture of dialuminium trioxide and zirconium dioxide, containing by weight: ~ 70 % or more but not more than 78 % of dialuminium trioxide and ~ 19 % or more but not more than 26 % of zirconium dioxide	5.2
0482	ex 3824 90 99 04	Crude lithium hypochlorite	0
0391	ex 3824 90 99 05	Polysilicate, modified with phosphoric acid, in the form of a solution in a mixture of ethanol, isopropanol and tetrahydrofuran, containing by weight 3 % or more but not more than 6 % of polysilicate	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0483	ex 3824 90 99 06	Preparation in the form: ~ of powder, containing by weight 75 % or more of zinc bis[3,5-bis(1-phenylethyl)salicylate] or ~ of aqueous dispersion, containing by weight 22 % or more but not more than 55 % of zinc bis[3,5-bis(1-phenylethyl)salicylate]	0
0484	ex 3824 90 99 07	Film consisting of the oxides of either barium or calcium and either titanium or zirconium, mixed with binding materials	0
0485	ex 3824 90 99 08	Preparation consisting essentially of alkaline asphalt sulfonate, of: ~ a specific gravity of 0,9 or more but not exceeding 1,5 and ~ a solubility in water of 70 % by weight or more	0
0486	ex 3824 90 99 09	Anti-corrosion preparations consisting of salts of dinonylnaphthalenesulfonic acid, either: ~ on a support of mineral wax, whether or not modified chemically, or ~ in the form of a solution in an organic solvent	0
0487	ex 3824 90 99 10	Calcined bauxite (refractory grade)	0
0488	ex 3824 90 99 11	Magnetisable iron oxide, in the form of powder, containing by weight: ~ 30 % or more but not more than 38 % of bivalent iron in relation to the total iron and ~ 1 % or more but not more than 4 % of cobalt	0
0489	ex 3824 90 99 12	Spent catalyst, in the form of rodlets of diameter of 1 mm or more but not exceeding 3 mm, containing a mixture of sulfides of tungsten and of nickel on a support of zeolite, containing by weight not more than 10 % of tungsten and not more than 10 % of nickel, for regeneration as a catalyst for hydrocarbon cracking (a)	0
0490	ex 3824 90 99 13	Mixture containing by weight: ~ 7 % or more but not more than 9 % of 2-methyl-1,3-phenylene diisocyanate, ~ 31 % or more but not more than 34 % of 4-methyl-1,3-phenylene diisocyanate, ~ 10 % or more but not more than 13 % of 2,4'-methylenediphenyl diisocyanate, ~ 46 % or more but not more than 49 % of 4,4'-methylenediphenyl diisocyanate	0
0491	ex 3824 90 99 14	Mixture of magnesium bromide 2-oxoperhydroazepin-1-ide and ϵ -caprolactam	0
0492	ex 3824 90 99 15	Mixture of disodium <i>N</i> -benzyloxycarbonyl-L-aspartate and sodium chloride, in the form of a solution in water	0
0493	ex 3824 90 99 16	Disodium 9,10-dihydro-9,10-dioxanthracene-2,7-disulfonate, containing by weight 10 % or more but not more than 20 % of sodium sulfate	0
0494	ex 3824 90 99 17	Eutectic alloy wholly of potassium and sodium, containing by weight 77 % or more but not more than 79 % of potassium	0
0495	ex 3824 90 99 18	Blend of terephthaloyl dichloride and isophthaloyl dichloride	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0496	ex 3824 90 99 20	Preparation consisting by weight of 83 % or more of 3a,4,7,7a-tetrahydro-4,7-methanoindene (dicyclopentadiene), a synthetic rubber, whether or not containing by weight 7 % or more of tricyclopentadiene, and: ~ either an aluminium-alkyl compound, ~ or an organic complex of tungsten ~ or an organic complex of molybdenum	0
0497	ex 3824 90 99 21	Mixture of tris[2-chloro-1-(chloromethyl)ethyl] phosphate and oligomers of methylphosphonic acid and phosphoric acid with ethane-1,2-diol	0
0498	ex 3824 90 99 22	Mixture of tris[2-chloro-1-(chloromethyl)ethyl] phosphate and oligomers of 2-chloroethyl phosphate with ethane-1,2-diol	0
0499	ex 3824 90 99 23	Mixture of sucrose esters, derived from the esterification of sucrose with industrial stearic acid	0
0500	ex 3824 90 99 24	Preparations consisting predominantly of phosphabicyclononanes and <i>P</i> -alkyl derivatives thereof, in the form of a solution in 4- <i>tert</i> -butyltoluene	0
0501	ex 3824 90 99 25	Lithium tantalate wafers, undoped	0
0502	ex 3824 90 99 28	Preparation consisting predominantly of ethylene glycol and <i>N,N</i> -dimethylformamide or ethylene glycol and γ -butyrolactone, for the manufacture of electrolytic capacitors (a)	0
0503	ex 3824 90 99 29	Preparation consisting predominantly of γ -butyrolactone and quaternary ammonium salts, for the manufacture of electrolytic capacitors (a)	0
0504	ex 3824 90 99 30	2,4,7,9-Tetramethyldec-5-yne-4,7-diol, hydroxyethylated	0
0505	ex 3824 90 99 31	Copper zinc ferrite, coated with a silicone resin, in the form of granules of a size not exceeding 120 μ m	0
0506	ex 3824 90 99 32	Styrene oligomer	0
0507	ex 3824 90 99 33	Preparation consisting of α -(4-allyloxycarbonylbenzoyl)- ω -allyloxypoly= [oxy(2-methylethylene)oxyterephthaloyl] and either diallyl-2,2'-oxydiethyl dicarbonate or diallyl isophthalate	0
0508	ex 3824 90 99 35	Nitrosylsulfuric acid of a purity by weight of 70 % or more but not exceeding 73 %	0
0477	ex 3824 90 99 36	Mixtures of silanol and diphosphorus pentaoxide, in the form of a solution in a mixture of ethanol and ethyl acetate, containing by weight 6 % or more but not more than 10 % of silanol and 0,1 % or more but not more than 0,3 % of diphosphorus pentaoxide	0
0478	ex 3824 90 99 37	Sintered bauxite pellets, of a diameter not exceeding 2 mm	0
0509	ex 3824 90 99 39	Mixture containing by weight 40 % or more but not more than 50 % of 2-hydroxyethyl methacrylate and 40 % or more but not more than 50 % of glycerol ester of boric acid	0
0510	ex 3824 90 99 40	Azelaic acid of a purity by weight of 75 % or more but not exceeding 85 %	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0511	ex 3824 90 99 42	Mixed metals oxides, in the form of powder, containing by weight: ~ either 5 % or more of barium, neodymium or magnesium and 15 % or more of titanium, ~ or 30 % or more of lead and 5 % or more of niobium, for use in the manufacture of dielectric films or for use as dielectric materials in the manufacture of multilayer ceramic capacitors (a)	0
0512	ex 3824 90 99 43	7-Aminonaphthalene-1,3,6-trisulfonic acid and its salts, of a purity by weight of 65 % or more	0
0513	ex 3824 90 99 44	Mixture containing by weight: ~ 60 % or more of 2-[<i>N</i> -(2-cyanoethyl)anilino]ethyl acetate and ~ 20 % or more of acetic acid	0
0514	ex 3824 90 99 45	Preparations consisting predominantly of ethylene glycol and: ~ either diethylene glycol, dodecandioic acid and ammonia water, ~ or silicon oxide, ~ or ammonium hydrogen azelate, ~ or ammonium hydrogen azelate and silicon oxide, ~ or dodecandioic acid, ammonia water and silicon oxide, for the manufacture of electrolytic capacitors (a)	0
0515	ex 3824 90 99 46	Carboxylic acid anhydride based hardener for epoxyde resin, in liquid form, of a specific weight at 25 °C of 1,15 g/cm ³ or more but not exceeding 1,18 g/cm ³	0
0516	ex 3824 90 99 49	Mixed oxides of metals, in the form of powder, containing by weight: ~ 70 % or more but not more than 75 % of iron oxide, ~ 10 % or more but not more than 20 % of zinc oxide, ~ 10 % or more but not more than 15 % of magnesium oxide, ~ 1 % or more but not more than 5 % of manganese oxide and ~ 1 % or more but not more than 3 % of copper oxide	0
0517	ex 3824 90 99 50	Zeolites consisting of oxides of barium, aluminium and silicon, containing by weight 30 % or more but not more than 40 % of barium oxide, in the form of spheres of which 80 % or more by weight have a diameter of 0,3 mm or more but not more than 1,2 mm	0
0518	ex 3824 90 99 53	Sodium 4-hydroxynaphthalene-1-sulfonate, of a purity by weight of 70 % or more but not exceeding 80 %	0
0519	ex 3824 90 99 54	2-Hydroxybenzotrile, in the form of a solution in <i>N,N</i> -dimethylformamide, containing by weight 45 % or more but not more than 50 % of 2-hydroxybenzotrile	0
0520	ex 3824 90 99 55	Mixture containing by weight 75 % or more of pentaerythritol triallyl ether	0
0521	ex 3824 90 99 57	Mixture of trialkylphosphine oxides	0
0522	ex 3824 90 99 58	Platinum oxide fixed on a porous support of aluminium oxide, containing by weight 0,1 % or more but not more than 1 % of platinum and 0,5 % or more but not more than 5 % of ethylaluminium dichloride	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0523	ex 3824 90 99 60	α -Phenoxy carbonyl- ω -phenoxy poly[oxy(2,6-dibromo-1,4-phenylene)= isopropylidene(3,5-dibromo-1,4-phenylene)oxycarbonyl]	0
0524	ex 3824 90 99 61	Mixture of metal oxides, in the form of powder, containing by weight: ~ 20 % or more of barium, ~ 10 % or more of titanium and ~ 4 % or more of lead or 3 % or more of niobium or 0,7 % or more of zirconium, for use as dielectric material in the manufacture of multilayer ceramic capacitors (a)	0
0525	ex 3824 90 99 63	Triethylborane, in the form of a solution in tetrahydrofuran	0
0526	ex 3824 90 99 64	Aluminium sodium silicate, in the form of spheres of a diameter of: ~ either 1,6 mm or more but not exceeding 3,4 mm, ~ or 4 mm or more but not exceeding 6 mm	0
0527	ex 3824 90 99 65	Mixture of tris(alkoxycarbonylamino)-1,3,5-triazines in which alkoxy groups are methoxy and butoxy	0
0528	ex 3824 90 99 66	Mixture of primary <i>tert</i> -alkylamines	0
0529	ex 3824 90 99 67	Preparation consisting of indium tin oxide dispersed in organic solvents	0
0530	ex 3824 90 99 72	Solution containing by weight 80 % or more of 2,4,6-trimethylbenzaldehyde in acetone	0
0531	ex 3824 90 99 73	Particles of silicon dioxide on which are covalently bonded organic compounds, for use in the manufacture of high performance liquid chromatography columns (HPLC) and sample preparation cartridges (a)	0
0532	ex 3824 90 99 75	Mixture of 2,2-bis[2-(perfluoroalkyl)ethylthiomethyl]propane-1,3-diols	0
0533	ex 3824 90 99 77	Diethylmethoxyborane, in the form of a solution in tetrahydrofuran	0
0534	ex 3901 10 10 10	Linear polyethylene, of a specific gravity of 0,928 or more but not exceeding 0,935 and of a melt flow index of less than 0,6 g/min, for the manufacture of shrinkmelt binder fibres (a)	0
0535	ex 3901 10 90 10	Polyethylene for the manufacture of photo-resist film for semiconductors or printed circuits (a)	0
0536	ex 3901 10 90 20	Polyethylene, in the form of granules, of a specific gravity of 0,925 (\pm 0,0015), a melt flow index of 0,3 g/10 min (\pm 0,05 g/10 min), for the manufacture of blown films of a Haze value not exceeding 6 % and an elongation at break (MD/TD) of 210/340 (a)	0
0537	ex 3901 20 90 10	Polyethylene, in one of the forms mentioned in note 6 (b) to Chapter 39, of a specific gravity of 0,945 or more but not exceeding 0,985, for the manufacture of films for typewriter ribbon or similar ribbon (a)	0
0538	ex 3901 20 90 20	Polyethylene, containing by weight 35 % or more but not more than 45 % of mica	0
0541	ex 3901 90 90 81	Copolymer of ethylene and propylene, modified with maleic anhydride, containing by weight more than 55 % of ethylene and not more than 3 % of maleic anhydride	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0542	ex 3901 90 90 82	Polyethylene modified with maleic anhydride, containing by weight not more than 4 % of maleic anhydride, for use in the manufacture of fuel tanks for motor vehicles (a)	0
0543	ex 3901 90 90 91	Ionomer resin consisting of a salt of a copolymer of ethylene with methacrylic acid	4
0544	ex 3901 90 90 93	Copolymer of ethylene, vinyl acetate and carbon monoxide, for use as a plasticizer in the manufacture of roof sheets (a)	0
0545	ex 3901 90 90 94	Mixtures of A-B block copolymer of polystyrene and ethylene-butylene copolymer and A-B-A block copolymer of polystyrene, ethylene-butylene copolymer and polystyrene, containing by weight not more than 35 % of styrene	0
0546	ex 3901 90 90 95 ex 3902 90 90 95	Copolymer of ethylene and butylene, having hydroxyl or acrylate end-groups, containing by weight 40 % or more but not more than 60 % of butylene	0
0547	ex 3901 90 90 96 ex 3902 90 90 96 ex 3903 90 90 50	Linear A-B block copolymer of polyisoprene, whether or not epoxidized, and either ethylene-butylene copolymer or styrene-ethylene-butylene copolymer, having hydroxyl end-groups	0
0548	ex 3901 90 90 97	Copolymer of ethylene and octene, containing by weight 5 % or more but not more than 15 % of octene, of a specific gravity of less than 0,93 and a melt index of 0,80 or more but not exceeding 0,95	0
0549	ex 3902 10 00 10	Polypropylene containing no plasticizer and not more than: ~ 7 mg/kg of aluminium, ~ 2 mg/kg of iron, ~ 1 mg/kg of magnesium, ~ 8 mg/kg of chloride	0
0550	ex 3902 10 00 20	Polypropylene, containing no plasticiser, ~ of a melting point of more than 150 °C (as determined by the ASTM D 3417 method), ~ of a heat of fusion of 15 J/g or more but not exceeding 70 J/g, ~ of an elongation at break of 1 000 % or more (as determined by the ASTM D 638 method), ~ of a tensile modulus of 69 MPa or more but not exceeding 379 MPa (as determined by the ASTM D 638 method)	0
0551	ex 3902 10 00 30	Polypropylene, containing not more than 1 mg/kg of aluminium, 0,05 mg/kg of iron, 1 mg/kg of magnesium and 1 mg/kg of chloride, for use in the manufacture of packaging for disposable contact lenses (a)	0
0552	ex 3902 30 00 91 ex 3903 90 90 25	A-B Block copolymer of polystyrene and an ethylene-propylene copolymer, containing by weight 40 % or less of styrene, in one of the forms mentioned in note 6 (b) to Chapter 39	0
0553	ex 3902 30 00 92	Copolymer of propylene, butylene and ethylene, containing by weight more than 65 % but less than 80 % of propylene and not less than 20 % of butylene	0
0554	ex 3902 90 90 92	Polymers of 4-methylpent-1-ene	0
0555	ex 3902 90 90 97	Hydrogenated polyisobutene, in liquid form	0
0556	ex 3903 19 00 20	Polystyrene of a molecular weight (M_n) not exceeding 5 000	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0557	ex 3903 90 90 10	Copolymer, entirely of styrene with maleic anhydride, or entirely of styrene with maleic anhydride and an acrylic monomer, whether or not containing a styrene-butadiene block copolymer, in one of the forms mentioned in note 6 (b) to Chapter 39, for the manufacture of sheetings for head-liners for cars (a)	0
0558	ex 3903 90 90 15	Copolymer, entirely of styrene with maleic anhydride, or entirely of styrene with maleic anhydride and an acrylic monomer, also partially esterified, of an average molecular weight (M_n) not exceeding 3 000, in one of the forms mentioned in note 6 (a) and (b) to Chapter 39	0
0559	ex 3903 90 90 20	Copolymer of styrene with 2-ethylhexyl acrylate or with <i>n</i> -butyl acrylate, containing: ~ 10 mole % or more but not more than 16 mole % of acrylate, ~ 0,2 mg/kg or less of sodium and ~ 0,1 mg/kg or less of calcium	0
0560	ex 3903 90 90 35 ex 3911 90 99 30	Copolymer of α -methylstyrene and styrene, having a softening point exceeding 113 °C	0
0561	ex 3903 90 90 40 ex 3906 90 90 40 ex 3911 90 99 50	Copolymer of styrene with α -methylstyrene and acrylic acid, of a molecular weight (M_n) of 500 or more but not exceeding 6 000	0
0562	ex 3903 90 90 55 ex 3906 90 90 45	Copolymer of styrene, methyl methacrylate, butyl acrylate and either acrylic acid or hydroxyethyl methacrylate, of a molecular weight (M_n) of 500 or more but not exceeding 6 000	0
0563	ex 3903 90 90 65	Copolymer of styrene, butyl acrylate, butyl methacrylate, methyl methacrylate and acrylic acid, in the form of powder, containing by weight (81 ± 1) % of styrene, (6 ± 1) % of butyl acrylate, (5 ± 1) % of butyl methacrylate, (7 ± 1) % of methyl methacrylate and (1 ± 0,5) % of acrylic acid	0
0564	ex 3903 90 90 70	Ammonium polystyrenesulfonate, in the form of an aqueous solution	0
0565	ex 3904 22 00 91 ex 3926 90 99 80	Poly(vinyl chloride), dyed in the mass, in the form of flakes, grains, pebbles or rectangular chips, for use as decorative elements in floor and wall coverings (a)	0
0566	ex 3904 30 00 10	Copolymer of vinyl chloride with vinyl acetate and maleic acid, containing by weight: ~ 81,5 % or more but not more than 84,5 % of vinyl chloride, ~ 13,8 % or more but not more than 16,2 % of vinyl acetate and ~ 0,8 % or more but not more than 1,2 % of maleic acid, for the manufacture of goods of heading No 3215 or for use in the manufacture of coatings for containers and closures of a kind used for preserving food and drink (a)	0
0567	ex 3904 30 00 20	Copolymer of vinyl chloride, vinyl acetate and maleic acid, for use in the manufacture of poly(vinyl chloride)-metal heat-sealing adhesive (a)	0
0570	ex 3904 40 00 91	Copolymer of vinyl chloride with vinyl acetate and vinyl alcohol, containing by weight: ~ 87 % or more but not more than 92 % of vinyl chloride, ~ 2 % or more but not more than 9 % of vinyl acetate and ~ 1 % or more but not more than 8 % of vinyl alcohol, in one of the forms mentioned in note 6 (a) or (b) to Chapter 39, for the manufacture of goods of heading No 3215 or 8523 or for use in the manufacture of coatings for containers and closures of a kind used for preserving food and drink (a)	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0571	ex 3904 40 00 92	Copolymer of vinyl chloride, vinyl acetate, hydroxypropyl acrylate and maleic acid, containing by weight 80 % or more but not more than 83 % of vinyl chloride, 1,6 % or more but not more than 2 % of hydroxy groups and 0,25 % or more but not more than 0,38 % of carboxyl groups	0
0569	ex 3904 40 00 93	Copolymer of vinyl chloride and methyl acrylate, containing by weight (80 ± 1) % of vinyl chloride and (20 ± 1) % of methyl acrylate, in the form of a aqueous emulsion	0
0572	ex 3904 50 90 91	Copolymer of vinylidene chloride with vinyl chloride, containing by weight 79,5 % or more of vinylidene chloride, in one of the forms mentioned in note 6 (a) or (b) to Chapter 39, for the manufacture of fibres, monofilament or strip (a)	0
0573	ex 3904 61 00 10	Mixture of polytetrafluoroethylene and mica, in one of the forms mentioned in note 6 (b) to Chapter 39	0
0574	ex 3904 61 00 20	Copolymer of tetrafluoroethylene and trifluoro(heptafluoropropoxy)ethylene, containing 3,2 % or more but not more than 4,6 % by weight of trifluoro(heptafluoropropoxy)ethylene and less than 1 mg/kg of extractable fluoride ions	0
0575	ex 3904 69 90 92	Copolymer of tetrafluoroethylene and trifluoro(trifluoromethoxy)ethylene	0
0576	ex 3904 69 90 93	Copolymer of ethylene with chlorotrifluoroethylene, in one of the forms mentioned in note 6 (b) to Chapter 39	0
0577	ex 3904 69 90 94	Copolymer of ethylene and tetrafluoroethylene	0
0578	ex 3904 69 90 96	Polychlorotrifluoroethylene, in one of the forms mentioned in note 6 (a) and (b) to Chapter 39	0
0579	ex 3905 91 00 91	Copolymer of <i>N</i> -vinylcaprolactam, <i>N</i> -vinyl-2-pyrrolidone and dimethylaminoethyl methacrylate	0
0580	ex 3905 99 90 93	Poly(vinyl acetate phthalate)	0
0581	ex 3905 99 90 94	Polymer of vinylpyrrolidone and dimethylaminoethyl methacrylate, containing by weight 97 % or more but not more than 99 % of vinylpyrrolidone, in the form of a solution in water	0
0582	ex 3905 99 90 95	Hexadecylated or eicosylated polyvinylpyrrolidone	0
0583	ex 3905 99 90 96	Polymer of vinyl formal, in one of the forms mentioned in note 6 (b) to Chapter 39, of a molecular weight (M_w) of 25 000 or more but not exceeding 150 000 and containing by weight: ~ 9,5 % or more but not more than 13 % of acetyl groups evaluated as vinyl acetate and ~ 5 % or more but not more than 6,5 % of hydroxy groups evaluated as vinyl alcohol	0
0584	ex 3906 10 00 10	Poly(methyl methacrylate), in the form of expansible beads containing 2-methylpentane as blowing agent	0
0585	3906 90 60	Copolymer of methyl acrylate with ethylene and a monomer containing a non-terminal carboxy group as a substituent, containing by weight 50 % or more of methyl acrylate, whether or not mixed with silicon dioxide	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0586	ex 3906 90 90 10	Polymerization product of acrylic acid with small quantities of a polyunsaturated monomer, for the manufacture of medicaments of heading No 3003 or 3004 (a)	0
0587	ex 3906 90 90 20	Polymerization product of acrylic acid with small quantities of a polyunsaturated monomer, for use as a stabilizer in emulsions or dispersions with a pH of more than 13 (a)	6
0588	ex 3906 90 90 30	Copolymer of styrene with hydroxyethyl methacrylate and 2-ethylhexyl acrylate, of a molecular weight (M_n) of 500 or more but not exceeding 6 000	0
0589	ex 3906 90 90 50	Acrylic polymers, containing by weight 2,5 % or more of chloroethyl vinyl ether or chloromethyl acrylate, in one of the forms mentioned in note 6 (b) to Chapter 39	0
0568	ex 3906 90 90 60	Aqueous emulsion containing predominantly a copolymer of butyl acrylate and vinyl chloride, containing by weight (58 ± 1) % of butyl acrylate and (42 ± 1) % of vinyl chloride	0
0590	ex 3907 20 11 10	Poly(ethylene oxide) of an average molecular weight (M_n) of 100 000 or more	0
0591	ex 3907 20 29 10	Polymer of dextrose, sorbitol and citric or phosphoric acid, containing by weight 90 % or more of dextrose monomer units	0
0592	ex 3907 20 29 20	Poly[oxy-1,4-phenyleneisopropylidene-1,4-phenyleneoxy-(2-hydroxytrimethylene)], of an average molecular weight (M_w) of more than 26 000, in one of the forms mentioned in note 6 (b) to Chapter 39	0
0593	ex 3907 20 99 10	Bis{2-[ω -hydroxy-poly(ethyleneoxy)]ethyl} hydroxymethylphosphonate	0
0594	ex 3907 20 99 15	Poly(oxypropylene) having alkoxysilyl end-groups	0
0595	ex 3907 20 99 25	α -4-Hydroxybutyl- ω -hydroxypoly(oxytetramethylene), containing less than 1 mg/kg of halogen and less than 1 mg/kg of metal, and of a colour not exceeding 20 units on the Hazen scale	0
0596	ex 3907 20 99 30	Homopolymer of 1-chloro-2,3-epoxypropane (epichlorohydrin)	0
0597	ex 3907 30 00 20	Epoxyde resin in the form of powder, containing by weight 44 % or more but not more than 55 % of quartz and 0,5 % or more but not more than 1 % of diantimony trioxide, for the coating of film capacitors (a)	0
0598	ex 3907 30 00 30	Epoxyde resin, without solvent, containing mineral fillers (silica), without glass fibre, of a specific weight at 25 °C of 1,55 g/cm ³ or more but not exceeding 1,60 g/cm ³	0
0599	ex 3907 30 00 40 ex 3926 90 99 70	Epoxyde resin, containing by weight 70 % or more of silicon dioxide, for the encapsulation of goods of heading No 8533, 8535, 8536, 8541, 8542 or 8548 (a)	0
0600	ex 3907 40 00 10	Copolymer of hexane-1,6-diol, cyclohexane-1,4-dimethanol and ethylene carbonate	0
0601	ex 3907 91 90 10	Diallyl phthalate prepolymer, in the form of powder	0
0602	ex 3907 99 19 10 ex 3907 99 99 10	Poly(oxy-1,4-phenylenecarbonyl), in the form of powder	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0603	ex 3907 99 19 20	Liquid crystal copolyester with a melting point of not less than 270 °C, whether or not containing fillers	0
0604	ex 3908 90 00 10	Poly(iminomethylene-1,3-phenylenemethyleneiminoadipoyl), in one of the forms mentioned in note 6 (b) to Chapter 39	0
0605	ex 3908 90 00 20	Copolymer consisting of hexamethylenediamine, isophthalic acid and terephthalic acid, in one of the forms mentioned in note 6(b) to Chapter 39	0
0606	ex 3909 40 00 10	Polycondensation product of phenol with formaldehyde, in the form of hollow spheres of a diameter of less than 150 µm	0
0607	ex 3910 00 00 10	3-[(2-Aminoethyl)amino]propyl(methyl)cyclosiloxane	0
0608	ex 3910 00 00 20	Block copolymer of poly(methyl-3,3,3-trifluoropropylsiloxane) and poly[methyl(vinyl)siloxane]	0
0609	ex 3911 90 19 10	Poly(oxy-1,4-phenylenesulfonyl-1,4-phenyleneoxy-4,4'-biphenylene)	0
0610	ex 3911 90 19 20	Hydrocarbon prepolymer, obtained by the reaction of cyclopentadiene and 1,3-pentadiene	0
0611	ex 3911 90 99 20	Copolymer of dibutyl maleate and <i>N</i> -vinyl-2-pyrrolidone, in one of the forms mentioned in note 6 (a) of Chapter 39	0
0612	ex 3911 90 99 25	Copolymer of vinyltoluene and <i>α</i> -methylstyrene	0
0613	ex 3911 90 99 40	Mixed calcium and sodium salt of a copolymer of maleic acid and methyl vinyl ether, having a calcium content of 9 % or more but not more than 16 % by weight	0
0614	ex 3911 90 99 45	Copolymer of maleic acid and methyl vinyl ether	0
0615	ex 3911 90 99 55	Solution containing: ~ (36 ± 0,5) % by weight of polyamide with lateral ester groups, ~ (2 ± 0,5) % by weight of acrylic ester, ~ (48 ± 0,5) % by weight of 1-methyl-2-pyrrolidone, ~ (12 ± 0,5) % by weight of bis(2-methoxyethyl) ether, ~ 500 µg/kg or less of potassium and ~ 500 µg/kg or less of iron, for use in the manufacture of goods of heading No 8542 (a)	0
0616	ex 3912 11 00 10	Non-plasticized cellulose triacetate, in the form of flakes, for the manufacture of cellulose triacetate yarn (a)	0
0617	ex 3912 39 10 10	Ethylcellulose, not plasticized	0
0618	ex 3912 39 10 20	Ethylcellulose, in the form of aqueous dispersion containing hexadecan-1-ol and sodium dodecyl sulfate, containing by weight (27 ± 3) % of ethylcellulose	0
0620	ex 3912 39 80 10	Cellulose, both hydroxyethylated and ethylated, insoluble in water	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0621	ex 3912 39 80 20	Cellulose, both hydroxyethylated and alkylated with alkyl chain-lengths of 3 or more carbon atoms	0
0622	ex 3912 90 10 10	Cellulose acetate propionate, non-plasticised, in the form of powder: ~ containing by weight 25 % or more of propionyl (as determined by the ASTM D 817-72 method) and ~ of a viscosity not exceeding 120 poise (as determined by the ASTM D 817-72 method), for the manufacture of printing inks, paints, lacquers and other coatings, and reprographic coatings (a)	0
0624	ex 3913 90 80 30	Chondroitinsulfuric acid, sodium salt	0
0623	ex 3913 90 80 40	Chitosonium pyrrolidonecarboxylate	0
0625	ex 3915 90 93 30	Waste, parings and scrap of photographic, cinematographic and radiographic films	0
0626	ex 3917 32 10 10	Flexible pipe of silicone foam, with continuous channels, of a Shore A hardness of 7 or more but not exceeding 48 and a density of 0,28 g/cm ³ or more but not exceeding 0,92 g/cm ³	0
0627	ex 3917 32 39 20	Pipe consisting of a block copolymer of polytetrafluoroethylene and polyperfluoroalkoxytrifluoroethylene, of a length of not more than 600 mm, a diameter of not more than 85 mm and a wall-thickness of 30 µm or more but not exceeding 110 µm	0
0628	ex 3919 10 31 10 ex 3919 10 38 30 ex 3919 90 31 50	Reflecting laminated sheet, consisting of a film of polycarbonate totally embossed on one side in a regular shaped pattern, covered on both sides with one or more layers of plastic material and on one side with an adhesive layer and a release sheet	0
0629	ex 3919 10 38 10	Self-adhesive tape of metallised polyurethane containing glass beads for use in the manufacture of marine life-saving equipment (a)	0
0630	ex 3919 10 38 20 ex 3919 90 38 10 ex 3920 99 28 20	Reflecting film, consisting of a layer of polyurethane with security imprints and embedded glass beads on one side and an adhesive layer on the other side, covered on one side or on both sides with a release film	0
0631	ex 3919 10 61 91 ex 3919 90 61 94	Reflecting film, consisting of a layer of poly(vinyl chloride), a layer of alkyd polyester, with security imprints and embedded glass beads on one side and an adhesive layer on the other side, covered on one side or on both sides with a release film	0
0634	ex 3919 90 10 10	Shaped sheet of plastic, with an adhesive layer containing polyisobutylene and pectin, for the manufacture of colostomy bags (a)	0
0633	ex 3919 90 10 20	Poly(ethylene terephthalate) film, covered on one side with an antistatic layer and a hardcoat layer and on the other side with an adhesive layer and a release sheet, in the form of sheets of dimensions not exceeding 450 × 750 mm	0
0635	ex 3919 90 31 40 ex 3920 62 19 20 ex 3920 62 90 20 ex 3920 63 00 30 ex 3920 69 00 30	Reflecting polyester sheeting embossed in a pyramidal pattern, for the manufacture of safety stickers and badges, safety clothing and accessories thereof, or of school satchels, bags or similar containers (a)	0
0636	ex 3919 90 61 92 ex 3919 90 69 92	Poly(vinyl chloride) sheeting, of a thickness of less than 1 mm, coated with an adhesive in which are embedded glass balls of a diameter not exceeding 100 µm	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0637	ex 3919 90 61 93 ex 3919 90 69 93 ex 3920 10 89 25	Adhesive film consisting of a base of a copolymer of ethylene and vinyl acetate (EVA) of a thickness of 120 µm or more and an adhesive part of acrylic type of a thickness of 10 µm or more, for the protection of the surface of silicon discs (a)	0
0638	ex 3919 90 69 94	Reflecting laminated sheet, consisting of a film of poly(methyl methacrylate) embossed on one side in a regular pyramidal or other shaped pattern, a film of a polymer of methyl methacrylate containing glass microprisms or microspheres, an adhesive layer and a release sheet	0
0639	ex 3920 10 26 20	Film of polyethylene, of a thickness of 20 µm or more but not exceeding 45 µm, containing calcium carbonate in the mass, for the manufacture of napkins for babies or of sanitary towels or of tampons or of disposable surgical gowns (a)	0
0640	ex 3920 10 26 30 ex 3920 10 89 20	Film of a thickness not exceeding 0,20 mm, of a blend of polyethylene and a copolymer of ethylene with oct-1-ene, embossed in a regular rhomboidal pattern, for coating both sides of a layer of unvulcanized rubber (a)	0
0641	ex 3920 10 28 92 ex 3920 10 89 30	Polyethylene sheet, of a thickness of 0,025 mm or more but not exceeding 3 mm, of an elongation at break of 100 % or more but not exceeding 1 100 % (as determined by the ASTM D 638 and 882 methods), in rolls of a width of 4,57 m, 4,9 m, 7,01 m or 9,3 m	0
0642	ex 3920 10 40 91	Synthetic paper pulp, in the form of moist sheets, made from unconnected finely-branched polyethylene fibrils, whether or not blended with cellulose fibres in a quantity not exceeding 15 %, containing poly(vinyl alcohol) dissolved in water as the moistening agent	0
0643	ex 3920 10 40 92	Laminated sheet or strip consisting of a film composed of a blend of a copolymer of ethylene with vinyl acetate and a modified ethylene-propylene-elastomer (EPM) or a modified ethylene-propylene-diene elastomer (EPDM), coated or covered on both sides with a film of a copolymer of ethylene with vinyl acetate	0
0644	ex 3920 10 89 35	Reflecting film, consisting of a layer of polyethylene, a layer of polyurethane, with security imprints and embedded glass beads on one side and a hot-melt adhesive layer on the other side, covered on one side or on both sides with a release film	0
0645	ex 3920 20 29 91	Mono-axial oriented film, consisting of three layers, each layer consisting of a mixture of polypropylene and a copolymer of ethylene and vinyl acetate, having: ~ a thickness of 55 µm or more but not exceeding 97 µm, ~ a tensile modulus in the machine direction of 0,75 GPa or more but not exceeding 1,45 GPa and ~ a tensile modulus in the transverse direction of 0,20 GPa or more but not exceeding 0,55 GPa	0
0646	ex 3920 20 90 91	Synthetic paper pulp, in the form of moist sheets, made from unconnected finely-branched polypropylene fibrils, whether or not blended with cellulose fibres in a quantity not exceeding 15 %, containing poly(vinyl alcohol) dissolved in water as the moistening agent	0
0647	ex 3920 20 90 92	Laminated sheet or strip, consisting of a film of a thickness of 181 µm or more but not exceeding 223 µm composed of a blend of a copolymer of propylene with ethylene and a copolymer of styrene-ethylene-butylene-styrene (SEBS) coated or covered on one side with a layer of a copolymer of styrene-ethylene-butylene-styrene (SEBS) and a layer of polyester	0
0648	ex 3920 20 90 93	Polypropylene sheet, of a thickness of 0,5 mm or more but not exceeding 1,0 mm, having a tensile strength at break of 14,7 MPa or more but not exceeding 21 MPa (as determined by the ASTM D 638 method), in rolls of a width of 3,81 m	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0649	ex 3920 30 00 20	Laminated sheet or strip, consisting of a film composed of a blend of a thermoplastic elastomer (TPE) of styrene-butadiene-styrene (SBS) with polyethylene or polypropylene, of a thickness of 100 µm or more but not exceeding 200 µm, coated or covered on both sides with a film of polypropylene of a thickness not exceeding 20 µm	0
0651	ex 3920 43 10 91 ex 3920 49 10 91	Reflecting sheeting, consisting solely of a single layer of poly(vinyl chloride), wholly embossed on one side in a regular pyramidal pattern	0
0653	ex 3920 43 10 92	Sheeting of poly(vinyl chloride), stabilized against ultraviolet rays, without any holes, even microscopic, of a thickness of 60 µm or more but not exceeding 80 µm, containing 30 or more but not more than 40 parts of plasticizer to 100 parts of poly(vinyl chloride)	0
0654	ex 3920 43 10 93	Poly(vinyl chloride) sheet, with relief printing, of a kind used in the templates for textile printing	0
0650	ex 3920 43 10 94 ex 3920 49 10 93	Film of a gloss level of 70 or more, measured at 60 ° using a gloss meter (as determined by the ISO 2813:2000 method), consisting of one or two layers of poly(vinyl chloride) coated on both sides with a layer of plastic, of a thickness of 0,26 mm or more but not exceeding 1,0 mm, covered on the gloss surface with a protective film of polyethylene, in rolls of a width of 1 000 mm or more but not exceeding 1 450 mm, for use in the manufacture of goods of heading No 9403 (a)	0
0652	ex 3920 43 10 95 ex 3920 49 10 92	Reflecting laminated sheet, consisting of a film of poly(vinyl chloride) and a film of an other plastic totally embossed in a regular pyramidal pattern, covered on one side with a release sheet	0
0655	ex 3920 51 00 10	Poly(methyl methacrylate) plate, with an antistatic coating, of dimensions of 738 × 972 mm (± 1,5 mm)	0
0656	ex 3920 51 00 20	Plate of poly(methyl methacrylate) containing aluminium trihydroxide, of a thickness of 3,5 mm or more but not exceeding 19 mm	0
0657	ex 3920 61 00 10	Polycarbonate film of a thickness not exceeding 15 µm, for the manufacture of film capacitors (a)	0
0658	ex 3920 62 19 05	Coextruded opaque sheet of poly(ethylene terephthalate), of a thickness of 50 µm or more but not exceeding 350 µm, consisting especially of a layer containing carbon black	0
0659	ex 3920 62 19 10	Poly(ethylene terephthalate) film, of a thickness of less than 11 µm, for the manufacture of audiodigital tapes for cassettes (a)	0
0660	ex 3920 62 19 15	Poly(ethylene terephthalate) film, not coated with an adhesive, of a thickness not exceeding 25 µm, either: ~ only dyed in the mass, or ~ dyed in the mass and metallized on one side	0
0661	ex 3920 62 19 25	Film of poly(ethylene terephthalate) only, of a total thickness not exceeding 120 µm, consisting of one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material	0
0662	ex 3920 62 19 30	Poly(ethylene terephthalate) film, of a thickness of 20 µm or more but not exceeding 30 µm, coated on one side with silicone, for use in the manufacture of window film (a)	5.6

	CN code & TARIC	Description	Rate of autonomous duty (%)
0663	ex 3920 62 19 35	Laminated film of poly(ethylene terephthalate) only, of a total thickness not exceeding 120 µm, consisting of one layer which is metallised only and one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material	0
0664	ex 3920 62 19 40	Film of poly(ethylene terephthalate), coated or covered on one side or on both sides with a layer of modified polyester, of a total thickness of 7 µm or more but not exceeding 11 µm, for the manufacture of video tapes with a magnetic layer of metallic pigments and a width of 8 mm or of 12,7 mm (a)	0
0665	ex 3920 62 19 45	Single ply film of poly(ethylene terephthalate) only, of a thickness not exceeding 120 µm, which only: ~ contains a colouring and/or UV-absorbing material throughout the mass and ~ is metallised on one side, whether or not coated on one or both sides with a vinyl acrylate polymer but having no other coating or adhesive	0
0666	ex 3920 62 19 50	Film of poly(ethylene terephthalate), of a total thickness not exceeding 120 µm, of a width of 100 mm or more but not exceeding 115 mm, coated on both sides with one or more layers containing different chemicals, for the manufacture of goods of subheading 3701 20 00 (a)	0
0667	ex 3920 62 19 55	Film of poly(ethylene terephthalate), on one side metallised and coated with white ink and a protective layer and on the other side coated with a thermosensitive seal layer, of a width of 100 mm or more but not exceeding 150 mm, for the manufacture of goods of subheading 3701 20 00 (a)	0
0668	ex 3920 62 19 60	Film of poly(ethylene terephthalate), coated on one side with a layer of modified polyester, of a thickness of 20 µm (± 0,7 µm) or of 30 µm (± 0,9 µm), for the manufacture of audio magnetic tapes of a total thickness of 33 µm or more (a)	0
0669	ex 3920 62 19 62	Poly(ethylene terephthalate) film, of a thickness not exceeding 12 µm, coated on one side with a layer of aluminium oxide of a thickness not exceeding 35 nm	0
0670	ex 3920 62 19 64	Poly(ethylene terephthalate) film, of a thickness of 18 µm or more but not exceeding 25 µm, having: ~ a shrinkage of (3,4 ± 0,1) % in the machine direction (as determined by the ASTM D 1204 method) and ~ a shrinkage of (0,3 ± 0,2) % in the transverse direction (as determined by the ASTM D 1204 method)	0
0671	ex 3920 62 19 65	Poly(ethylene terephthalate) film, of a thickness not exceeding 19 µm or of a weight of 20 g/m ² or more but not exceeding 26,7 g/m ² , for use in the manufacture of photo-resist film (a)	0
0672	ex 3920 62 19 70	Film of poly(ethylene terephthalate), coated on both sides with a layer of epoxy acrylic resin, of a total thickness of 37 µm (± 3 µm)	0
0673	ex 3920 62 19 75	Film of poly(ethylene terephthalate), coated on one side with metal and/or metal oxides, containing by weight less than 0,1 % of aluminium, of a thickness not exceeding 300 µm and having a surface resistivity not exceeding 10 000 ohms (per square) (as determined by the ASTM D 257-93 method)	0
0674	ex 3920 62 19 80	Mat film of poly(ethylene terephthalate), of a gloss of 15 at an angle of 45 ° and 18 at an angle of 60 ° (as determined by the ASTM D 523 method) and a width of 1 600 mm or more	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0675	ex 3920 62 19 81	Film of white poly(ethylene terephthalate), dyed in the mass, of a thickness of 185 µm or more but not exceeding 253 µm, coated on both sides with an antistatic layer	0
0676	ex 3920 62 19 85	Film of a total thickness of 4,5 µm (± 0,16 µm), consisting of a biaxially-oriented poly(ethylene terephthalate) film, of an elastic modulus (in the machine direction) of 12 kg/mm ² (± 2 kg/mm ²) and a tensile strength (in the machine direction) of more than 28 kg/mm ² , and of an anti-adherent coating	0
0677	ex 3920 62 19 87	Poly(ethylene terephthalate) film, coated with a wax layer, a scratch resistant layer and a thermoadhesive layer, of a nominal width of 790 mm and a total thickness of 23 µm or more but not exceeding 26 µm	0
0678	ex 3920 62 19 88	Laminated sheet, consisting of a biaxially oriented film of poly(ethylene terephthalate), covered on one side or on both sides with a layer of poly(ethylene terephthalate), for use in the manufacture of identity cards, credit cards and similar products (including "smart" cards) (a)	0
0679	ex 3920 62 19 89	Multilayer film of a thickness not exceeding 150 µm, consisting of a polyester film coated on one side with polycarbonate resin, metallized on the other side with titanium coated with polycarbonate resin and other layers containing <i>N,N'</i> -diphenyl- <i>N,N'</i> -di- <i>m</i> -tolylbiphenyl-4,4'-ylenediamine	0
0680	ex 3920 62 90 30	Film of poly(ethylene terephthalate), of a thickness of 500 µm (± 25 µm)	0
0681	ex 3920 62 90 40	Strips of poly(ethylene terephthalate), covered on both sides with a layer of chemically modified polyester, of a width not exceeding 16 mm and a thickness of 0,5 mm or more but not exceeding 2 mm, having a tensile strength at break of 0,7 GPa or more (as determined by the ASTM D 638 method)	0
0682	ex 3920 69 00 20	Film of poly(ethylene naphthalene-2,6-dicarboxylate), of a thickness of 0,6 µm or more but not exceeding 10 µm or 82 µm or more but not exceeding 88 µm	0
0683	ex 3920 69 00 40	Iridescent film of polyester and poly(methyl methacrylate)	0
0684	ex 3920 69 00 50	Polycondensation product of terephthalic acid with a mixture of cyclohex-1,4-ylenedimethanol and ethane-1,2-diol, in the form of a film	0
0685	ex 3920 69 00 60	Film of a copolymer of ethylene terephthalate and ethylene isophthalate, of a thickness not exceeding 2 µm	0
0686	ex 3920 91 00 91	Poly(vinyl butyral) film having a graduated coloured band	6
0687	ex 3920 91 00 93	Film of poly(ethylene terephthalate), metallised on one or both sides, or laminated film of poly(ethylene terephthalate) films, metallised on the external sides only, and having the following characteristics: ~ a visible light transmission of 50 % or more, ~ coated on both sides with a layer of poly(vinyl butyral) but not coated with an adhesive or any other material except poly(vinyl butyral), ~ a total thickness not exceeding 0,2 mm without taking the presence of poly(vinyl butyral) into account, for use in the manufacture of heat-reflecting laminated glass (a)	0
0688	ex 3920 99 28 10	Reflecting sheet of metallised polyurethane, containing glass beads, coated with a hot-melt adhesive layer, covered on one or both sides with a release sheet, in rolls of a width of 1 020 mm (± 20 mm), for slitting into safety clothing reflecting strip (a)	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0689	ex 3920 99 28 30 ex 3921 90 55 10 ex 7410 21 00 30	Film of polyimide, not containing epoxyde resin and/or glass fibres,: ~ metallized by sputtering with copper on one side or on both sides, ~ metallized by sputtering with copper and plated on one side or on both sides with refined copper or ~ covered on one side or on both sides with a copper foil	0
0690	3920 99 53 ex 3920 99 59 55	Ion-exchange membranes of fluorinated plastic material	0
0691	ex 3920 99 59 20	Film entirely of poly(vinyl alcohol), of a thickness not exceeding 1 mm and containing by weight: ~ 2 % or less of unhydrolysed acetate groups evaluated as vinyl acetate and ~ 5 % or more but not more than 25 % of glycerol as plasticizer, for the manufacture of roof-windows (a)	0
0692	ex 3920 99 59 25	Poly(1-chlorotrifluoroethylene) film	0
0693	ex 3920 99 59 30	Film and sheet of a copolymer of ethylene with chlorotrifluoroethylene, of a thickness of 12 µm or more but not exceeding 400 µm	0
0694	ex 3920 99 59 35	Film entirely of poly(vinyl alcohol), of a thickness not exceeding 1 mm and of a width of 2,20 m or more, with an extension at break, in the transverse direction, of 350 % or more	0
0695	ex 3920 99 59 40	Biaxially-oriented film of poly(vinyl alcohol), coated on both sides, of a total thickness of less than 1 mm	0
0696	ex 3920 99 59 45	Iridescent film of polyester, polyethylene and an ethylene-vinyl acetate copolymer	0
0697	ex 3920 99 59 50	Polytetrafluoroethylene film, non-microporous, in the form of rolls, of a thickness of 0,019 mm or more but not exceeding 0,14 mm, impermeable to water vapour	0
0698	ex 3921 19 00 91	Microporous polypropylene film of a thickness not exceeding 100 µm	0
0699	ex 3921 19 00 92	Microporous film consisting of mixtures of cellulose acetate and cellulose nitrate, of a thickness not exceeding 200 µm	0
0700	ex 3921 19 00 93	Strip of microporous polytetrafluoroethylene on a support of a non-woven, for use in the manufacture of filters for kidney dialysis equipment (a)	0
0701	ex 3921 90 19 35	Composite plate of polycarbonate and poly(butylene terephthalate), reinforced with glass fibres	0
0702	ex 3921 90 19 45	Composite plate of poly(ethylene terephthalate) or of poly(butylene terephthalate), reinforced with glass fibres	0
0704	ex 3921 90 60 91 ex 5407 71 00 20 ex 5903 90 99 10	Woven polytetrafluoroethylene fabric, coated or covered with a copolymer of tetrafluoroethylene and trifluoroethylene having perfluorinated alkoxy side-chains ending in carboxylic acid or sulfonic acid groups, whether or not in the potassium or sodium salt form	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0705	ex 3921 90 60 92	Reinforced polypropylene sheet, of a thickness of 0,91 mm or more but not exceeding 1,12 mm, having a breaking strength of 890 N or more but not exceeding 1 500 N (as determined by the ASTM D 751 method), in rolls of a width of 3,81 m	0
0706	ex 3926 90 91 20	Reflecting sheeting or tape, consisting of a facing-strip of poly(vinyl chloride) embossed in a regular pyramidal pattern, heat-sealed in parallel lines or in a grid-pattern to a backing-strip of plastic material, or of knitted or woven fabric covered on one side with plastic material	0
0707	ex 3926 90 99 10	Microspheres of polymer of divinylbenzene, of a diameter of 4,5 µm or more but not exceeding 80 µm	0
0708	ex 3926 90 99 20	Tape pad, for use in the manufacture of goods of heading No 8523 (a)	0
0709	ex 3926 90 99 30	Guide pin and pole, for use in the manufacture of goods of subheadings 8523 11 00, 8523 12 00 and 8523 13 00 (a)	0
0710	ex 3926 90 99 35	Microspheres of polyalkylsiloxane, on which are covalently bonded organic compounds, of a diameter of 1 µm or more but not exceeding 30 µm	0
0711	ex 4007 00 00 10	Siliconated vulcanised rubber thread and cord	0
0712	ex 4008 11 00 10	Blocks or sheets of cellular vulcanised rubber of modified ethylene-propylene-diene (EPDM) blended with chloroprene, which satisfy the Underwriters Laboratories Flammability Standard UL94HF-1	0
0713	ex 4016 99 88 10	Soft rubber sealing stoppers for the manufacture of electrolytic capacitors (a)	0
0714	4105 10 10 4105 10 90 4105 30 91 4105 30 99	Sheep or lamb skin leather, without wool on, tanned or retanned but not further prepared, whether or not split, other than leather of heading No 4114	0
0715	4106 21 10 4106 21 90 4106 22 90	Goat or kid skin leather, without hair on, tanned or retanned but not further prepared, whether or not split, other than leather of heading No 4114	0
0716	4106 31 10 4106 31 90 4106 32 10 4106 32 90 4106 40 90 4106 91 00 4106 92 00	Leather of other animals, without hair on, not further prepared than tanned, other than leather of heading No 4114	0
0717	ex 4802 54 90 10 ex 4802 55 00 10 ex 4802 57 00 10	Overlay paper, of a width of more than 110 cm and containing by weight more than 5 % of corundum	0
0718	ex 4805 91 99 20	Paper, in cross-wise rewinded spiral rolls, of a weight of less than 150 g/m ² and of a thickness not exceeding 0,05 mm, for the manufacture of electrolytic capacitors (a)	0
0719	ex 4810 99 10 10	Bleached paper coated with kaolin, for use in the manufacture of tampons applicators (a)	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0720	ex 4811 41 10 10	Impregnated paper coated or covered with a pressure-sensitive self-adhesive layer, the whole: ~ of a tensile of 2 700 N/m or more but not exceeding 3 700 N/m in the machine direction ~ (as determined by the EN ISO 1924-2 and ISO 3781 methods), ~ of a stretch factor of 1,5 % or more but not exceeding 3,0 % in the machine direction (as determined by the EN ISO 1924-2 and ISO 3781 methods)	0
0721	ex 4811 51 00 10	Paper coated with acrylic polymer, with a gloss of 75 or more but not exceeding 90 (as determined by the Hunter method), of a weight of 160 g/m ² or more but not exceeding 180 g/m ² , for use as casting paper in the manufacture of films of plastics (a)	0
0722	ex 4811 59 00 10	Kraft paper impregnated with an acrylic polymer, of a weight of 83 g/m ² or more but not exceeding 87 g/m ² or 176 g/m ² or more but not exceeding 216 g/m ²	0
0723	ex 4823 90 50 10	Paper coated with dye retention and dye releasing agents used to produce a positive image, for the manufacture of goods of subheading 3701 20 00 (a)	0
0724	ex 4823 90 50 20	Honeycomb filter, of paper impregnated with carbon, of a thickness greater than 10 mm but not exceeding 30 mm	0
0725	ex 4823 90 90 12	Strips of paper glued to one another to form a honeycomb of a height not exceeding 13 cm, for agricultural purposes (a)	0
0726	ex 4911 99 00 10	Polyester film, partially coated with a magnetic metal layer showing a regular repeating logo or motif, for the manufacture of security threads (a)	0
0727	ex 5004 00 10 10 ex 5004 00 90 10	Yarn spun entirely from silk, not put up for retail sale	2.5
0728	ex 5005 00 10 10 ex 5005 00 90 10	Yarn spun entirely from silk waste (noil), not put up for retail sale	0
0729	5208 11 10	Fabrics for the manufacture of bandages, dressings and medical gauzes	5.4
0730	ex 5402 41 00 10	Polyamide yarn, not textured, untwisted or with a twist not exceeding 22 turns per metre, of crimpable bicomponent filaments consisting of poly(hexamethylene adipamide) with a copolyamide, for the manufacture of: ~ knee-length stockings of subheadings 6115 20 11 and 6115 93 30, ~ women's stockings of subheadings 6115 20 19 and 6115 93 91 or ~ panty hose (tights) of subheading 6115 11 00 (a)	0
0731	ex 5402 41 00 20	Yarn of synthetic textile fibres solely of aromatic polyamides obtained by the polycondensation of <i>m</i> -phenylenediamine and isophthalic acid	0
0732	ex 5402 43 00 20	Synthetic bicomponent filament yarn, not textured, untwisted, measuring 1 650 decitex, consisting of 110 filaments each having a core of poly(ethylene terephthalate) and a skin of polyamide-6, containing by weight 75 % or more but not exceeding 77 % of poly(ethylene terephthalate), for use in the manufacture of roofings (a)	0
0733	ex 5402 49 99 10 ex 5402 69 90 20	Multifilaments yarn of polytetrafluoroethylene	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0734	ex 5402 49 99 30	Yarn of a copolymer of glycollic acid with lactic acid, for the manufacture of surgical sutures (a)	0
0735	ex 5402 49 99 50 ex 5402 59 90 20 ex 5402 69 90 40	Non-textured filament yarn of poly(vinyl alcohol)	0
0736	ex 5402 49 99 60 ex 5402 69 90 10	Yarn wholly of polyglycollic acid	0
0737	ex 5402 49 99 70	Synthetic filament yarn, single, containing by weight 85 % or more of acrylonitrile, in the form of a wick containing 1 000 continuous filaments or more but not more than 25 000 continuous filaments, of a weight per metre of 0,12 g or more but not exceeding 3,75 g and of a length of 100 m or more, for the manufacture of carbon-fibre yarn (a)	0
0738	ex 5402 49 99 80	Polyethylene filament yarn, untwisted, of either 55, 110, 165 or 1 760 decitex, for the manufacture of goods of heading No 5607 (a)	0
0739	ex 5402 49 99 85	Synthetic filament yarn, single, untwisted, wholly of poly(thio-1,4-phenylene)	0
0740	ex 5404 10 90 10	Monofilament of polytetrafluoroethylene	0
0741	ex 5404 10 90 20	Monofilament of poly(1,4-dioxanone)	0
0742	ex 5404 10 90 30	Monofilament of a copolymer of 1,3-dioxan-2-one with 1,4-dioxan-2,5-dione, for the manufacture of surgical sutures (a)	0
0743	ex 5404 90 90 20	Strip of polyimide	0
0744	ex 5407 71 00 10	Woven fabrics of poly(vinyl alcohol) fibres, for machine embroidery	0
0745	ex 5501 90 90 10	Poly(vinyl alcohol) tow	0
0746	ex 5503 20 00 10	Polyester staple fibres, loaded with zeolite impregnated with a mixture of salts of copper and silver or of salts of zinc and silver	4
0747	ex 5503 90 10 10 ex 5503 90 90 30	Acetalized, multicomponent spun fibres with a matrix fibril structure, consisting of emulsion-polymerized poly(vinyl alcohol) and poly(vinyl chloride)	0
0748	ex 5503 90 90 10	Textile fibres of polytetrafluoroethylene	4
0749	ex 5503 90 90 20 ex 5506 90 90 10 ex 5601 30 00 10	Poly(vinyl alcohol) fibres, whether or not acetalized	0
0750	ex 5503 90 90 40	Fibres wholly of poly(thio-1,4-phenylene)	0
0751	ex 5601 30 00 20	Polyester fibres, measuring 0,56 decitex, of a length of 3 mm or more but not exceeding 5 mm	0
0752	ex 5601 30 00 30	Acrylic fibres, measuring 0,11 and 0,56 decitex, of a length of 3 mm or more but not exceeding 5 mm	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0753	ex 5603 11 10 10 ex 5603 11 90 10 ex 5603 12 10 10 ex 5603 12 90 10 ex 5603 91 10 10 ex 5603 91 90 10 ex 5603 92 10 10 ex 5603 92 90 10	Poly(vinyl alcohol) non-wovens, in the piece or cut into rectangles: ~ of a thickness of 200 µm or more but not exceeding 280 µm and ~ of a weight of 20 g/m ² or more but not exceeding 50 g/m ²	0
0754	ex 5603 11 10 20 ex 5603 11 90 20 ex 5603 12 10 20 ex 5603 12 90 50	Non-wovens, containing spunbonded fibres of polypropylene or of polypropylene and polyethylene, for the manufacture of napkins and napkin liners for babies and similar sanitary articles (a)	0
0755	ex 5603 12 90 30 ex 5603 13 90 30 ex 5603 14 90 10	Non-wovens of aromatic polyamide fibres obtained by polycondensation of <i>m</i> -phenylenediamine and isophthalic acid, in the piece or cut into rectangles	0
0756	ex 5603 12 90 60 ex 5603 13 90 60	Non-woven of spunbonded polyethylene, of a weight of more than 60 g/m ² but not exceeding 80 g/m ² and an air resistance (Gurley) of 8 s or more but not exceeding 36 s (as determined by the ISO 5636/5 method)	0
0759	ex 5603 12 90 70 ex 5603 13 90 70 ex 5603 92 90 40 ex 5603 93 90 10	Non-wovens of polypropylene, consisting of a meltblown layer, laminated on each side with spunbonded filaments of polypropylene, of a thickness not exceeding 550 µm and of a weight not exceeding 80 g/m ² , in the piece or simply cut into squares or rectangles, not impregnated	0
0757	ex 5603 13 90 40 ex 5603 14 90 20	Non-wovens consisting of a central layer of polycarbonate fibres, laminated on each side with spunbonded filaments of polyester, of a weight of more than 130 g/m ² but not exceeding 200 g/m ²	0
0758	ex 5603 92 90 20 ex 5603 93 90 20	Non-wovens consisting of a meltblown central layer of a thermoplastic elastomer laminated on each side with spunbonded filaments of polypropylene	0
0760	ex 5603 92 90 50	Non-wovens of staple fibres, in rolls, of a width of 78 mm or more but not exceeding 252 mm, for the manufacture of floppy discs (a)	0
0761	ex 5603 94 90 20	Acrylic fibre rods, having a length of not more than 50 cm, for the manufacture of pen tips (a)	0
0762	ex 5607 50 90 10	Twine, unsterilised, wholly of polyglycollic acid, plaited or braided, with an inner core, for the manufacture of surgical sutures (a)	0
0763	ex 5903 10 90 10 ex 5903 20 90 10 ex 5903 90 99 20	Knitted or woven fabrics, coated or covered on one side with artificial plastic material in which are embedded microspheres	0
0764	ex 5903 20 90 20	Tape of polyester fabric laminated with a metallised polyurethane film containing glass beads, for use in the manufacture of marine life-saving equipment (a)	0
0765	ex 5907 00 90 10	Textile fabrics, coated with adhesive in which are embedded spheres of a diameter not exceeding 75 µm	0
0766	ex 5911 10 00 10	Needle-punched synthetic-fibre felts, not containing polyester, whether or not containing catalytic particles entrapped within the synthetic fibres, coated or covered on one side with polytetrafluoroethylene film, for the manufacture of filtration products (a)	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0767	ex 5911 90 90 10	Yarn and strip of impregnated polytetrafluoroethylene, whether or not oiled or graphited	0
0768	ex 5911 90 90 30 ex 8421 99 00 92	Parts of equipment for the purification of water by reverse osmosis, consisting essentially of plastic-based membranes, supported internally by woven or non-woven textile materials which are wound round a perforated tube, and enclosed in a cylindrical plastic casing of a wall-thickness not exceeding 4 mm, whether or not housed in a cylinder of a wall-thickness of 5 mm or more	0
0770	6305 10 10	Sacks and bags, of a kind used for the packing of goods, used, of jute or of other textile bast fibres of heading No 5303	0
0771	ex 6305 90 00 10 ex 6305 90 00 91	Sacks and bags, of a kind used for the packing of goods, used, of flax or of sisal	0
0772	ex 6307 90 10 10	Sterile mesh-implant, consisting of a knitted fabric of polypropylene monofilaments, with rounded edges, in forms covered by a square of dimensions not exceeding 31 × 31 cm	0
0773	ex 6813 90 90 10	Friction material, of a thickness of less than 20 mm, not mounted, for the manufacture of friction components of a kind used in automatic transmissions and clutches (a)	0
0774	ex 6903 20 90 10	Yarn of continuous ceramic filaments, each filament containing by weight: ~ 12 % or more of diboron trioxide, ~ 26 % or less of silicon dioxide and ~ 60 % or more of dialuminium trioxide	0
0775	ex 6903 90 80 10 ex 6909 19 00 40	Beryllium oxide, of a purity by weight of more than 99 %, in the form of blanks, bars, blocks or plates	0
0776	ex 6903 90 80 20	Silicon carbide reactor tubes and holders, of a kind used for insertion into diffusion and oxidation furnaces for production of semiconductor materials	0
0777	ex 6909 12 00 20	Plate, of dialuminium trioxide and titanium carbide, of dimensions not exceeding 48 × 48 mm, or of a diameter not exceeding 125 mm, for the manufacture of magnetic heads (a)	0
0778	ex 6909 19 00 30	Supports for catalysts, consisting of porous cordierite or mullite ceramic pieces, of an overall volume not exceeding 65 l, having, per cm ² of the cross-section, not less than one continuous channel which may be open at both ends or stopped at one end	0
0780	ex 7006 00 90 10	Glass plate, coated on one side with chromium and/or with a mixture of diindium trioxide and tin dioxide, of dimensions of 260 × 320 mm or more but not exceeding 400 × 400 mm, of a thickness not exceeding 1,2 mm, for the manufacture of liquid crystal displays (a)	0
0781	ex 7006 00 90 20	Colour filter, consisting of a glass plate with red, blue and green pixels, having a total thickness of 1,1 mm (± 0,1 mm) and exterior dimensions of 320 × 352 mm or more but not exceeding 320 × 400 mm, for the manufacture of liquid crystal displays (a)	0
0782	ex 7006 00 90 30	Glass plate, uncoated, of dimensions of 320 × 352 mm or more but not exceeding 320 × 400 mm, of a thickness of 0,6 mm or more but not exceeding 1,2 mm, for the manufacture of liquid crystal displays (a)	0
0783	ex 7006 00 90 40	Disk of glass, with a hole in the centre, with the edges having been worked, of a total thickness not exceeding 1,5 mm	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0784	ex 7011 10 00 10	Glass lenses with a stippled front refractor or with a front refractor composed of prismatic elements, with an external diameter of more than 121 mm but not exceeding 125 mm	0
0785	ex 7011 10 00 20	Parabolic glass reflectors, with an external diameter of more than 121 mm but not exceeding 125 mm	0
0786	ex 7011 20 00 40	Glass face-plate: ~ with a diagonal measurement of 366,4 mm ($\pm 1,5$ mm) and of dimensions of 246,4 \times 315,4 mm ($\pm 1,5$ mm), ~ with a diagonal measurement of 391 mm ($\pm 1,5$ mm) and of dimensions of 261,4 \times 326,8 mm ($\pm 1,5$ mm), ~ with a diagonal measurement of 442 mm ($\pm 1,5$ mm) and of dimensions of 293,4 \times 369,2 mm ($\pm 1,5$ mm), ~ with a diagonal measurement of 544,5 mm ($\pm 1,6$ mm) and of dimensions of 358 \times 454 mm ($\pm 1,6$ mm), having a cylindrical curvature, ~ with a diagonal measurement of 570,5 mm ($\pm 1,6$ mm) and of dimensions of 360 \times 486 mm ($\pm 1,6$ mm), ~ with a diagonal measurement of 629,8 mm (± 3 mm) and of dimensions of 406,5 \times 519 mm (± 2 mm), having a cylindrical curvature, or ~ with a diagonal measurement of 753 mm ($\pm 1,6$ mm) and of dimensions of 471 \times 640 mm ($\pm 1,6$ mm), and with a raised edge, for the manufacture of colour cathode-ray tubes (a)	0
0787	ex 7011 20 00 75	Glass face-plate: ~ with a diagonal measurement of 604,5 mm (± 3 mm) and of dimensions of 340 \times 541 mm (± 2 mm), ~ with a diagonal measurement of 639,3 mm (± 3 mm) and of dimensions of 413,6 \times 527 mm (± 2 mm), ~ with a diagonal measurement of 708 mm (± 3 mm) and of dimensions of 404 \times 633 mm (± 2 mm), ~ with a diagonal measurement of 723 mm (± 3 mm) and of dimensions of 477 \times 602 mm (± 2 mm), or ~ with a diagonal measurement of 812,8 mm (± 3 mm) and of dimensions of 463,8 \times 725,5 mm (± 2 mm), having a cylindrical curvature, for the manufacture of colour cathode-ray tubes (a)	0
0788	ex 7011 20 00 80	Glass bulb for monochrome cathode-ray tube, of a diagonal measurement of 3,8 cm or more but not exceeding 51 cm and a nominal neck diameter of 13 mm, 20 mm, 29 mm or 37 mm	0
0789	ex 7014 00 00 10	Optical elements of glass (other than those of heading No 7015), not optically worked, other than signalling glassware	0
0792	ex 7019 12 00 10	Rovings, measuring 2 600 tex or more but not more than 3 300 tex and of a loss on ignition of 4 % or more but not exceeding 8 % by weight (as determined by the ASTM D 2584-94 method)	0
0791	ex 7019 12 00 15	Rovings, measuring 745, 830, 1 500, 1 600 or 2 220 tex (± 10 %), coated with a layer consisting of a mixture of polyurethane and wax	0
0793	ex 7019 12 00 20	Rovings, measuring 700 tex or more but not more than 2 000 tex, coated with a layer of polyurethane	0
0790	ex 7019 12 00 25	Rovings, measuring 745 tex (± 10 %), coated with a layer consisting of a mixture of polyurethane, acrylic polymer and wax	0
0794	ex 7019 12 00 30	Rovings, measuring 1 693 tex (± 10 %), coated with a layer of styrene-butadiene rubber (SBR)	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0795	ex 7019 12 00 40	Rovings, measuring 2 040 tex ($\pm 10\%$), coated with carbon	0
0796	ex 7019 19 10 10	Yarn of 33 tex or a multiple thereof, $\pm 7,5\%$, obtained from continuous spun-glass filaments of a nominal diameter of $3,5\ \mu\text{m}$ or of $4,5\ \mu\text{m}$, in which filaments of a diameter of $3\ \mu\text{m}$ or more but not exceeding $5,2\ \mu\text{m}$ predominate, other than those treated so as to improve their adhesion to elastomers	0
0797	ex 7019 19 10 30	Yarn of 22 tex $\pm 7,5\%$, obtained from continuous spun-glass filaments of a nominal diameter of $5\ \mu\text{m}$, in which filaments of a diameter of $4,2\ \mu\text{m}$ or more but not exceeding $5,8\ \mu\text{m}$ predominate	0
0798	ex 7019 19 10 40	Yarn of 33, 34 or 51 tex or a multiple thereof, $\pm 7,5\%$, obtained from continuous spun-glass filaments of a nominal diameter of $6\ \mu\text{m}$, in which filaments of a diameter of $5,1\ \mu\text{m}$ or more but not exceeding $6,9\ \mu\text{m}$ predominate	0
0799	ex 7019 32 00 10 ex 7019 39 00 10	Non-woven product of non-textile glass fibre, for the manufacture of air-filters or of air-filtration products (a)	0
0800	ex 7019 90 10 10	Non-textile glass fibres in which fibres of a diameter of less than $3,5\ \mu\text{m}$ predominate	0
0801	ex 7019 90 10 20	Non-textile E-glass fibres, of a length not exceeding 3 mm and a diameter of $5\ \mu\text{m}$, for the manufacture of catalysts for the purification of smokes (a)	0
0802	ex 7116 20 90 10	Disc of silicon on sapphire	0
0803	7202 50 00	Ferro-silico-chromium	0
0804	ex 7212 50 91 10	Perforated steel strip, plated or coated with nickel, of a width of 140 mm or more but not exceeding 400 mm and a thickness of $40\ \mu\text{m}$ or more but not exceeding $140\ \mu\text{m}$	0
0805	ex 7212 50 99 10	Cold-rolled steel, coated on both sides with a nickel-zinc layer, in the form of strip of a width of $40,15 (\pm 0,08)$ mm and a thickness of $0,3 (\pm 0,01)$ mm, containing by weight: <ul style="list-style-type: none"> ~ not more than 0,1 % of carbon, ~ not more than 0,04 % of phosphorus, ~ not more than 0,05 % of sulfur and ~ 0,2 % or more but not more than 0,5 % of manganese 	0
0806	ex 7306 30 29 91	Non-alloy steel precision tube, welded and cold finished, of an external diameter exceeding 160 mm and a wall thickness exceeding 2 mm	0
0807	ex 7409 19 00 10	Sheet or plate of polytetrafluoroethylene, with aluminium oxide or titanium dioxide as a filler or reinforced with glass-fibre fabric, laminated on both sides with copper foil	0
0808	ex 7410 21 00 10	Sheet or plate of polytetrafluoroethylene, containing aluminium oxide or titanium dioxide as filler or reinforced with glass-fibre fabric, covered on both sides with copper foil	0
0779	ex 7419 99 00 91 ex 7616 99 90 60	Disc (target) with deposition material, consisting of molybdenum silicide: <ul style="list-style-type: none"> ~ containing 1 mg/kg or less of sodium and ~ mounted on a metal support 	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0815	ex 7419 99 00 92 ex 7616 99 90 70	Disc (target) with deposition material, of tungsten or an alloy containing by weight 90 % of tungsten and 10 % of titanium: ~ containing 100 µg/kg or less of sodium and ~ mounted on a copper or aluminium support	0
0823	ex 7419 99 00 93 ex 7616 99 90 80	Disc (target) with deposition material, of titanium: ~ containing 50 µg/kg or less of sodium and ~ mounted on a copper or aluminium support	0
0810	ex 7606 11 91 20 ex 7606 11 93 20	Strip with depth-etching, of anodic oxidation treated aluminium of a purity by weight of 99,9 % and a thickness of less than 3 mm, for incorporation in bodies for motor vehicles (a)	0
0811	ex 7613 00 00 20 ex 8708 99 98 10	Aluminium container, seamless, for compressed natural gas or compressed hydrogen, wholly embedded in an overwrap of epoxy-carbon fibres composite, of a capacity of 172 l (± 10 %) and an unfilled weight not exceeding 64 kg	0
0812	ex 7616 99 90 40	Discs of aluminium alloy, coated or covered on both sides with a nickel-phosphorus layer, having a total thickness not exceeding 3,02 mm	0
0813	ex 7616 99 90 50	Discs of aluminium alloy, of a thickness not exceeding 0,84 mm, for the manufacture of goods of subheading 8523 20 10 (a)	0
0814	ex 7905 00 00 10	Plate of an alloy of zinc, ground and polished on one surface and coated with an epoxide resin on the other surface, of rectangular or square shape, of a length of 300 mm or more but not exceeding 2 000 mm and of a width of 300 mm or more but not exceeding 1 000 mm, and containing: ~ 10 mg/kg or less of iron, ~ 10 mg/kg or less of lead, ~ 700 mg/kg or more but not more than 900 mg/kg of aluminium and ~ 500 mg/kg or more but not more than 900 mg/kg of magnesium, for the manufacture of sensitised printing plates (a)	0
0816	ex 8103 90 90 10	Welded tube solely of tantalum, or solely of an alloy of tantalum with tungsten containing by weight 3,5 % or less of tungsten	0
0817	ex 8104 11 00 30	Unwrought magnesium, of a purity by weight of 99,95 % or more, in the form of ingots, for the manufacture of zirconium sponge or elements used in the nuclear industry (a)	0
0818	ex 8104 90 00 10	Ground and polished magnesium sheets, of dimensions not exceeding 1 500 × 2 000 mm, coated on one side with an epoxy resin insensitive to light	0
0819	ex 8104 90 00 20	Sections, of extruded magnesium, of a length of 800 mm or more but not exceeding 2 900 mm and a width of 15 mm or more but not exceeding 70 mm	0
0820	ex 8108 20 00 10	Titanium sponge	0
0821	8108 30 00	Waste and scrap of titanium	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0822	ex 8108 90 70 20	Welded titanium tubes, of an external diameter of 19,0 (± 0,1) mm, having an external structure of 36 fins per 2,54 cm, for use in the manufacture of refrigerant condensers (a)	0
0824	ex 8109 20 00 10	Non-alloy zirconium, in the form of ingots, containing by weight more than 0,01 % of hafnium, for use in the manufacture of tubes for the chemical industry (a)	0
0825	ex 8110 10 00 10	Antimony in the form of ingots	0
0826	ex 8112 19 00 10	Beryllium, of a purity by weight of 94 % or more, in the form of bars, plates and sheets	0
0827	ex 8112 99 30 10	Alloy of niobium (columbium) and titanium, in the form of bars and rods	0
	CN code & TARIC	Description	Rate of autonomous duty (%)
0002	ex 8407 31 00 10	Two stroke internal combustion engine, of a cylinder capacity not exceeding 30 cm ³ for use in the manufacture of portable motorised scooters falling within subheading 8711 10 00 (a)	0
0003	ex 8414 90 90 10	Aluminium pistons, partially covered with polytetrafluoroethylene, for incorporation into compressors of air conditioning machines of motor vehicles (a)	0
0004	ex 8414 90 90 20	Pressure-regulating system, for incorporation into compressors of air conditioning machines of motor vehicles (a)	0
0005	ex 8418 99 90 91	Welded cooling micro-elements, of an alloy of aluminium, for the manufacture of condensers (a)	0
0006	ex 8419 19 00 10	Heat accumulator for motor vehicles, of a coolant capacity of 4 l or more but not exceeding 10 l	0
0007	ex 8419 89 98 10	Immersion-tube (coils) bundles, consisting of an assembly of plastic tubes terminating at each end in a honeycomb-structure (end-fitting) surrounded by a pipe-connector	0
0008	ex 8419 89 98 20 ex 8543 89 95 58	Sputtering machines and apparatus, comprising disk handling equipment, for use in the manufacture of products falling within subheading 8523 20 10 (a)	0
0009	ex 8421 99 00 91	Parts of equipment, for the purification of water by reverse osmosis, consisting of a bundle of hollow fibres of artificial plastic material with permeable walls, embedded in a block of artificial plastic material at one end and passing through a block of artificial plastic material at the other end, whether or not housed in a cylinder	0
0010	ex 8421 99 00 93	Components of separators for the separation or purification of gases from gas mixtures, consisting of a bundle of permeable hollow fibres enclosed within a container, whether or not perforated, of an overall length of 300 mm or more but not exceeding 3 700 mm and a diameter not exceeding 500 mm	0
0011	ex 8421 99 00 95	Parts of equipment for the filtration of magnetic dispersions, consisting essentially of nylon-6 fibres, enclosed in a plastic casing of a diameter of 70 mm (± 2 mm) and a length of 520 mm (± 5 mm)	0
0019	ex 8422 30 00 10 ex 8479 89 98 70	Machines and apparatus, other than injection moulding machines, for the manufacture of ink-jet printer cartridges (a)	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0012	ex 8424 89 95 10 ex 8460 21 90 10 ex 8460 40 10 10 ex 8460 90 90 10 ex 8464 20 19 10 ex 8479 89 98 10	Machines and apparatus providing automated lapping, polishing, grinding, cleaning or surface lubrication of disks, comprising disk handling equipment, for use in the manufacture of products falling within subheading 8523 20 10 (a)	0
0013	ex 8424 89 95 20 ex 8479 89 98 30	Machines and apparatus providing automated cleaning or cleaning and drying of disks, by means of de-ionised water, ultra sonic waves, chemical solutions, heat or a combination of these processes, comprising disk handling equipment, for use in the manufacture of products falling within subheading 8523 20 10 (a)	0
0014	ex 8439 99 10 10 ex 8439 99 90 10	Suction-roll shells, not drilled, in the form of alloy-steel tubes, of a length of 5 207 mm or more and an external diameter of 754 mm or more, for use in machinery for making paper or paperboard (a)	0
0015	ex 8455 90 00 10	Helical turn device for cold-rolling mill	0
0016	ex 8456 10 90 10	Machine-tool operating by laser beam, for the cutting of slots on the surface of a cylindrical tube for use in the manufacture of endo-vascular prosthesis (so-called "stents") (a)	0
0017	ex 8460 90 90 20 ex 8463 90 00 10 ex 8479 89 98 20	Machine-tool providing automated creation of a texture (a head landing zone) on the surface of disks by means of abrasion or exposure to laser beams, comprising disk handling equipment, for use in the manufacture of products falling within subheading 8523 20 10 (a)	0
0018	ex 8473 40 19 20	Thermal printer head	0
0024	ex 8479 89 98 40 ex 8501 10 99 78	Motor, whether or not mounted on a baseplate, for use in the manufacture of products falling within subheading 8525 20 91 or 8527 90 92 (a)	0
0025	ex 8481 80 59 10	Air control valve, consisting of a stepping motor and a valve pintle, for the regulation of idle air flow in fuel injection engines	0
0026	ex 8483 10 80 10	Integrally forged and roughly shaped generator and turbine shafts of a weight exceeding 215 tonnes	0
0027	ex 8501 10 99 54	DC motor, brushless, with an external diameter not exceeding 25,4 mm, a rated speed of 2 260 (± 15 %) or 5 420 (± 15 %) rpm, a supply voltage of 1,5 or 3 V	0
0028	ex 8501 10 99 59	DC stepping motor, with an angle of step of 1,8° ($\pm 0,09^\circ$), a holding torque of 0,156 Nm or more, a coupling flange the exterior dimensions of which do not exceed 43 × 43 mm, a chuck of a diameter of 4 mm ($\pm 0,1$ mm), a two-phase winding and an output not exceeding 5 W	0
0029	ex 8501 10 99 73	DC motor, whether or not mounted on a baseplate, for use in the manufacture of products falling within subheading 8471 70 53 (a)	0
0030	ex 8501 10 99 77	DC motor, with brushes, with a typical running torque of 0,004 Nm ($\pm 0,001$ Nm), with a coupling flange of a diameter of 32 mm ($\pm 0,5$ mm) and a chuck of a diameter of 2 mm ($\pm 0,004$ mm), with an internal rotor, a three-phase winding, a rated speed of 2 800 (± 10 %) rpm and a supply voltage of 12 V (± 15 %)	0
0031	ex 8502 40 90 10	Rotary converter, with a ferrite core, having coils with 2 or 6 windings and a diameter of 0,1 mm, connected to a flexible printed circuit	0
0032	ex 8503 00 91 31 ex 8503 00 99 32	Rotor, at the innerside provided with one or two magnetic rings whether or not incorporated in a steel ring	0

	CN code & TARIC	Description	Rate of autonomou s duty (%)
0033	ex 8503 00 99 31	Stamped collector of an electric motor, having an external diameter not exceeding 16 mm	0
0035	ex 8504 40 99 20	Direct current to direct current converter	0
0036	ex 8504 40 99 30	Static converter comprising a power switch with insulated-gate bipolar transistors (IGBTs), contained in a housing, for use in the manufacture of microwave ovens of subheading 8516 50 00 (a)	0
0037	ex 8504 50 80 30	Inductor with an inductance not exceeding 62 mH	0
0038	ex 8504 50 80 40	Multilayer monolithic inductors, contained in a housing of the SMD (surface mounted device) type the exterior dimensions of which do not exceed 1,8 × 3,4 mm, for use in the manufacture of products falling within subheading 8517 11 00, 8525 20 91 or 8527 90 92 (a)	0
0039	8504 90 11	Ferrite cores	0
0040	ex 8504 90 18 32	Part of a rotary transformer, comprising a ferrite core provided with circular grooves with copper wire windings	0
0041	ex 8505 11 00 31	Ferrite magnet having a remanence of 455 mT (±15 mT)	0
0042	ex 8505 19 90 31	Neodymium-ferro ring with an external diameter not exceeding 13 mm, an internal diameter not exceeding 9 mm	0
0043	ex 8505 90 10 91	Solenoid with a plunger, operating at a nominal supply voltage of 24 V at a nominal DC of 0,08 A, for use in the manufacture of products falling within heading No 8517 (a)	0
0044	ex 8505 90 10 92	Electro-mechanical throttle plate actuator for automotive engines	0
0045	ex 8506 50 90 10	Lithium iodine single cell battery the dimensions of which do not exceed 9 × 23 × 45 mm and a voltage not exceeding 2,8 V	0
0046	ex 8506 50 90 20	Unit consisting of not more than 2 lithium batteries embedded in a socket for integrated circuits (battery-buffered socket), with not more than 32 connections and incorporating a control circuit	0
0047	ex 8506 50 90 30	Lithium-iodine or lithium-silver vanadium oxide single cell battery of dimensions not exceeding 28 x 45 x 15 mm and a capacity of not less than 1,05 Ah	0
0048	ex 8507 30 91 20 ex 8507 80 91 10 ex 8507 80 99 10	Rectangular accumulator, with a length not exceeding 69 mm, a width not exceeding 36 mm and a thickness not exceeding 12 mm, for use in the manufacture of rechargeable batteries (a)	0
0049	ex 8507 30 91 30	Cylindrical nickel-cadmium accumulator, with a length of 65,3 mm (±1,5 mm) and a diameter of 14,5 mm (±1 mm), having a nominal capacity of 1 000 mAh or more, for use in the manufacture of rechargeable batteries (a)	0
0052	ex 8507 80 91 20	Cylindrical nickel-hydride accumulator, with a length of 44 mm (±0,5 mm) and a diameter of 10 mm (±0,5 mm), having a nominal capacity of 450 mAh or more, for use in the manufacture of rechargeable batteries (a)	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0053	ex 8507 80 91 30	Cylindrical nickel-hydride accumulator, with a length of 42,5 mm ($\pm 0,5$ mm) and a diameter of 14 mm ($\pm 0,5$ mm), having a nominal capacity of 855 mAh or more, for use in the manufacture of rechargeable batteries (a)	0
0054	ex 8507 80 91 40	Cylindrical nickel-hydride accumulator, with a length of 49,5 mm ($\pm 0,5$ mm) and a diameter of 10 mm ($\pm 0,5$ mm), having a nominal capacity of 540 mAh or more, for use in the manufacture of rechargeable batteries (a)	0
0055	ex 8507 80 91 50	Cylindrical nickel-hydride accumulator with a length of 66,5 mm (± 1 mm) and a diameter of 10 mm ($\pm 0,5$ mm), having a nominal capacity of 900 mAh or more, for use in the manufacture of rechargeable batteries (a)	0
0050	ex 8507 80 91 60	Cylindrical nickel-hydride accumulator, with a length of 67 mm ($\pm 0,5$ mm) and a diameter of 8,4 mm ($\pm 0,5$ mm), having a nominal capacity of 670 mAh or more, for use in the manufacture of rechargeable batteries (a)	0
0051	ex 8507 80 91 70	Cylindrical nickel-hydride accumulator, with a length of 55 mm (± 1 mm) and a diameter of 8,6 mm ($\pm 0,5$ mm), having a nominal capacity of 630 mAh or more, for use in the manufacture of rechargeable batteries (a)	0
0056	ex 8507 80 99 20	Cylindrical lithium-ion accumulator, with a length of 64,6 mm or more and a diameter of 18,1 mm or more, having a nominal capacity of 1 200 mAh or more, for use in the manufacture of rechargeable batteries (a)	0
0057	ex 8516 90 00 31	Dual diode, consisting of a power rectifying diode connected with a transformer protector diode through a wire, with a peak reverse power rate of 2 J or more, for use in the manufacture of products falling within subheading 8516 50 00 (a)	0
0058	ex 8518 29 80 20	Loudspeaker having a power of 5 W and an impedance of 4 ohms, with a diameter not exceeding 50 mm, for use in the manufacture of portable phones (a)	0
0059	ex 8518 30 80 20	Headphone and earphone for hearing aids, contained in a housing the exterior dimensions of which, excluding connecting points, do not exceed $5 \times 6 \times 8$ mm	0
0060	ex 8518 90 00 91	Integrally cold-upsetted steel coreplate, in the form of a disk on one side provided with a cylinder, for use in the manufacture of loudspeakers (a)	0
0061	ex 8520 90 90 20	Drive-unit capable of magneto-optical signal recording and optical signal reproducing, comprising at least an optical unit, DC motors and a printed circuit on which are mounted integrated circuits providing drive and signal processing functions for reading optical discs having an external diameter not exceeding 70 mm, not comprising circuits with amplification functions or power supply drive functions	0
0062	ex 8522 90 59 93	Optical unit consisting of a laser diode with one photodiode, emitting light of a nominal wavelength of 780 nm, contained in a housing with a diameter of not more than 10 mm and a height of not more than 9 mm, with not more than 10 connections and bearing: <ul style="list-style-type: none"> – an identification marking consisting of or including (one of) the following combination(s): LDGU LT 022 or – other identification markings relating to devices complying with the abovementioned description 	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0063	ex 8522 90 59 94	Electronic assembly for a laser read-head of a compact disc player, comprising: <ul style="list-style-type: none"> – a printed circuit, – a photo-detector, in the form of a monolithic integrated circuit, contained in a housing, – not more than 3 connectors, – not more than 1 transistor, – not more than 3 variable and 4 fixed resistors, – not more than 5 capacitors, the whole mounted on a support	0
0064	ex 8522 90 98 31	Thin-film recording and reproducing device, having at least 9 parallel channels for digital signals and at least 2 channels for analogue signals, to which a non-magnetic ceramic substrate is fixed, the whole rounded at one side, for use in the manufacture of magnetic heads for digital sound recording and digital/analogue sound reproducing apparatus of the cassette-type (a)	0
0065	ex 8522 90 98 32	Sound reproducing assembly, consisting of a disc mechanism with an optical reading system and DC motors, for use in the manufacture of products falling within subheading 8519 99, 8527 21 20 or 8527 21 70 (a)	0
0066	ex 8522 90 98 34	Cassette-deck sub-assembly for sound recording and reproducing apparatus, for use in the manufacture of telephone answering machines (a)	0
0067	ex 8522 90 98 35	Sound reproducing assembly, comprising a tape deck mechanism of the cassette type, comprising a DC motor, for use in the manufacture of products falling within heading No 8519 (a)	0
0068	ex 8522 90 98 36	Roll for magnetic tape guiding and winding, for use in the manufacture of products falling within heading No 8521 or 8522 (a)	0
0069	ex 8522 90 98 37	Magnetic head for erasing video tapes, for use in the manufacture of products falling within heading No 8521 or 8522 (a)	0
0070	ex 8522 90 98 38	Read-head assembly, comprising a laser read-head, 2 motors, a flexible printed circuit, the whole mounted on a plastic support, for use in the manufacture of products falling within subheading 8519 99 12 or 8519 99 18 (a)	0
0071	ex 8522 90 98 39	Assembly consisting of a driver circuit, a tacho-sensor and a brushless DC motor	0
0072	ex 8522 90 98 40	Compact disc changing and selection mechanism, comprising electronic components, not comprising circuits with amplification functions or power supply drive functions, for use in the manufacture of products falling within subheading 8527 31 91 (a)	0
0073	ex 8522 90 98 41	Assembly consisting of a drive-unit, comprising at least an optical unit, DC motors and a printed circuit on which are mounted integrated circuits providing drive and signal processing functions for reading optical discs, not capable of recording, for use in the manufacture of products falling within heading No 8521 (a)	0
0074	ex 8522 90 98 42	Sound reproducing assembly, consisting of a compact disc changing and selection mechanism, comprising an optical reading system, DC motors and an electronic assembly not comprising circuits with amplification functions or power drive functions, for use in the manufacture of products falling within heading No 8527 (a)	0
0075	ex 8522 90 98 43	Analogue sound recording and reproducing assembly, comprising a record/playback head and a twin tape deck mechanism of the cassette type, not comprising circuits with amplification functions or power supply drive functions, for use in the manufacture of products falling within subheadings 8527 31 91 and 8527 31 98 (a)	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0076	ex 8528 21 90 20	Colour video monitor having an operating voltage of not less than 10 V and not exceeding 35 V, comprising a liquid crystal display (LCD), whether or not contained in a housing	0
0077	ex 8528 22 00 10	Video monitor comprising: <ul style="list-style-type: none"> – a flat screen monochrome cathode-ray tube with a diagonal measurement of the screen not exceeding 110 mm and equipped with a deflector yoke, and – a printed circuit on which are mounted a deflection unit, a video-amplifier and a transformer, the whole mounted on a chassis, for the manufacture of video entry-phones, video telephones or surveillance apparatus (a)	0
0078	ex 8529 10 70 10	Ceramic filter package comprising 2 ceramic filters and 1 ceramic resonator for a frequency of 10,7 MHz (± 30 kHz), contained in a housing	0
0079	ex 8529 10 70 15	Ceramic filter for a centre frequency of 10,7 MHz, with a bandwidth not exceeding 330 kHz at 3 dB and not exceeding 950 kHz at 20 dB, contained in a housing	0
0080	ex 8529 10 70 20	Ceramic filters for frequencies of 4,5 MHz or more but not exceeding 6,6 MHz contained in a housing	0
0081	ex 8529 10 70 25	Ceramic filter for a centre frequency of 450 kHz or more but not exceeding 470 kHz, with a bandwidth not exceeding 13 kHz at 3 dB, contained in a housing	0
0082	ex 8529 10 70 30	Ceramic filter for a frequency of 450 kHz, with a bandwidth not exceeding 18 kHz at 10 dB, contained in a housing	0
0083	ex 8529 10 70 35	Ceramic filter for a centre frequency of 455 kHz ($\pm 1,5$ kHz), with a bandwidth not exceeding 25 kHz at 6 dB and not exceeding 60 kHz at 40 dB, contained in a housing	0
0084	ex 8529 10 70 45	Ceramic filter for a centre frequency of 450 kHz ($\pm 1,5$ kHz) or 455 kHz ($\pm 1,5$ kHz), with a bandwidth not exceeding 30 kHz at 6 dB and not exceeding 70 kHz at 40 dB, contained in a housing	0
0085	ex 8529 10 70 50	Radio frequency (RF) signal isolator for frequencies of 890 MHz or more but not exceeding 1 990 MHz, having an insertion loss not exceeding 0,7 dB, contained in a housing	0
0086	ex 8529 10 70 55	Filters, excluding surface acoustic wave filters, for a center frequency of 485 MHz or more but not exceeding 1 990 MHz with an insertion loss not exceeding 3,5 dB, contained in a housing	0
0087	ex 8529 10 70 80	Ceramic filter package, excluding surface acoustic wave filters, consisting of: <ul style="list-style-type: none"> – a transmit filter with a centre frequency of 1 747,5 MHz and an insertion loss not exceeding 2,3 dB at a bandwidth of 75 MHz and <ul style="list-style-type: none"> – a receive filter with a centre frequency of 1 842,5 MHz and an insertion loss not exceeding 3,3 dB at a bandwidth of 75 MHz, the whole contained in a housing	0
0088	ex 8529 10 70 85	Ceramic filter package, excluding surface acoustic wave filters, comprising 2 filters with one of the following combinations of characteristics: <ul style="list-style-type: none"> – a transmit centre frequency of 902,5 MHz, a receive centre frequency of 947,5 MHz and an insertion loss not exceeding 3,2 dB at a bandwidth of 25 MHz or <ul style="list-style-type: none"> – a transmit centre frequency of 1 747,5 MHz, a receive centre frequency of 1 842,5 MHz and an insertion loss not exceeding 3,5 dB at a bandwidth of 75 MHz, the whole contained in a housing	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0089	ex 8529 10 90 20	Antenna switch, comprising:- a transmit filter with a centre frequency of 942,5 MHz or more but not exceeding 1990 MHz and- a receive filter with a centre frequency of 847,5 MHz or more but not exceeding 1990 MHz, the whole contained in a housing	0
0090	ex 8529 90 81 31	Demagnetisation coil, with cables and connectors	0
0091	ex 8529 90 81 32	Optical unit for video projection, comprising a colour separation system, a positioning mechanism and lenses, for use in the manufacture of products falling within heading No 8528 (a)	0
0092	ex 8529 90 81 34	Assembly consisting of a lens unit, having an adjustable focal length of 4 mm or more but not exceeding 69 mm and comprising a zoom encoder, a stepping motor unit, a zoom motor unit, an iris motor unit and a photo interrupter	0
0093	ex 8529 90 81 35	Video recording and reproducing assembly, comprising a tape deck mechanism of the cassette type, comprising a DC motor, for use in the manufacture of products falling within heading No 8525 (a)	0
0094	ex 8529 90 81 36	Assembly consisting of a monochrome cathode-ray tube with a diagonal measurement of the screen of 143 mm or more but not exceeding 230 mm and a concave focus lens mounted on a liquid-filled cooling armature	0
0095	ex 8529 90 81 37 ex 8529 90 88 33	Filter, consisting of 2 piezo-electric crystals each with a frequency of 21 MHz or more but not exceeding 30 MHz and separately mounted on a bracket, with not more than 7 connections	0
0096	ex 8529 90 81 40	Assembly comprising prisms, digital micromirror device (DMD)-chips and electronic control circuits, for use in the manufacture of video projectors (a)	0
0097	ex 8529 90 81 41	Digital micromirror device (DMD)-chips, for use in the manufacture of video projectors (a)	0
0098	ex 8531 80 80 01	Indicator lamp, consisting of 4 light-emitting diodes made from silicon-carbide (SiC) semiconductor material, operating at a nominal wavelength of 481, 560 or 630 nm, contained in a housing	0
0099	ex 8531 80 80 15	Indicator lamp, consisting of 2 light-emitting diodes made from aluminium-gallium-arsenic (AlGaAs) or gallium-phosphor (GaP) semiconductor material, having a rectangular base, contained in a housing of the SMD (surface mounted device) type and having a lens	0
0100	ex 8531 80 80 25	Electro-acoustic transducer	0
0101	ex 8531 80 80 30	An electromagnetic display, consisting of 7 electromagnetic coils which by means of the residual magnetism in the stators provide that the last indication remains available (set state), and 7 pivoting light-reflecting segments each of which is attached to a bar magnet; assembly comprising such displays	0
0102	ex 8536 30 30 11 ex 8536 30 90 31 ex 8536 50 80 96	Thermo-electric switch with a cut-off current of 50 A or more, comprising a snap action switch, for direct mounting on an electric motor coil, contained in a hermetically sealed housing	0
0103	ex 8536 41 10 91 ex 8536 41 90 91 ex 8536 49 00 91	Thermal relays contained in a hermetically sealed glass cartridge not exceeding 35 mm in length excluding wires, with a maximum leakage rate of 10^{-6} cm ³ He/sec at one bar in the temperature range 0 to 160 °C, to be incorporated into compressors for refrigerating equipment (a)	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0104	ex 8536 50 11 31	Switch of the printed circuit mount type, operating at a force of 4,9 N ($\pm 0,9$ N), contained in a housing	0
0105	ex 8536 50 15 32	Rotary switch in form of a wheel with a diameter of between 15 and 16 mm and contacts for closing the circuit, for a rated voltage of 12 V at 50 mA	0
0106	ex 8536 50 19 91	Hall effect switch, comprising 1 magnet, 1 Hall effect sensor and 2 capacitors, contained in a housing with 3 connections and bearing: <ul style="list-style-type: none"> – an identification marking consisting of or including (one of) the following combination(s): 2AV28E 2AV31E 2AV56 or – other identification markings relating to devices complying with the abovementioned description 	0
0107	ex 8536 50 19 92	Hydraulic pressure switch, incorporating a pressure sensitive snap action disc, operating at a supply voltage of 6 V or more but not exceeding 18 V	0
0108	ex 8536 50 80 93	Switch unit for coaxial cable, comprising 3 electromagnetic switches, with a switching time not exceeding 50 ms and an actuating current not exceeding 500 mA at a voltage of 12 V	0
0109	ex 8536 50 80 95	Reed switch having a switching power of 20 W or more within the range of 17-43 A.turn, in the form of a glass capsule, not containing mercury, the dimensions of which do not exceed 3 × 21 mm, for use in the manufacture of automotive airbag shock-sensors (a)	0
0110	ex 8536 90 85 92	Metallic stamped frame with connections	0
0111	ex 8536 90 85 93	Contact element with a hold-force of more than 3 N, in the form of 2 rectangular plastic frames interconnected by electric conductors	0
0112	ex 8536 90 85 94 ex 8544 49 80 10	Elastomeric connector, consisting of one or more conductor elements and of a rubber or silicon substrate	0
0113	ex 8537 10 99 92	Touch sensitive screen panel, consisting of a conductive grid between two glass or plastic plates or sheets, fitted with electric conductors and connectors	0
0114	ex 8538 90 99 92	Part of an electrothermal fuse, consisting of a tin coated copper wire attached to a cylindrical casing, the exterior dimensions of which do not exceed 5 × 48 mm	0
0115	ex 8540 11 11 91	Colour cathode-ray tube with a slit or slot mask, equipped with electron guns placed side by side (in-line technology) and with a diagonal measurement of the screen of 12 cm or more but not exceeding 26 cm	0
0116	ex 8540 11 11 93	Colour cathode-ray tube, equipped with 1 gun with 3 rays and with a diagonal measurement of the screen of 22 cm or more but not exceeding 26 cm	0
0117	ex 8540 11 13 91	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,42 mm and a diagonal measurement of the screen of 49 cm, for use in the manufacture of professional video monitors including security and medical monitor applications (a)	0
0119	ex 8540 11 19 91	Colour cathode-ray tube equipped with electron guns placed side by side (in-line technology), with a diagonal measurement of the screen of 85 cm or more	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0120	ex 8540 11 91 31	Colour cathode-ray tube with a screen width/height ratio of 16/9 and a diagonal measurement of the screen of 39,8 cm ($\pm 0,3$ cm)	0
0121	ex 8540 11 99 31	Colour cathode-ray tube with a diagonal measurement of the screen of 85,5 cm or more	0
0122	ex 8540 12 00 82	Monochrome cathode-ray tube with a diagonal measurement of the screen of 250 mm or more but not exceeding 320 mm and an anode voltage of 18 kV or more but not exceeding 22 kV	0
0123	ex 8540 12 00 83	Monochrome cathode-ray tube, with a diagonal measurement of the screen of 150 mm or more but not exceeding 182 mm, a neck diameter of less than 30 mm and an anode voltage of 25 kV or more but not exceeding 32 kV	0
0124	ex 8540 12 00 84	Flat screen monochrome cathode-ray tube, with a diagonal measurement of the screen not exceeding 102 mm	0
0125	ex 8540 20 80 91	Photomultiplier consisting of a photocathode tube with 9 dynodes, for light of a wavelength of 160 nm or more but not exceeding 930 nm, of a diameter not exceeding 14 mm and a height not exceeding 94 mm	0
0126	ex 8540 40 00 31 ex 8540 60 00 31	Colour cathode-ray tube with a dot mask, equipped with 3 electron guns placed side by side (in-line technology) or 1 gun with 3 rays, with a diagonal measurement of the screen of more than 72 cm and a distance of less than 0,5 mm between dots of the same colour	0
0127	ex 8540 40 00 32 ex 8540 60 00 32	Colour cathode-ray tube with a dot mask, equipped with 3 electron guns placed side by side (in-line technology) or 1 gun with 3 rays, having a diagonal measurement of the screen not exceeding 72 cm	0
0128	ex 8540 40 00 33	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,35 mm and a diagonal measurement of the screen not exceeding 53 cm	0
0129	ex 8540 40 00 34	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,39 mm and a diagonal measurement of the screen of 33 cm or more but not exceeding 38 cm	0
0130	ex 8540 40 00 35	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,35 mm and a diagonal measurement of the screen not exceeding 72 cm, for use in the manufacture of monitors (a)	0
0131	ex 8540 40 00 36	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,30 mm and a diagonal measurement of the screen not exceeding 58 cm	0
0132	ex 8540 50 00 31 ex 8540 60 00 33	Flat screen monochrome cathode-ray tube, with a diagonal measurement of the screen of 142 mm or more but not exceeding 190 mm, a luminescence of 300 lumen or more but not exceeding 2 000 lumen, a resolution of 0,06 mm or more but not exceeding 0,1 mm, phosphor types P1 or P22 or P53 or P55 or P56, an anode voltage of more than 34 kV, a focus voltage of more than 7 kV and a cathode current of 3 mA or more	0
0133	ex 8540 50 00 32 ex 8540 60 00 34	Monochrome cathode-ray tube with a diagonal measurement of the screen of 176 mm or more but not exceeding 520 mm and a neck diameter not exceeding 21 mm	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0134	ex 8540 89 00 91	Displays in the form of a tube consisting of a glass housing mounted on a board the dimensions of which do not exceed 300 × 350 mm excluding leads. The tube contains one or more rows of characters or lines arranged in rows, each character or line consisting of fluorescent or phosphorescent elements. These elements are mounted on a metallised base which is covered with fluorescent substances or phosphorescent salts which give off light when bombarded with electrons	0
0135	ex 8540 89 00 92	Vacuum fluorescent display tube	0
0136	ex 8540 91 00 31	Electron gun, for use in the manufacture of colour cathode-ray tubes of subheading 8540 40 00 with a diagonal measurement of the screen of 34 cm or more but not exceeding 39 cm (a)	0
0137	ex 8540 91 00 32	Electron gun of colour cathode-ray tubes with an anode voltage of 27,5 kV or more but not exceeding 33 kV	0
0138	ex 8540 91 00 91	Deflector yoke for cathode-ray tubes with an operating frequency of 31 250 Hz or more but not exceeding 64 000 Hz, incorporating a quadripolar magnet	0
0139	ex 8540 91 00 92	Slit or slot mask, excluding masks with continuously vertical slits, with a diagonal measurement of 39 cm or less	0
0140	ex 8540 91 00 93	Electron gun for the production of monochrome cathode-ray tubes with a diagonal measurement of the screen of 7,6 cm or more but not exceeding 30,5 cm (a)	0
0141	ex 8540 91 00 94	Deflector yoke for colour cathode-ray tubes, with an operating frequency of 15 625 or 31 250 Hz, comprising 2 two-pole ring magnets, 2 four-pole ring magnets and 2 six-pole ring magnets	0
0142	ex 8540 91 00 96	Assembly for cathode-ray tubes with 2 or more but not more than 6 coils, a plastic support and a metal fixing ring, for the adjustment of display sharpness and/or convergence	0
0143	ex 8540 91 00 97	Slit mask, consisting of continuously vertical slits measuring more than 275 mm in the length	0
0144	ex 8540 91 00 98	Frame of molybdenum chrome steel, for use in the manufacture of cathode-ray tubes (a)	0
0145	ex 8540 99 00 91	Anode, cathode or output part, or an assembly comprising these components (magnetron core tube), for the manufacture of magnetrons of subheading 8540 71 00 (a)	0
0146	ex 8543 19 00 10	Electron beam accelerator systems, with an operating voltage not exceeding 1,5 MV and a beam current not exceeding 70 mA	0
0147	ex 8543 89 95 46	<p>Amplifier, consisting of active and passive elements mounted on a printed circuit, contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): FA 01314 MHW 2707 MHW 9002 PF 0144 PHW 902 FA 01317 MHW 607 MHW 910 PF 0146 PHW 925 FA 01321 MHW 704 MHW 914 PF 0148 SHW 5115 FMC 1717 MHW 707 MHW 915 PF 0412 XHW 105 FMC 1819 MHW 720 MHW 916 PHW 2905 XHW 2803 ISO 122 MHW 803 MHW 926 PHW 2907 XHW 2902 MHW 105 MHW 820-1 MHW 927 PHW 5113 XHW 5115 MHW 1815 MHW 820-2 MHW 953 PHW 9012 XHW 903 MHW 2701 or - other identification markings relating to devices complying with the abovementioned description 	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0148	ex 8543 89 95 48	Radio frequency (RF) modulator, operating with a frequency range of 43 MHz or more but not exceeding 870 MHz, capable of switching VHF and UHF signals, consisting of active and passive elements mounted on a printed circuit, contained in a housing	0
0149	ex 8543 89 95 49	Rectifier assembly of power barrier diodes, consisting of 2 diodes with an average forward current not exceeding 600 A and a repetitive reverse peak voltage not exceeding 40 V, each contained in a housing and connected by a common cathode	0
0150	ex 8543 89 95 50	Piezo-electric crystal clock oscillator with a fixed frequency, within a frequency range of 1,8 MHz to 67 MHz, contained in a housing bearing: <ul style="list-style-type: none"> – an identification marking consisting of or including (one of) the following combination(s): R4000.8 R4000.9 or – other identification markings relating to devices complying with the abovementioned description 	0
0151	ex 8543 89 95 51	Mechanical vibratory gyroscope driven by a 25 or 26 kHz oscillator, comprising a differential amplifier and a detector circuit, contained in a housing bearing: <ul style="list-style-type: none"> – an identification marking consisting of or including (one of) the following combination(s): ENC05D or – other identification markings relating to devices complying with the abovementioned description 	0
0152	ex 8543 89 95 52	Opto-electronic circuit comprising one or more light-emitting diodes (LEDs) and one photodiode with amplifier circuit and an integrated logic gate arrays circuit or one or more light-emitting diodes and at least 2 photodiodes with an amplifier circuit, contained in a plastic housing bearing: <ul style="list-style-type: none"> – an identification marking consisting of or including (one of) the following combination(s): HC PL 2400 HC PL 2730 or – other identification markings relating to devices complying with the abovementioned description 	0
0153	ex 8543 89 95 53	Oscillator, with a centre frequency of 20 GHz or more but not exceeding 42 GHz, consisting of active and passive elements not mounted on a substrate, contained in a housing bearing: <ul style="list-style-type: none"> – an identification marking consisting of or including (one of) the following combination(s): 372-02 372-03 or – other identification markings relating to devices complying with the abovementioned description 	0
0154	ex 8543 89 95 55	Audio recording and reproducing circuit, capable of stereo audio data storage and simultaneous record and playback, comprising 2 or 3 monolithic integrated circuits mounted on a printed circuit or a lead frame, contained in a housing bearing: <ul style="list-style-type: none"> – an identification marking consisting of or including (one of) the following combination(s): RWA010 RWA100 RWA200 RWA300 or – other identification markings relating to devices complying with the abovementioned description 	0
0155	ex 8543 89 95 56	Overvoltage suppression assembly, comprising 8 diodes, having a reverse stand-off voltage not exceeding 4,5 V, a reverse leakage current not exceeding 10 µA, a peak pulse current not exceeding 30 A and a nominal capacitance of 50 pF, contained in a housing	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0156	ex 8543 89 95 57	Frequency converter for the conversion of frequencies of 10,7 GHz or more but not exceeding 12,75 GHz to frequencies of 950 MHz or more but not exceeding 3 GHz and operating at a supply voltage of 11 V or more but not exceeding 20 V	0
0157	ex 8543 89 95 59	Charged coupled device (CCD) scanner assembly, for a real-time film scanning system, having optical functions, illumination functions and signal processing functions	0
0158	ex 8543 90 80 40	Stainless steel cathode in the form of a plate with a hanger bar and plastic side strips	0
0159	ex 8543 90 80 50	Assembly of products falling within heading No 8541 or 8542 mounted on a printed circuit, contained in a housing	0
0160	ex 8545 90 90 01	Cell and battery carbon, in the form of rods, with a length of 34 mm or more but not exceeding 160 mm and a diameter not exceeding 12 mm	0
0161	ex 8548 90 90 38	Parts, for use in the manufacture or the repair of products falling within subheading 8517 21 00 (a)	0
0162	ex 8548 90 90 39	Optical unit, consisting of a laserdiode and a photodiode, operating at a typical wavelength of 635 or 670 nm	0
0163	ex 8548 90 90 40	Infrared signal receiver unit, consisting of a photodiode and at least an amplifier in the form of a monolithic integrated circuit, contained in a housing bearing: <ul style="list-style-type: none"> – an identification marking consisting of or including (one of) the following combination(s): GPIU58XB SBX 1610 or – other identification markings relating to devices complying with the abovementioned description 	0
0164	ex 8548 90 90 41	Unit, consisting of a resonator operating within a frequency range of 1,8 MHz or more but not exceeding 40 MHz and a capacitor, contained in a housing	0
0165	ex 8548 90 90 42 ex 9110 90 00 94	Clock/calendar circuit, consisting of a printed circuit on which are mounted at least a quartz oscillator and a monolithic integrated circuit, the whole contained in a housing bearing: <ul style="list-style-type: none"> – an identification marking consisting of or including (one of) the following combination(s): DS 1287 DS 1387 MK 48T08 MK 48T18 RTC 65271 DS 12887A MK 48T02 MK 48T12 RTC 63421 RTC 72423 or – other identification markings relating to devices complying with the abovementioned description 	0
0166	ex 8548 90 90 43	Contact image sensor	0
0167	ex 8711 10 00 10 ex 8714 19 00 10	Portable motorised scooter disassembled kit (a)	0
0168	ex 9001 10 90 10	Image reverser made up from an assembly of optical fibres	0
0169	ex 9001 20 00 10	Material consisting of a polarising film, supported on one or both sides by transparent material	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0170	ex 9001 90 90 20	Rear projection screen, comprising a Fresnel lens of plastic and a polarising sheet of plastic, for use in the manufacture of products falling within heading No 8528 (a)	0
0171	ex 9001 90 90 30	Lens of plastic, unmounted, having a focal length of 3,86 mm ($\pm 0,1$ mm) and with a diameter not exceeding 8 mm, for use in the manufacture of compact disc players (a)	0
0172	ex 9001 90 90 40	Optical fibre plate, for use in the manufacture of screens and photocathodes for image intensifiers (a)	0
0173	ex 9001 90 90 50	Rear projection screen, comprising a lenticular plastic plate	0
0174	ex 9001 90 90 60	Prism for the splitting of light, unmounted, for use in the manufacture of charged-coupled image (CCD) cameras (a)	0
0175	ex 9001 90 90 70	Rod of neodymium-doped yttrium-aluminium garnet (YAG) material, polished at both ends	0
0176	ex 9001 90 90 80	Lens of plastic, unmounted, for use in the manufacture of products falling within subheading 9006 40 00 (a)	0
0177	ex 9002 11 00 10	Adjustable lens unit, having a focal length of 90 mm or more but not exceeding 180 mm and comprising a combination of between 4 and 8 glass or methacrylic lenses with a diameter of 120 mm or more but not exceeding 180 mm, each lens coated on at least one side with a magnesium fluoride layer, for use in the manufacture of video projectors (a)	0
0178	ex 9002 11 00 50	Lens unit, having a focal length of 25 mm or more but not exceeding 150 mm, consisting of glass or plastic lenses, with a diameter of 60 mm or more but not exceeding 190 mm	0
0179	ex 9002 11 00 60	Optical element, comprising one or more mounted lenses of plastic, for use in the manufacture of products falling within subheading 9006 40 00 (a)	0
0180	ex 9002 19 00 10	Lens unit, having a focal length of 24,96 mm ($\pm 0,1$ mm), a diameter of 16 mm and a length of 16 mm, for use in the manufacture of products falling within subheading 8517 21 00 (a)	0
0181	ex 9002 20 00 10	Filter, consisting of a plastic polarising membrane, a glass plate and a transparent protective film, mounted on a metal frame, for use in the manufacture of products falling within heading 8528 (a)	0
0182	ex 9002 90 90 20	Lens, mounted, having a fixed focal length of 3,8 mm ($\pm 0,19$ mm) or 8 mm ($\pm 0,4$ mm), with a relative aperture of F2.0 and a diameter not exceeding 33 mm, for use in the manufacture of charged-coupled (CCD) cameras (a)	0
0183	ex 9002 90 90 30	Optical unit, comprising 1 or 2 rows of optical glass fibres in the form of lenses and with a diameter of 0,85 mm or more but not exceeding 1,15 mm, embedded between 2 plastic plates	0
0184	ex 9002 90 90 50	Lens and image gate assembly, for a real-time film scanning system, comprising a lens consisting of 9 or 11 elements and having an illumination function	0
0185	ex 9006 91 90 10	Parts, for use in the manufacture of products falling within subheading 9006 40 00 (a)	0
0186	ex 9013 80 90 10	Polarisation insensitive fibre-optic isolator, operating at a wavelength of 1 200 nm or more, contained in a cylindrical housing	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0187	ex 9013 80 90 20	Optical switch, comprising at least one optical input and two optical outputs and with electrical connectors	0
0188	ex 9017 90 90 20	Thermal printer head, comprising at least 7 168 heater elements mounted on 2 or more ceramic supports, the whole contained in a housing the exterior dimensions of which exceed 21 × 39 × 639 mm	0
0189	ex 9022 30 00 10	X-ray tube with a target voltage of 4 kV or more but not exceeding 30 kV, a power not exceeding 9 W and a target current not exceeding 2 mA	0
0191	ex 9031 80 34 10 ex 9031 80 39 30 ex 9031 80 99 10	Machines and apparatus providing automated quality inspection of rigid magnetic disks, for use in the manufacture of products falling within subheading 8523 20 10 (a)	0
0190	ex 9031 80 34 20	Yaw rate sensor for measuring the angle and direction of rotation of motor vehicles, consisting of a housing with a single-crystal quartz	0
0193	ex 9031 80 39 10	Acceleration measurement device for automotive applications, comprising one or more active and/or passive elements and one or more sensors, the whole contained in a housing	0
0192	ex 9031 80 39 40	Machines and apparatus for the automatic testing of the integrity of ink-jet cartridge housings (a)	0
0194	ex 9031 90 80 20	Read and write test head for checking the quality of rigid magnetic disks, mounted on a carrier arm	0
0195	ex 9031 90 80 30	Assembly for a laser align sensor, in the form of a printed circuit comprising optical filters and a charge-coupled image (CCD) sensor, the whole contained in a housing	0
0196	ex 9031 90 80 40	Test head for checking the mechanical quality of rigid magnetic disks, mounted on a carrier arm	0
0197	ex 9031 90 80 50	Burnishing head, for removing asperities on and polishing of the surface of rigid magnetic disks, mounted on a carrier arm	0
0198	ex 9032 10 91 10	Thermostat, comprising a snap-action switch, for direct mounting on an electric motor coil, contained in a hermetically sealed housing	0
0199	ex 9032 89 90 10	Automotive airbag shock-sensor, comprising a contact capable of switching a current of 12 A at a voltage of 30 V, having a typical contact resistance of 80 mohm	0
0200	ex 9106 90 10 10	Timer assembly, for use in the manufacture of goods of subheading 8516 50 00 (a)	0
0201	ex 9110 12 00 91	Assembly consisting of a printed circuit on which are mounted one quartz oscillator, at least one watch circuit and, whether or not integrated, at least one capacitor, of a thickness not exceeding 5 mm	0
0202	ex 9110 90 00 92 ex 9114 90 00 91	Assembly consisting of a printed circuit on which is mounted a watch circuit or a watch circuit and a quartz oscillator, of a thickness not exceeding 5 mm	0
0203	ex 9110 90 00 93	Assembly consisting of a printed circuit on which is mounted at least one watch circuit, a quartz oscillator and a piezo-electric sound element, with a thickness exceeding 5 mm	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0204	ex 9608 91 00 10	Non-fibrous plastic pen-tips with an internal channel	0
0205	ex 9608 91 00 20	Felt tips and other porous-tips for markers, without internal canal	0
0206	ex 9612 10 10 10	Ribbons of plastic with segments of different colours, providing the penetration of dyes by heat into a support (so called dye-sublimation)	0
0207	ex 9613 90 00 20	Piezo-electric ignition mechanism	0

(a)	Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.
(b)	<p>The suspension shall apply to fish intended to undergo any operation unless they are intended to undergo exclusively one or more of the following operations:</p> <ul style="list-style-type: none"> – cleaning, gutting, tailing, heading, – cutting (excluding filleting or cutting of frozen blocks), – sampling, sorting, – labelling, – packing, – chilling, – freezing, – deep freezing, – thawing, separation. <p>The suspension is not allowed for products intended, in addition, to undergo treatment (or operations) qualifying for suspension where such treatment (or operations) is (are) carried out at retail or catering level. The suspension of customs duties shall apply only to fish intended for human consumption.</p>
(c)	Imports of these products shall only qualify for the suspension if the declared customs value is not lower than the reference price fixed or to be fixed in accordance with Article 29 of Council Regulation (EC) No 104/2000 of 17 December 1999 on the common organisation of the market in fishery and aquaculture products (OJ L 17, 21.1.2000, p. 22).
(d)	However, the suspension is not allowed where processing is carried out by retail or catering undertakings.

FINANCIAL STATEMENT

1. TITLE OF OPERATION

Proposal for a Council Regulation amending Regulation (EC) No 1255/96 temporarily suspending the autonomous common customs tariff duties on certain industrial, agricultural and fishery products.

2. BUDGET HEADING(S) INVOLVED

Chapter 12 Article 120.

3. LEGAL BASIS

Article 26 of the EC Treaty.

4. DESCRIPTION OF OPERATION

Suspension of the common customs tariff duties for the above products.

7. FINANCIAL IMPACT

In order to reduce the economic problems arising from the period of validity of previous Regulations, Council Regulation (EC) No 1255/96, now in force, does not have an expiry date.

This proposal contains only the amendments which must be made to the annex to the existing Regulation in order to take account of the following:

1. new requests for suspension which have been presented and accepted;
2. technical product developments and economic trends on the market resulting in the lifting of certain existing suspensions;
3. amendments to Nomenclature codes.

This time the amendments take the form of a consolidated annex.

Obviously only the amendments described in 1 and 2 have a financial impact.

Addition

This Annex, in addition to the amendments resulting from changes to CN codes, contains 39 new products. The uncollected duties corresponding to these suspensions, calculated on the basis of expected imports into the requesting Member State for 2002, total MEUR 8.7.

On the basis of the existing statistics for the preceding years, it would appear, however, that this amount must be increased by an average factor, estimated at 1.8, to take account of imports into other Member States using the same suspensions. This means a **loss of revenue of some MEUR 15.7**.

Withdrawal:

2 products have been withdrawn from this annex reflecting the reintroduction of customs duties. This represents **an increase of MEUR 0.5 in resources**, as calculated from requests for suspension or available statistics (2000).

Estimated cost of this operation

Taking available statistics (2000) as a basis, the impact on the loss of revenue resulting from this Regulation may therefore be estimated at **15.7 - 0.5 = MEUR 15.2**, then an increase of loss of revenue, with a **total loss estimated for 2002 of 635.3 + 15.2 = MEUR 650.5**.

The shortfall in traditional own resources will have to be made up by the Member States by topping up the GNP component.

8. FRAUD PREVENTION MEASURES

Checks on the end-use of some of the products covered by this Council Regulation will be carried out in accordance with Articles 291 to 300 of Commission Regulation (EEC) No 2454/93 laying down provisions for the implementation of the Community Customs Code.