



COMMISSION OF THE EUROPEAN COMMUNITIES

Brussels, 1.12.2006
COM(2006) 750 final

Proposal for a

COUNCIL REGULATION

**amending Regulation (EC) No 1255/96 temporarily suspending the autonomous
common customs tariff duties on certain industrial, agricultural and fishery products**

(presented by the Commission)

EXPLANATORY MEMORANDUM

1) CONTEXT OF THE PROPOSAL

- **Grounds for and objectives of the proposal**

The Commission, assisted by the Economic Tariff Questions Group, has reviewed all the requests for temporary suspension of autonomous common customs tariff duties presented to it by the Member States. The attached proposal concerns certain industrial, agricultural and fishery products. Requests for suspension relating to the above products were examined in the light of the criteria set out in the communication from the Commission concerning autonomous tariff suspensions and quotas (see OJ C 128, 25.4.1998, p. 2). Following this review, the Commission considers that the suspension or the reduction of duties is justified for the products listed in the Annex to the attached proposal for a Regulation. Products for which suspension is no longer in the Community's economic interests have been withdrawn. The annex to this Regulation lists the products for which suspension is proposed, or for which the wording has to be changed. The validity period of the measure is limited, in order to carry out economic examinations of the individual suspensions in this period. The suspensions, whose cancellation or continuation is considered necessary by the Commission and Economic Tariff Questions Group shall be extended or deleted after this date.

- **General context**

It is in the interest of the Community to suspend partially or totally the autonomous common customs tariff duties for a number of new products not listed in the Annex to Council Regulation (EC) No 1255/96 temporarily suspending the autonomous common customs tariff duties on certain industrial, agricultural and fishery products.

- **Existing provisions in the area of the proposal**

OJ L 158, 29.6.1996, p. 1. Regulation last amended by Regulation (EC) No 963/2006 (OJ L 176, 30.06.2006, p. 3).

- **Consistency with the other policies and objectives of the Union**

In line with agricultural, trade, enterprise, development and external relations policies. Especially this proposal is not at the expense of developing countries enjoying a preferential trading agreement with the EU (e.g. GSP, ACP regime).

2) CONSULTATION OF INTERESTED PARTIES AND IMPACT ASSESSMENT

- **Consultation of interested parties**

Consultation methods, main sectors targeted and general profile of respondents

The Economic Tariff Questions Group representing the industries of each Member State was consulted.

Summary of responses and how they have been taken into account

All listed suspensions correspond to the agreement of the discussions inside the group.

- **Collection and use of expertise**

Scientific/expertise domains concerned

Experts representing the MS on the Economic Tariff Questions Group

Methodology used

Open consultation

Main organisations/experts consulted

Experts designated by each of the MS

Summary of advice received and used

The existence of potentially serious risks with irreversible consequences has not been mentioned.

Means used to make the expert advice publicly available

Publication of the Proposal

- **Impact assessment**

Not applicable

Proposal not included in the Commission's Working and Legislative Programme 2006

3) LEGAL ELEMENTS OF THE PROPOSAL

- **Summary of the proposed action**

Proposal for a Council Regulation amending Regulation (EC) No 1255/96 temporarily suspending the autonomous common customs tariff duties on certain industrial, agricultural and fishery products

- **Legal basis**

Art 26

- **Subsidiarity principle**

The proposal falls under the exclusive competence of the Community. The subsidiarity principle therefore does not apply.

- **Proportionality principle**

The proposal complies with the proportionality principle for the following reason(s).

The proposed measures are in accordance with the objectives of the "Customs 2007" action programme.

This set of measures is in line with the principles set out to simplify the procedures for the operators engaged in foreign trade and in accordance with the Commission communication concerning autonomous tariff suspensions and quotas.

- **Choice of instruments**

Proposed instruments: regulation.

Other means would not be adequate for the following reason(s).

By virtue of Article 26 of the EC Treaty autonomous tariff suspensions and quotas are approved by the Council acting on a qualified majority on the basis of a Commission proposal.

4) BUDGETARY IMPLICATION

Uncollected customs duties

5) ADDITIONAL INFORMATION

- **Simplification**

The proposal provides for simplification of legislation.

In the annex of the proposed regulation a consolidated list of all duty suspensions will be published, therefore it is no longer necessary to consult more than one regulation to find a certain measure.

Proposal for a

COUNCIL REGULATION

amending Regulation (EC) No 1255/96 temporarily suspending the autonomous common customs tariff duties on certain industrial, agricultural and fishery products

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty establishing the European Community, and in particular Article 26 thereof,

Having regard to the proposal from the Commission¹,

Whereas:

- (1) It is in the interest of the Community to suspend partially or totally the autonomous common customs tariff duties for a number of new products not listed in the Annex to Council Regulation (EC) No 1255/96².
- (2) A number of products which are referred to in the said Regulation should be withdrawn from the list in the Annex to that regulation because it is no longer in the Community's interest to maintain suspension of autonomous common customs tariff duties or because the description needs to be altered in order to take account of technical product developments and economic trends on the market.
- (3) Accordingly, products whose description needs to be altered should be regarded as new products.
- (4) For ease of comprehension, in view of the large number of amendments coming into force on 1 January 2007, the Annex to Regulation (EC) No 1255/96 should be replaced by a completely new version with effect from that date.
- (5) The validity period of the measure should be limited, in order to be able to carry out economic examinations of the individual suspensions in this period. Experience has shown the necessity to provide for an expiry date to the suspensions listed in Regulation (EC) No 1255/96 to ensure that account is taken of technological and economic changes. This should not exclude the premature termination of certain measures or their continuation beyond this period, if economic reasons are submitted, in accordance with the principles laid down in the Commission Communication concerning autonomous tariff suspensions and quotas³.

¹ OJ C[],[],p.[]

² OJ L 158, 29.6.1996, p. 1. Regulation as last amended by Regulation (EC) No 963/2006 (OJ L 176, 30.6.2006, p. 3).

³ OJ C128, 25.4.1998, p.2.

- (6) Regulation (EC) No 1255/96 should therefore be amended accordingly.
- (7) Since this Regulation is to apply from 1 January 2007, it should enter into force immediately,

HAS ADOPTED THIS REGULATION:

Article 1

The Annex to Regulation (EC) No 1255/96 is replaced by the Annex to this Regulation.

Article 2

The temporary suspensions of the autonomous duties of the Common customs tariff for the products set out in the Annex shall apply from 1 January 2007. They shall expire on the dates listed in that Annex.

Article 3

This Regulation shall enter into force on the day of its publication in the *Official Journal of the European Union*.

It shall apply from 1 January 2007.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels, [...]

For the Council
The President

ANNEX

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 0302 69 99	10	Sturgeons, fresh, chilled or frozen, for processing (1) (2)	0 %	1.1.2007 - 31.12.2008
ex 0303 79 98	10			
ex 0302 69 99	20	Lump fish (<i>Cyclopterus lumpus</i>) with roe, fresh or chilled, for processing (1)	0 %	1.1.2007 - 31.12.2008
ex 0302 69 99	30	Red snapper (<i>Lutjanus purpureus</i>), fresh, chilled or frozen, for processing (1) (3)	0 %	1.1.2007 - 31.12.2008
ex 0303 79 98	20			
ex 0302 70 00	11	Hard fish roes, fresh, chilled or frozen	0 %	1.1.2007 - 31.12.2008
ex 0302 70 00	31			
ex 0302 70 00	41			
ex 0302 70 00	82			
ex 0302 70 00	83			
ex 0302 70 00	84			
ex 0302 70 00	89			
ex 0303 80 90	10			
ex 0303 80 90	19			
ex 0303 11 00	12	Pacific salmon (<i>Oncorhynchus spp.</i>), frozen and headless, for the processing industry for manufacture into pastes or spreads (1)	0 %	1.1.2007 - 31.12.2008
ex 0303 11 00	18			
ex 0303 19 00	12			
ex 0303 19 00	18			
ex 0304 19 39	45	Fillets and meat of dogfish (<i>Squalus acanthias</i>), fresh, chilled or frozen	6 %	1.1.2007 - 31.12.2008
ex 0304 19 99	60			
ex 0304 29 61	10			
ex 0304 99 99	21			
ex 0305 20 00	11	Hard fish roes, salted or in brine	0 %	1.1.2007 - 31.12.2008
ex 0305 20 00	18			

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 0305 20 00	19			
ex 0305 20 00	21			
ex 0305 20 00	30			
ex 0306 19 90	10	Krill for processing (1)	0 %	1.1.2007 - 31.12.2008
ex 0306 29 90	10			
ex 0603 90 00	10	Flowers, flower buds, foliage, leaves and other parts of plants, not further prepared than dried, dyed or bleached, for use in the manufacture of pot pourri of subheading 3307 49 00 (1)	0 %	1.1.2007 - 31.12.2008
ex 0604 99 90	10			
ex 0710 21 00	10	Peas in pods, of the species <i>Pisum sativum</i> of the variety <i>Hortense axiphium</i> , frozen, of a thickness not exceeding 6 mm, to be used, in their pods, in the manufacture of prepared meals (1) (3)	0 %	1.1.2007 - 31.12.2008
ex 0710 80 95	50	Bamboo shoots, frozen, not put up for retail sale	0 %	1.1.2007 - 31.12.2008
ex 0711 59 00	11	Mushrooms, excluding mushrooms of the genera <i>Agaricus</i> , <i>Calocybe</i> , <i>Clitocybe</i> , <i>Lepista</i> , <i>Leucoagaricus</i> , <i>Leucopaxillus</i> , <i>Lyophyllum</i> and <i>Tricholoma</i> , provisionally preserved in brine, in sulphur water, or in other preservative solutions, but unsuitable in that state for immediate consumption, for the food-canning industry (1)	0 %	1.1.2007 - 31.12.2011
ex 0712 32 00	10	Mushrooms, excluding mushrooms of the genus <i>Agaricus</i> , dried, whole or in identifiable slices or pieces, for treatment other than simple repacking for retail sale (1) (3)	0 %	1.1.2007 - 31.12.2008
ex 0712 33 00	10			
ex 0712 39 00	31			
ex 0804 10 00	10	Dates, fresh or dried, not put up for retail sale	0 %	1.1.2007 - 31.12.2008
ex 0810 40 50	10	Fruit of the species <i>Vaccinium macrocarpon</i> , fresh	0 %	1.1.2007 - 31.12.2008
ex 0810 90 95	10	Rose-hips, fresh	0 %	1.1.2007 - 31.12.2008
0811 90 50		Fruit of the genus <i>Vaccinium</i> , uncooked or cooked by steaming or boiling in water, frozen, not containing added sugar or other sweetening matter	0 %	1.1.2007 - 31.12.2008
0811 90 70				
ex 0811 90 95	69			

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 0811 90 95	20	Boysenberries, frozen, not containing added sugar, not put up for retail sale	0 %	1.1.2007 - 31.12.2008
ex 0811 90 95	30	Pineapple (<i>Ananas comosus</i>), in pieces, frozen	0 %	1.1.2007 - 31.12.2008
ex 0811 90 95	40	Rose-hips, uncooked or cooked by steaming or boiling in water, frozen, not containing added sugar or other sweetening matter	0 %	1.1.2007 - 31.12.2008
ex 1511 90 19	10	Palm oil, coconut (copra) oil, palm kernel oil, for the manufacture of:	0 %	1.1.2007 - 31.12.2008
ex 1511 90 91	10	— industrial monocarboxylic fatty acids of subheading 3823 19 10,		
ex 1513 11 10	10	— mixtures of methyl esters of fatty acids of subheading 3824 90 98,		
ex 1513 19 30	10	— methyl esters of fatty acids of heading 2915 or 2916,		
ex 1513 21 10	10	— stearic acid of subheading 3823 11 00 or		
ex 1513 29 30	10	— goods of heading No 3401		
		(1)		
ex 1515 90 99	92	Vegetable oil, refined, containing by weight 35 % or more but not more than 50 % of arachidonic acid or 35 % or more but not more than 50 % of docosahexaenoic acid	0 %	1.1.2007 - 31.12.2008
ex 1517 90 99	10	Vegetable oil, refined, containing by weight 35 % or more but not more than 50 % arachidonic acid or 35 % or more but not more than 50 % docosahexaenoic acid and standardized with high oleic sunflower oil (HOSO)	0 %	1.1.2007 - 31.12.2011
ex 1518 00 91	10	Soya-bean oil, modified with maleic acid, for the manufacture of cosmetic products (1)	0 %	1.1.2007 - 31.12.2008
ex 1604 11 00	20	Pacific salmon (<i>Oncorhynchus spp.</i>), for the processing industry for manufacture into pastes or spreads (1)	0 %	1.1.2007 - 31.12.2008
ex 1604 20 10	20			
ex 1604 30 90	10	Hard fish roes, washed, cleaned of adherent organs and simply salted or in brine, for processing (1)	0 %	1.1.2007 - 31.12.2008
ex 1605 10 00	11	Crabs of the species "King" (<i>Paralithodes camchaticus</i>), "Hanasaki" (<i>Paralithodes brevipes</i>), "Kegani" (<i>Erimacrus isenbecki</i>), "Queen" and	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 1605 10 00	19	"Snow" (<i>Chionoecetes spp.</i>), "Red" (<i>Geryon quinquedens</i>), "Rough stone" (<i>Neolithodes asperrimus</i>), <i>Lithodes antarctica</i> , "Mud" (<i>Scylla serrata</i>), "Blue" (<i>Portunus spp.</i>), simply boiled in water and shelled, whether or not frozen, in immediate packings of a net content of 2 kg or more		
ex 1605 10 00	92	Crabs of the species <i>Paralomis granulosa</i>	0 %	1.1.2007 - 31.12.2008
ex 1605 10 00	94			
ex 1902 30 10	10	Transparent noodles, cut in pieces, obtained from beans (<i>Vigna radiata</i> (L.) Wilczek), not put up for retail sale	0 %	1.1.2007 - 31.12.2008
ex 1903 00 00	20			
ex 2005 91 00	10	Bamboo shoots, prepared or preserved, in immediate packings of a net content exceeding 5 kg	0 %	1.1.2007 - 31.12.2008
ex 2106 10 20	10	Soya protein isolate, containing by weight 6,6 % or more but not more than 8,6 % of calcium phosphate	0 %	1.1.2007 - 31.12.2008
ex 2309 90 99	20	Calcium sodium phosphate, with a fluorine content of 0,005 % or more but less than 0,2 % by weight on the dry anhydrous product, for use in the manufacture of additives for animal feeding (1)	0 %	1.1.2007 - 31.12.2008
ex 2707 99 11	10	Crude light oils containing by weight: <ul style="list-style-type: none"> — 10 % or more of vinyltoluenes, — 10 % or more of indene and — 1 % or more but not more than 5 % of naphthalene 	0 %	1.1.2007 - 31.12.2008
ex 2710 11 25	10	Mixture of isomers 2,4,4-trimethylpent-1-ene and 2,4,4-trimethylpent-2-ene	0 %	1.1.2007 - 31.12.2008
ex 2805 30 10	10	Alloy of cerium and other rare-earth metals, containing by weight 47 % or more of cerium	0 %	1.1.2007 - 31.12.2008
ex 2805 30 10	20	Alloy of lanthanum and other rare-earth metals, containing by weight 43 % or more of lanthanum	0 %	1.1.2007 - 31.12.2008
ex 2805 30 90	10	Lanthanum of a purity by weight of 99 % or more	0 %	1.1.2007 - 31.12.2008
ex 2811 19 80	10	Sulfamidic acid	0 %	1.1.2007 - 31.12.2008
ex 2811 22 00	10	Silicon dioxide in the form of powder, for use in the manufacture of high performance liquid chromatography columns (HPLC) and sample	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		preparation cartridges (1)		
ex 2811 29 90	10	Tellurium dioxide	0 %	1.1.2007 - 31.12.2008
ex 2812 90 00	10	Nitrogen trifluoride	0 %	1.1.2007 - 31.12.2008
ex 2812 90 00	20	Silicon tetrafluoride	0 %	1.1.2007 - 31.12.2008
ex 2818 30 00	10	Aluminium hydroxide oxide in the form of pseudo-boehmite	4 %	1.1.2007 - 31.12.2008
2819 10 00		Chromium trioxide	0 %	1.1.2007 - 31.12.2011
ex 2819 90 90	10	Dichromium trioxide: — of a specific surface of 37 m ² /g or more (as determined by the BET method), — of a purity by weight of 99,5 % or more calculated on the dry substance, — of a specific gravity of 1,2 g/cm ³ or less, for the manufacture of magnetic chromium dioxide (1)	0 %	1.1.2007 - 31.12.2008
ex 2820 90 90	10	Manganese (II,III) oxide containing by weight 70 % or more of manganese	0 %	1.1.2007 - 31.12.2008
ex 2821 10 00	10	Diiron trioxide, in the form of powder, of a purity by weight of 99,2 % or more, for the manufacture of goods of heading No 8504 (1)	0 %	1.1.2007 - 31.12.2008
ex 2823 00 00	10	Titanium dioxide, of a purity by weight of 99,9 % or more, with an average grain-size of 1,2 µm or more but not exceeding 1,8 µm, for the manufacture of goods of heading No 8532 or 8533 (1)	0 %	1.1.2007 - 31.12.2008
ex 2825 50 00	10	Copper (I or II) oxide containing by weight 78 % or more of copper and not more than 0,03 % of chloride	0 %	1.1.2007 - 31.12.2008
ex 2826 90 80	10	Potassium hexafluorophosphate	0 %	1.1.2007 - 31.12.2008
ex 2827 39 85	10	Copper monochloride of a purity by weight of 96 % or more but not exceeding 99 %	0 %	1.1.2007 - 31.12.2008
ex 2827 60 00	10	Titanium tetraiodide	0 %	1.1.2007 - 31.12.2008
ex 2830 10 00	10	Disodium tetrasulfide, containing by weight 38 % or less of sodium calculated on the dry weight	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2830 90 85	10	Zinc sulfide containing: — 20,0 mg/kg or less of chloride, — 0,2 mg/kg or less of copper, — 0,5 mg/kg or less of iron and — 1,0 mg/kg or less of lead	0 %	1.1.2007 - 31.12.2008
ex 2833 29 90	10	Manganese sulphate monohydrate	0 %	1.1.2007 - 31.12.2008
ex 2836 91 00	20	Lithium carbonate, containing one or more of the following impurities at the concentrations indicated: — 2 mg/kg or more of arsenic, — 200 mg/kg or more of calcium, — 200 mg/kg or more of chlorides, — 20 mg/kg or more of iron, — 150 mg/kg or more of magnesium, — 20 mg/kg or more of heavy metals, — 300 mg/kg or more of potassium, — 300 mg/kg or more of sodium, — 200 mg/kg or more of sulfates, determined according to the methods specified in the European Pharmacopœia	0 %	1.1.2007 - 31.12.2008
ex 2836 99 17	10	Zirconium (IV) basic carbonate	0 %	1.1.2007 - 31.12.2008
ex 2837 19 00	10	Zinc cyanide	0 %	1.1.2007 - 31.12.2008
ex 2837 19 00	20	Copper cyanide	0 %	1.1.2007 - 31.12.2008
ex 2837 20 00	10	Tetrasodium hexacyanoferrate (II)	0 %	1.1.2007 - 31.12.2011
ex 2839 90 90	10	Lead silicate hydrate, of a lead content by weight of $(84,5 \pm 1,5)$ %, evaluated as lead monoxide, in the form of powder	0 %	1.1.2007 - 31.12.2008
ex 2839 90 90	20	Calcium silicate	0 %	1.1.2007 - 31.12.2008
ex 2842 90 80	10	Ammonium sulfamidate	0 %	1.1.2007 - 31.12.2008
ex 2843 29 00	10	Silver oxide, nitrate- and carbonate-free, with a silver content of at least 99,99 % by weight of the metal content, for the manufacture of silver oxide batteries (1)	0 %	1.1.2007 - 31.12.2011
ex 2843 90 90	20	Palladium monoxide	0 %	1.1.2007 - 31.12.2008
ex 2843 90 90	30	Mixture of palladium phthalocyanines	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
2845 10 00		Heavy water (deuterium oxide) (<i>Euratom</i>)	0 %	1.1.2007 - 31.12.2008
2845 90 10		Deuterium and compounds thereof; hydrogen and compounds thereof, enriched in deuterium; mixtures and solutions containing these products (<i>Euratom</i>)	0 %	1.1.2007 - 31.12.2008
ex 2846 10 00	10	Rare-earth concentrate containing by weight 60 % or more but not more than 95 % of rare-earth oxides and not more than 1 % each of zirconium oxide, aluminium oxide or iron oxide, and having a loss on ignition of 5 % or more by weight	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	48			
ex 2846 10 00	20	Dicerium tricarbonat, whether or not hydrated	0 %	1.1.2007 - 31.12.2008
ex 2846 10 00	30	Cerium lanthanum carbonate, whether or not hydrated	0 %	1.1.2007 - 31.12.2008
ex 2846 10 00	40	Cerium lanthanum neodymium praseodymium carbonate, whether or not hydrated	0 %	1.1.2007 - 31.12.2008
2846 90 00		Compounds, inorganic or organic, of rare-earth metals, of yttrium or of scandium or of mixtures of these metals, other than those of subheading 2846 10 00	0 %	1.1.2007 - 31.12.2008
ex 2848 00 00	10	Phosphine	0 %	1.1.2007 - 31.12.2008
ex 2850 00 20	10	Silane	0 %	1.1.2007 - 31.12.2008
ex 2850 00 20	20	Arsine	0 %	1.1.2007 - 31.12.2008
ex 2903 39 90	10	Carbon tetrafluoride (tetrafluoromethane)	0 %	1.1.2007 - 31.12.2008
ex 2903 39 90	20	1,1,1,2,3,3,3-Heptafluoropropane	0 %	1.1.2007 - 31.12.2008
ex 2903 39 90	30	Perfluoroethane	0 %	1.1.2007 - 31.12.2008
ex 2903 39 90	40	1,1-Difluoroethane	0 %	1.1.2007 - 31.12.2008
ex 2903 39 90	50	1,1,1,3,3-Pentafluoropropane	0 %	1.1.2007 - 31.12.2008
ex 2903 39 90	70	1,1,1,2 Tetrafluoroethane, certified odourless containing a maximum : — 600 ppm by weight of 1,1,2,2-Tetrafluoroethane, — 2 ppm by weight of pentafluoroethane,	0 %	1.1.2007 - 31.12.2011

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		<ul style="list-style-type: none"> — 2 ppm by weight of chlorodifluoromethane, — 2 ppm by weight of chloropentafluoroethane, — 2 ppm by weight of dichlorodifluoromethane <p>For use in the manufacture of pharmaceutical grade propellant for medical metred dose inhalers (1)</p>		
ex 2903 39 90	80	Hexafluoropropene	0 %	1.1.2007 - 31.12.2011
ex 2903 43 00	10	1,1,1-Trichlorotrifluoroethane	0 %	1.1.2007 - 31.12.2008
ex 2903 49 10	10	Chloro-1,1,1-trifluoroethane	0 %	1.1.2007 - 31.12.2008
ex 2903 49 80	20	1-Bromo-3-chloropropane	0 %	1.1.2007 - 31.12.2011
ex 2903 59 80	10	1,6,7,8,9,14,15,16,17,17,18,18-Dodecachloropentacyclo [12.2.1.1 ^{6,9} .0 ^{2,13} .0 ^{5,10}]octadeca-7,15-diene	0 %	1.1.2007 - 31.12.2008
ex 2903 59 80	20	Hexachlorocyclopentadiene	0 %	1.1.2007 - 31.12.2008
ex 2903 59 80	30	Octafluorocyclopentene	0 %	1.1.2007 - 31.12.2011
ex 2903 69 90	10	Di- or tetrachlorotricyclo[8.2.2.2 ^{4,7}]hexadeca-1(12),4,6,10,13,15-hexaene, mixed isomers	0 %	1.1.2007 - 31.12.2008
ex 2903 69 90	20	1,2-Bis(pentabromophenyl)ethane	0 %	1.1.2007 - 31.12.2008
ex 2903 69 90	40	2,6-Dichlorotoluene, of a purity by weight of 99 % or more and containing: <ul style="list-style-type: none"> — 0,001 mg/kg or less of tetrachlorodibenzodioxines, — 0,001 mg/kg or less of tetrachlorodibenzofurans, — 0,2 mg/kg or less of tetrachlorobiphenyls 	0 %	1.1.2007 - 31.12.2008
ex 2903 69 90	50	1-(Chloromethyl)naphthalene	0 %	1.1.2007 - 31.12.2008
ex 2903 69 90	60	α -Chloro(ethyl)toluenes	0 %	1.1.2007 - 31.12.2008
ex 2904 10 00	30	Sodium <i>p</i> -styrenesulfonate	0 %	1.1.2007 - 31.12.2008
ex 2904 20 00	10	Nitromethane	0 %	1.1.2007 - 31.12.2008
ex 2904 20 00	20	Nitroethane	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2904 20 00	30	1-Nitropropane	0 %	1.1.2007 - 31.12.2008
ex 2904 20 00	40	2-Nitropropane	0 %	1.1.2007 - 31.12.2008
ex 2904 20 00	50	2,2'-Dinitro-bibenzyl	0 %	1.1.2007 - 31.12.2008
ex 2904 90 20	10	Tosyl chloride	0 %	1.1.2007 - 31.12.2008
ex 2904 90 40	10	Trichloronitromethane, for the manufacture of goods of subheading 3808 92 (1)	0 %	1.1.2007 - 31.12.2008
ex 2904 90 85	10	Quintozene (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2904 90 85	20	1-Chloro-2,4-dinitrobenzene	0 %	1.1.2007 - 31.12.2008
ex 2904 90 85	30	5-Nitro-1,2,4-trichlorobenzene	0 %	1.1.2007 - 31.12.2008
ex 2904 90 85	40	3-Bromo-5-nitro-trifluoromethyl benzene	0 %	1.1.2007 - 31.12.2008
ex 2905 19 00	11	Potassium <i>tert</i> -butanolate (potassium <i>tert</i> -butoxide), whether or not in the form of a solution in tetrahydrofuran	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	56			
ex 2905 19 00	30	2,6-Dimethylheptan-4-ol	0 %	1.1.2007 - 31.12.2008
ex 2905 39 85	20	Hexa-1,5-diene-3,4-diol	0 %	1.1.2007 - 31.12.2008
ex 2905 49 10	10	Ethylidynetrimethanol	0 %	1.1.2007 - 31.12.2008
2906 11 00		Menthol	0 %	1.1.2007 - 31.12.2008
ex 2906 19 00	10	Cyclohex-1,4-ylenedimethanol	0 %	1.1.2007 - 31.12.2008
ex 2906 19 00	20	4,4'-Isopropylidenedicyclohexanol	0 %	1.1.2007 - 31.12.2008
ex 2906 29 00	10	2,2'-(<i>m</i> -Phenylene)dipropan-2-ol	0 %	1.1.2007 - 31.12.2008
ex 2906 29 00	20	1-Hydroxymethyl-4-methyl-2,3,5,6-tetrafluorobenzene	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2907 19 90	10	2,3,5-Trimethylphenol	0 %	1.1.2007 - 31.12.2008
ex 2907 21 00	10	Resorcinol	0 %	1.1.2007 - 31.12.2008
ex 2907 29 00	10	Disodium 1,4-dihydroanthracene-9,10-diolate, in the form of an aqueous solution	0 %	1.1.2007 - 31.12.2008
ex 2907 29 00	20	4,4'-(3,3,5-Trimethylcyclohexylidene)diphenol	0 %	1.1.2007 - 31.12.2008
ex 2907 29 00	30	4,4',4''-Ethylidynetriphenol	0 %	1.1.2007 - 31.12.2008
ex 2907 29 00	40	Mixture of isomers of methylenediphenol	0 %	1.1.2007 - 31.12.2008
ex 2907 29 00	50	6,6',6''-Tricyclohexyl-4,4',4''-butane-1,1,3-triyltri(<i>m</i> -cresol)	0 %	1.1.2007 - 31.12.2008
ex 2907 29 00	60	4,4'-(1,3-Phenylenediisopropylidene)diphenol	0 %	1.1.2007 - 31.12.2008
ex 2907 29 00	70	2,2',2'',6,6',6''-Hexa- <i>tert</i> -butyl- <i>α,α',α''</i> -(mesitylene-2,4,6-triyl)tri- <i>p</i> -cresol	0 %	1.1.2007 - 31.12.2008
ex 2907 29 00	80	Pyrogallol	0 %	1.1.2007 - 31.12.2008
ex 2907 29 00	85	Phloroglucinol whether or not hydrated	0 %	1.1.2007 - 31.12.2008
ex 2908 99 10	10	Disodium 3-hydroxynaphthalene-2,7-disulfonate	0 %	1.1.2007 - 31.12.2008
ex 2908 99 10	20	Dipotassium 7-hydroxynaphthalene-1,3-disulfonate	0 %	1.1.2007 - 31.12.2008
ex 2908 99 10	30	6-Hydroxynaphthalene-2-sulfonic acid and its salts	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	74			
ex 2908 99 90	10	4-Nitroso- <i>o</i> -cresol	0 %	1.1.2007 - 31.12.2008
ex 2908 99 90	30	4-Nitrophenol	0 %	1.1.2007 - 31.12.2008
ex 2908 99 90	40	3-Nitro- <i>p</i> -cresol	0 %	1.1.2007 - 31.12.2008
ex 2909 19 00	10	1,2-Bis(2-chloroethoxy)ethane	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2909 19 00	20	Bis(2-chloroethyl) ether	0 %	1.1.2007 - 31.12.2008
ex 2909 19 00	30	Mixture of isomers of nonafluorobutyl methyl ether or nonafluorobutyl ethyl ether, of a purity by weight of 99 % or more	0 %	1.1.2007 - 31.12.2008
ex 2909 19 00	40	Bis(2-ethoxyethyl)ether	0 %	1.1.2007 - 31.12.2008
ex 2909 19 00	50	3-Ethoxy-perfluoro-2-methylhexane	0 %	1.1.2007 - 31.12.2011
ex 2909 30 38	10	Bis(pentabromophenyl) ether	0 %	1.1.2007 - 31.12.2008
ex 2909 30 90	10	4-(<i>p</i> -Tolyloxy)biphenyl	0 %	1.1.2007 - 31.12.2008
ex 2909 30 90	20	1,2-Bis(<i>m</i> -tolyloxy)ethane	0 %	1.1.2007 - 31.12.2008
ex 2909 30 90	30	1,2-Diphenoxyethane	0 %	1.1.2007 - 31.12.2008
ex 2909 44 00	10	2-Hexyloxyethanol	0 %	1.1.2007 - 31.12.2008
ex 2909 49 18	10	1- <i>tert</i> -Butoxypropan-2-ol	0 %	1.1.2007 - 31.12.2008
ex 2909 50 90	10	4-(2-Methoxyethyl)phenol	0 %	1.1.2007 - 31.12.2008
ex 2909 60 00	10	Bis(α,α -dimethylbenzyl) peroxide	0 %	1.1.2007 - 31.12.2008
ex 2910 90 00	30	2,3-Epoxypropan-1-ol (glycidol)	0 %	1.1.2007 - 31.12.2008
ex 2910 90 00	40	Perfluoroepoxypropane	0 %	1.1.2007 - 31.12.2008
ex 2910 90 00	60	1,2-Epoxyoctadecane, of a purity by weight of 82 % or more	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	59			
ex 2910 90 00	70	(Epoxyethyl)benzene (styrene oxide)	0 %	1.1.2007 - 31.12.2008
ex 2912 29 00	10	Terephthalaldehyde	0 %	1.1.2007 - 31.12.2008
ex 2912 29 00	20	<i>p</i> -Phenylbenzaldehyde	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2912 49 00	10	3-Phenoxybenzaldehyde	0 %	1.1.2007 - 31.12.2008
ex 2912 49 00	20	4-Hydroxybenzaldehyde	0 %	1.1.2007 - 31.12.2011
ex 2914 19 90	10	3,3-Dimethylbutan-2-one	0 %	1.1.2007 - 31.12.2008
2914 21 00		Camphor	0 %	1.1.2007 - 31.12.2008
ex 2914 29 00	10	Estr-4-ene-3,17-dione	0 %	1.1.2007 - 31.12.2008
ex 2914 29 00	20	Cyclohexadec-8-enone	0 %	1.1.2007 - 31.12.2008
ex 2914 39 00	10	Benz[de]anthracen-7-one	0 %	1.1.2007 - 31.12.2008
ex 2914 50 00	30	2'-Hydroxyacetophenone	0 %	1.1.2007 - 31.12.2008
ex 2914 50 00	40	4'-Hydroxyacetophenone	0 %	1.1.2007 - 31.12.2008
ex 2914 50 00	50	6'-Methoxy-2'-acetonaphthone	0 %	1.1.2007 - 31.12.2008
ex 2914 69 90	10	2-Ethylanthraquinone	0 %	1.1.2007 - 31.12.2008
ex 2914 69 90	20	2-Pentylanthraquinone	0 %	1.1.2007 - 31.12.2008
ex 2914 69 90	30	1,4-Dihydroxyanthraquinone	0 %	1.1.2007 - 31.12.2008
ex 2914 69 90	40	2,3-Dihydro-1,4-dihydroxyanthraquinone	0 %	1.1.2007 - 31.12.2008
ex 2914 69 90	50	2-Methylanthraquinone	0 %	1.1.2007 - 31.12.2008
ex 2914 70 00	10	1-Chloro-3,3-dimethylbutan-2-one	0 %	1.1.2007 - 31.12.2008
ex 2914 70 00	30	4,4'-Dibromobenzil	0 %	1.1.2007 - 31.12.2008
ex 2914 70 00	40	Perfluoro(2-methylpentan-3-one)	0 %	1.1.2007 - 31.12.2008
ex 2914 70 00	50	3'-Chloropropiophenone	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2915 29 00	10	Antimony triacetate	0 %	1.1.2007 - 31.12.2008
ex 2915 39 80	20	5 α -Bromo-6 β -hydroxy-17-oxo-androstan-3 β -yl acetate	0 %	1.1.2007 - 31.12.2008
ex 2915 39 80	30	But-3-ene-1,2-diyl di(acetate)	0 %	1.1.2007 - 31.12.2008
ex 2915 39 80	40	<i>tert</i> -Butyl acetate	0 %	1.1.2007 - 31.12.2008
ex 2915 39 80	50	3-Acetylphenyl acetate	0 %	1.1.2007 - 31.12.2008
ex 2915 39 80	60	1-Phenylethyl acetate	0 %	1.1.2007 - 31.12.2008
ex 2915 40 00	10	Vinyl chloroacetate	0 %	1.1.2007 - 31.12.2008
ex 2915 90 80	20	Trimethyl orthoacetate	0 %	1.1.2007 - 31.12.2008
ex 2915 90 80	30	2-Ethylbutyric acid	0 %	1.1.2007 - 31.12.2008
ex 2915 90 80	40	Nonanoic acid (pelargonic acid)	0 %	1.1.2007 - 31.12.2008
ex 2916 12 90	10	2- <i>tert</i> -Butyl-6-(3- <i>tert</i> -butyl-2-hydroxy-5-methylbenzyl)-4-methylphenyl acrylate	0 %	1.1.2007 - 31.12.2008
ex 2916 12 90	20	2-Ethoxyethyl acrylate	0 %	1.1.2007 - 31.12.2008
ex 2916 12 90	30	Isobutyl acrylate	0 %	1.1.2007 - 31.12.2008
ex 2916 12 90	40	2,4-Di- <i>tert</i> -pentyl-6-[1-(3,5-di- <i>tert</i> -pentyl-2-hydroxyphenyl)ethyl]phenylacrylate	0 %	1.1.2007 - 31.12.2008
ex 2916 13 00	10	Hydroxyzinc methacrylate, in the form of powder	0 %	1.1.2007 - 31.12.2008
ex 2916 13 00	20	Zinc dimethacrylate, in the form of powder	0 %	1.1.2007 - 31.12.2008
ex 2916 14 90	10	2,3-Epoxypropyl methacrylate	0 %	1.1.2007 - 31.12.2008
ex 2916 19 70	20	Methyl 3,3-dimethylpent-4-enoate	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2916 20 00	10	Methyl 3-(2,2-dichlorovinyl)-2,2-dimethylcyclopropanecarboxylate	0 %	1.1.2007 - 31.12.2008
ex 2916 20 00	30	Empenthrin (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2916 20 00	50	Ethyl 2,2-dimethyl-3-(2-methylpropenyl)cyclopropanecarboxylate	0 %	1.1.2007 - 31.12.2008
ex 2916 39 00	15	Biphenyl-4-carboxylic acid	0 %	1.1.2007 - 31.12.2008
ex 2916 39 00	20	3,5-Dichlorobenzoyl chloride	3.6 %	1.1.2007 - 31.12.2008
ex 2916 39 00	25	<i>p</i> -Toluic acid	0 %	1.1.2007 - 31.12.2008
ex 2916 39 00	35	<i>o</i> -Chlorophenylacetic acid	0 %	1.1.2007 - 31.12.2008
ex 2916 39 00	40	Vinyl 4- <i>tert</i> -butylbenzoate	0 %	1.1.2007 - 31.12.2008
ex 2916 39 00	50	3,5-Dimethylbenzoyl chloride	0 %	1.1.2007 - 31.12.2008
ex 2916 39 00	60	4-Ethylbenzoyl chloride	0 %	1.1.2007 - 31.12.2008
ex 2916 39 00	70	Ibuprofen (INN)	0 %	1.1.2007 - 31.12.2008
ex 2916 39 00	80	Ethyl 2-(4-nitrophenyl)butyrate	0 %	1.1.2007 - 31.12.2008
ex 2916 39 00	85	2,6-Difluorobenzoic acid	0 %	1.1.2007 - 31.12.2008
ex 2917 11 00	20	Bis(<i>p</i> -methylbenzyl) oxalate	0 %	1.1.2007 - 31.12.2008
ex 2917 19 90	20	Sodium 1,2-bis(cyclohexyloxycarbonyl)ethanesulfonate	0 %	1.1.2007 - 31.12.2008
ex 2917 19 90	40	Dodecanedioic acid, of a purity by weight of more than 98,5 %	0 %	1.1.2007 - 31.12.2008
ex 2917 19 90	50	Glutaric anhydride	0 %	1.1.2007 - 31.12.2008
ex 2917 19 90	60	Diethyl isobutylmalonate	0 %	1.1.2007 - 31.12.2008
ex 2917 19 90	70	Itaconic acid	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2917 20 00	30	1,4,5,6,7,7-Hexachloro-8,9,10-trinorborn-5-ene-2,3-dicarboxylic anhydride	0 %	1.1.2007 - 31.12.2008
ex 2917 20 00	40	3-Methyl-1,2,3,6-tetrahydrophthalic anhydride	0 %	1.1.2007 - 31.12.2008
ex 2917 34 90	10	Diallyl phthalate	0 %	1.1.2007 - 31.12.2008
ex 2917 39 80	10	Dimethyl naphthalene-2,6-dicarboxylate	0 %	1.1.2007 - 31.12.2008
ex 2917 39 80	20	Benzene-1,2,4,5-tetracarboxylic acid (pyromellitic acid)	0 %	1.1.2007 - 31.12.2008
ex 2917 39 80	30	Benzene-1,2:4,5-tetracarboxylic dianhydride (pyromellitic dianhydride)	0 %	1.1.2007 - 31.12.2008
ex 2917 39 80	40	Biphenyl-3,4:3',4'-tetracarboxylic dianhydride	0 %	1.1.2007 - 31.12.2008
ex 2918 13 00	10	L-(-)-Di- <i>p</i> -toluoyltartaric acid	0 %	1.1.2007 - 31.12.2008
ex 2918 19 85	20	L-Malic acid	0 %	1.1.2007 - 31.12.2008
ex 2918 19 85	30	2,2-Bis(hydroxymethyl)butyric acid	0 %	1.1.2007 - 31.12.2008
ex 2918 19 85	50	DL-mandelic acid	0 %	1.1.2007 - 31.12.2008
ex 2918 29 10	10	Monohydroxynaphthoic acids	0 %	1.1.2007 - 31.12.2008
ex 2918 29 80	10	Hexamethylene bis[3-(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)propionate]	0 %	1.1.2007 - 31.12.2008
ex 2918 29 80	20	Gallic acid, of a purity by weight of 98,5 % or more calculated on the dry weight (measured by acidimetry)	0 %	1.1.2007 - 31.12.2008
ex 2918 29 80	30	Octadecyl-3-(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)propionate	0 %	1.1.2007 - 31.12.2011
ex 2918 30 00	20	2-(4-Ethylbenzoyl)benzoic acid	0 %	1.1.2007 - 31.12.2008
ex 2918 99 90	10	3,4-Epoxy-cyclohexylmethyl 3,4-epoxy-cyclohexanecarboxylate	0 %	1.1.2007 - 31.12.2008
ex 2918 99 90	20	Methyl 3-methoxyacrylate	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2918 99 90	30	Methyl 2-(4-hydroxyphenoxy)propionate	0 %	1.1.2007 - 31.12.2008
ex 2918 99 90	40	<i>trans</i> -4-Hydroxy-3-methoxycinnamic acid	0 %	1.1.2007 - 31.12.2008
ex 2918 99 90	50	Methyl 3,4,5-trimethoxybenzoate	0 %	1.1.2007 - 31.12.2008
ex 2918 99 90	60	3,4,5-Trimethoxybenzoic acid	0 %	1.1.2007 - 31.12.2008
ex 2918 99 90	70	methyl 5-methoxy-3-oxopentanoate	0 %	1.1.2007 - 31.12.2008
ex 2919 90 90	10	2,2'-Methylenebis(4,6-di- <i>tert</i> -butylphenyl) phosphate, monosodium salt	0 %	1.1.2007 - 31.12.2008
ex 2919 90 90	20	Diammonium salt of tetramyristoylcardiolipin	0 %	1.1.2007 - 31.12.2008
ex 2919 90 90	30	Aluminium hydroxybis[2,2'-methylenebis(4,6-di- <i>tert</i> -butylphenyl)phosphate]	0 %	1.1.2007 - 31.12.2008
ex 2919 90 90	40	Tri-n-hexylphosphate	0 %	1.1.2007 - 31.12.2008
ex 2920 19 00	10	Fenitrothion (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2920 19 00	20	Tolclofos-methyl (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2920 90 10	10	Diethyl sulfate	0 %	1.1.2007 - 31.12.2008
ex 2920 90 10	20	Diallyl 2,2'-oxydiethyl dicarbonate	0 %	1.1.2007 - 31.12.2008
ex 2920 90 10	30	4-Ethyl-1,3-dioxolan-2-one	0 %	1.1.2007 - 31.12.2008
ex 2920 90 10	40	Dimethyl carbonate	0 %	1.1.2007 - 31.12.2008
ex 2920 90 10	50	Di- <i>tert</i> -butyl dicarbonate	0 %	1.1.2007 - 31.12.2008
2920 90 30		Trimethyl phosphite	0 %	1.1.2007 - 31.12.2008
ex 2920 90 85	10	<i>O,O'</i> -Dioctadecyl pentaerythritol bis(phosphite)	0 %	1.1.2007 - 31.12.2008
ex 2920 90 85	40	Tritolyl phosphite	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2920 90 85	50	Triisooctylphosphite	0 %	1.1.2007 - 31.12.2008
ex 2921 19 80	10	Triallylamine	0 %	1.1.2007 - 31.12.2008
ex 2921 19 80	20	Ethyl(2-methylallyl)amine	0 %	1.1.2007 - 31.12.2008
ex 2921 19 80	30	Allylamine	0 %	1.1.2007 - 31.12.2008
ex 2921 29 00	10	<i>N,N,N',N'</i> -Tetrabutylhexamethylenediamine	0 %	1.1.2007 - 31.12.2008
ex 2921 29 00	20	Tris[3-(dimethylamino)propyl]amine	0 %	1.1.2007 - 31.12.2008
ex 2921 29 00	30	Bis[3-(dimethylamino)propyl]methylamine	0 %	1.1.2007 - 31.12.2008
ex 2921 29 00	40	<i>N,N'</i> -Di- <i>tert</i> -butylethylenediamine	0 %	1.1.2007 - 31.12.2008
ex 2921 30 99	10	Dicyclohexyl(methyl)amine	0 %	1.1.2007 - 31.12.2008
ex 2921 30 99	20	Cyclohex-1,3-ylenebis(methylamine), for the manufacture of dishwashing products (1)	0 %	1.1.2007 - 31.12.2008
ex 2921 42 10	10	2,6-Dichloro-4-nitroaniline	0 %	1.1.2007 - 31.12.2008
ex 2921 42 10	15	4-Amino-3-nitrobenzenesulphonic acid	0 %	1.1.2007 - 31.12.2008
ex 2921 42 10	20	2-Bromo-4,6-dinitroaniline	0 %	1.1.2007 - 31.12.2008
ex 2921 42 10	25	Sodium hydrogen 2-aminobenzene-1,4-disulphonate	0 %	1.1.2007 - 31.12.2008
ex 2921 42 10	30	4-Aminobenzene-1,3-disulfonic acid and its salts	0 %	1.1.2007 - 31.12.2008
ex 2921 42 10	35	2-Nitroaniline	0 %	1.1.2007 - 31.12.2008
ex 2921 42 10	40	2-Bromo-6-chloro-4-nitroaniline	0 %	1.1.2007 - 31.12.2008
ex 2921 42 10	45	2,4,5-Trichloroaniline	0 %	1.1.2007 - 31.12.2008
ex 2921 42 10	50	3-Aminobenzenesulfonic acid	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2921 42 10	70	2-Aminobenzene-1,4-disulfonic acid	0 %	1.1.2007 - 31.12.2008
ex 2921 42 10	80	4-Chloro-2-nitroaniline	0 %	1.1.2007 - 31.12.2008
ex 2921 42 10	85	3,5-Dichloroaniline	0 %	1.1.2007 - 31.12.2008
ex 2921 43 00	10	5-Amino-2-chlorotoluene-4-sulfonic acid	0 %	1.1.2007 - 31.12.2008
ex 2921 43 00	20	4-Amino-6-chlorotoluene-3-sulfonic acid	0 %	1.1.2007 - 31.12.2008
ex 2921 43 00	30	3-Nitro- <i>p</i> -toluidine	0 %	1.1.2007 - 31.12.2008
ex 2921 43 00	40	4-Aminotoluene-3-sulphonic acid	0 %	1.1.2007 - 31.12.2008
ex 2921 44 00	10	Methyldiphenylamine	0 %	1.1.2007 - 31.12.2008
ex 2921 44 00	20	Diphenylamine	0 %	1.1.2007 - 31.12.2008
ex 2921 45 00	10	Sodium hydrogen 3-aminonaphthalene-1,5-disulfonate	0 %	1.1.2007 - 31.12.2008
ex 2921 45 00	20	2-Aminonaphthalene-1,5-disulfonic acid and its sodium salts	0 %	1.1.2007 - 31.12.2008
ex 2921 45 00	30	2-Aminonaphthalene-1-sulfonic acid	0 %	1.1.2007 - 31.12.2008
ex 2921 45 00	40	1-Naphthylamine	0 %	1.1.2007 - 31.12.2008
ex 2921 49 10	20	Pendimethalin (ISO)	3.5 %	1.1.2007 - 31.12.2008
ex 2921 49 80	10	8-Anilinonaphthalene-1-sulfonic acid	0 %	1.1.2007 - 31.12.2008
ex 2921 49 80	20	<i>N</i> -1-Naphthylaniline	0 %	1.1.2007 - 31.12.2008
ex 2921 51 19	20	Toluene diamine (TDA), containing by weight 78 % or more but not more than 82 % of 4-methyl- <i>m</i> -phenylenediamine and 18 % or more but not more than 22 % of 2-methyl- <i>m</i> -phenylenediamine, and with a residual tar content of not more than 0.23 % by weight	0 %	1.1.2007 - 31.12.2008
ex 2921 51 19	30	2-Methyl- <i>p</i> -phenylenediamine sulphate	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2921 59 90	10	Mixture of isomers of 3,5-diethyltoluenediamine	0 %	1.1.2007 - 31.12.2008
ex 2921 59 90	20	4-(4-Aminoanilino)-3-nitrobenzenesulfonic acid	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	68			
ex 2921 59 90	40	4,4'-diaminostilbene-2,2'-disulphonic acid	0 %	1.1.2007 - 31.12.2008
ex 2922 19 80	10	4,4-Dimethoxybutylamine	0 %	1.1.2007 - 31.12.2008
ex 2922 19 80	30	<i>N,N,N',N'</i> -Tetramethyl-2,2'-oxybis(ethylamine)	0 %	1.1.2007 - 31.12.2008
ex 2922 19 80	40	2-Amino-2-methylpropanol, for use in the manufacture of goods of subheadings 3004 90 and 3305 30 (1)	0 %	1.1.2007 - 31.12.2008
ex 2922 19 80	50	2-(2-Methoxyphenoxy)ethylamine	0 %	1.1.2007 - 31.12.2008
ex 2922 19 80	60	<i>N,N,N'</i> -trimethyl- <i>N'</i> -(2-hydroxy-ethyl) 2,2'-oxybis(ethylamine)	0 %	1.1.2007 - 31.12.2008
ex 2922 19 80	70	D-(-)-threo-2-amino-1-(<i>p</i> -nitrophenyl)propane-1,3-diol	0 %	1.1.2007 - 31.12.2011
ex 2922 21 00	10	2-Amino-5-hydroxynaphthalene-1,7-disulfonic acid and its salts, of a purity by weight of 60 % or more	0 %	1.1.2007 - 31.12.2008
ex 2922 21 00	20	4-Hydroxy-7-methylaminonaphthalene-2-sulfonic acid	0 %	1.1.2007 - 31.12.2008
ex 2922 21 00	30	6-Amino-4-hydroxynaphthalene-2-sulfonic acid	0 %	1.1.2007 - 31.12.2008
ex 2922 21 00	40	7-Amino-4-hydroxynaphthalene-2-sulfonic acid	0 %	1.1.2007 - 31.12.2008
ex 2922 21 00	50	Sodium hydrogen 4-amino-5-hydroxynaphthalene-2,7-disulphonate	0 %	1.1.2007 - 31.12.2008
ex 2922 29 00	10	2-Methyl- <i>N</i> -phenyl- <i>p</i> -anisidine	0 %	1.1.2007 - 31.12.2008
ex 2922 29 00	15	<i>N</i> -Methyl-2-(3,4-dimethoxyphenyl)ethylamine	0 %	1.1.2007 - 31.12.2008
ex 2922 29 00	20	3-Aminophenol	0 %	1.1.2007 - 31.12.2008
ex 2922 29 00	25	5-Amino- <i>o</i> -cresol	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2922 29 00	30	4-Amino-5-methoxy-2-methylbenzenesulfonic acid	0 %	1.1.2007 - 31.12.2008
ex 2922 29 00	35	2-Amino-4,6-dinitrophenol sodium salt, containing at least 20 % water	0 %	1.1.2007 - 31.12.2011
ex 2922 29 00	40	2-Amino-4- <i>tert</i> -pentyl-6-nitrophenol	0 %	1.1.2007 - 31.12.2008
ex 2922 29 00	45	Anisidines	0 %	1.1.2007 - 31.12.2008
ex 2922 29 00	50	6-Methoxy- <i>m</i> -toluidine	0 %	1.1.2007 - 31.12.2008
ex 2922 29 00	60	3,5-Dichloro-4-(1,1,2,2-tetrafluoroethoxy)aniline	0 %	1.1.2007 - 31.12.2008
ex 2922 29 00	70	4-Nitro- <i>o</i> -anisidine	0 %	1.1.2007 - 31.12.2008
ex 2922 29 00	80	3-Diethylaminophenol	0 %	1.1.2007 - 31.12.2008
ex 2922 39 00	10	1-Amino-4-bromo-9,10-dioxanthracene-2-sulfonic acid and its salts	0 %	1.1.2007 - 31.12.2008
ex 2922 39 00	20	1-Aminoanthraquinone	0 %	1.1.2007 - 31.12.2008
ex 2922 39 00	30	1-Bromo-4-methylaminoanthraquinone	0 %	1.1.2007 - 31.12.2008
ex 2922 39 00	40	1,4-Diamino-2,3-dichloroanthraquinone	0 %	1.1.2007 - 31.12.2008
ex 2922 39 00	50	2-Aminoanthraquinone	0 %	1.1.2007 - 31.12.2008
ex 2922 39 00	60	1,4-Diamino-2,3-dihydroanthraquinone	0 %	1.1.2007 - 31.12.2008
ex 2922 39 00	70	<i>p</i> -[(2-Chloroethyl)ethylamino]benzaldehyde	0 %	1.1.2007 - 31.12.2011
ex 2922 43 00	10	Anthranilic acid	0 %	1.1.2007 - 31.12.2008
ex 2922 49 95	10	Ornithine aspartate (INN)	0 %	1.1.2007 - 31.12.2008
ex 2922 49 95	20	12-Aminododecanoic acid	0 %	1.1.2007 - 31.12.2008
ex 2922 49 95	30	DL-Aspartic acid	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2922 49 95	40	Norvaline	0 %	1.1.2007 - 31.12.2008
ex 2922 49 95	50	D-(-)-Dihydrophenylglycine	0 %	1.1.2007 - 31.12.2008
ex 2922 50 00	30	2-(3-Amino-4-chlorobenzoyl)benzoic acid	0 %	1.1.2007 - 31.12.2008
ex 2922 50 00	50	2-(4-Dibutylaminosalicyloyl)benzoic acid	0 %	1.1.2007 - 31.12.2008
ex 2922 50 00	70	2-(1-Hydroxycyclohexyl)-2-(4-methoxyphenyl)ethylammonium acetate	0 %	1.1.2007 - 31.12.2008
ex 2923 90 00	10	Tetramethylammonium hydroxide, in the form of an aqueous solution containing: — (25 ± 0,5) % by weight of tetramethylammonium hydroxide, — 500 mg/kg or less of carbonate, — 200 mg/kg or less of chloride and — 5 mg/kg or less of potassium	0 %	1.1.2007 - 31.12.2008
ex 2923 90 00	15	3-Chloro-2-hydroxypropyldimethyldodecylammoniumchloride in the form of an aqueous solution	0 %	1.1.2007 - 31.12.2008
ex 2923 90 00	30	Tetramethylammonium hydroxide pentahydrate, of a purity by weight of 98 % or more	0 %	1.1.2007 - 31.12.2008
ex 2923 90 00	35	Tetrabutylammonium fluoride trihydrate	0 %	1.1.2007 - 31.12.2011
ex 2923 90 00	40	Benzyltrimethyl(octadecyl)ammonium salts, for use in the manufacture of toner for photocopiers (1)	0 %	1.1.2007 - 31.12.2008
ex 2923 90 00	50	Tetraethylammonium hydroxide, in the form of an aqueous solution containing: — (35 ± 0,5) % by weight of tetraethylammonium hydroxide, — 2 000 mg/kg or less of chloride, — 2 mg/kg or less of iron and — 10 mg/kg or less of potassium	0 %	1.1.2007 - 31.12.2008
ex 2923 90 00	60	Tetrabutylammonium hydroxide, in the form of an aqueous solution containing by weight: — (55 ± 1,0) % of tetrabutylammonium hydroxide, — 0,5 % or less of bromide, — 0,4 % or less of tributylamine, — 0,3 % or less of carbonate and — 0,2 % or less of potassium and sodium taken together	0 %	1.1.2007 - 31.12.2008
ex 2923 90 00	70	Tetrapropylammonium hydroxide, in the form of an aqueous solution containing: — (40 ± 2) % by weight of tetrapropylammonium hydroxide, — 0,3 % by weight or less of carbonate,	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		<ul style="list-style-type: none"> — 0,1 % by weight or less of tripropylamine, — 500 mg/kg or less of bromide and — 25 mg/kg or less of potassium and sodium taken together 		
ex 2923 90 00	80	Diallyldimethylammonium chloride, in the form of an aqueous solution containing by weight 63 % or more but not more than 67 % of diallyldimethylammonium chloride	0 %	1.1.2007 - 31.12.2008
ex 2924 19 00	10	2-Acrylamido-2-methylpropanesulfonic acid and its sodium or ammonium salts	0 %	1.1.2007 - 31.12.2008
ex 2924 19 00	30	Methyl 2-acetamido-3-chloropropionate	0 %	1.1.2007 - 31.12.2008
ex 2924 19 00	40	<i>N</i> -(1,1-Dimethyl-3-oxobutyl)acrylamide	0 %	1.1.2007 - 31.12.2008
ex 2924 19 00	50	Acrylamide	0 %	1.1.2007 - 31.12.2008
ex 2924 21 90	10	4,4'-Dihydroxy-7,7'-ureylenedi(naphthalene-2-sulfonic acid) and its sodium salts	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	62			
ex 2924 29 95	10	Alachlor (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2924 29 95	15	Acetochlor (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2924 29 95	20	3'-Amino-4'-methoxyacetanilide	0 %	1.1.2007 - 31.12.2008
ex 2924 29 95	25	3'-Diethylaminoacetanilide	0 %	1.1.2007 - 31.12.2008
ex 2924 29 95	30	Propachlor (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2924 29 95	35	Diethofencarb (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2924 29 95	40	7-Acetamido-4-hydroxynaphthalene-2-sulfonic acid and its sodium salts	0 %	1.1.2007 - 31.12.2008
ex 2924 29 95	45	3'-Diethylamino-4'-methoxyacetanilide	0 %	1.1.2007 - 31.12.2008
ex 2924 29 95	50	5-[<i>N</i> -(2-Acetoxyethyl)acetoxyacetamido]- <i>N,N'</i> -bis(2,3-diacetoxypropyl)-2,4,6-triiodoisophthalamide	0 %	1.1.2007 - 31.12.2008
ex 2924 29 95	55	4'-Amino- <i>N</i> -methylacetanilide	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period	
ex 2924 29 95	60	Beflubutamid (ISO)	0 %	1.1.2007 - 31.12.2008	
ex 2924 29 95	65	2-(4-Hydroxyphenyl)acetamide	0 %	1.1.2007 - 31.12.2008	
ex 2924 29 95	70	4-Acetamido-2-aminobenzenesulfonic acid	0 %	1.1.2007 - 31.12.2008	
ex 2924 29 95	75	3-Amino- <i>p</i> -anisilide	0 %	1.1.2007 - 31.12.2008	
ex 2924 29 95	80	5'-Chloro-3-hydroxy-2',4'-dimethoxy-2-naphtanilide	0 %	1.1.2007 - 31.12.2008	
ex 2924 29 95	85	<i>p</i> -Aminobenzamide	0 %	1.1.2007 - 31.12.2008	
ex 2924 29 95	91	3-Hydroxy-2'-methoxy-2-naphtanilide	0 %	1.1.2007 - 31.12.2008	
ex 2924 29 95	92	3-Hydroxy-2-naphtanilide	0 %	1.1.2007 - 31.12.2008	
ex 2924 29 95	93	3-Hydroxy-2'-methyl-2-naphtanilide	0 %	1.1.2007 - 31.12.2008	
ex 2924 29 95	94	2'-Ethoxy-3-hydroxy-2-naphtanilide	0 %	1.1.2007 - 31.12.2008	
ex 2924 29 95	95	<i>N</i> -{3-[3-(Dimethylamino)prop-2-enoyl]phenyl}- <i>N</i> -ethylacetamide	0 %	1.1.2007 - 31.12.2008	
ex 2924 29 95	96	4'-Chloro-3-hydroxy-2',5'-dimethoxy-2-naphtanilide	0 %	1.1.2007 - 31.12.2008	
ex 2924 29 95	97	1,1-Cyclohexanediacetic acid monoamide	0 %	1.1.2007 - 31.12.2008	
ex 2925 11 00	20	Saccharin and its sodium salt	0 %	1.1.2007 - 31.12.2008	
ex 2925 19 95	10	<i>N</i> -Phenylmaleimide	0 %	1.1.2007 - 31.12.2008	
ex 2925 19 95	20	<i>N</i> -(9-Fluorenylmethoxycarbonyloxy)succinimide	0 %	1.1.2007 - 31.12.2008	
ex 2925 29 00	10	Dicyclohexylcarbodiimide	0 %	1.1.2007 - 31.12.2008	
ex 2926 90 95	10	Methacrylonitrile	0 %	1.1.2007 - 31.12.2008	
ex 2926 90 95	15	Cyano(3-phenoxyphenyl)methyl dimethylcyclopropanecarboxylate	3-(2,2-dichlorovinyl)-2,2-	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2926 90 95	20	2-(<i>m</i> -Benzoylphenyl)propionitrile	0 %	1.1.2007 - 31.12.2008
ex 2926 90 95	25	Aminoacetonitrile hydrochloride	0 %	1.1.2007 - 31.12.2008
ex 2926 90 95	30	2-Amino-5-nitrobenzonitrile	0 %	1.1.2007 - 31.12.2008
ex 2926 90 95	35	2-Bromo-2(bromomethyl)pentanedinitrile	0 %	1.1.2007 - 31.12.2008
ex 2926 90 95	45	2-Cyanoacetamide	0 %	1.1.2007 - 31.12.2008
ex 2926 90 95	50	Alkyl or alkoxyalkyl esters of cyanoacetic acid	0 %	1.1.2007 - 31.12.2008
ex 2926 90 95	55	Methyl-2-cyano-2-phenylbutyrate	0 %	1.1.2007 - 31.12.2011
ex 2926 90 95	60	Cyanoacetic acid in crystalline form	0 %	1.1.2007 - 31.12.2008
ex 2926 90 95	65	Malononitrile	0 %	1.1.2007 - 31.12.2008
ex 2926 90 95	70	Tetrachloroterephthalonitrile	0 %	1.1.2007 - 31.12.2008
ex 2926 90 95	75	Ethyl 2-cyano-2-ethyl-3-methylhexanoate	0 %	1.1.2007 - 31.12.2008
ex 2926 90 95	80	Ethyl 2-cyano-2-phenylbutyrate	0 %	1.1.2007 - 31.12.2008
ex 2926 90 95	85	Ethyl 2-allyl-2-cyano-3-methylhexanoate	0 %	1.1.2007 - 31.12.2008
ex 2926 90 95	86	Ethylenediaminetetraacetonitrile	0 %	1.1.2007 - 31.12.2008
ex 2926 90 95	87	Nitriлотriacetonitrile	0 %	1.1.2007 - 31.12.2008
ex 2926 90 95	88	1,3-Propylenediaminetetraacetonitrile	0 %	1.1.2007 - 31.12.2008
ex 2926 90 95	89	Butyronitrile	0 %	1.1.2007 - 31.12.2008
ex 2927 00 00	10	2,2'-Dimethyl-2,2'-azodipropionamide dihydrochloride	0 %	1.1.2007 - 31.12.2008
ex 2927 00 00	20	4-Anilino-2-methoxybenzenediazonium hydrogen sulfate	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2927 00 00	30	4'-Aminoazobenzene-4-sulfonic acid	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	69			
ex 2927 00 00	40	2-Hydroxynaphthalene-1-diazonium-4-sulfonate	0 %	1.1.2007 - 31.12.2008
ex 2927 00 00	50	2-Hydroxy-6-nitronaphthalene-1-diazonium-4-sulfonate, of a purity by weight of 60 % or more	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	41			
ex 2927 00 00	60	4,4'-Dicyano-4,4'-azodivaleric acid	0 %	1.1.2007 - 31.12.2008
ex 2928 00 90	10	3,3'-Bis(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)- <i>N,N'</i> -bipropionamide	0 %	1.1.2007 - 31.12.2008
ex 2928 00 90	15	1,1'-(Hydroxyimino)bis-(2-propanol)	0 %	1.1.2007 - 31.12.2011
ex 2928 00 90	20	2,4,6-Trichlorophenylhydrazine	0 %	1.1.2007 - 31.12.2008
ex 2928 00 90	40	<i>O</i> -Ethylhydroxylamine, in the form of an aqueous solution	0 %	1.1.2007 - 31.12.2008
ex 2928 00 90	50	<i>N</i> -Isopropylhydroxylamine, in the form of an aqueous solution	0 %	1.1.2007 - 31.12.2008
ex 2928 00 90	60	Adipohydrazide	0 %	1.1.2007 - 31.12.2008
ex 2928 00 90	70	Tetrakis(4-methylpentan-2-oximino)silane	0 %	1.1.2007 - 31.12.2008
ex 2928 00 90	80	Cyflufenamid (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2929 10 90	10	Methylenedicyclohexyl diisocyanates	0 %	1.1.2007 - 31.12.2008
ex 2929 10 90	30	3,3'-Dimethylbiphenyl-4,4'-diyl diisocyanate	0 %	1.1.2007 - 31.12.2008
ex 2929 10 90	40	<i>m</i> -Isopropenyl- α,α -dimethylbenzyl isocyanate	0 %	1.1.2007 - 31.12.2008
ex 2929 10 90	50	<i>m</i> -Phenylenediisopropylidene diisocyanate	0 %	1.1.2007 - 31.12.2008
ex 2929 10 90	60	Trimethylhexamethylene diisocyanate, mixed isomers	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2929 10 90	70	9,9'-(3-Heptyl-4-pentylcyclohex-1,2-ylene)dinonyl diisocyanate	0 %	1.1.2007 - 31.12.2008
ex 2929 90 00	20	Ethyl isocyanoacetate	0 %	1.1.2007 - 31.12.2008
ex 2930 90 85	10	Thiophenol	0 %	1.1.2007 - 31.12.2008
ex 2930 90 85	15	Ethoprophos (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2930 90 85	20	3,3-Dimethyl-1-methylthiobutanone oxime	0 %	1.1.2007 - 31.12.2008
ex 2930 90 85	25	Thiophanate-methyl (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2930 90 85	30	4-(4-Isopropoxyphenylsulfonyl)phenol	0 %	1.1.2007 - 31.12.2008
ex 2930 90 85	35	Glutathione	0 %	1.1.2007 - 31.12.2011
ex 2930 90 85	40	3,3'-Thiodi(propionic acid)	0 %	1.1.2007 - 31.12.2008
ex 2930 90 85	45	2-[(<i>p</i> -Aminophenyl)sulfonyl]ethyl hydrogen sulfate	0 %	1.1.2007 - 31.12.2008
ex 2930 90 85	50	2-Chlorophenylsulfonyl isocyanate, in the form of a solution in xylene	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	51			
ex 2930 90 85	60	Methyl phenyl sulfide	0 %	1.1.2007 - 31.12.2008
ex 2930 90 85	65	Diiodomethyl <i>p</i> -tolyl sulfone	0 %	1.1.2007 - 31.12.2008
ex 2930 90 85	70	2-Aminophenyl phenyl sulfone, of a purity by weight of 75 % or more	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	71			
ex 2930 90 85	75	4,4'-[Methylenebis(oxyethylenethio)]diphenol	0 %	1.1.2007 - 31.12.2008
ex 2930 90 85	76	2,2'-Dithiodi(benzoic acid)	0 %	1.1.2007 - 31.12.2008
ex 2930 90 85	77	4-[4-(2-Propenyloxy)phenylsulphonyl]phenol	0 %	1.1.2007 - 31.12.2008
ex 2930 90 85	80	Captan (ISO)	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2930 90 85	85	Mesotrione (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2930 90 85	86	4-Hydroxybenzenethiol	0 %	1.1.2007 - 31.12.2008
ex 2930 90 85	87	3-Sulfino benzoic acid	0 %	1.1.2007 - 31.12.2008
ex 2930 90 85	88	Methylene dithiocyanate	0 %	1.1.2007 - 31.12.2008
ex 2930 90 85	89	Potassium- or sodium-salt of O-ethyl-, O-isopropyl-, O-butyl-, O-isobutyl- or O-pentyl-dithiocarbonates	0 %	1.1.2007 - 31.12.2011
2931 00 10		Dimethyl methylphosphonate	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	05	Butylethylmagnesium, in the form of a solution in heptane	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	10	2-Diphenylphosphinobenzoic acid	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	20	Bis(2-chloroethyl) 2-chloroethylphosphonate	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	25	Sodium phenylphosphinate	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	30	Bis(2-chloroethyl) vinylphosphonate	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	35	Sodium tetraphenylborate	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	40	<i>N</i> -(Phosphonomethyl)iminodiacetic acid	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	45	Tributylphosphine	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	50	Bis(2,4,4-trimethylpentyl)phosphinic acid	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	55	Dimethyl[dimethylsilyldiindenyl]hafnium	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	60	Trioctylphosphine oxide	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	65	Triethylborane	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	70	<i>N,N</i> -Dimethylanilinium tetrakis(pentafluorophenyl)borate	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2931 00 95	75	{2,7-Di- <i>tert</i> -butyl-9-[(η^5 -cyclopentadienyl)bis(4-triethylsilylphenyl)methyl]-4a,4b,8a,9,9a- η -fluorene} dimethylhafnium, in the form of a solution in hexane	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	84	Methylbis(4-methylpentan-2-oximino)vinylsilane	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	85	Tributyl(tetradecyl)phosphonium chloride, whether or not in the form of an aqueous solution	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	86	Mixture of the isomers 9-icosyl-9-phosphabicyclo[3.3.1]nonane and 9-icosyl-9-phosphabicyclo[4.2.1]nonane	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	87	Tris(4-methylpentan-2-oximino)methylsilane	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	88	Tris(4-methylpentan-2-oximino)vinylsilane	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	89	Tetrabutylphosphonium acetate, in the form of an aqueous solution	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	91	Trimethylsilane	0 %	1.1.2007 - 31.12.2011
ex 2931 00 95	95	Trichloro(3-chloropropyl)silane	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	96	3-(Hydroxyphenylphosphinoyl)propionic acid	0 %	1.1.2007 - 31.12.2008
ex 2931 00 95	97	Potassium 4-tolylphosphinate, in the form of an aqueous solution	0 %	1.1.2007 - 31.12.2008
ex 2932 13 00	10	Tetrahydrofurfuryl alcohol	0 %	1.1.2007 - 31.12.2008
ex 2932 19 00	40	Furan of a purity by weight of 99 % or more	0 %	1.1.2007 - 31.12.2008
ex 2932 19 00	50	2,3-Dihydrofuran	0 %	1.1.2007 - 31.12.2008
ex 2932 19 00	70	Furfurylamine	0 %	1.1.2007 - 31.12.2008
ex 2932 19 00	75	Tetrahydro-2-methylfuran	0 %	1.1.2007 - 31.12.2008
ex 2932 19 00	80	Octafluorotetrahydrofuran	0 %	1.1.2007 - 31.12.2008
ex 2932 29 85	10	2'-Anilino-6'-[ethyl(isopentyl)amino]-3'-methylspiro[isobenzofuran-1(3 <i>H</i>),9'-xanthen]-3-one	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2932 29 85	15	13,14,15,16-Tetranorlabdano-12,8 α -lactone	0 %	1.1.2007 - 31.12.2008
ex 2932 29 85	25	2'-(2-Chloroanilino)-6'-dibutylaminospiro[isobenzofuran-1(3H),9'-xanthen]-3-one	0 %	1.1.2007 - 31.12.2008
ex 2932 29 85	30	2'-Anilino-3'-methyl-6'-methyl(propyl)aminospiro[isobenzofuran-1(3H),9'-xanthen]-3-one	0 %	1.1.2007 - 31.12.2008
ex 2932 29 85	35	6'-Diethylamino-3'-methyl-2'-(2,4-xylydino)spiro[isobenzofuran-1(3H),9'-xanthen]-3-one	0 %	1.1.2007 - 31.12.2008
ex 2932 29 85	40	2'-Anilino-6'-(N-ethyl-p-toluidino)-3'-methylspiro[isobenzofuran-1(3H),9'-xanthen]-3-one	0 %	1.1.2007 - 31.12.2008
ex 2932 29 85	45	2'-Anilino-6'-ethyl(isobutyl)amino-3'-methylspiro[isobenzofuran-1(3H),9'-xanthen]-3-one	0 %	1.1.2007 - 31.12.2008
ex 2932 29 85	50	2'-Anilino-6'-cyclohexyl(methyl)amino-3'-methylspiro[isobenzofuran-1(3H),9'-xanthen]-3-one	0 %	1.1.2007 - 31.12.2008
ex 2932 29 85	55	6-Dimethylamino-3,3-bis(4-dimethylaminophenyl)phthalide	0 %	1.1.2007 - 31.12.2008
ex 2932 29 85	70	3',6'-Bis(ethylamino)-2',7'-dimethylspiro[isobenzofuran-1(3H),9'-[9H]-xanthen]-3-one	0 %	1.1.2007 - 31.12.2008
ex 2932 29 85	75	Rofecoxib (INN)	0 %	1.1.2007 - 31.12.2008
ex 2932 29 85	80	Gibberellic acid with a minimum purity by weight of 88 %	0 %	1.1.2007 - 31.12.2008
ex 2932 99 70	10	Bendiocarb (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2932 99 70	20	Androsta-1,4-diene-3,17-dione 17-(2,2-dimethylpropylene) acetal	0 %	1.1.2007 - 31.12.2008
ex 2932 99 70	40	1,3:2,4-Bis-O-(3,4-dimethylbenzylidene)-D-glucitol	0 %	1.1.2007 - 31.12.2008
ex 2932 99 70	50	5-Propyl-1,3-benzodioxole	0 %	1.1.2007 - 31.12.2008
ex 2932 99 70	60	Calcium bis[4-O-(β -D-galactopyranosyl)-D-gluconate] dihydrate	0 %	1.1.2007 - 31.12.2008
ex 2932 99 70	70	1,3:2,4-bis-O-Benzylidene-D-glucitol	0 %	1.1.2007 - 31.12.2011

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2932 99 70	75	3-(3,4-Methylenedioxyphenyl)-2-methylpropanal	0 %	1.1.2007 - 31.12.2011
ex 2932 99 70	80	1,3:2,4-bis-O-(4-Methylbenzylidene)-D-glucitol	0 %	1.1.2007 - 31.12.2011
ex 2932 99 85	20	(2-Butylbenzofuran-3-yl) (4-hydroxy-3,5-diiodophenyl) ketone	0 %	1.1.2007 - 31.12.2008
ex 2932 99 85	30	Carbofuran (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2933 19 90	10	4,5-Diamino-1-(2-hydroxyethyl)-1H-pyrazole sulfate	0 %	1.1.2007 - 31.12.2008
ex 2933 19 90	20	4-Amino-1-methyl-3-propylpyrazole-5-carboxamide	0 %	1.1.2007 - 31.12.2008
ex 2933 19 90	30	3-Methyl-1-p-tolyl-5-pyrazolone	0 %	1.1.2007 - 31.12.2008
ex 2933 19 90	40	Edaravone (INN)	0 %	1.1.2007 - 31.12.2008
ex 2933 19 90	50	Fenpyroximate (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2933 21 00	10	Hydantoin	0 %	1.1.2007 - 31.12.2008
ex 2933 21 00	20	2-(3-Benzyl-2,5-dioximidazolidin-1-yl)-2'-chloro-5'-(3-dodecylsulfonyl-2-methylpropionamido)-4,4-dimethyl-3-oxovaleranilide	0 %	1.1.2007 - 31.12.2008
ex 2933 21 00	40	1-[1,3-Bis(hydroxymethyl)-2,5-dioximidazolidin-4-yl]-1,3-bis(hydroxymethyl)urea	0 %	1.1.2007 - 31.12.2008
ex 2933 21 00	50	1-Bromo-3-chloro-5,5-dimethylhydantoin	0 %	1.1.2007 - 31.12.2011
ex 2933 21 00	60	DL-p-Hydroxyphenylhydantoin	0 %	1.1.2007 - 31.12.2011
ex 2933 29 90	20	Reaction product consisting of the methyl esters of (±)-6-(4-isopropyl-4-methyl-5-oxo-2-imidazolin-2-yl)-m-toluic acid and (±)-2-(4-isopropyl-4-methyl-5-oxo-2-imidazolin-2-yl)-p-toluic acid (Imazamethabenzmethyl)	4 %	1.1.2007 - 31.12.2008
ex 2933 29 90	40	Triflumizole (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2933 29 90	50	1,3-Dimethylimidazolidin-2-one	0 %	1.1.2007 - 31.12.2008
ex 2933 39 99	10	Cloperastine fendizoate (INN ^M)	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2933 39 99	15	Pyridine-2,3-dicarboxylic acid	0 %	1.1.2007 - 31.12.2008
ex 2933 39 99	20	5-Methyl-2-pyridylamine	0 %	1.1.2007 - 31.12.2008
ex 2933 39 99	25	Imazethapyr (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2933 39 99	30	4,4'-Trimethylenedipiperidine	0 %	1.1.2007 - 31.12.2008
ex 2933 39 99	35	Aminopyralid (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2933 39 99	40	2-Chloropyridine	0 %	1.1.2007 - 31.12.2008
ex 2933 39 99	45	3-(Carboxymethyl)pyridinium chloride	0 %	1.1.2007 - 31.12.2008
ex 2933 39 99	60	2-Fluoro-6-(trifluoromethyl)pyridine	0 %	1.1.2007 - 31.12.2008
ex 2933 39 99	65	Acetamiprid (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2933 39 99	70	Etoricoxib (INN)	0 %	1.1.2007 - 31.12.2008
ex 2933 39 99	75	Picolinafen (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2933 49 10	10	Quinmerac (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2933 49 90	20	5,7-Dichloro-4-(4-fluorophenoxy)quinoline	0 %	1.1.2007 - 31.12.2008
ex 2933 49 90	40	<i>N</i> -Ethyl-5,6,7,8-tetrahydroquinolinium <i>p</i> -toluenesulfonate, in the form of a solution in water	0 %	1.1.2007 - 31.12.2008
ex 2933 49 90	50	Methyl 2-[(<i>S</i>)-3-[(<i>E</i>)-3-[2-(7-chloro-2-quinolyl)vinyl]phenyl]-3-hydroxypropyl] benzoate monohydrate	0 %	1.1.2007 - 31.12.2008
ex 2933 49 90	60	5,6,7,8-Tetrahydroquinoline	0 %	1.1.2007 - 31.12.2008
ex 2933 49 90	70	Quinolin-8-ol	0 %	1.1.2007 - 31.12.2008
ex 2933 52 00	10	Malonylurea (barbituric acid)	0 %	1.1.2007 - 31.12.2011

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2933 59 95	10	1-Ethyl-6-fluoro-1,4-dihydro-4-oxo-7-piperazin-1-yl-1,8-naphthyridine-3-carboxylic acid and its salts and esters	0 %	1.1.2007 - 31.12.2008
ex 2933 59 95	15	(2R)-4-Oxo-4-[3-(trifluoromethyl)-5,6-dihydro[1,2,4]triazolo[4,3-a]pyrazin-7(8H)-yl]-1-(2,4,5-trifluorophenyl)butyl-2-ammonium phosphate monohydrate	0 %	1.1.2007 - 31.12.2008
ex 2933 59 95	20	2,4-Diamino-6-chloropyrimidine	0 %	1.1.2007 - 31.12.2008
ex 2933 59 95	25	2,5-Diamino-4,6-dihydroxypyrimidine monohydrochloride monohydrate	0 %	1.1.2007 - 31.12.2008
ex 2933 59 95	30	Mepanipirim (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2933 59 95	35	4-Amino-2,6-dichloropyrimidine	0 %	1.1.2007 - 31.12.2011
ex 2933 59 95	40	Guanine	0 %	1.1.2007 - 31.12.2008
ex 2933 59 95	50	1-Chloromethyl-4-fluoro-1,4-diazoniabicyclo[2.2.2]octane bis(tetrafluoroborate)	0 %	1.1.2007 - 31.12.2008
ex 2933 59 95	60	2,6-Dichloro-4,8-dipiperidinopyrimido[5,4-d]pyrimidine	0 %	1.1.2007 - 31.12.2008
ex 2933 59 95	70	N-(4-Ethyl-2,3-dioxopiperazin-1-ylcarbonyl)-D-2-phenylglycine	0 %	1.1.2007 - 31.12.2008
ex 2933 59 95	80	N-(4-Ethyl-2,3-dioxopiperazin-1-ylcarbonyl)-D-2-(4-hydroxyphenyl)glycine	0 %	1.1.2007 - 31.12.2008
ex 2933 59 95	85	Adenine	0 %	1.1.2007 - 31.12.2008
ex 2933 69 80	20	1,3,5-Tris[(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)methyl]-1,3,5-triazine-2,4,6(1 <i>H</i> ,3 <i>H</i> ,5 <i>H</i>)-trione	0 %	1.1.2007 - 31.12.2008
ex 2933 69 80	40	Cyanazine (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2933 69 80	50	1,3,5-Tris(2,3-dibromopropyl)-1,3,5-triazinane-2,4,6-trione	0 %	1.1.2007 - 31.12.2008
ex 2933 69 80	60	Hexazinone (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2933 69 80	80	Tris(2-hydroxyethyl)-1,3,5-triazinetriene	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2933 79 00	10	Ezetimibe (INN)	0 %	1.1.2007 - 31.12.2008
ex 2933 99 30	10	Azepane, for the manufacture of goods of subheading 3808 93 (1)	0 %	1.1.2007 - 31.12.2008
ex 2933 99 30	20	5 <i>H</i> -Dibenz[<i>b,f</i>]azepine-5-carbonyl chloride	0 %	1.1.2007 - 31.12.2008
ex 2933 99 90	10	2-(2 <i>H</i> -Benzotriazol-2-yl)-4,6-di- <i>tert</i> -butylphenol	0 %	1.1.2007 - 31.12.2008
ex 2933 99 90	15	2-(2 <i>H</i> -Benzotriazol-2-yl)-4,6-di- <i>tert</i> -pentylphenol	0 %	1.1.2007 - 31.12.2008
ex 2933 99 90	20	2-(2 <i>H</i> -Benzotriazol-2-yl)-4,6-bis(1-methyl-1-phenylethyl)phenol	0 %	1.1.2007 - 31.12.2008
ex 2933 99 90	25	6,6'-Di-2 <i>H</i> -benzotriazol-2-yl-4,4'-bis(1,1,3,3-tetramethylbutyl)-2,2'-methylenediphenol	0 %	1.1.2007 - 31.12.2008
ex 2933 99 90	30	Quizalofop-P-ethyl (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2933 99 90	35	Indoline	0 %	1.1.2007 - 31.12.2008
ex 2933 99 90	40	<i>trans</i> -4-Hydroxy-L-proline	0 %	1.1.2007 - 31.12.2008
ex 2933 99 90	45	Maleic hydrazide (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2933 99 90	50	Metconazole (ISO)	3.2 %	1.1.2007 - 31.12.2008
ex 2933 99 90	55	5-Nitroindole	0 %	1.1.2007 - 31.12.2008
ex 2933 99 90	60	1,3-Bis(3-isocyanatomethylphenyl)-1,3-diazetidone-2,4-dione (dimeric 2,4-toluene diisocyanate)	0 %	1.1.2007 - 31.12.2008
ex 2933 99 90	65	Candesartan cilexetil (INNM)	0 %	1.1.2007 - 31.12.2008
ex 2933 99 90	69	[(3 <i>R</i>)-4-(4-chlorobenzyl)-7-fluoro-5-(methylsulphonyl)-1,2,3,4-tetrahydrocyclopenta[<i>b</i>]indole-3-yl]acetic acid	0 %	1.1.2007 - 31.12.2011
ex 2933 99 90	70	6,7-Dihydro-5 <i>H</i> -cyclopenta[<i>b</i>]pyridine	0 %	1.1.2007 - 31.12.2008
ex 2933 99 90	75	2,3-Dichloropyrazine	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2933 99 90	80	1-Methyltetrazole-5-thiol	0 %	1.1.2007 - 31.12.2008
ex 2933 99 90	86	Pyridaben (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2933 99 90	87	Pyridate (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2933 99 90	88	2,6-Dichloroquinoxaline	0 %	1.1.2007 - 31.12.2008
ex 2933 99 90	89	Carbendazim (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2934 10 00	10	Hexythiazox (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2934 10 00	20	2-(4-Methylthiazol-5-yl)ethanol	0 %	1.1.2007 - 31.12.2008
ex 2934 10 00	30	5-[(2,4-Dioxo-5-thiazolidinyl)methyl]-2-methoxy- <i>N</i> -{[4-(trifluoromethyl)phenyl] methyl}benzamide	0 %	1.1.2007 - 31.12.2008
ex 2934 20 80	10	4-Chloro-1,3-benzothiazol-2(3 <i>H</i>)-one	0 %	1.1.2007 - 31.12.2008
ex 2934 20 80	20	<i>S</i> -(1,3-Benzothiazol-2-yl) (methoxyimino)thioacetate (Z)-2-(2-aminothiazol-4-yl)-2-	0 %	1.1.2007 - 31.12.2008
ex 2934 20 80	30	Benthiavalcarb-isopropyl (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2934 99 90	10	7-Chloro-5-methyl-2 <i>H</i> -1,4-benzothiazin-3-(4 <i>H</i>)-one	0 %	1.1.2007 - 31.12.2008
ex 2934 99 90	15	Carboxin (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2934 99 90	20	4-[4-(Tridecyl[branched]oxy)phenyl]-1,4-thiazinane 1,1-dioxide	0 %	1.1.2007 - 31.12.2008
ex 2934 99 90	25	Oxycarboxin (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2934 99 90	30	Etridiazole (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2934 99 90	35	Dimethenamide (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2934 99 90	40	2,3,5,6-Tetrahydroxy-1,4-diisobutyl-1,4-dioxo-1,4-diphosphinane	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2934 99 90	45	Tris(2,3-epoxypropyl)-1,3,5-triazinetrione	0 %	1.1.2007 - 31.12.2008
ex 2934 99 90	50	1-[2-(1,3-Dioxan-2-yl)ethyl]-2-ethylpyridinium bromide	0 %	1.1.2007 - 31.12.2008
ex 2934 99 90	55	Olmesartan medoxomil (INN)	0 %	1.1.2007 - 31.12.2008
ex 2934 99 90	60	DL-Homocysteine thiolactone hydrochloride	0 %	1.1.2007 - 31.12.2008
ex 2934 99 90	65	Methyl 3-aminothiophene-2-carboxylate	0 %	1.1.2007 - 31.12.2008
ex 2934 99 90	72	1-[3-(5-Nitro-2-furyl)allylideneamino]imidazolidine-2,4-dione	0 %	1.1.2007 - 31.12.2008
ex 2934 99 90	73	<i>N</i> -(5-Mercapto-1,3,4-thiadiazol-2-yl)acetamide	0 %	1.1.2007 - 31.12.2008
ex 2934 99 90	75	(4 <i>R</i> - <i>cis</i>)-1,1-Dimethylethyl-6-[2[2-(4-fluorophenyl)-5-(1-isopropyl)-3-phenyl-4-[(phenylamino)carbonyl]-1 <i>H</i> -pyrrol-1-yl]ethyl]-2,2-dimethyl-1,3-dioxane-4-acetate	0 %	1.1.2007 - 31.12.2011
ex 2934 99 90	76	2,5-Thiophenediylbis(5- <i>tert</i> -butyl-1,3-benzoxazole)	0 %	1.1.2007 - 31.12.2011
ex 2934 99 90	77	Potassium 5-methyl-1,3,4-oxadiazole-2-carboxylate	0 %	1.1.2007 - 31.12.2011
ex 2934 99 90	80	Oblimersen sodium (INNM)	0 %	1.1.2007 - 31.12.2008
ex 2934 99 90	85	Aprepitant (INN)	0 %	1.1.2007 - 31.12.2008
ex 2935 00 90	10	Salts of sulfathiazole (INN)	0 %	1.1.2007 - 31.12.2008
ex 2935 00 90	15	Flupyr sulfuron-methyl-sodium (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2935 00 90	20	Toluenesulfonamides	0 %	1.1.2007 - 31.12.2008
ex 2935 00 90	25	Triflurosulfuron-methyl (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2935 00 90	30	Mixture of isomers consisting of <i>N</i> -ethyltoluene-2-sulfonamide and <i>N</i> -ethyltoluene-4-sulfonamide	0 %	1.1.2007 - 31.12.2008
ex 2935 00 90	35	Chlorsulfuron (ISO)	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 2935 00 90	40	1-(4,6-Dimethoxypyrimidin-2-yl)-3-(2-ethylsulfonylimidazo[1,2-a]pyridin-3-ylsulfonyl)urea (sulfosulfuron)	0 %	1.1.2007 - 31.12.2008
ex 2935 00 90	45	Rimsulfuron (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2935 00 90	50	4,4'-Oxydi(benzenesulfonylhydrazide)	0 %	1.1.2007 - 31.12.2008
ex 2935 00 90	55	Thifensulfuron-methyl (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2935 00 90	60	5-Amino- <i>N</i> -(2,6-dichloro- <i>m</i> -tolyl)-1 <i>H</i> -1,2,4-triazole-3-sulfonamide	0 %	1.1.2007 - 31.12.2008
ex 2935 00 90	65	Tribenuron-methyl (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2935 00 90	70	Methyl 3-aminosulfonylthiophene-2-carboxylate	0 %	1.1.2007 - 31.12.2008
ex 2935 00 90	75	Metsulfuron-methyl (ISO)	0 %	1.1.2007 - 31.12.2008
ex 2935 00 90	76	4-Toluenesulphonyl urea	0 %	1.1.2007 - 31.12.2011
ex 2935 00 90	80	<i>N</i> -(3-Amino-2-hydroxy-4-phenylbutyl)- <i>N</i> -(2-methylpropyl)-4-aminobenzenesulfonamide	0 %	1.1.2007 - 31.12.2008
ex 2935 00 90	81	4-Amino- <i>N</i> -(4-aminophenyl)benzenesulphonamide	0 %	1.1.2007 - 31.12.2008
ex 2935 00 90	82	<i>N</i> -(5,7-Dimethoxy[1,2,4]triazolo[1,5-a]pyrimidin-2-yl)-2-methoxy-4-(trifluoromethyl)pyridine-3-sulphonamide	0 %	1.1.2007 - 31.12.2008
ex 2935 00 90	85	<i>N</i> -[4-(Isopropylaminoacetyl)phenyl]methanesulfonamide hydrochloride	0 %	1.1.2007 - 31.12.2008
ex 2935 00 90	86	4-(<i>m</i> -Tolylamino)pyridine-3-sulfonamide	0 %	1.1.2007 - 31.12.2008
ex 2935 00 90	87	4'-Sulfamoylacetanilide	0 %	1.1.2007 - 31.12.2008
ex 2935 00 90	88	<i>N</i> -(2-(4-amino- <i>N</i> -ethyl- <i>m</i> -toluidino)ethyl)methanesulfonamide sesquisulfate monohydrate	0 %	1.1.2007 - 31.12.2008
ex 2935 00 90	89	3-(3-Bromo-6-fluoro-2-methylindol-1-ylsulphonyl)- <i>N,N</i> -dimethyl-1,2,4-triazol-1-sulphonamide	0 %	1.1.2007 - 31.12.2011
ex 2938 90 90	10	Hesperidin	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
3201 20 00		Wattle extract	0 %	1.1.2007 - 31.12.2008
ex 3201 90 90	10	Tanning extracts of eucalyptus	3.2 %	1.1.2007 - 31.12.2008
ex 3201 90 90	20	Tanning extracts derived from gambier and myrobalan fruits	0 %	1.1.2007 - 31.12.2008
ex 3204 13 00	10	C.I. Basic Red 1 dye	0 %	1.1.2007 - 31.12.2011
ex 3204 15 00	10	Dye C.I. Vat Orange 7	0 %	1.1.2007 - 31.12.2008
ex 3204 15 00	20	Dye C.I. Vat Red 15	0 %	1.1.2007 - 31.12.2008
ex 3204 15 00	30	Dye C.I. Vat Red 14	0 %	1.1.2007 - 31.12.2008
ex 3204 15 00	40	Dye C.I. Vat Brown 57	0 %	1.1.2007 - 31.12.2008
ex 3204 15 00	50	Dye C.I. Vat Blue 47	0 %	1.1.2007 - 31.12.2008
ex 3204 15 00	60	Dyestuff C.I. Vat Blue 4	0 %	1.1.2007 - 31.12.2008
ex 3204 17 00	10	Dye C.I. Pigment Yellow 81	0 %	1.1.2007 - 31.12.2008
ex 3204 19 00	10	Nickel bis {4-methoxy-2-[6-(pentafluoroethylthio)benzothiazol-2-ylazo]-5-(dipropylamino)benzenesulfonate}	0 %	1.1.2007 - 31.12.2008
ex 3204 19 00	15	4-{4-[3-(4-Methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo [h]indeno[2,1-f]chromen-3-yl]phenyl} morpholine	0 %	1.1.2007 - 31.12.2008
ex 3204 19 00	20	13-Ethyl-3-[4-(morpholino)phenyl]-3-phenyl-3,13-dihydrobenzo [h]indeno[2,1-f]chromen-13-ol	0 %	1.1.2007 - 31.12.2008
ex 3204 19 00	25	Cyclohexyl 8-methyl-2,2-diphenyl-2 <i>H</i> -benzo[h]chromene-5-carboxylate	0 %	1.1.2007 - 31.12.2008
ex 3204 19 00	30	13-Isopropyl-3,3-bis(4-methoxyphenyl)-6,11-dimethyl-3,13-dihydrobenzo [h]indeno[2,1-f]chromen-13-ol	0 %	1.1.2007 - 31.12.2008
ex 3204 19 00	35	13-Butyl-13-ethoxy-6,11-dimethoxy-3,3-bis(4-methoxyphenyl)-3,13-dihydrobenzo [h]indeno[2,1-f]chromene	0 %	1.1.2007 - 31.12.2008
ex 3204 19 00	40	Methyl 8'-acetoxy-1,3,3,5,6-pentamethyl-2,3-dihydrospiro[1 <i>H</i> -indole-	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		2,3'-naphtho[2,1- <i>b</i>][1,4]oxazine-9'-carboxylate		
ex 3204 19 00	45	6,7-Dimethoxy-3,3-bis(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo [<i>h</i>]indeno[2,1- <i>f</i>]chromene	0 %	1.1.2007 - 31.12.2008
ex 3204 19 00	50	Methyl 6-(isobutyryloxy)-2,2-diphenyl-2 <i>H</i> -benzo[<i>h</i>]chromene-5-carboxylate	0 %	1.1.2007 - 31.12.2008
ex 3204 19 00	60	Ethoxycarbonylmethyl 8-methyl-2,2-diphenyl-2 <i>H</i> -benzo[<i>h</i>]chromene-5-carboxylate	0 %	1.1.2007 - 31.12.2008
ex 3204 19 00	65	6-Methoxy-7-morpholino-13-ethyl-13-methoxy-3,3-bis-(4-methoxyphenyl)-3,13-dihydrobenzo[<i>h</i>]indeno[2,1- <i>f</i>]chromene	0 %	1.1.2007 - 31.12.2008
ex 3204 19 00	70	Dye C.I. Solvent Red 49	0 %	1.1.2007 - 31.12.2008
ex 3204 19 00	75	6,7-Dimethoxy-13-ethyl-13-methoxy-3,3-bis-(4-methoxyphenyl)-3,13-dihydrobenzo[<i>h</i>]indeno[2,1- <i>f</i>]chromene	0 %	1.1.2007 - 31.12.2008
ex 3204 19 00	80	((<i>R</i>) and (<i>S</i>) isomers of 6,7-Dimethoxy-13-ethyl-13-[2-(2-methoxyethoxy)-ethoxy]-3-(4-methoxyphenyl)-3-(4-fluorophenyl)-3,13-dihydrobenzo[<i>h</i>]indeno[2,1- <i>f</i>]chromene	0 %	1.1.2007 - 31.12.2008
ex 3204 19 00	81	6,11-Difluoro-3,3-di-(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo[<i>h</i>]indeno[2,1- <i>f</i>]chromene	0 %	1.1.2007 - 31.12.2008
ex 3204 19 00	82	3-(4-Fluorophenyl)-3-(4-piperidinophenyl)-13,13-dimethyl-3,13-dihydrobenzo[<i>h</i>]indeno[2,1- <i>f</i>]chromene	0 %	1.1.2007 - 31.12.2008
ex 3204 19 00	83	6,7-Dimethoxy-11-cyano-3,3-di-(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo[<i>h</i>]indeno[2,1- <i>f</i>]chromene	0 %	1.1.2007 - 31.12.2008
ex 3205 00 00	10	Aluminium lakes prepared from dyes for use in the manufacture of pigments for the pharmaceutical industry (1)	0 %	1.1.2007 - 31.12.2008
ex 3206 11 00	10	Titanium dioxide coated with isopropoxytitanium triisostearate, containing by weight 1,5 % or more but not more than 2,5 % of isopropoxytitanium triisostearate	0 %	1.1.2007 - 31.12.2008
ex 3206 19 00	10	Preparation based on titanium dioxide, containing by weight 66 % or more but not more than 71 % of titanium dioxide and 1 % or more but not more than 2 % of isopropoxytitanium triisostearate	0 %	1.1.2007 - 31.12.2008
ex 3206 42 00	10	Lithopone	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3206 49 80	10	Black preparation of iron-oxide pigments, in liquid form, with a maximum particle size not exceeding 20 nanometres and containing by weight 25 % or more of iron evaluated as Fe ₂ O ₃ , for the manufacture of goods of heading No 3304 or 9608 (1)	0 %	1.1.2007 - 31.12.2008
3206 50 00		Inorganic products of a kind used as luminophores	0 %	1.1.2007 - 31.12.2008
ex 3207 30 00	10	Preparation containing : <ul style="list-style-type: none"> — not more than 85 % by weight of silver, — not less than 2 % by weight of palladium, — barium titanate, — terpineol, and — ethyl cellulose, used for screen printing in the manufacture of multilayer ceramic capacitors (1)	0 %	1.1.2007 - 31.12.2008
ex 3207 40 80	20	Glass flakes coated with silver, of an average diameter of 40 (± 10) µm	0 %	1.1.2007 - 31.12.2008
ex 3207 40 80	30	Glass frit, for use in the manufacture of cathode-ray tubes (1)	0 %	1.1.2007 - 31.12.2008
ex 3208 10 90	10	Anti-reflection coating, consisting of an ester based polymer modified with a chromophore group, in the form of a solution of either 2-methoxy-1-propanol, 2-methoxy-1-methylethyl acetate or methyl-2-hydroxyisobutyrate, containing by weight not more than 10 % of polymer	0 %	1.1.2007 - 31.12.2008
ex 3707 90 90	60			
ex 3208 20 10	10	Copolymer of <i>N</i> -vinylcaprolactam, <i>N</i> -vinyl-2-pyrrolidone and dimethylaminoethyl methacrylate, in the form of a solution in ethanol containing by weight 34 % or more but not more than 40 % of copolymer	0 %	1.1.2007 - 31.12.2008
ex 3208 20 10	20	Copolymer of vinylpyrrolidone and dimethylaminoethyl methacrylate, partially quaternized by diethyl sulfate, in the form of a solution in ethanol	0 %	1.1.2007 - 31.12.2008
ex 3905 91 00	92			
ex 3208 20 10	30	Solution of diundecyl phthalate and a copolymer of dibutyl maleate and isobutyl methacrylate in a hydrocarbon solvent	0 %	1.1.2007 - 31.12.2008
ex 3208 20 10	40	Poly(1H,1H-heptafluorobutyl methacrylate) dissolved in a mixture of methyl perfluorobutyl ether and methyl perfluoroisobutyl ether	0 %	1.1.2007 - 31.12.2011
ex 3208 90 19	10	Copolymer of maleic acid and methyl vinyl ether, monoesterified with ethyl and/or isopropyl and/or butyl groups, in the form of a solution in ethanol, ethanol and butanol, isopropanol or isopropanol and butanol	0 %	1.1.2007 - 31.12.2008
ex 3911 90 99	35			

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3208 90 19 ex 3902 90 90	15 94	Modified, chlorinated polyolefins, whether or not in a solution or dispersion	0 %	1.1.2007 - 31.12.2008
ex 3208 90 19	20	Copolymer of polyurethane and silicone, in the form of a solution in a mixture of butanone, toluene and cyclohexanone, containing by weight 13 % or more but not more than 16 % of copolymer	0 %	1.1.2007 - 31.12.2008
ex 3208 90 19	30	Solution containing: — (30 ± 5) % by weight of polyamide resin, — (6,5 ± 3,5) % by weight of diazonaphthoquinone, — (55 ± 5) % by weight of 1-methyl-2-pyrrolidone, — 1 000 µg/kg or less of chloride, — 1 000 µg/kg or less of potassium and — 1 000 µg/kg or less of iron	0 %	1.1.2007 - 31.12.2008
ex 3208 90 19	40	Polymer of methylsiloxane, in the form of a solution in a mixture of acetone, butanol, ethanol and isopropanol, containing by weight 5 % or more but not more than 11 % of polymer of methylsiloxane	0 %	1.1.2007 - 31.12.2008
ex 3208 90 19	50	Solution containing by weight: — (65 ± 10) % of γ -butyrolactone, — (30 ± 10) % of polyamide resin, — (3,5 ± 1,5) % of naphthoquinone ester derivative and — (1,5 ± 0,5) % of arylsilicic acid	0 %	1.1.2007 - 31.12.2008
ex 3208 90 19	60	Copolymer of hydroxystyrene and either styrene or alkoxy styrene or both, dissolved in ethyl lactate	0 %	1.1.2007 - 31.12.2011
ex 3208 90 19	85	Mixture containing by weight : — 30~45 % Polyamide resin; — 2~10 % Diazonaphthoquinone; — 50~65 % γ -Butyrolactone.	0 %	1.1.2007 - 31.12.2008
ex 3208 90 99	10	Solution based on chemically modified natural polymers, containing two or more of the following dyes: — methyl 8'-acetoxy-1,3,3,5,6-pentamethyl-2,3-dihydrospiro[1 <i>H</i> -indole-2,3'-naphtho[2,1- <i>b</i>][1,4]oxazine]-9'-carboxylate, — methyl 6-(isobutyryloxy)-2,2-diphenyl-2 <i>H</i> -benzo[<i>h</i>]chromene-5-carboxylate, — 13-isopropyl-3,3-bis(4-methoxyphenyl)-6,11-dimethyl-3,13-dihydrobenzo[<i>h</i>]indeno[2,1- <i>f</i>]chromen-13-ol, — ethoxycarbonylmethyl 8-methyl-2,2-diphenyl-2 <i>H</i> -benzo[<i>h</i>]chromene-5-carboxylate, — 13-ethyl-3-[4-(morpholino)phenyl]-3-phenyl-3,13-dihydrobenzo[<i>h</i>]indeno[2,1- <i>f</i>]chromen-13-ol	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3208 90 99	20	Solution based on chemically modified natural polymers, containing two or more of the following dyes: <ul style="list-style-type: none"> — 4-[4-(13,13-dimethyl-3-phenyl-3,13-dihydrobenzo [h]indeno[2,1-f]chromen-3-yl)phenyl]morpholine, — 4-{4-[3-(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo [h]indeno[2,1-f]chromen-3-yl]phenyl}morpholine, — cyclohexyl 8-methyl-2,2-diphenyl-2<i>H</i>-benzo[h]chromene-5-carboxylate, — ethoxycarbonylmethyl 6-acetoxy-2,2-diphenyl-2<i>H</i>-benzo[h]chromene-5-carboxylate, — 2-pentyl-7,7-diphenylbenzo[h]chromeno[6,5-<i>d</i>]-1,3-dioxin-4(7<i>H</i>)-one, — 13-butyl-13-ethoxy-6,11-dimethoxy-3,3-bis(4-methoxyphenyl)-3,13-dihydrobenzo [h]indeno[2,1-f]chromene, — 3-(4-methoxyphenyl)-13,13-dimethyl-3-phenyl-3,13-dihydrobenzo [h]indeno[2,1-f]chromene, — 6,7-dimethoxy-3,3-bis(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo [h]indeno[2,1-f]chromene 	0 %	1.1.2007 - 31.12.2008
ex 3215 11 00	10	Printing ink, liquid, consisting of a dispersion of a vinyl acrylate copolymer and colour pigments in isoparaffins, containing by weight not more than 13 % of vinyl acrylate copolymer and colour pigments	0 %	1.1.2007 - 31.12.2008
ex 3215 19 00	10			
ex 3215 90 80	10	Ink formulation, for use in the manufacture of ink-jet cartridges (1)	0 %	1.1.2007 - 31.12.2008
ex 3215 90 80	20	Heat sensitive ink fixed on a plastic film	0 %	1.1.2007 - 31.12.2008
ex 3215 90 80	30	Ink preparation, in the form of powder, for use in the manufacture of ink-filled bottles of a kind used in colour digital presses of heading No 8443 (1)	0 %	1.1.2007 - 31.12.2008
3301 12 10		Essential oil of orange, not deterpenated	0 %	1.1.2007 - 31.12.2008
ex 3402 11 90	10	Surfactant mixture, of disodium salts of dodecyl (sulphophenoxy)benzenesulphonic acid and oxybis (dodecylbenzenesulphonic acid)	0 %	1.1.2007 - 31.12.2008
ex 3402 13 00	10	Vinyl copolymer surface active agent based on polypropylene glycol	0 %	1.1.2007 - 31.12.2008
ex 3402 90 10	20	Mixture of docusate sodium (INN) and sodium benzoate	0 %	1.1.2007 - 31.12.2008
ex 3402 90 10	30	Non-aqueous surface-active preparation, containing: <ul style="list-style-type: none"> — polyethylene glycol alkylphenyl ether, — 2,4,7,9-tetramethyldec-5-yne-4,7-diol and — phosphoric acid esters 	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3402 90 10	40	Amphoteric fluorinated surfactant in a mixture of water and ethanol, containing by weight 25 % or more but not more than 30 % surfactant.	0 %	1.1.2007 - 31.12.2008
ex 3402 90 90	10	Crystalline powder obtained by the reaction of trisodium phosphate with a mixture of sodium hypochlorite and sodium chloride ("chlorinated trisodium phosphate"), containing by weight: <ul style="list-style-type: none"> — 3,5 % or more of available chlorine, measured iodometrically and — 17,0 % or more of phosphorus evaluated as P₂O₅ 	0 %	1.1.2007 - 31.12.2008
ex 3403 99 90	10	Cutting-fluid preparation based on an aqueous solution of synthetic polypeptides	0 %	1.1.2007 - 31.12.2008
ex 3504 00 00	10	Purified antigens obtained from genetically manipulated yeast cells, for the manufacture of detection tests for hepatitis-C (1)	0 %	1.1.2007 - 31.12.2008
ex 3504 00 00	20	Glycoprotein 160 obtained from Human Immunodeficiency Virus, HIV-1 strain	0 %	1.1.2007 - 31.12.2008
ex 3505 10 50	20	<i>O</i> -(2-Hydroxyethyl)-derivative of hydrolysed maize starch	0 %	1.1.2007 - 31.12.2008
ex 3506 10 00	11	Cartridge containing an adhesive based on a mixture of silicon modified polymer and aluminium hydroxide for use in the manufacture of deflection yokes (1)	0 %	1.1.2007 - 31.12.2008
ex 3506 91 00	10	Adhesive based on an aqueous dispersion of a mixture of dimerised rosin and a copolymer of ethylene and vinyl acetate (EVA)	0 %	1.1.2007 - 31.12.2008
ex 3506 91 00	20	Heat-activated adhesive based on phenolic resin and rubber, in the form of a film on a release paper, for use in the manufacture of brake pads for the automotive industry (1)	0 %	1.1.2007 - 31.12.2008
ex 3506 91 00	30	Two component microencapsulated epoxy adhesive dispersed in a solvent	0 %	1.1.2007 - 31.12.2008
ex 3507 90 90	10	Asparaginase	0 %	1.1.2007 - 31.12.2008
ex 3507 90 90	20	Enzymatic preparation based on thermolysine	0 %	1.1.2007 - 31.12.2008
ex 3507 90 90	40	Avian myeloblastosis virus (AMV) reverse transcriptase	0 %	1.1.2007 - 31.12.2008
ex 3507 90 90	60	Trypsin certified to be produced in compliance with EC Good Manufacturing Practice (cGMP) and having a specific enzyme activity of 0,45 µkat/mg or more, for the manufacture of goods of heading No 3004 (1)	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3507 90 90	70	Chymotrypsin	0 %	1.1.2007 - 31.12.2008
ex 3701 30 00	10	Relief printing plate, of a kind used for printing on newsprint, consisting of a metal substrate coated with a photopolymer layer of a thickness of 0,2 mm or more but not exceeding 0,8 mm, not covered with a release film, of a total thickness not exceeding 1 mm	0 %	1.1.2007 - 31.12.2008
ex 3701 99 00	10	Plate of quartz or of glass, covered with a film of chromium and coated with a photosensitive or electron-sensitive resin, for the manufacture of masks for the goods of heading No 8541 or 8542 (1)	0 %	1.1.2007 - 31.12.2008
ex 3702 31 98	10	Colour negative film, for the manufacture of instant-picture film-packs (1)	0 %	1.1.2007 - 31.12.2008
ex 3702 43 00	10	Photographic film, of a nominal width of 459, 669 or 761 mm, composed of several layers, including two polyester films, a carbon layer, an adhesive layer, whether or not with a layer of a copolymer of styrene with acrylonitrile	0 %	1.1.2007 - 31.12.2008
ex 3702 44 00	10			
ex 3703 90 10	10	Paper sheet, coated with silver halide emulsion, for the manufacture of goods of subheading 3701 20 00 (1)	0 %	1.1.2007 - 31.12.2008
ex 3707 10 00	10	Photosensitive emulsion for the sensitization of silicon discs (1)	0 %	1.1.2007 - 31.12.2008
ex 3707 10 00	15	Sensitising emulsion, consisting of diazooxonaphthalenesulphonic acid ester and phenolic resins, containing by weight not more than 12 % of diazooxonaphthalenesulphonic acid ester, in 2-methoxy-1-methylethyl acetate or ethyl lactate	0 %	1.1.2007 - 31.12.2008
ex 3707 10 00	20	Sensitising emulsion, consisting of diazooxonaphthalenesulphonic acid ester and phenolic resins, containing by weight not more than 6 % of diazooxonaphthalenesulphonic acid ester, in 2-methoxy-1-methylethyl acetate	0 %	1.1.2007 - 31.12.2008
ex 3707 10 00	25	Sensitising emulsion containing: — phenolic or acrylic resins — a maximum 2 % by weight of light sensitive acid precursor, in a solution containing 2-methoxy-1-methylethyl acetate or ethyl lactate	0 %	1.1.2007 - 31.12.2008
ex 3707 10 00	30	Preparation based on photosensitive acrylic containing polymer, containing colour pigments, 2-methoxy-1-methylethylacetate and cyclohexanone and whether or not containing ethyl-3-ethoxypropionate	0 %	1.1.2007 - 31.12.2008
ex 3707 10 00	35	Sensitising emulsion, consisting of acrylate and/or methacrylate polymers, containing by weight not more than 7 % photosensitive acid precursors dissolved in an organic solvent containing at least 2-methoxy-	0 %	1.1.2007 - 31.12.2011

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		1-methylethyl acetate		
ex 3707 90 30	10	Toner, in the form of powder, consisting of a copolymer of styrene and butyl acrylate and either magnetite or carbon black, for use as a developer in the manufacture of cartridges for facsimile machines or computer printers (1)	0 %	1.1.2007 - 31.12.2008
ex 3707 90 30	20	Toner, based on a polyol resin, in the form of powder	0 %	1.1.2007 - 31.12.2008
ex 3707 90 30	30	Two-component toner, liquid, in the form of a set consisting of a container containing a dispersion of a vinyl acrylate copolymer and colour pigments in isoparaffins, containing by weight not more than 13 % of vinyl acrylate copolymer and colour pigments, and a container containing isoparaffins	0 %	1.1.2007 - 31.12.2008
ex 3707 90 30	40	Polyester resin based toner, manufactured by a polymerisation process, for use as a developer in the manufacture of computer printer and copier cartridges (1)	0 %	1.1.2007 - 31.12.2008
ex 3707 90 90	10	Anti-reflection coating, consisting of a modified methacrylic polymer, containing by weight not more than 10 % of polymer, in the form of a solution in 2-methoxy-1-methylethyl acetate and 1-methoxypropan-2-ol	0 %	1.1.2007 - 31.12.2008
ex 3707 90 90	20	Anti-reflection coating, consisting of a copolymer of hydroxystyrene and methyl methacrylate, modified with chromophore groups, containing by weight not more than 10 % of polymer, in the form of a solution in 1-methoxypropan-2-ol and ethyl lactate	0 %	1.1.2007 - 31.12.2008
ex 3707 90 90	30	Anti-reflection coating, in the form of an aqueous solution, containing by weight:	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	91	<ul style="list-style-type: none"> — not more than 2 % of perhalogenated sulfonic acid derivatives, — not more than 1 % of a vinyl polymer 		
ex 3707 90 90	40	Anti-reflection coating, consisting of amino-resin and modified phenolic resin, in the form of a solution in 1-methoxypropan-2-ol and ethyl lactate, containing by weight 15 % or more but not more than 24 % of both polymers taken together	0 %	1.1.2007 - 31.12.2008
ex 3707 90 90	50	Anti-reflection coating, containing by weight: <ul style="list-style-type: none"> — 30 % or more but not more than 40 % of cyclohexanone, — 30 % or more but not more than 40 % of 1-methyl-2-pyrrolidone, — 20 % or more but not more than 30 % of tetrahydrofurfuryl alcohol 	0 %	1.1.2007 - 31.12.2008
ex 3801 20 90	10	Colloidal graphite in suspension in water, for use as internal coating in colour cathode-ray tubes (1)	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
3805 90 10		Pine oil	1.7 %	1.1.2007 - 31.12.2008
ex 3808 91 90	10	Indoxacarb (ISO) and its (<i>R</i>) isomer, fixed on a support of silicon dioxide	0 %	1.1.2007 - 31.12.2008
ex 3808 91 90	20	Preparation containing by weight 2 % or more but not more than 4 % of azadirachtin (ISO), not put up for retail sale	0 %	1.1.2007 - 31.12.2008
ex 3808 91 90	30	Preparation containing endospores and protein crystals derived from the hybrid strain GC 91 of <i>Bacillus thuringiensis</i> Berliner subsp. aizawai and kurstaki	0 %	1.1.2007 - 31.12.2008
ex 3808 91 90	40	Spinosad (ISO)	0 %	1.1.2007 - 31.12.2008
ex 3808 92 90	10	Fungicide in the form of a powder, containing by weight 65 % or more but not more than 75 % of hymexazole (ISO), not put up for retail sale	0 %	1.1.2007 - 31.12.2008
ex 3808 92 90	20	Preparation based on diiodomethyl <i>p</i> -tolyl sulfone, not put up for retail sale	0 %	1.1.2007 - 31.12.2008
ex 3808 92 90	30	Preparation consisting of a suspension of pyriithione zinc (INN) in water, containing by weight 24 % or more but not more than 26 % of pyriithione zinc (INN)	0 %	1.1.2007 - 31.12.2008
ex 3808 94 20	10	Preparation containing by weight: <ul style="list-style-type: none"> — 58 % or more but not more than 62 % of 1-bromo-3-chloro-5,5-dimethylhydantoin, — 26 % or more but not more than 29 % of 1,3-dichloro-5,5-dimethylhydantoin, — 10 % or more but not more than 12 % of 1,3-dichloro-5-ethyl-5-methylhydantoin, for the manufacture of swimming-pool disinfectants (1)	0 %	1.1.2007 - 31.12.2008
ex 3808 94 90	10	1-Dodecylguanidine hydrochloride, in the form of a solution in isopropanol and water, containing by weight 40 % or less of 1-dodecylguanidine hydrochloride	0 %	1.1.2007 - 31.12.2008
ex 3809 91 00	10	Mixture of 5-ethyl-2-methyl-2-oxo-1,3,2λ ⁵ -dioxaphosporan-5-ylmethyl methyl phosphonate and bis(5-ethyl-2-methyl-2-oxo-1,3,2λ ⁵ -dioxaphosporan-5-ylmethyl) methylphosphonate	0 %	1.1.2007 - 31.12.2008
ex 3809 92 00	10	Paper anti-fading agent, consisting of a mixture of magnesium trisilicate and monosodium salt of 2,2'-methylenebis(4,6-di- <i>tert</i> -butylphenyl) phosphate	0 %	1.1.2007 - 31.12.2008
ex 3811 21 00	10	Salts of dinonylnaphthalenesulfonic acid, in the form of a solution in	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		mineral oils		
ex 3811 21 00	20	Additives for lubricating oils, based on complex organic molybdenum compounds, in the form of a solution in mineral oil	0 %	1.1.2007 - 31.12.2008
ex 3811 90 00	10	Dinonylnaphthylsulphonic acid salt, in a mineral oil solution	0 %	1.1.2007 - 31.12.2008
ex 3811 90 00	20	Corrosion inhibitor, containing reaction products of fatty acids and tall oil with formaldehyde and (Z)-N-9-octadecenyl-1,3-propanediamine	0 %	1.1.2007 - 31.12.2011
ex 3812 30 80	20	Mixture containing predominantly bis(2,2,6,6-tetramethyl-1-octyloxy-4-piperidyl) sebacate	0 %	1.1.2007 - 31.12.2008
ex 3812 30 80	30	Compound stabilisers containing by weight 15 % or more but not more than 40 % of sodium perchlorate and not more than 70 % of 2-(2-methoxyethoxy)ethanol	0 %	1.1.2007 - 31.12.2008
ex 3814 00 90	10	Mixture containing by weight 25 % or more but not more than 35 % of dimethyl sulfoxide and 65 % or more but not more than 75 % of monoethanolamine	3 %	1.1.2007 - 31.12.2008
ex 3814 00 90	20	Mixture containing by weight: <ul style="list-style-type: none"> — 69 % or more but not more than 71 % of 1-methoxypropan-2-ol, — 29 % or more but not more than 31 % of 2-methoxy-1-methylethyl acetate 	0 %	1.1.2007 - 31.12.2008
ex 3814 00 90	30	Azeotrope mixture containing by weight 30 % or more but not more than 50 % of <i>trans</i> -dichloroethylene and a mixture of isomers of nonafluorobutyl methyl ether or nonafluorobutyl ethyl ether	0 %	1.1.2007 - 31.12.2008
ex 3814 00 90	40	Azeotrope mixtures containing isomers of nonafluorobutyl methyl ether and/or nonafluorobutyl ethyl ether	0 %	1.1.2007 - 31.12.2008
ex 3815 12 00	10	Catalyst, in the form of granules or rings of a diameter of 3 mm or more but not exceeding 10 mm, consisting of silver on an aluminium oxide support and containing by weight 8 % or more but not more than 40 % of silver	0 %	1.1.2007 - 31.12.2008
ex 3815 12 00	20	Catalyst, consisting of palladium and rhenium, fixed on a support of active carbon, in the form of powder, containing: <ul style="list-style-type: none"> — 0,5 % or more but not more than 1,5 % by weight of palladium, — 3 % or more but not more than 5 % by weight of rhenium and — 0,1 mole % or more but not more than 1 mole % of alkaline metals, for use in the manufacture of tetrahydrofuran (1)	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3815 12 00	30	Catalyst, consisting of platinum and palladium fixed on a support, containing by weight: <ul style="list-style-type: none"> — not more than 1,5 % of platinum, — not more than 1,5 % of palladium and — not more than 0,1 % of alkali metals, for use in hydrogenation of white oils (1)	0 %	1.1.2007 - 31.12.2008
ex 3815 19 90	10	Catalyst, consisting of chromium trioxide or dichromium trioxide fixed on a support of silicon dioxide, of a pore volume, as determined by the nitrogen absorption method, of 2 cm ³ /g or more	0 %	1.1.2007 - 31.12.2008
ex 3815 19 90	15	Catalyst, in the form of a powder, consisting of a mixture of metal oxides fixed on a support of silicon dioxide, containing by weight 20 % or more but not more than 40 % of molybdenum, bismuth and iron evaluated together, for use in the manufacture of acrylonitrile (1)	0 %	1.1.2007 - 31.12.2008
ex 3815 19 90	20	Catalyst consisting of chromium oxides and titanium dioxide fixed on a support of silicon dioxide, aluminium oxide or aluminium phosphate	0 %	1.1.2007 - 31.12.2008
ex 3815 19 90	30	Catalyst containing titanium tetrachloride supported on magnesium dichloride, for use in the manufacture of polypropylene (1)	0 %	1.1.2007 - 31.12.2008
ex 3815 19 90	35	Catalyst, in the form of rodlets of a length of 5,5 mm or more but not exceeding 6,5 mm, consisting of copper oxide and zinc oxide fixed on a support of aluminium oxide, containing by weight: <ul style="list-style-type: none"> — 55 % or more but not more than 60 % of copper oxide and — 30 % or more but not more than 35 % of zinc oxide 	0 %	1.1.2007 - 31.12.2008
ex 3815 19 90	40	Catalyst, in the form of spheres of a diameter of 4,2 mm or more but not exceeding 9 mm, consisting of a mixture of metals oxides containing predominantly oxides of molybdenum, vanadium and copper, on a support of silicon dioxide and/or aluminium oxide, for use in the manufacture of acrylic acid (1)	0 %	1.1.2007 - 31.12.2008
ex 3815 19 90	45	Catalyst, consisting predominantly of dichromium copper tetraoxide and copper (II) oxide, containing by weight 38 % or more but not more than 48 % of copper, evaluated as copper (II) oxide, fixed on a support of silicon dioxide, for the hydrogenation of acetophenones (1)	0 %	1.1.2007 - 31.12.2008
ex 3815 19 90	50	Catalyst consisting of organo-metallic compounds of titanium, magnesium and aluminium on a support of silicon dioxide, in the form of a suspension in tetrahydrofuran	0 %	1.1.2007 - 31.12.2008
ex 3815 19 90	55	Catalyst consisting of a mixture of metal oxides containing chromium trioxide, fixed on a support of silicon dioxide	0 %	1.1.2007 - 31.12.2008
ex 3815 19 90	60	Catalyst consisting of dichromium trioxide, fixed on a support of aluminium oxide	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3815 19 90	65	Catalyst consisting of phosphoric acid chemically bonded to a support of silicon dioxide	0 %	1.1.2007 - 31.12.2008
ex 3815 19 90	70	Catalyst consisting of organo-metallic compounds of aluminium and zirconium, fixed on a support of silicon dioxide	0 %	1.1.2007 - 31.12.2008
ex 3815 19 90	75	Catalyst consisting of organo-metallic compounds of aluminium and chromium, fixed on a support of silicon dioxide	0 %	1.1.2007 - 31.12.2008
ex 3815 19 90	80	Catalyst consisting of organo-metallic compounds of magnesium and titanium, fixed on a support of silicon dioxide, in the form of a suspension in mineral oil	0 %	1.1.2007 - 31.12.2008
ex 3815 19 90	85	Catalyst consisting of organo-metallic compounds of aluminium, magnesium and titanium, fixed on a support of silicon dioxide, in the form of powder	0 %	1.1.2007 - 31.12.2008
ex 3815 19 90	86	Catalyst containing titanium tetrachloride supported on magnesium dichloride, for use in the manufacture of polyolefins (1)	0 %	1.1.2007 - 31.12.2008
ex 3815 90 90	15	Catalyst, consisting of a mixture of oxides containing by weight more than 96 % of oxides of molybdenum, vanadium, nickel and antimony, whether or not mixed with porcelain balls, for use in the manufacture of acrylic acid (1)	0 %	1.1.2007 - 31.12.2008
ex 3815 90 90	16	Initiator based on dimethylaminopropyl urea for the manufacture of polyurethane foam systems (1)	0 %	1.1.2007 - 31.12.2008
ex 3815 90 90	20	Catalyst, in powder form, consisting of a mixture of titanium trichloride and aluminium chloride, containing by weight: <ul style="list-style-type: none"> — 20 % or more but not more than 30 % of titanium and — 55 % or more but not more than 72 % of chlorine 	0 %	1.1.2007 - 31.12.2008
ex 3815 90 90	25	Catalyst, consisting of a mixture of oxides containing by weight more than 96 % of oxides of molybdenum, bismuth, nickel, iron and silicon, whether or not mixed with porcelain balls, for use in the manufacture of acrylaldehyde (1)	0 %	1.1.2007 - 31.12.2008
ex 3815 90 90	30	Catalyst, in the form of a powder, containing by weight 82 % or more of copper and of a specific surface of 0,5 m ² /g or more but not exceeding 8 m ² /g	0 %	1.1.2007 - 31.12.2008
ex 3815 90 90	35	Catalyst, in the form of a suspension in oil, consisting of titanium trichloride and aluminium trichloride, containing by weight (on an oil-free basis): <ul style="list-style-type: none"> — 15 % or more but not more than 30 % of titanium and — 40 % or more but not more than 72 % of chlorine 	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3815 90 90	40	Catalyst, in the form of rodlets of a length of 5 mm or more but not exceeding 8 mm, consisting of a mixture of metals oxides containing predominantly oxides of iron, molybdenum and bismuth, whether or not containing silicon dioxide as filler, for use in the manufacture of acrylic acid (1)	0 %	1.1.2007 - 31.12.2008
ex 3815 90 90	50	Catalyst containing titanium trichloride, in the form of a suspension in hexane or heptane containing by weight, in the hexane- or heptane-free material, 9 % or more but not more than 30 % of titanium	0 %	1.1.2007 - 31.12.2008
ex 3815 90 90	60	Catalyst, in the form of rodlets, consisting of an acid aluminosilicate (zeolite): — with a mole-ratio of silicon dioxide : dialuminium trioxide of not less than 500 : 1 and — containing by weight 0,2 % or more but not more than 0,8 % of platinum	0 %	1.1.2007 - 31.12.2008
ex 3815 90 90	65	Catalyst based on a mordenite zeolite, in the form of granules, for use in the manufacture of mixtures of methylamines containing by weight 50 % or more of dimethylamine (1)	0 %	1.1.2007 - 31.12.2008
ex 3815 90 90	70	Catalyst, consisting of a mixture of (2-hydroxypropyl)trimethylammonium formate and dipropylene glycols	0 %	1.1.2007 - 31.12.2008
ex 3815 90 90	75	Catalyst, consisting of a mixture of 1,4-diazabicyclo[2.2.2]octane, 2-hydroxyethyliminodi(acetic acid) and dibutyltin di(acetate), containing by weight 5 % or more but not more than 10 % of 1,4-diazabicyclo[2.2.2]octane	0 %	1.1.2007 - 31.12.2008
ex 3815 90 90	80	Catalyst consisting predominantly of dinonylnaphthalenedisulfonic acid in the form of a solution in isobutanol	0 %	1.1.2007 - 31.12.2008
ex 3815 90 90	81	Catalyst, containing by weight 69 % or more but not more than 79 % of (2-hydroxy-1-methylethyl)trimethylammonium 2-ethylhexanoate	0 %	1.1.2007 - 31.12.2008
ex 3815 90 90	82	Catalyst, containing by weight 35 % or more but not more than 55 % of (2-hydroxy-1-methylethyl)trimethylammonium formate and formic acid	0 %	1.1.2007 - 31.12.2008
ex 3815 90 90	83	Catalyst, in the form of powder, containing aluminium magnesium hydroxide hydrate, rare-earth metals oxides and divanadium pentaoxide	0 %	1.1.2007 - 31.12.2008
ex 3815 90 90	84	Powder catalyst containing by weight a minimum 96 % of oxides of copper, chromium and iron	0 %	1.1.2007 - 31.12.2008
ex 3815 90 90	85	Catalyst based on aluminosilicate (zeolite), for the transalkylation of alkylaromatic hydrocarbons or the oligomerization of olefins (1)	0 %	1.1.2007 - 31.12.2008
ex 3815 90 90	86	Catalyst, in the form of rodlets, consisting of an aluminosilicate	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		(zeolite), containing by weight 2 % or more but not more than 3 % of rare-earth metals oxides and less than 1 % of disodium oxide		
ex 3815 90 90	87	Reaction initiator, consisting of diisopropyl peroxydicarbonate, in the form of a solution in diallyl 2,2'-oxydiethyl dicarbonate	0 %	1.1.2007 - 31.12.2008
ex 3815 90 90	88	Catalyst, consisting of titanium tetrachloride and magnesium chloride, containing by weight on an oil- and hexane-free basis : — 4 % or more but not more than 10 % of titanium and — 10 % or more but not more than 20 % magnesium	0 %	1.1.2007 - 31.12.2008
ex 3815 90 90	89	Rhodococcus rhodocrous J1 bacteria, containing enzymes, suspended in a polyacrylamide gel or in water, for use as a catalyst in the production of acrylamide by the hydration of acrylonitrile (1)	0 %	1.1.2007 - 31.12.2011
ex 3817 00 80	10	Mixture of alkylnaphthalenes, containing by weight: — 88 % or more but not more than 98 % of hexadecylnaphthalene — 2 % or more but not more than 12 % of dihexadecylnaphthalene	0 %	1.1.2007 - 31.12.2008
ex 3819 00 00	20	Fire resistant hydraulic fluid based on phosphate ester	0 %	1.1.2007 - 31.12.2008
ex 3823 19 10	91	Mixture of fatty acids containing by weight: — 2 % or more but not more than 6 % of hexanoic acid, — 53 % or more but not more than 60 % of octanoic acid, — 34 % or more but not more than 42 % of decanoic acid and — not more than 2 % of dodecanoic acid	0 %	1.1.2007 - 31.12.2008
ex 3824 90 15	10	Acid aluminosilicate (artificial zeolite of the Y type) in the sodium form, containing by weight not more than 11 % of sodium evaluated as sodium oxide, in the form of rodlets	0 %	1.1.2007 - 31.12.2008
ex 3824 90 64	01	Intermediate products of the antibiotics manufacturing process obtained from the fermentation of <i>Micromonospora purpurea</i> , whether or not dried	0 %	1.1.2007 - 31.12.2008
ex 3824 90 64	02	Cholic acid and 3 α ,12 α -dihydroxy-5 β -cholan-24-oic acid (deoxycholic acid), crude	0 %	1.1.2007 - 31.12.2008
ex 3824 90 64	03	Products obtained by the <i>N</i> -ethylation of sisomycin (INN)	0 %	1.1.2007 - 31.12.2008
ex 3824 90 64	04	Intermediate products of the antibiotics manufacturing process obtained from the fermentation of <i>Micromonospora inyoensis</i> , whether or not dried	0 %	1.1.2007 - 31.12.2008
ex 3824 90 64	05	Residues of manufacture containing by weight 40 % or more of 11 β ,17,20,21-tetrahydroxy-6-methylpregna-1,4-dien-3-one 21-acetate	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3824 90 64	06	Mixture of inosine (INN), dimepranol (INN) and acedoben (INN)	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	01	Colloidal diantimony pentoxide	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	02	Mixture of nitromethane and 1,2-epoxybutane	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	03	Grains or granules, consisting of a mixture of dialuminium trioxide and zirconium dioxide, containing by weight: <ul style="list-style-type: none"> — 70 % or more but not more than 78 % of dialuminium trioxide and — 19 % or more but not more than 26 % of zirconium dioxide 	5.2 %	1.1.2007 - 31.12.2008
ex 3824 90 98	04	Crude lithium hypochlorite	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	05	Polysilicate, modified with phosphoric acid, in the form of a solution in a mixture of ethanol, isopropanol and tetrahydrofuran, containing by weight 3 % or more but not more than 6 % of polysilicate	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	06	Preparation in the form: <ul style="list-style-type: none"> — of powder, containing by weight 75 % or more of zinc bis[3,5-bis(1-phenylethyl)salicylate] or — of aqueous dispersion, containing by weight 22 % or more but not more than 55 % of zinc bis[3,5-bis(1-phenylethyl)salicylate] 	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	07	Film consisting of the oxides of either barium or calcium and either titanium or zirconium, mixed with binding materials	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	08	Preparation consisting essentially of alkaline asphalt sulfonate, of: <ul style="list-style-type: none"> — a specific gravity of 0,9 or more but not exceeding 1,5 and — a solubility in water of 70 % by weight or more 	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	09	Anti-corrosion preparations consisting of salts of dinonylnaphthalenesulfonic acid, either: <ul style="list-style-type: none"> — on a support of mineral wax, whether or not modified chemically, or — in the form of a solution in an organic solvent 	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	10	Calcined bauxite (refractory grade)	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	11	Magnetisable iron oxide, in the form of powder, containing by weight: <ul style="list-style-type: none"> — 30 % or more but not more than 38 % of bivalent iron in relation to the total iron and — 1 % or more but not more than 4 % of cobalt 	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	12	Oligomer of tetrafluoroethylene, having one iodoethyl end-group	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3824 90 98	13	Preparations containing not less than 92 % but not more than 96.5 % by weight of 1,3:2,4- <i>bis</i> - <i>O</i> -(4-methylbenzylidene)- <i>D</i> -glucitol and also containing carboxylic acid derivatives and an alkyl sulphate	0 %	1.1.2007 - 31.12.2011
ex 3824 90 98	14	Calcium phosphonate phenate, dissolved in mineral oil	0 %	1.1.2007 - 31.12.2011
ex 3824 90 98	15	Mixture of disodium <i>N</i> -benzyloxycarbonyl-L-aspartate and sodium chloride, in the form of a solution in water	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	16	Disodium 9,10-dihydro-9,10-dioxoanthracene-2,7-disulfonate, containing by weight 10 % or more but not more than 20 % of sodium sulfate	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	17	Eutectic alloy wholly of potassium and sodium, containing by weight 77 % or more but not more than 79 % of potassium	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	18	4-Methylmandelic acid, crude	0 %	1.1.2007 - 31.12.2011
ex 3824 90 98	20	Preparation consisting by weight of 83 % or more of 3a,4,7,7a-tetrahydro-4,7-methanoindene (dicyclopentadiene), a synthetic rubber, whether or not containing by weight 7 % or more of tricyclopentadiene, and: <ul style="list-style-type: none"> — either an aluminium-alkyl compound, — or an organic complex of tungsten — or an organic complex of molybdenum 	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	21	Mixture of tris[2-chloro-1-(chloromethyl)ethyl] phosphate and oligomers of methylphosphonic acid and phosphoric acid with ethane-1,2-diol	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	22	Preparations containing not less than 47 % by weight of 1,3:2,4- <i>bis</i> - <i>O</i> -benzylidene- <i>D</i> -glucitol	0 %	1.1.2007 - 31.12.2011
ex 3824 90 98	23	Mixture of sucrose esters, derived from the esterification of sucrose with industrial stearic acid	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	24	Preparations consisting predominantly of phosphabicyclononanes and <i>P</i> -alkyl derivatives thereof, in the form of a solution in 4- <i>tert</i> -butyltoluene	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	25	Lithium tantalate wafers, undoped	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	27	Preparation based on: 2-pentanone, 4-methyl- <i>O</i> , <i>O'</i> , <i>O''</i> -(methylsilylidyne)trioxime and 4-methyl-2-butanone- <i>O</i> , <i>O'</i> , <i>O''</i> , <i>O'''</i> -silane tetrayl tetraoxime	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	28	Preparation consisting predominantly of ethylene glycol and <i>N,N</i> -dimethylformamide or ethylene glycol and γ -butyrolactone, for the	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		manufacture of electrolytic capacitors (1)		
ex 3824 90 98	29	Preparation consisting predominantly of γ -butyrolactone and quaternary ammonium salts, for the manufacture of electrolytic capacitors (1)	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	30	2,4,7,9-Tetramethyldec-5-yne-4,7-diol, hydroxyethylated	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	31	Copper zinc ferrite, coated with a silicone resin, in the form of granules of a size not exceeding 120 μ m	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	32	Styrene oligomer	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	33	Preparation consisting of α -(4-allyloxycarbonylbenzoyl)- ω -allyloxypoly[oxy(2-methylethylene)oxyterephthaloyl] and either diallyl-2,2'-oxydiethyl dicarbonate or diallyl isophthalate	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	34	Mixture of phytosterols in the form of a crystalline waxy powder, containing by weight: <ul style="list-style-type: none"> — 36 % or more, but not more than 79 % of sitosterols, — 15 % or more, but not more than 34 % of sitostanols, — 4 % or more, but not more than 25 % of campesterols, — 0 % or more, but not more than 14 % of campestanols 	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	35	Nitrosylsulfuric acid of a purity by weight of 70 % or more but not exceeding 73 %	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	39	Mixture containing by weight 40 % or more but not more than 50 % of 2-hydroxyethyl methacrylate and 40 % or more but not more than 50 % of glycerol ester of boric acid	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	40	Azelaic acid of a purity by weight of 75 % or more but not exceeding 85 %	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	42	Mixed metals oxides, in the form of powder, containing by weight: <ul style="list-style-type: none"> — either 5 % or more of barium, neodymium or magnesium and 15 % or more of titanium, — or 30 % or more of lead and 5 % or more of niobium, for use in the manufacture of dielectric films or for use as dielectric materials in the manufacture of multilayer ceramic capacitors (1)	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	43	7-Aminonaphthalene-1,3,6-trisulfonic acid and its salts, of a purity by weight of 65 % or more	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	45	Preparations consisting predominantly of ethylene glycol and: <ul style="list-style-type: none"> — either diethylene glycol, dodecandioic acid and ammonia water, — or silicon oxide, 	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		<ul style="list-style-type: none"> — or ammonium hydrogen azelate, — or ammonium hydrogen azelate and silicon oxide, — or dodecandioic acid, ammonia water and silicon oxide, for the manufacture of electrolytic capacitors (1)		
ex 3824 90 98	46	Carboxylic acid anhydride based hardener for epoxyde resin, in liquid form, of a specific weight at 25 °C of 1,15 g/cm ³ or more but not exceeding 1,18 g/cm ³	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	49	Mixed oxides of metals, in the form of powder, containing by weight: <ul style="list-style-type: none"> — 70 % or more but not more than 75 % of iron oxide, — 10 % or more but not more than 20 % of zinc oxide, — 10 % or more but not more than 15 % of magnesium oxide, — 1 % or more but not more than 5 % of manganese oxide and — 1 % or more but not more than 3 % of copper oxide 	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	50	Zeolites consisting of oxides of barium, aluminium and silicon, containing by weight 30 % or more but not more than 40 % of barium oxide, in the form of spheres of which 80 % or more by weight have a diameter of 0,3 mm or more but not more than 1,2 mm	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	54	2-Hydroxybenzonnitrile, in the form of a solution in <i>N,N</i> -dimethylformamide, containing by weight 45 % or more but not more than 55 % of 2-hydroxybenzonnitrile	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	55	Mixture containing by weight 75 % or more of pentaerythritol triallyl ether	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	57	Mixture of trialkylphosphine oxides	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	58	Platinum oxide fixed on a porous support of aluminium oxide, containing by weight 0,1 % or more but not more than 1 % of platinum and 0,5 % or more but not more than 5 % of ethylaluminium dichloride	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	60	<i>α</i> -Phenoxy carbonyl- <i>ω</i> -phenoxy poly[oxy(2,6-dibromo-1,4-phenylene) isopropylidene(3,5-dibromo-1,4-phenylene)oxycarbonyl]	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	61	Mixture of metal oxides, in the form of powder, containing by weight: <ul style="list-style-type: none"> — 20 % or more of barium, — 10 % or more of titanium and — 4 % or more of lead or 3 % or more of niobium or 0,7 % or more of zirconium, for use as dielectric material in the manufacture of multilayer ceramic capacitors (1)	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	63	Triethylborane, in the form of a solution in tetrahydrofuran	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3824 90 98	64	Aluminium sodium silicate, in the form of spheres of a diameter of: — either 1,6 mm or more but not exceeding 3,4 mm, — or 4 mm or more but not exceeding 6 mm	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	65	Mixture of tris(alkoxycarbonylamino)-1,3,5-triazines in which alkoxy groups are methoxy and butoxy	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	66	Mixture of primary <i>tert</i> -alkylamines	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	67	Preparation consisting of indium tin oxide dispersed in organic solvents	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	72	Solution containing by weight 80 % or more of 2,4,6-trimethylbenzaldehyde in acetone	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	73	Particles of silicon dioxide on which are covalently bonded organic compounds, for use in the manufacture of high performance liquid chromatography columns (HPLC) and sample preparation cartridges (1)	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	77	Diethylmethoxyborane, in the form of a solution in tetrahydrofuran	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	80	Preparation containing by weight 81 % or more but not more than 89 % bis (3,4-epoxy-cyclohexylmethyl)-adipate	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	81	Calcium oxide stabilised zirconia in the form of lumps of which 94 % or more by weight is retained on a 16 mm sieve, containing by weight: — 92 % or more of zirconium dioxide and — 2 % or more but not more than 6 % of calcium oxide	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	82	α -(2,4,6-Tribromophenyl)- ω -(2,4,6-tribromophenoxy)poly[oxy(2,6-dibromo-1,4-phenylene)isopropylidene(3,5-dibromo-1,4-phenylene)oxycarbonyl]	0 %	1.1.2007 - 31.12.2008
ex 3907 40 00	20			
ex 3824 90 98	83	Mixture containing: — unsaturated, dimerised fatty acids, hydrogenated and polymerized with ethylenediamine and octadecan-1-ol, — white oil, — 2-methylpentane-2,4-diol and — glycerides of decanoic and octanoic acids	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	84	Reaction product, containing by weight: — 1 % or more but not more than 40 % of molybdenum oxide, — 10 % or more but not more than 50 % of nickel oxide, — 30 % or more but not more than 70 % of tungsten oxide	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	85	Particles of magnesium sodium silicate on which are ionically bonded chiral complexes of tris(1,10-phenanthroline)ruthenium, for use in the	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		manufacture of high performance liquid chromatography columns (HPLC) (1)		
ex 3824 90 98	88	Oligomeric reaction product, consisting of bis(4-hydroxyphenyl) sulfone and 1,1'-oxybis(2-chloroethane)	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	89	Oligomer of tetrafluoroethylene, having tetrafluoroiodoethyl end-groups	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	90	Hollow spheres of fused aluminosilicate containing 65-80 % amorphous aluminosilicate, with the following characteristics: — a melting point of between 1600 °C and 1800 °C, — a density of 0.6 - 0.8 g/cm ³ , for use in the manufacture of particle filters in motor vehicles (1)	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	92	Bis{4-[(5-chloro-2-hydroxyphenyl)azo]-3-hydroxy- <i>N</i> -phenyl-2-naphthalene carboxyamidate} ferrate with a mixture of ammonium, sodium and hydrogen cations	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	93	Prepared resin, based on diallyl 2,2'-oxydiethyl dicarbonate and oligomers thereof, containing by weight 42 % or more but not more than 52 % of diallyl 2,2'-oxydiethyl dicarbonate and 33 % or more but not more than 43 % of a copolymer of terephthalic acid, propane-1,2-diol and allyl alcohol	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	94	Prepared resin, based on diallyl 2,2'-oxydiethyl dicarbonate and oligomers thereof, containing by weight 73 % or more of diallyl 2,2'-oxydiethyl dicarbonate	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	95	Mixture of phytosterols, in the form of flakes, containing by weight 80 % or more of sterols and not more than 4 % of stanols	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	96	Zirconium dioxide, stabilised with calcium oxide, in the form of a powder	0 %	1.1.2007 - 31.12.2008
ex 3824 90 98	97	Preparation containing by weight either 10 % or more but not more than 20 % of lithiumfluorophosphate or 5 % or more but not more than 10 % of lithium perchlorate in mixtures of organic solvents	0 %	1.1.2007 - 31.12.2008
ex 3825 69 00	10	Spent catalyst, in the form of rodlets of diameter of 1 mm or more but not exceeding 3 mm, containing a mixture of sulfides of tungsten and of nickel on a support of zeolite, containing by weight not more than 10 % of tungsten and not more than 10 % of nickel, for regeneration as a catalyst for hydrocarbon cracking (1)	0 %	1.1.2007 - 31.12.2008
ex 3901 10 10	10	Linear polyethylene, of a specific gravity of 0,928 or more but not exceeding 0,935 and of a melt flow index of less than 0,6 g/min, for the manufacture of shrinkmelt binder fibres (1)	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3901 10 90	10	Polyethylene for the manufacture of photo-resist film for semiconductors or printed circuits (1)	0 %	1.1.2007 - 31.12.2008
ex 3901 10 90	20	Polyethylene, in the form of granules, of a specific gravity of 0,925 ($\pm 0,0015$), a melt flow index of 0,3 g/10 min ($\pm 0,05$ g/10 min), for the manufacture of blown films of a Haze value not exceeding 6 % and an elongation at break (MD/TD) of 210/340 (1)	0 %	1.1.2007 - 31.12.2008
ex 3901 10 90	30	Polyethylene, in the form of granules, containing by weight 15 % or more of copper, for the purpose of protecting against static charge build up and corrosion	0 %	1.1.2007 - 31.12.2008
ex 3901 20 90	10	Polyethylene, in one of the forms mentioned in note 6 (b) to Chapter 39, of a specific gravity of 0,945 or more but not exceeding 0,985, for the manufacture of films for typewriter ribbon or similar ribbon (1)	0 %	1.1.2007 - 31.12.2008
ex 3901 20 90	20	Polyethylene, containing by weight 35 % or more but not more than 45 % of mica	0 %	1.1.2007 - 31.12.2008
ex 3901 20 90	30	Polyethylene, in one of the forms mentioned in note 6 (b) to Chapter 39, of a specific gravity of 0,940 or more but not exceeding 0,943 and a melt flow index of 27 g/10 min (± 5 g/10 min) (MFI 190 °C/2,16 kg as determined by the ISO 1133 method), for the manufacture of bicomponent spunbonded non-wovens (1)	0 %	1.1.2007 - 31.12.2008
ex 3901 90 90	81	Copolymer of ethylene and propylene, modified with maleic anhydride, containing by weight more than 55 % of ethylene and not more than 3 % of maleic anhydride	0 %	1.1.2007 - 31.12.2008
ex 3901 90 90	82	Polyethylene modified with maleic anhydride, containing by weight not more than 4 % of maleic anhydride, for use in the manufacture of fuel tanks for motor vehicles (1)	0 %	1.1.2007 - 31.12.2008
ex 3901 90 90	91	Ionomer resin consisting of a salt of a copolymer of ethylene with methacrylic acid	4 %	1.1.2007 - 31.12.2008
ex 3901 90 90	92	Chlorosulphonated polyethylene	0 %	1.1.2007 - 31.12.2008
ex 3901 90 90	93	Copolymer of ethylene, vinyl acetate and carbon monoxide, for use as a plasticizer in the manufacture of roof sheets (1)	0 %	1.1.2007 - 31.12.2008
ex 3901 90 90	94	Mixtures of A-B block copolymer of polystyrene and ethylene-butylene copolymer and A-B-A block copolymer of polystyrene, ethylene-butylene copolymer and polystyrene, containing by weight not more than 35 % of styrene	0 %	1.1.2007 - 31.12.2008
ex 3901 90 90	95	Copolymer of ethylene and butylene, having hydroxyl or acrylate end-groups, containing by weight 40 % or more but not more than 60 % of	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3902 90 90	95	butylene		
ex 3901 90 90	96	Linear A-B block copolymer of polyisoprene, whether or not epoxidized, and either ethylene-butylene copolymer or styrene-ethylene-butylene copolymer, having hydroxyl end-groups	0 %	1.1.2007 - 31.12.2008
ex 3902 90 90	96			
ex 3903 90 90	50			
ex 3901 90 90	97	Chlorinated polyethylene, in the form of powder	0 %	1.1.2007 - 31.12.2008
ex 3902 10 00	10	Polypropylene containing no plasticizer and not more than: <ul style="list-style-type: none"> — 7 mg/kg of aluminium, — 2 mg/kg of iron, — 1 mg/kg of magnesium, — 8 mg/kg of chloride 	0 %	1.1.2007 - 31.12.2008
ex 3902 10 00	20	Polypropylene, containing no plasticiser, <ul style="list-style-type: none"> — of a melting point of more than 150 °C (as determined by the ASTM D 3417 method), — of a heat of fusion of 15 J/g or more but not exceeding 70 J/g, — of an elongation at break of 1 000 % or more (as determined by the ASTM D 638 method), — of a tensile modulus of 69 MPa or more but not exceeding 379 MPa (as determined by the ASTM D 638 method) 	0 %	1.1.2007 - 31.12.2008
ex 3902 10 00	30	Polypropylene, containing not more than 1 mg/kg of aluminium, 0,05 mg/kg of iron, 1 mg/kg of magnesium and 1 mg/kg of chloride, for use in the manufacture of packaging for disposable contact lenses (1)	0 %	1.1.2007 - 31.12.2008
ex 3902 20 00	10	Polyisobutylene, of an average molecular weight (M_n) of 700 or more but not exceeding 800	0 %	1.1.2007 - 31.12.2008
ex 3902 30 00	91	A-B Block copolymer of polystyrene and an ethylene-propylene copolymer, containing by weight 40 % or less of styrene, in one of the forms mentioned in note 6 (b) to Chapter 39	0 %	1.1.2007 - 31.12.2008
ex 3903 90 90	25			
ex 3902 30 00	94	Chlorinated polypropylene, chemically modified with maleic anhydride, containing by weight 23 % or more but not more than 26 % of chlorine and less than 5 % of epoxy resin	0 %	1.1.2007 - 31.12.2008
ex 3902 90 90	92	Polymers of 4-methylpent-1-ene	0 %	1.1.2007 - 31.12.2008
ex 3902 90 90	97	Hydrogenated polyisobutene, in liquid form	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3902 90 90	98	Synthetic poly-alpha-olefin with a viscosity at 100° Celsius (measured according to method ASTM D 445) ranging from 3 centistokes to 9 centistokes and obtained by polymerization of a mixture of dodecene and tetradecene, containing a maximum of 40 % of tetradecene	0 %	1.1.2007 - 31.12.2011
ex 3903 19 00	20	Polystyrene of a molecular weight (M_n) not exceeding 5 000	0 %	1.1.2007 - 31.12.2008
ex 3903 90 90	10	Copolymer, entirely of styrene with maleic anhydride, or entirely of styrene with maleic anhydride and an acrylic monomer, whether or not containing a styrene-butadiene block copolymer, in one of the forms mentioned in note 6 (b) to Chapter 39, for the manufacture of sheetings for head-liners for cars (1)	0 %	1.1.2007 - 31.12.2008
ex 3903 90 90	15	Copolymer, entirely of styrene with maleic anhydride, or entirely of styrene with maleic anhydride and an acrylic monomer, also partially esterified, of an average molecular weight (M_n) not exceeding 3 000, in one of the forms mentioned in note 6 (a) and (b) to Chapter 39	0 %	1.1.2007 - 31.12.2008
ex 3903 90 90	20	Copolymer of styrene with 2-ethylhexyl acrylate or with <i>n</i> -butyl acrylate, containing: <ul style="list-style-type: none"> — 10 mole % or more but not more than 16 mole % of acrylate, — 0,2 mg/kg or less of sodium and — 0,1 mg/kg or less of calcium 	0 %	1.1.2007 - 31.12.2008
ex 3903 90 90	35	Copolymer of α -methylstyrene and styrene, having a softening point exceeding 113 °C	0 %	1.1.2007 - 31.12.2008
ex 3911 90 99	30			
ex 3903 90 90	40	Copolymer of styrene with α -methylstyrene and acrylic acid, of a molecular weight (M_n) of 500 or more but not exceeding 6 000	0 %	1.1.2007 - 31.12.2008
ex 3906 90 90	40			
ex 3911 90 99	50			
ex 3903 90 90	55	Copolymer of styrene, methyl methacrylate, butyl acrylate and either acrylic acid or hydroxyethyl methacrylate, of a molecular weight (M_n) of 500 or more but not exceeding 6 000	0 %	1.1.2007 - 31.12.2008
ex 3906 90 90	45			
ex 3903 90 90	65	Copolymer of styrene, butyl acrylate, butyl methacrylate, methyl methacrylate and acrylic acid, in the form of powder, containing by weight (81 ± 1) % of styrene, (6 ± 1) % of butyl acrylate, (5 ± 1) % of butyl methacrylate, (7 ± 1) % of methyl methacrylate and (1 ± 0,5) % of acrylic acid	0 %	1.1.2007 - 31.12.2008
ex 3903 90 90	70	Ammonium polystyrenesulfonate, in the form of an aqueous solution	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3903 90 90	75	Copolymer of styrene and vinyl pyrrolidone, containing by weight not more than 1 % of sodium dodecyl sulfate, in the form of an aqueous emulsion, for the manufacture of goods of subheading 3305 20 00 or of hair dyes of subheading 3305 90 90 (1)	0 %	1.1.2007 - 31.12.2008
ex 3903 90 90	80	Granules of copolymer of styrene and divinylbenzene a minimum diameter of 150 µm and a maximum 800 µm and containing by weight : — minimum 65 % styrene, — maximum 25 % divinylbenzene for use in the manufacture of ion exchange resins (1)	0 %	1.1.2007 - 31.12.2008
ex 3904 22 00	91	Poly(vinyl chloride), dyed in the mass, in the form of flakes, grains, pebbles or rectangular chips, for use as decorative elements in floor and wall coverings (1)	0 %	1.1.2007 - 31.12.2008
ex 3926 90 98	80			
ex 3904 30 00	10	Copolymer of vinyl chloride with vinyl acetate and maleic acid, containing by weight: — 81,5 % or more but not more than 84,5 % of vinyl chloride, — 13,8 % or more but not more than 16,2 % of vinyl acetate and — 0,8 % or more but not more than 1,2 % of maleic acid, for the manufacture of goods of heading No 3215 or for use in the manufacture of coatings for containers and closures of a kind used for preserving food and drink (1)	0 %	1.1.2007 - 31.12.2008
ex 3904 30 00	20	Copolymer of vinyl chloride with vinyl acetate and maleic acid, containing by weight: — 80,5 % or more but not more than 81,5 % of vinyl chloride, — 16,5 % or more but not more than 17,5 % of vinyl acetate and — 1,5 % or more but not more than 2,5 % of maleic acid, for use in heat-sealing of plastics onto steel substrate for industrial uses (1)	0 %	1.1.2007 - 31.12.2008
ex 3904 40 00	91	Copolymer of vinyl chloride with vinyl acetate and vinyl alcohol, containing by weight: — 87 % or more but not more than 92 % of vinyl chloride, — 2 % or more but not more than 9 % of vinyl acetate and — 1 % or more but not more than 8 % of vinyl alcohol, in one of the forms mentioned in note 6 (a) or (b) to Chapter 39, for the manufacture of goods of heading No 3215 or 8523 or for use in the manufacture of coatings for containers and closures of a kind used for preserving food and drink (1)	0 %	1.1.2007 - 31.12.2008
ex 3904 40 00	92	Copolymer of vinyl chloride, vinyl acetate, hydroxypropyl acrylate and maleic acid, containing by weight 80 % or more but not more than 83 % of vinyl chloride, 1,6 % or more but not more than 2 % of hydroxy groups and 0,25 % or more but not more than 0,38 % of carboxyl groups	0 %	1.1.2007 - 31.12.2008
ex 3904 40 00	93	Copolymer of vinyl chloride and methyl acrylate, containing by weight	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		(80 ± 1) % of vinyl chloride and (20 ± 1) % of methyl acrylate, in the form of a aqueous emulsion		
ex 3904 50 90	91	Copolymer of vinylidene chloride with vinyl chloride, containing by weight 79,5 % or more of vinylidene chloride, in one of the forms mentioned in note 6 (a) or (b) to Chapter 39, for the manufacture of fibres, monofilament or strip (1)	0 %	1.1.2007 - 31.12.2008
ex 3904 61 00	10	Mixture of polytetrafluoroethylene and mica, in one of the forms mentioned in note 6 (b) to Chapter 39	0 %	1.1.2007 - 31.12.2008
ex 3904 61 00	20	Copolymer of tetrafluoroethylene and trifluoro(heptafluoropropoxy)ethylene, containing 3,2 % or more but not more than 4,6 % by weight of trifluoro(heptafluoropropoxy)ethylene and less than 1 mg/kg of extractable fluoride ions	0 %	1.1.2007 - 31.12.2008
ex 3904 61 00	30	Polytetrafluoroethylene, in the form of powder, of a specific surface of 8 m ² /g or more but not exceeding 12 m ² /g, a particle size distribution of 10 % of less than 10 µm and 90 % of less than 35 µm and an average particle size of 20 µm	0 %	1.1.2007 - 31.12.2008
ex 3904 61 00	60	Mixture of polytetrafluoroethylene (PTFE), sodium chloride and a nonionic surfactant	0 %	1.1.2007 - 31.12.2008
ex 3904 69 90	92	Copolymer of tetrafluoroethylene and trifluoro(trifluoromethoxy)ethylene	0 %	1.1.2007 - 31.12.2008
ex 3904 69 90	93	Copolymer of ethylene with chlorotrifluoroethylene, in one of the forms mentioned in note 6 (b) to Chapter 39	0 %	1.1.2007 - 31.12.2008
ex 3904 69 90	94	Copolymer of ethylene and tetrafluoroethylene	0 %	1.1.2007 - 31.12.2008
ex 3904 69 90	96	Polychlorotrifluoroethylene, in one of the forms mentioned in note 6 (a) and (b) to Chapter 39	0 %	1.1.2007 - 31.12.2008
ex 3904 69 90	97	Copolymer of chlorotrifluoroethylene and vinylidene difluoride	0 %	1.1.2007 - 31.12.2008
ex 3905 29 00	91	Copolymer of vinyl acetate, dibutyl maleate and acrylic acid, in the form of a solution in isopropyl acetate and toluene	0 %	1.1.2007 - 31.12.2008
ex 3905 91 00	91	Copolymer of <i>N</i> -vinylcaprolactam, <i>N</i> -vinyl-2-pyrrolidone and dimethylaminoethyl methacrylate	0 %	1.1.2007 - 31.12.2008
ex 3905 99 90	93	Poly(vinyl acetate phthalate)	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3905 99 90	94	Polymer of vinylpyrrolidone and dimethylaminoethyl methacrylate, containing by weight 97 % or more but not more than 99 % of vinylpyrrolidone, in the form of a solution in water	0 %	1.1.2007 - 31.12.2008
ex 3905 99 90	95	Hexadecylated or eicosylated polyvinylpyrrolidone	0 %	1.1.2007 - 31.12.2008
ex 3905 99 90	96	Polymer of vinyl formal, in one of the forms mentioned in note 6 (b) to Chapter 39, of a molecular weight (M_w) of 25 000 or more but not exceeding 150 000 and containing by weight: <ul style="list-style-type: none"> — 9,5 % or more but not more than 13 % of acetyl groups evaluated as vinyl acetate and — 5 % or more but not more than 6,5 % of hydroxy groups evaluated as vinyl alcohol 	0 %	1.1.2007 - 31.12.2008
ex 3905 99 90	97	Povidone (INN)-iodine	0 %	1.1.2007 - 31.12.2008
ex 3905 99 90	98	Poly(vinyl pyrrolidone) partially substituted by triacontyl groups, containing by weight 78 % or more but not more than 82 % of triacontyl groups	0 %	1.1.2007 - 31.12.2008
ex 3906 10 00	10	Poly(methyl methacrylate), in the form of expansible beads containing 2-methylpentane as blowing agent	0 %	1.1.2007 - 31.12.2008
3906 90 60		Copolymer of methyl acrylate with ethylene and a monomer containing a non-terminal carboxy group as a substituent, containing by weight 50 % or more of methyl acrylate, whether or not mixed with silicon dioxide	0 %	1.1.2007 - 31.12.2008
ex 3906 90 90	10	Polymerization product of acrylic acid with small quantities of a polyunsaturated monomer, for the manufacture of medicaments of heading No 3003 or 3004 (1)	0 %	1.1.2007 - 31.12.2008
ex 3906 90 90	20	Polymerization product of acrylic acid with small quantities of a polyunsaturated monomer, for use as a stabilizer in emulsions or dispersions with a pH of more than 13 (1)	6 %	1.1.2007 - 31.12.2008
ex 3906 90 90	30	Copolymer of styrene with hydroxyethyl methacrylate and 2-ethylhexyl acrylate, of a molecular weight (M_n) of 500 or more but not exceeding 6 000	0 %	1.1.2007 - 31.12.2008
ex 3906 90 90	50	Polymers of esters of acrylic acid with one or more of the following monomers in the chain: <ul style="list-style-type: none"> — chloromethyl vinyl ether, — chloroethyl vinyl ether, — chloromethylstyrene, — vinyl chloroacetate, — methacrylic acid, — butenedioic acid monobutyl ester, containing by weight not more than 5 % of each of the monomeric units, in one of the forms mentioned in note 6 (b) to Chapter 39	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3906 90 90	55	Mixtures containing copolymers of methyl acrylate and ethylene and polyether-ester copolymers containing terephthalic acid, in the form of granules or pellets	0 %	1.1.2007 - 31.12.2008
ex 3906 90 90	60	Copolymer of butyl acrylate and vinyl chloride, containing by weight (58 ± 1) % of butyl acrylate and (42 ± 1) % of vinyl chloride, in the form of a aqueous emulsion	0 %	1.1.2007 - 31.12.2008
ex 3906 90 90	70	Copolymer of ethylene dimethacrylate with either methyl methacrylate or dodecyl methacrylate	0 %	1.1.2007 - 31.12.2008
ex 3906 90 90	75	Copolymer of <i>N</i> -[4,5-dihydro-5-oxo-1-(2,4,6-trichlorophenyl)(1',4-bi-1 <i>H</i> -pyrazol)-3-yl]= methacrylamide, butyl acrylate and styrene, in the form of powder	0 %	1.1.2007 - 31.12.2008
ex 3906 90 90	80	Polydimethylsiloxane-graft-(polyacrylates; polymethacrylates)	0 %	1.1.2007 - 31.12.2008
ex 3906 90 90	85	Non aqueous dispersion type polymers of esters of acrylic acid with a hydrolyzable silyl group at one or both polymer ends	0 %	1.1.2007 - 31.12.2008
ex 3907 20 11	10	Poly(ethylene oxide) of an average molecular weight (M_n) of 100 000 or more	0 %	1.1.2007 - 31.12.2008
ex 3907 20 21	10	Mixture, containing by weight 70 % or more but not more than 80 % of a polymer of glycerol and 1,2-epoxypropane and 20 % or more but not more than 30 % of a copolymer of dibutyl maleate and <i>N</i> -vinyl-2-pyrrolidone	0 %	1.1.2007 - 31.12.2008
ex 3907 20 21	20	Copolymer of tetrahydrofuran and tetrahydro-3-methylfuran with an average molecular weight of 3500 (± 100)	0 %	1.1.2007 - 31.12.2008
ex 3907 20 29	10	Products containing co-polymers of dextrose, sorbitol and citric or phosphoric acid, containing not less than 90 % by weight of co-polymers on the ashfree and anhydrous basis	0 %	1.1.2007 - 31.12.2011
ex 3907 20 29	20	Poly[oxy-1,4-phenyleneisopropylidene-1,4-phenyleneoxy-(2-hydroxytrimethylene)], of an average molecular weight (M_w) of more than 26 000, in one of the forms mentioned in note 6 (b) to Chapter 39	0 %	1.1.2007 - 31.12.2008
ex 3907 20 99	10	Bis{2-[ω -hydroxy-poly(ethyleneoxy)]ethyl} hydroxymethylphosphonate	0 %	1.1.2007 - 31.12.2008
ex 3907 20 99	15	Poly(oxypropylene) having alkoxy-silyl end-groups	0 %	1.1.2007 - 31.12.2008
ex 3907 20 99	30	Homopolymer of 1-chloro-2,3-epoxypropane (epichlorohydrin)	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3907 20 99	35	Polyethylene glycol chemically modified with an isocyanate group containing a carbodiimide group, in the form of a solution in 2-methoxy-1-methylethyl acetate	0 %	1.1.2007 - 31.12.2008
ex 3907 20 99	40	Polydimethylsiloxane grafted with a poly(ethylene oxide) having C ₂₀ and C ₂₂ fatty acids ester end-groups	0 %	1.1.2007 - 31.12.2008
ex 3907 20 99	45	Copolymer of ethylene oxide and propylene oxide, having aminopropyl and methoxy end-groups	0 %	1.1.2007 - 31.12.2008
ex 3907 20 99	50	Copolymer of ethylene oxide and propylene oxide, having 2-aminopropyl end-groups	0 %	1.1.2007 - 31.12.2008
ex 3907 30 00	20	Epoxyde resin in the form of powder, containing by weight 44 % or more but not more than 55 % of quartz and 0,5 % or more but not more than 1 % of diantimony trioxide, for the coating of film capacitors (1)	0 %	1.1.2007 - 31.12.2008
ex 3907 30 00	30	Epoxyde resin, without solvent, containing mineral fillers (silica), without glass fibre, of a specific weight at 25 °C of 1,55 g/cm ³ or more but not exceeding 1,60 g/cm ³	0 %	1.1.2007 - 31.12.2008
ex 3907 30 00	40	Epoxyde resin, containing by weight 70 % or more of silicon dioxide, for the encapsulation of goods of heading No 8533, 8535, 8536, 8541, 8542 or 8548 (1)	0 %	1.1.2007 - 31.12.2008
ex 3916 90 15	10			
ex 3926 90 98	70			
ex 3907 30 00	50	Liquid epoxide resin of 2-propenenitrile/1,3-butadiene-epoxide copolymer, not containing any solvent, with: <ul style="list-style-type: none"> — a zinc borate hydrate content not exceeding 40 % by weight, — a diantimony trioxide content not exceeding 5 % by weight 	0 %	1.1.2007 - 31.12.2008
ex 3907 40 00	10	Copolymer of hexane-1,6-diol, cyclohexane-1,4-dimethanol and ethylene carbonate	0 %	1.1.2007 - 31.12.2008
ex 3907 60 80	10	Copolymer of terephthalic acid and isophthalic acid with ethylene glycol, butane-1,4-diol and hexane-1,6-diol	0 %	1.1.2007 - 31.12.2008
ex 3907 60 80	20	Oxygen binding copolymer (as determined by the ASTM D 1434 and 3985 methods), obtained from benzenedicarboxylic acids, ethylene glycol and polybutadiene substituted by hydroxy groups	0 %	1.1.2007 - 31.12.2008
3907 70 00		Poly(lactic acid)	0 %	1.1.2007 - 31.12.2008
ex 3907 91 90	10	Diallyl phthalate prepolymer, in the form of powder	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3907 99 19	10	Poly(oxy-1,4-phenylenecarbonyl), in the form of powder	0 %	1.1.2007 - 31.12.2008
ex 3907 99 98	10			
ex 3907 99 19	20	Liquid crystal copolyester with a melting point of not less than 270 °C, whether or not containing fillers	0 %	1.1.2007 - 31.12.2008
ex 3907 99 19	40	Copolymer of isophthalic acid and 5-sodiosulphoisophthalic acid with cyclohexanedimethanol and diethylene glycol	0 %	1.1.2007 - 31.12.2008
ex 3907 99 19	50	Semi-crystalline polycyclohexylenedimethylene terephthalate polymer resin, containing by weight 10 % or more but not more than 40 % of glass fibre, in the form of granules or pellets	0 %	1.1.2007 - 31.12.2011
ex 3908 90 00	10	Poly(iminomethylene-1,3-phenylenemethyleneiminoadipoyl), in one of the forms mentioned in note 6 (b) to Chapter 39	0 %	1.1.2007 - 31.12.2008
ex 3908 90 00	20	Copolymer consisting of hexamethylenediamine, isophthalic acid and terephthalic acid, in one of the forms mentioned in note 6(b) to Chapter 39	0 %	1.1.2007 - 31.12.2008
ex 3908 90 00	30	Reaction product of mixtures of octadecanecarboxylic acids polymerised with an aliphatic polyetherdiamine	0 %	1.1.2007 - 31.12.2008
ex 3908 90 00	40	Thermoplastic polyamide resin having a fire point of more than 750 °C, for use in the manufacture of deflection yokes of cathode ray tubes (1)	0 %	1.1.2007 - 31.12.2008
ex 3909 40 00	10	Polycondensation product of phenol with formaldehyde, in the form of hollow spheres of a diameter of less than 150 µm	0 %	1.1.2007 - 31.12.2008
ex 3910 00 00	10	3-[(2-Aminoethyl)amino]propyl(methyl)cyclosiloxane	0 %	1.1.2007 - 31.12.2008
ex 3910 00 00	20	Block copolymer of poly(methyl-3,3,3-trifluoropropylsiloxane) and poly[methyl(vinyl)siloxane]	0 %	1.1.2007 - 31.12.2008
ex 3910 00 00	40	Biocompatible silicones for the manufacture of long term surgical implants (1)	0 %	1.1.2007 - 31.12.2011
ex 3911 90 19	10	Poly(oxy-1,4-phenylenesulfonyl-1,4-phenyleneoxy-4,4'-biphenylene)	0 %	1.1.2007 - 31.12.2008
ex 3911 90 99	25	Copolymer of vinyltoluene and α -methylstyrene	0 %	1.1.2007 - 31.12.2008
ex 3911 90 99	40	Mixed calcium and sodium salt of a copolymer of maleic acid and methyl vinyl ether, having a calcium content of 9 % or more but not	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		more than 16 % by weight		
ex 3911 90 99	45	Copolymer of maleic acid and methyl vinyl ether	0 %	1.1.2007 - 31.12.2008
ex 3911 90 99	55	Solution containing: <ul style="list-style-type: none"> — (36 ± 0,5) % by weight of polyamide with lateral ester groups, — (2 ± 0,5) % by weight of acrylic ester, — (48 ± 0,5) % by weight of 1-methyl-2-pyrrolidone, — (12 ± 0,5) % by weight of bis(2-methoxyethyl) ether, — 500 µg/kg or less of potassium and — 500 µg/kg or less of iron, for use in the manufacture of goods of heading No 8542 (1)	0 %	1.1.2007 - 31.12.2008
ex 3911 90 99	60	Hydrocarbon prepolymer, obtained by the reaction of cyclopentadiene and 1,3-pentadiene	0 %	1.1.2007 - 31.12.2008
ex 3911 90 99	65	Calcium zinc salt of a copolymer of maleic acid and methyl vinyl ether	0 %	1.1.2007 - 31.12.2008
ex 3911 90 99	75	Microspheres of a copolymer of divinylbenzene and styrene, of an average diameter of 220 µm or more but not exceeding 575 µm	0 %	1.1.2007 - 31.12.2008
ex 3926 90 97	75			
ex 3911 90 99	80	Poly[(8-methyl-8-methoxycarbonyltricyclo[5.2.1.0 ^{2,6}]decane-3,5-diyl)ethylene]	0 %	1.1.2007 - 31.12.2008
ex 3911 90 99	85	Polymer of ethylene and styrene, cross-linked with divinylbenzene, in the form of a suspension	0 %	1.1.2007 - 31.12.2008
ex 3911 90 99	86	Copolymer of methyl vinyl ether and maleic acid anhydride	0 %	1.1.2007 - 31.12.2011
ex 3912 11 00	10	Non-plasticized cellulose triacetate, in the form of flakes, for the manufacture of cellulose triacetate yarn (1)	0 %	1.1.2007 - 31.12.2008
ex 3912 39 10	10	Ethylcellulose, not plasticized	0 %	1.1.2007 - 31.12.2008
ex 3912 39 10	20	Ethylcellulose, in the form of aqueous dispersion containing hexadecan-1-ol and sodium dodecyl sulfate, containing by weight (27 ± 3) % of ethylcellulose	0 %	1.1.2007 - 31.12.2008
ex 3912 39 80	10	Cellulose, both hydroxyethylated and ethylated, insoluble in water	0 %	1.1.2007 - 31.12.2008
ex 3912 39 80	20	Cellulose, both hydroxyethylated and alkylated with alkyl chain-lengths of 3 or more carbon atoms	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3912 90 10	10	Cellulose acetate propionate, non-plasticised, in the form of powder: <ul style="list-style-type: none"> — containing by weight 25 % or more of propionyl (as determined by the ASTM D 817-72 method) and — of a viscosity not exceeding 120 poise (as determined by the ASTM D 817-72 method), for the manufacture of printing inks, paints, lacquers and other coatings, and reprographic coatings (1)	0 %	1.1.2007 - 31.12.2008
ex 3912 90 10	20	Hydroxypropyl methylcellulose phthalate	0 %	1.1.2007 - 31.12.2008
ex 3913 90 00	92	Protein, chemically modified by carboxylation and/or phthalic acid addition, having a molecular weight of 100 000 to 300 000	0 %	1.1.2007 - 31.12.2008
ex 3913 90 00	94	Granules containing by weight: <ul style="list-style-type: none"> — 35 % or more but less than 75 % of a high amylose extruded biopolymer produced from corn starch, — 5 % or more but less than 16 % polyvinyl alcohol, — 10 % or more but less than 46 % of polyol plasticisers, — 0.25 % or more but less than 3 % of stearic acid, — whether or not containing 30 % (\pm 10 %) of biodegradable polyester resin but never to a level that exceeds the amount of the high amylose biopolymer 	0 %	1.1.2007 - 31.12.2011
ex 3913 90 00	95	Chondroitinsulfuric acid, sodium salt	0 %	1.1.2007 - 31.12.2008
ex 3913 90 00	96	Powder consisting of 90 % (\pm 5 %) by weight of a high amylose extruded biopolymer produced from corn starch, 10 % (\pm 5 %) by weight of a synthetic polymer and 0.5 % (\pm 0.25 %) of stearic acid	0 %	1.1.2007 - 31.12.2011
ex 3913 90 00	97	Chitosonium pyrrolidonecarboxylate	0 %	1.1.2007 - 31.12.2008
ex 3913 90 00	98	Sodium hyaluronate	0 %	1.1.2007 - 31.12.2008
ex 3915 90 90	10	Waste, parings and scrap of photographic, cinematographic and radiographic films	0 %	1.1.2007 - 31.12.2008
ex 3916 90 90	10	Composite profile shape, reinforced with glass fibres, produced by pultrusion, for the manufacture of window frames (1)	0 %	1.1.2007 - 31.12.2008
ex 3917 32 10	10	Flexible pipe of silicone foam, with continuous channels, of a Shore A hardness of 7 or more but not exceeding 48 and a density of 0,28 g/cm ³ or more but not exceeding 0,92 g/cm ³	0 %	1.1.2007 - 31.12.2008
ex 3917 32 31	91	Assembly of heat-shrinkable tubing of polyethylene with poly(vinyl acetate), arranged in parallel at equally spaced intervals and attached at one or both ends by perforated plastic strips, in rolls	0 %	1.1.2007 - 31.12.2008
ex 3917 32 99	10			

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3926 90 97	45			
ex 3917 32 39	20	Pipe consisting of a block copolymer of polytetrafluoroethylene and polyperfluoroalkoxytrifluoroethylene, of a length of not more than 600 mm, a diameter of not more than 85 mm and a wall-thickness of 30 µm or more but not exceeding 110 µm	0 %	1.1.2007 - 31.12.2008
ex 3917 32 39	30	Thermo-shrinkable polystyrene tube for use in the manufacture of zinc-carbon batteries (1)	0 %	1.1.2007 - 31.12.2008
ex 3919 10 19	10	Reflecting film, consisting of a layer of polyurethane, with, on one side, security imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use, and embedded glass beads and, on the other side, an adhesive layer, covered on one side or on both sides with a release film	0 %	1.1.2007 - 31.12.2008
ex 3919 10 38	20			
ex 3919 90 38	10			
ex 3920 99 28	20			
ex 3919 10 31	10			
ex 3919 10 38	30	Reflecting laminated sheet, consisting of a film of polycarbonate totally embossed on one side in a regular shaped pattern, covered on both sides with one or more layers of plastic material, whether or not covered on one side with an adhesive layer and a release sheet	0 %	1.1.2007 - 31.12.2008
ex 3919 90 31	50			
ex 3920 61 00	20			
ex 3919 10 38	10	Self-adhesive tape of metallised polyurethane containing glass beads for use in the manufacture of marine life-saving equipment (1)	0 %	1.1.2007 - 31.12.2008
ex 3919 10 38	40	Double-sided, self-adhesive modified epoxy resin foil, put up in rolls, 16 cm wide, 140-200 m long and with a total thickness of 20 µm, not for retail sale	0 %	1.1.2007 - 31.12.2008
ex 3919 10 61	91	Reflecting film, consisting of a layer of poly(vinyl chloride), a layer of alkyd polyester, with, on one side, security imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use, only visible by means of a retroreflecting lighting, and embedded glass beads and, on the other side, an adhesive layer, covered on one side or on both sides with a release film	0 %	1.1.2007 - 31.12.2008
ex 3919 90 61	94			

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3919 10 61	92	Black polyvinyl chloride film having a high gloss of more than 90 degrees as determined by test method ASTM D 2457 covered on one side with a protective polyethylene terephthalate film and on the other side a pressure sensitive adhesive with channels and a polyethylene terephthalate release liner	0 %	1.1.2007 - 31.12.2011
ex 3919 90 61	95			
ex 3919 10 69	91	Black acrylic foam tape, covered on one side with a heat activatable adhesive or an acrylic pressure sensitive adhesive and on the other side with an acrylic pressure sensitive adhesive and a release sheet, of a peel adhesion at an angle of 90 ° of more than 25 N/cm (as determined by the ASTM D 3330 method)	0 %	1.1.2007 - 31.12.2008
ex 3919 90 69	96			
ex 3919 10 69	95	Reflecting laminated sheet showing a regular pattern, consisting of a film of poly(methylmethacrylate), followed by a layer of acrylic polymer containing microprisms, a film of poly(methylmethacrylate), an adhesive layer and a release sheet	0 %	1.1.2007 - 31.12.2008
ex 3919 90 69	98			
ex 3919 90 10	10	Shaped sheet of plastic, with an adhesive layer containing polyisobutylene and pectin, for the manufacture of colostomy bags (1)	0 %	1.1.2007 - 31.12.2008
ex 3919 90 31	15	Poly(ethylene terephthalate) film, with a coloured layer on one side and a self adhesive layer on the other, coated on both sides with protective film, with an overall thickness of 100 (± 10) µm, in rolls, for the manufacture of optical filters (1)	0 %	1.1.2007 - 31.12.2008
ex 3919 90 31	25	Polyethylene terephthalate film: <ul style="list-style-type: none"> — laminated on one side with a copper mesh of a line width of 10 to 15 µm, — a coloured adhesive layer on the other, — coated on both sides with a protective film, — with a total thickness of 110–210 µm for use in the manufacture of optical filters (1)	0 %	1.1.2007 - 31.12.2008
ex 3919 90 31	35	Polyethylene terephthalate film, covered on one side with a tinted layer and on the other with an adhesive layer, coated on both sides with a protective film, with an overall thickness of 235 (± 5) µm, for the manufacture of optical filters (1)	0 %	1.1.2007 - 31.12.2008
ex 3919 90 31	40	Reflecting polyester sheeting embossed in a pyramidal pattern, for the manufacture of safety stickers and badges, safety clothing and accessories thereof, or of school satchels, bags or similar containers (1)	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	20			
ex 3920 62 90	20			
ex 3920 63 00	30			

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3920 69 00	30			
ex 3919 90 31	60	Film consisting of 1 to 3 laminated layers of poly(ethylene terephthalate) and a copolymer of terephthalic acid, sebacic acid and ethylene glycol, coated on one side with an acrylic abrasion resistant coating and on the other side with an acrylic pressure sensitive adhesive, a water soluble methylcellulose coating and a poly(ethylene terephthalate) protective liner	0 %	1.1.2007 - 31.12.2008
ex 3919 90 31	70	Poly(ethylene terephthalate) sheet, covered on one side with an antistatic layer and a hardcoat layer and on the other side with an adhesive layer and a release sheet, in rolls, for the manufacture of optical filters (1)	0 %	1.1.2007 - 31.12.2008
ex 3919 90 61	92	Poly(vinyl chloride) sheeting, of a thickness of less than 1 mm, coated with an adhesive in which are embedded glass balls of a diameter not exceeding 100 µm	0 %	1.1.2007 - 31.12.2008
ex 3919 90 69	92			
ex 3919 90 61	93	Adhesive film consisting of a base of a copolymer of ethylene and vinyl acetate (EVA) of a thickness of 70 µm or more and an adhesive part of acrylic type of a thickness of 5 µm or more, for the protection of the surface of silicon discs (1)	0 %	1.1.2007 - 31.12.2008
ex 3919 90 69	93			
ex 3920 10 89	25			
ex 3919 90 69	95	Biaxially-oriented film of poly(methyl methacrylate), of a thickness of 50 µm or more but not exceeding 90 µm, whether or not covered on one side with an adhesive layer and a release sheet	0 %	1.1.2007 - 31.12.2008
ex 3920 51 00	30			
ex 3920 10 26	20	Film of polyethylene, of a thickness of 20 µm or more but not exceeding 45 µm, containing calcium carbonate in the mass, for the manufacture of napkins for babies or of sanitary towels or of tampons or of disposable surgical gowns (1)	0 %	1.1.2007 - 31.12.2008
ex 3920 10 26	30	Film of a thickness not exceeding 0,20 mm, of a blend of polyethylene and a copolymer of ethylene with oct-1-ene, embossed in a regular rhomboidal pattern, for coating both sides of a layer of unvulcanized rubber (1)	0 %	1.1.2007 - 31.12.2008
ex 3920 10 89	20			
ex 3920 10 26	40	Film of polyethylene, of a kind used for typewriter ribbon	0 %	1.1.2007 - 31.12.2008
ex 3920 10 40	91	Synthetic paper pulp, in the form of moist sheets, made from unconnected finely-branched polyethylene fibrils, whether or not blended with cellulose fibres in a quantity not exceeding 15 %, containing poly(vinyl alcohol) dissolved in water as the moistening	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		agent		
ex 3920 10 40	92	Laminated sheet or strip consisting of a film composed of a blend of a copolymer of ethylene with vinyl acetate and a modified ethylene-propylene-elastomer (EPM) or a modified ethylene-propylene-diene elastomer (EPDM), coated or covered on both sides with a film of a copolymer of ethylene with vinyl acetate	0 %	1.1.2007 - 31.12.2008
ex 3920 10 89	35	Reflecting film, consisting of a layer of polyethylene, a layer of polyurethane, with, on one side, security imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use, only visible by means of a retroreflecting lighting, and embedded glass beads and, on the other side, a hot-melt adhesive layer, covered on one side or on both sides with a release film	0 %	1.1.2007 - 31.12.2008
ex 3920 10 89	40	Composite sheet containing an acrylic coating and laminated to a high-density polyethylene layer, of a total thickness of 0.8 mm or more but not exceeding 1.2 mm	0 %	1.1.2007 - 31.12.2011
ex 3920 20 21	30	Biaxially oriented polypropylene film with a coextruded layer of polyethylene on one side and a total thickness of 11.5 µm or more but not more than 13.5 µm.	0 %	1.1.2007 - 31.12.2008
ex 3920 20 29	91	Mono-axial oriented film, consisting of three layers, each layer consisting of a mixture of polypropylene and a copolymer of ethylene and vinyl acetate, having: <ul style="list-style-type: none"> — a thickness of 55 µm or more but not exceeding 97 µm, — a tensile modulus in the machine direction of 0,75 GPa or more but not exceeding 1,45 GPa and — a tensile modulus in the transverse direction of 0,20 GPa or more but not exceeding 0,55 GPa 	0 %	1.1.2007 - 31.12.2008
ex 3920 20 90	91	Synthetic paper pulp, in the form of moist sheets, made from unconnected finely-branched polypropylene fibrils, whether or not blended with cellulose fibres in a quantity not exceeding 15 %, containing poly(vinyl alcohol) dissolved in water as the moistening agent	0 %	1.1.2007 - 31.12.2008
ex 3920 20 90	92	Laminated sheet or strip, consisting of a film of a thickness of 181 µm or more but not exceeding 223 µm composed of a blend of a copolymer of propylene with ethylene and a copolymer of styrene-ethylene-butylene-styrene (SEBS) coated or covered on one side with a layer of a copolymer of styrene-ethylene-butylene-styrene (SEBS) and a layer of polyester	0 %	1.1.2007 - 31.12.2008
ex 3920 20 90	93	Polypropylene sheet, of a thickness of 0,5 mm or more but not exceeding 1,0 mm, having a tensile strength at break of 14,7 MPa or more but not exceeding 21 MPa (as determined by the ASTM D 638 method), in rolls of a width of 3,81 m	0 %	1.1.2007 - 31.12.2008
ex 3920 30 00	20	Laminated sheet or strip, consisting of a film composed of a blend of a thermoplastic elastomer (TPE) of styrene-butadiene-styrene (SBS) with polyethylene or polypropylene, of a thickness of 100 µm or more but not exceeding 200 µm, coated or covered on both sides with a film of	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		polypropylene of a thickness not exceeding 20 µm		
ex 3920 43 10	91	Reflecting sheeting, consisting solely of a single layer of poly(vinyl chloride), wholly embossed on one side in a regular pyramidal pattern	0 %	1.1.2007 - 31.12.2008
ex 3920 49 10	91			
ex 3920 43 10	92	Sheeting of poly(vinyl chloride), stabilized against ultraviolet rays, without any holes, even microscopic, of a thickness of 60 µm or more but not exceeding 80 µm, containing 30 or more but not more than 40 parts of plasticizer to 100 parts of poly(vinyl chloride)	0 %	1.1.2007 - 31.12.2008
ex 3920 43 10	93	Poly(vinyl chloride) sheet, with relief printing, of a kind used in the templates for textile printing	0 %	1.1.2007 - 31.12.2008
ex 3920 43 10	94	Film of a specular gloss of 70 or more, measured at an angle of 60 ° using a glossmeter (as determined by the ISO 2813:2000 method), consisting of one or two layers of poly(vinyl chloride) coated on both sides with a layer of plastic, of a thickness of 0,26 mm or more but not exceeding 1,0 mm, covered on the gloss surface with a protective film of polyethylene, in rolls of a width of 1 000 mm or more but not exceeding 1 450 mm, for use in the manufacture of goods of heading No 9403 (1)	0 %	1.1.2007 - 31.12.2008
ex 3920 49 10	93			
ex 3920 43 10	95	Reflecting laminated sheet, consisting of a film of poly(vinyl chloride) and a film of an other plastic totally embossed in a regular pyramidal pattern, covered on one side with a release sheet	0 %	1.1.2007 - 31.12.2008
ex 3920 49 10	92			
ex 3920 43 10	96	Film, of a specular gloss of 70 or more measured at an angle of 60 ° using a glossmeter (as determined by the ISO 2813:2000 method), consisting of a layer of poly(ethylene terephthalate) and a layer of colored poly(vinyl chloride), for coating panels and doors of a kind used in the manufacture of domestic appliances (1)	0 %	1.1.2007 - 31.12.2008
ex 3920 43 10	97	Film embossed to a depth of not more than 12 µm, of a specular gloss of 7 or more but not exceeding 17, measured at an angle of 60 ° using a glossmeter (as determined by the ISO 2813:2000 method), consisting of at least two layers of poly(vinyl chloride), of a total thickness not exceeding 0,5 mm, covered on the embossed side with a protective film, in rolls of a width of 1 400 mm or more but not exceeding 1 420 mm, for use in the manufacture of goods of heading No 9403 (1)	0 %	1.1.2007 - 31.12.2008
ex 3920 51 00	10	Poly(methyl methacrylate) plate, with an antistatic coating, of dimensions of 738 × 972 mm (± 1,5 mm)	0 %	1.1.2007 - 31.12.2008
ex 3920 51 00	20	Plate of poly(methyl methacrylate) containing aluminium trihydroxide, of a thickness of 3,5 mm or more but not exceeding 19 mm	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3920 61 00	10	Polycarbonate film of a thickness not exceeding 15 µm, for the manufacture of film capacitors (1)	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	01	Coextruded opaque sheet of poly(ethylene terephthalate), of a thickness of 50 µm or more but not exceeding 350 µm, consisting especially of a layer containing carbon black	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	03			
ex 3920 62 19	04	Poly(ethylene terephthalate) film, of a thickness of less than 11 µm, for the manufacture of audiodigital tapes for cassettes (1)	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	06			
ex 3920 62 19	07	Poly(ethylene terephthalate) film, not coated with an adhesive, of a thickness not exceeding 25 µm, either:	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	09			
ex 3920 62 19	11	Film of poly(ethylene terephthalate) only, of a total thickness not exceeding 120 µm, consisting of one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	13			
ex 3920 62 19	14	Poly(ethylene terephthalate) film, of a thickness of 20 µm or more but not exceeding 150 µm, coated on one side with silicone, for use in the manufacture of window film (1)	3 %	1.1.2007 - 31.12.2011
ex 3920 62 19	16			
ex 3920 62 19	17	Laminated film of poly(ethylene terephthalate) only, of a total thickness not exceeding 120 µm, consisting of one layer which is metallised only and one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	19			
ex 3920 62 19	21	Film of poly(ethylene terephthalate), coated or covered on one side or on both sides with a layer of modified polyester, of a total thickness of 7 µm or more but not exceeding 11 µm, for the manufacture of video tapes with a magnetic layer of metallic pigments and a width of 8 mm or of 12,7 mm (1)	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	23			
ex 3920 62 19	24	Single ply film of poly(ethylene terephthalate) only, of a thickness not exceeding 120 µm, which only:	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3920 62 19	26	<ul style="list-style-type: none"> — contains a colouring and/or UV-absorbing material throughout the mass and — is metallised on one side, <p>whether or not coated on one or both sides with a vinyl acrylate polymer but having no other coating or adhesive</p>		
ex 3920 62 19	27	Film of poly(ethylene terephthalate), of a total thickness not exceeding 120 µm, of a width of 100 mm or more but not exceeding 115 mm,	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	29	coated on both sides with one or more layers containing different chemicals, for the manufacture of goods of subheading 3701 20 00 (1)		
ex 3920 62 19	31	Film of poly(ethylene terephthalate), on one side metallised and coated with white ink and a protective layer and on the other side coated with a thermosensitive seal layer, of a width of 100 mm or more but not exceeding 150 mm, for the manufacture of goods of subheading 3701 20 00 (1)	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	33			
ex 3920 62 19	34	Film of poly(ethylene terephthalate), coated on one side with a layer of modified polyester, of a thickness of 20 µm (± 0,7 µm) or of 30 µm	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	36	(± 0,9 µm), for the manufacture of audio magnetic tapes of a total thickness of 33 µm or more (1)		
ex 3920 62 19	37	Poly(ethylene terephthalate) film, of a thickness not exceeding 12 µm,	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	39	coated on one side with a layer of aluminium oxide of a thickness not exceeding 35 nm		
ex 3920 62 19	41	Poly(ethylene terephthalate) film, of a thickness of 18 µm or more but not exceeding 25 µm, having:	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	43	<ul style="list-style-type: none"> — a shrinkage of (3,4 ± 0,1) % in the machine direction (as determined by the ASTM D 1204 method) and — a shrinkage of (0,3 ± 0,2) % in the transverse direction (as determined by the ASTM D 1204 method) 		
ex 3920 62 19	44	Poly(ethylene terephthalate) film, of a thickness not exceeding 19 µm or of a weight of 20 g/m ² or more but not exceeding 26,7 g/m ² , for use in the manufacture of photo-resist film (1)	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	46			
ex 3920 62 19	47	Film of poly(ethylene terephthalate), coated on both sides with a layer of epoxy acrylic resin, of a total thickness of 37 µm (± 3 µm)	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3920 62 19	49			
ex 3920 62 19	51	Film of poly(ethylene terephthalate), coated on one side with metal and/or metal oxides, containing by weight less than 0,1 % of aluminium, of a thickness not exceeding 300 µm and having a surface resistivity not exceeding 10 000 ohms (per square) (as determined by the ASTM D 257-93 method)	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	53			
ex 3920 62 19	54	Matt film of poly(ethylene terephthalate), of a specular gloss of 15 measured at an angle of 45 ° and 18 measured at an angle of 60 ° using a glossmeter (as determined by the ISO 2813:2000 method) and a width of 1 600 mm or more	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	56			
ex 3920 62 19	57	Film of white poly(ethylene terephthalate), dyed in the mass, of a thickness of 185 µm or more but not exceeding 253 µm, coated on both sides with an antistatic layer	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	59			
ex 3920 62 19	61	Film of a total thickness of 4,5 µm (± 0,16 µm), consisting of a biaxially-oriented poly(ethylene terephthalate) film, of an elastic modulus (in the machine direction) of 12 kg/mm ² (± 2 kg/mm ²) and a tensile strength (in the machine direction) of more than 28 kg/mm ² , and of an anti-adherent coating	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	63			
ex 3920 62 19	67	Poly(ethylene terephthalate) film, coated with among other a scratch resistant layer based on polyacrylate and a thermoadhesive layer, of a nominal width of 790 mm and a total thickness of 23 µm or more but not exceeding 26 µm	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	69			
ex 3920 62 19	71	Non-metallised reflecting film, consisting of outside layers of poly(ethylene terephthalate) or poly(ethylene naphthalate) and multiple layers of poly(methyl methacrylate), of a reflectance coefficient of 95 % or more (as determined by the ASTM E 1164-94 and ASTM E 387-95 methods) and a total thickness not exceeding 70 µm	0 %	1.1.2007 - 31.12.2008
ex 3920 69 00	70			
ex 3920 62 19	72	Non-metallised reflecting film, consisting of outside layers of poly(ethylene terephthalate) and multiple layers of poly(methyl methacrylate), of a total thickness of 51 µm (± 10 %), for use in the manufacture of laminated solar-reflecting automotive glass (1)	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	73	Iridescent film of polyester and poly(methyl methacrylate)	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3920 69 00	40			
ex 3920 62 19	74	Multilayer film of a thickness not exceeding 150 µm, consisting of a polyester film coated on one side with polycarbonate resin, metallized on the other side with titanium coated with polycarbonate resin and other layers containing <i>N,N'</i> -diphenyl- <i>N,N'</i> -di- <i>m</i> -tolylbiphenyl-4,4'-ylenediamine	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	76			
ex 3920 62 19	77	Sheet of poly(ethylene terephthalate), containing: <ul style="list-style-type: none"> — temperature-sensitive layers which form primary colours after heating, — reflective layer, — protective layer, to be used in polychromatic thermal printers (1)	0 %	1.1.2007 - 31.12.2008
ex 3920 62 19	88	Laminated sheet, consisting of a biaxially oriented film of poly(ethylene terephthalate), covered on one side or on both sides with a layer of poly(ethylene terephthalate), for use in the manufacture of identity cards, credit cards and similar products (including "smart" cards) (1)	0 %	1.1.2007 - 31.12.2008
ex 3920 62 90	31	Film of poly(ethylene terephthalate), of a thickness of 500 µm (± 25 µm)	0 %	1.1.2007 - 31.12.2008
ex 3920 62 90	33			
ex 3920 62 90	40	Strips of poly(ethylene terephthalate), covered on both sides with a layer of chemically modified polyester, of a width not exceeding 16 mm and a thickness of 0,5 mm or more but not exceeding 2 mm, having a tensile strength at break of 0,7 GPa or more (as determined by the ASTM D 638 method)	0 %	1.1.2007 - 31.12.2008
ex 3920 69 00	20	Film of poly(ethylene naphthalene-2,6-dicarboxylate)	0 %	1.1.2007 - 31.12.2008
ex 3920 69 00	50	Polycondensation product of terephthalic acid with a mixture of cyclohex-1,4-ylenedimethanol and ethane-1,2-diol, in the form of a film	0 %	1.1.2007 - 31.12.2008
ex 3920 69 00	60	Film of a copolymer of ethylene terephthalate and ethylene isophthalate, of a thickness not exceeding 2 µm	0 %	1.1.2007 - 31.12.2008
ex 3920 91 00	91	Poly(vinyl butyral) film having a graduated coloured band	3 %	1.1.2007 - 31.12.2008
ex 3920 91 00	92	Plasticized film of polyvinyl butyral, containing by weight: <ul style="list-style-type: none"> — either 14,5 % or more but not more than 17,5 % of dihexyl adipate, — or 14,5 % or more but not more than 28,5 % of dibutyl sebacate 	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3920 91 00	93	Film of poly(ethylene terephthalate), whether or not metallised on one or both sides, or laminated film of poly(ethylene terephthalate) films, metallised on the external sides only, and having the following characteristics: <ul style="list-style-type: none"> — a visible light transmission of 50 % or more, — coated on one or both sides with a layer of poly(vinyl butyral) but not coated with an adhesive or any other material except poly(vinyl butyral), — a total thickness not exceeding 0,2 mm without taking the presence of poly(vinyl butyral) into account, for use in the manufacture of heat-reflecting or decorative laminated glass (1)	0 %	1.1.2007 - 31.12.2008
ex 3920 99 28	10	Reflecting sheet of metallised polyurethane, containing glass beads, coated with a hot-melt adhesive layer, covered on one or both sides with a release sheet, in rolls of a width of 1 020 mm (\pm 20 mm), for slitting into safety clothing reflecting strip (1)	0 %	1.1.2007 - 31.12.2008
ex 3920 99 28	30	Film of polyimide, not containing epoxyde resin and/or glass fibres,:	0 %	1.1.2007 - 31.12.2008
ex 3921 90 55	10	— metallized by sputtering with copper on one side or on both sides,		
ex 7410 21 00	30	— metallized by sputtering with copper and plated on one side or on both sides with refined copper or — covered on one side or on both sides with a copper foil		
ex 3920 99 28	40	Mono-axially oriented polymer film containing the following monomers: <ul style="list-style-type: none"> — Poly (tetramethylene ether glycol), — Bis (4-isocyanotocyclohexyl) methane, — 1,4-Butanediol or 1,3-Butanediol, — with a thickness of 0.25mm or more but not more than 5.0mm, — embossed with a regular pattern on one surface, — and covered with a release sheet 	0 %	1.1.2007 - 31.12.2008
3920 99 53		Ion-exchange membranes of fluorinated plastic material	0 %	1.1.2007 - 31.12.2008
ex 3920 99 59	55			
ex 3920 99 59	20	Film entirely of poly(vinyl alcohol), of a thickness not exceeding 1 mm and containing by weight: <ul style="list-style-type: none"> — 2 % or less of unhydrolysed acetate groups evaluated as vinyl acetate and — 5 % or more but not more than 25 % of glycerol as plasticizer, for the manufacture of roof-windows (1)	0 %	1.1.2007 - 31.12.2008
ex 3920 99 59	25	Poly(1-chlorotrifluoroethylene) film	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3920 99 59	30	Film and sheet of a copolymer of ethylene with chlorotrifluoroethylene, of a thickness of 12 µm or more but not exceeding 400 µm	0 %	1.1.2007 - 31.12.2008
ex 3920 99 59	35	Film entirely of poly(vinyl alcohol), of a thickness not exceeding 1 mm and of a width of 2,20 m or more, with an extension at break, in the transverse direction, of 350 % or more	0 %	1.1.2007 - 31.12.2008
ex 3920 99 59	40	Biaxially-oriented film of poly(vinyl alcohol), coated on both sides, of a total thickness of less than 1 mm	0 %	1.1.2007 - 31.12.2008
ex 3920 99 59	45	Iridescent film of polyester, polyethylene and an ethylene-vinyl acetate copolymer	0 %	1.1.2007 - 31.12.2008
ex 3920 99 59	50	Polytetrafluoroethylene film, non-microporous, in the form of rolls, of a thickness of 0,019 mm or more but not exceeding 0,14 mm, impermeable to water vapour	0 %	1.1.2007 - 31.12.2008
ex 3920 99 59	60	Film of a vinyl alcohol copolymer, soluble in cold water, of a thickness of 34 µm or more but not exceeding 90 µm, a tensile strength at break of 20 MPa or more but not exceeding 45 MPa and an elongation at break of 250 % or more but not exceeding 900 %	0 %	1.1.2007 - 31.12.2008
ex 3920 99 90	10	Biodegradable sheet of a thickness not exceeding 1 mm containing by weight: <ul style="list-style-type: none"> — 90 % (± 5 %) starch, — 10 % (± 5 %) of a synthetic polymer, — 0.5 % (± 0.5 %) of stearic acid 	0 %	1.1.2007 - 31.12.2008
ex 3920 99 90	20	Anisotropic conductive film, in rolls, of a width of 1,5 mm or more but not exceeding 2 mm and a maximum length of 300 m, used for joining electronic components in the production of LCD displays	0 %	1.1.2007 - 31.12.2011
ex 3921 13 10	10	Sheet of polyurethane foam, of a thickness of 3 mm (± 15 %) and of a specific gravity of 0,09435 or more but not exceeding 0,10092	0 %	1.1.2007 - 31.12.2008
ex 3921 14 00	10	Cellular film of regenerated cellulose, of a thickness not exceeding 350 µm	0 %	1.1.2007 - 31.12.2008
ex 3921 19 00	91	Microporous polypropylene film of a thickness not exceeding 100 µm	0 %	1.1.2007 - 31.12.2008
ex 3921 19 00	92	Microporous film consisting of mixtures of cellulose acetate and cellulose nitrate, of a thickness not exceeding 200 µm	0 %	1.1.2007 - 31.12.2008
ex 3921 19 00	93	Strip of microporous polytetrafluoroethylene on a support of a non-woven, for use in the manufacture of filters for kidney dialysis equipment (1)	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3921 19 00	94	<p>Polyethylene film, of a thickness of 16 µm or more but not exceeding 24 µm, having:</p> <ul style="list-style-type: none"> — a weight of 19 g/m² (± 2 g/m²), — a water vapour transmission rate of 5 000 g/m² or more but not exceeding 30 000 g/m² per day (as determined by the ASTM D 6701-01 method), — an elongation in the transverse direction of 25 % or more at a load of 500 g or less, — an elongation in the machine direction of 50 % or more but not exceeding 100 % (as determined by the ASTM D 882-91 method), <p>for use in the manufacture of napkins and napkin liners for babies and similar sanitary articles (1)</p>	0 %	1.1.2007 - 31.12.2008
ex 3921 19 00	95	Film of polyethersulfone, of a thickness not exceeding 200 µm	0 %	1.1.2007 - 31.12.2008
ex 3921 19 00	96	Cellular film, consisting of a layer of polyethylene of a thickness of 90 µm or more but not exceeding 140 µm and a layer of regenerated cellulose of a thickness of 10 µm or more but not exceeding 40 µm	0 %	1.1.2007 - 31.12.2008
ex 3921 90 19	35	Composite plate of polycarbonate and poly(butylene terephthalate), reinforced with glass fibres	0 %	1.1.2007 - 31.12.2008
ex 3921 90 19	45	Composite plate of poly(ethylene terephthalate) or of poly(butylene terephthalate), reinforced with glass fibres	0 %	1.1.2007 - 31.12.2008
ex 3921 90 60	91	Woven polytetrafluoroethylene fabric, coated or covered with a copolymer of tetrafluoroethylene and trifluoroethylene having perfluorinated alkoxy side-chains ending in carboxylic acid or sulfonic acid groups, whether or not in the potassium or sodium salt form	0 %	1.1.2007 - 31.12.2008
ex 5407 71 00	20			
ex 5903 90 99	10			
ex 3921 90 60	92	Reinforced polypropylene sheet, of a thickness of 0,91 mm or more but not exceeding 1,12 mm, having a breaking strength of 890 N or more but not exceeding 1 500 N (as determined by the ASTM D 751 method), in rolls of a width of 3,81 m	0 %	1.1.2007 - 31.12.2008
ex 3921 90 60	93	Film, of a specular gloss of 30 or more but not exceeding 60 measured at an angle of 60 ° using a glossmeter (as determined by the ISO 2813:2000 method), consisting of a layer of poly(ethylene terephthalate) and a layer of colored poly(vinyl chloride), joined by a metallized adhesive coating, for coating panels and doors of a kind used in the manufacture of domestic appliances (1)	0 %	1.1.2007 - 31.12.2008
ex 3926 90 92	20	Reflecting sheeting or tape, consisting of a facing-strip of poly(vinyl chloride) embossed in a regular pyramidal pattern, heat-sealed in parallel lines or in a grid-pattern to a backing-strip of plastic material, or of knitted or woven fabric covered on one side with plastic material	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 3926 90 97	10	Microspheres of polymer of divinylbenzene, of a diameter of 4,5 µm or more but not exceeding 80 µm	0 %	1.1.2007 - 31.12.2008
ex 3926 90 97	15	Glass fibre reinforced plastic traverse leaf spring for use in the manufacture of motor vehicle suspension systems (1)	0 %	1.1.2007 - 31.12.2008
ex 3926 90 97	20	Tape pad, for use in the manufacture of goods of heading No 8523 (1)	0 %	1.1.2007 - 31.12.2008
ex 3926 90 97	25	Unexpandable microspheres of a copolymer of acrylonitrile, methacrylonitrile and isobornyl methacrylate, of a diameter of 3 µm or more but not exceeding 4,6 µm	0 %	1.1.2007 - 31.12.2008
ex 3926 90 97	30	Guide pin and pole, for use in the manufacture of goods of subheading 8523 29 15 (1)	0 %	1.1.2007 - 31.12.2008
ex 3926 90 97	35	Microspheres of polyalkylsiloxane, on which are covalently bonded organic compounds, of a diameter of 1 µm or more but not exceeding 30 µm	0 %	1.1.2007 - 31.12.2008
ex 3926 90 97	40	Hollow microspheres of a copolymer of isooctylacrylate and acrylic acid, having a diameter of 10 µm or more but not exceeding 1000 µm, dispersed in water	0 %	1.1.2007 - 31.12.2008
ex 3926 90 97	55	Flat product of polyethylene, perforated in opposing directions, of a thickness of 600 µm or more but not exceeding 1 200 µm and of a weight of 21 g/m ² or more but not exceeding 42 g/m ²	0 %	1.1.2007 - 31.12.2008
ex 4007 00 00	10	Siliconated vulcanised rubber thread and cord	0 %	1.1.2007 - 31.12.2008
ex 4008 11 00	10	Blocks or sheets of cellular vulcanised rubber of modified ethylene-propylene-diene (EPDM) blended with chloroprene, which satisfy the Underwriters Laboratories Flammability Standard UL94HF-1	0 %	1.1.2007 - 31.12.2008
ex 4016 99 99	20	Soft rubber sealing stoppers for the manufacture of electrolytic capacitors (1)	0 %	1.1.2007 - 31.12.2008
4105 10 10		Sheep or lamb skin leather, without wool on, tanned or retanned but not further prepared, whether or not split, other than leather of heading No 4114	0 %	1.1.2007 - 31.12.2008
4105 10 90				
4105 30 91				
4105 30 99				
4106 21 10		Goat or kid skin leather, without hair on, tanned or retanned but not further prepared, whether or not split, other than leather of heading	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
4106 21 90		No 4114		
4106 22 90				
4106 31 10		Leather of other animals, without hair on, not further prepared than tanned, other than leather of heading No 4114	0 %	1.1.2007 - 31.12.2008
4106 31 90				
4106 32 10				
4106 32 90				
4106 40 90				
4106 91 00				
4106 92 00				
ex 5004 00 10	10	Yarn spun entirely from silk, not put up for retail sale	2.5 %	1.1.2007 - 31.12.2008
ex 5004 00 90	10			
ex 5005 00 10	10	Yarn spun entirely from silk waste (noil), not put up for retail sale	0 %	1.1.2007 - 31.12.2008
ex 5005 00 90	10			
ex 5205 31 00	10	Six ply yarn of bleached cotton, measuring 925 dtex or more but not more than 989 dtex per single yarn, for the manufacture of tampons (1)	0 %	1.1.2007 - 31.12.2008
5208 11 10		Fabrics for the manufacture of bandages, dressings and medical gauzes	5.2 %	1.1.2007 - 31.12.2008
ex 5402 45 00	10	Polyamide yarn, not textured, untwisted or with a twist not exceeding 22 turns per metre, of crimpable bicomponent filaments consisting of poly(hexamethylene adipamide) with a copolyamide, for the manufacture of: <ul style="list-style-type: none"> — knee-length stockings of subheadings 6115 10 90, 6115 30 11 and 6115 96 10, — women's stockings of subheadings 6115 30 19 and 6115 96 91 or — panty hose (tights) of subheading 6115 21 00 (1)	0 %	1.1.2007 - 31.12.2008
ex 5402 45 00	20	Yarn of synthetic textile fibres solely of aromatic polyamides obtained by the polycondensation of <i>m</i> -phenylenediamine and isophthalic acid	0 %	1.1.2007 - 31.12.2008
ex 5402 47 00	10	Synthetic bicomponent filament yarn, not textured, untwisted, measuring 1 650 decitex or more but not more than 1 800 decitex, consisting of 110 filaments or more but not more than 120 filaments, each having a core of	0 %	1.1.2007 - 31.12.2011

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		poly(ethylene terephthalate) and a skin of polyamide-6, containing by weight 75 % or more but not exceeding 77 % of poly(ethylene terephthalate), for use in the manufacture of roofings (1)		
ex 5402 49 00	10	Multifilaments yarn of polytetrafluoroethylene	0 %	1.1.2007 - 31.12.2008
ex 5402 69 90	20			
ex 5402 49 00	30	Yarn of a copolymer of glycollic acid with lactic acid, for the manufacture of surgical sutures (1)	0 %	1.1.2007 - 31.12.2008
ex 5402 49 00	50	Non-textured filament yarn of poly(vinyl alcohol)	0 %	1.1.2007 - 31.12.2008
ex 5402 59 90	20			
ex 5402 69 90	40			
ex 5402 49 00	60	Yarn wholly of poly(glycollic acid)	0 %	1.1.2007 - 31.12.2008
ex 5402 69 90	10			
ex 5402 49 00	70	Synthetic filament yarn, single, containing by weight 85 % or more of acrylonitrile, in the form of a wick containing 1 000 continuous filaments or more but not more than 25 000 continuous filaments, of a weight per metre of 0,12 g or more but not exceeding 3,75 g and of a length of 100 m or more, for the manufacture of carbon-fibre yarn (1)	0 %	1.1.2007 - 31.12.2008
ex 5402 49 00	80	Polyethylene filament yarn, untwisted, of either 55, 110, 165 or 1 760 decitex, for the manufacture of goods of heading No 5607 (1)	0 %	1.1.2007 - 31.12.2008
ex 5402 49 00	85	Synthetic filament yarn, single, untwisted, wholly of poly(thio-1,4-phenylene)	0 %	1.1.2007 - 31.12.2008
ex 5404 19 00	10	Monofilament of polytetrafluoroethylene	0 %	1.1.2007 - 31.12.2008
ex 5404 19 00	20	Monofilament of poly(1,4-dioxanone)	0 %	1.1.2007 - 31.12.2008
ex 5404 19 00	30	Monofilament of a copolymer of 1,3-dioxan-2-one with 1,4-dioxan-2,5-dione, for the manufacture of surgical sutures (1)	0 %	1.1.2007 - 31.12.2008
ex 5404 19 00	40	Monofilaments of a stabilised blend of polyester with polyurethane, of 67 decitex or more and of which no cross-sectional dimension exceeds 1 mm	0 %	1.1.2007 - 31.12.2008
ex 5404 19 00	50	Monofilaments of polyester or poly(butylene terephthalate), with crosssectional dimension of 0,5mm or more but not exceeding 1mm, for use in the manufacture of zippers (1)	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 5404 90 90	20	Strip of polyimide	0 %	1.1.2007 - 31.12.2008
ex 5407 71 00	10	Woven fabrics of poly(vinyl alcohol) fibres, for machine embroidery	0 %	1.1.2007 - 31.12.2008
ex 5501 90 00	10	Poly(vinyl alcohol) tow	0 %	1.1.2007 - 31.12.2008
ex 5503 11 00	10	Synthetic staple fibres of a copolymer of terephthalic acid, <i>p</i> -phenylenediamine and 3,4'-oxybis(phenyleneamine), of a length not exceeding 7 mm	0 %	1.1.2007 - 31.12.2008
ex 5601 30 00	40			
ex 5503 90 10	10	Acetalized, multicomponent spun fibres with a matrix fibril structure, consisting of emulsion-polymerized poly(vinyl alcohol) and poly(vinyl chloride)	0 %	1.1.2007 - 31.12.2008
ex 5503 90 90	30			
ex 5503 90 90	20	Poly(vinyl alcohol) fibres, whether or not acetalized	0 %	1.1.2007 - 31.12.2008
ex 5506 90 90	10			
ex 5601 30 00	10			
ex 5503 90 90	40	Fibres wholly of poly(thio-1,4-phenylene)	0 %	1.1.2007 - 31.12.2008
ex 5601 30 00	20	Polyester fibres, measuring 0,56 decitex, of a length of 3 mm or more but not exceeding 5 mm	0 %	1.1.2007 - 31.12.2008
ex 5601 30 00	30	Acrylic fibres, measuring 0,11 and 0,56 decitex, of a length of 3 mm or more but not exceeding 5 mm	0 %	1.1.2007 - 31.12.2008
ex 5603 11 10	10	Poly(vinyl alcohol) non-wovens, in the piece or cut into rectangles: — of a thickness of 200 µm or more but not exceeding 280 µm and — of a weight of 20 g/m ² or more but not exceeding 50 g/m ²	0 %	1.1.2007 - 31.12.2008
ex 5603 11 90	10			
ex 5603 12 10	10			
ex 5603 12 90	10			
ex 5603 91 10	10			
ex 5603 91 90	10			
ex 5603 92 10	10			
ex 5603 92 90	10			

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 5603 11 10	20	Non-wovens, containing spunbonded fibres of polypropylene or of polypropylene and polyethylene, for the manufacture of napkins and napkin liners for babies and similar sanitary articles (1)	0 %	1.1.2007 - 31.12.2008
ex 5603 11 90	20			
ex 5603 12 10	20			
ex 5603 12 90	50			
ex 5603 12 90	30	Non-wovens of aromatic polyamide fibres obtained by polycondensation of <i>m</i> -phenylenediamine and isophthalic acid, in the piece or cut into rectangles	0 %	1.1.2007 - 31.12.2008
ex 5603 13 90	30			
ex 5603 14 90	10			
ex 5603 92 90	60			
ex 5603 93 90	40			
ex 5603 94 90	30			
ex 5603 12 90	60	Non-woven of spunbonded polyethylene, of a weight of more than 60 g/m ² but not exceeding 80 g/m ² and an air resistance (Gurley) of 8 s or more but not exceeding 36 s (as determined by the ISO 5636/5 method)	0 %	1.1.2007 - 31.12.2008
ex 5603 13 90	60			
ex 5603 12 90	70	Non-wovens of polypropylene, consisting of a meltblown layer, laminated on each side with spunbonded filaments of polypropylene, of a thickness not exceeding 550 µm and of a weight not exceeding 80 g/m ² , in the piece or simply cut into squares or rectangles, not impregnated	0 %	1.1.2007 - 31.12.2008
ex 5603 13 90	70			
ex 5603 92 90	40			
ex 5603 93 90	10			
ex 5603 13 90	40	Non-wovens consisting of a central layer of polycarbonate fibres, laminated on each side with spunbonded filaments of polyester, of a weight of more than 130 g/m ² but not exceeding 200 g/m ²	0 %	1.1.2007 - 31.12.2008
ex 5603 14 90	20			
ex 5603 13 90	80	Polyethylene non-woven, covered on both sides with a non-woven of polypropylene and wood pulp, of a weight of 70 g/m ² or more but not exceeding 90 g/m ² , in rolls, for use in the manufacture of wet wipes (1)	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 5603 93 90	30			
ex 5603 14 90	30	Non-wovens, consisting of a central elastomeric film laminated on each side with spunbonded filaments of polypropylene, of a weight of 200 g/m ² or more but not exceeding 300 g/m ²	0 %	1.1.2007 - 31.12.2008
ex 5603 91 90	30	Nonwoven viscose rayon, with a watersoluble starch based binder and having a weight of 12 or more but not more than 18g/m ²	0 %	1.1.2007 - 31.12.2008
ex 5603 92 90	20	Non-wovens consisting of a meltblown central layer of a thermoplastic elastomer laminated on each side with spunbonded filaments of polypropylene	0 %	1.1.2007 - 31.12.2008
ex 5603 93 90	20			
ex 5603 92 90	50	Non-wovens of staple fibres, in rolls, of a width of 78 mm or more but not exceeding 252 mm, for the manufacture of floppy discs (1)	0 %	1.1.2007 - 31.12.2008
ex 5603 92 90	70	Non-wovens, consisting of multiple layers of a mixture of meltblown fibres and staple fibres of polypropylene and polyester, whether or not laminated on one side or on both sides with spunbonded filaments of polypropylene, of a total thickness not exceeding 50 mm	0 %	1.1.2007 - 31.12.2008
ex 5603 93 90	50			
ex 5603 94 90	40			
ex 5603 94 90	20	Acrylic fibre rods, having a length of not more than 50 cm, for the manufacture of pen tips (1)	0 %	1.1.2007 - 31.12.2008
ex 5604 90 90	60	Strip, of: — a polyester layer, laminated on one or both sides to a polymer layer containing glass beads, — a maximum width of 1.2 mm, — a maximum thickness of 0.05 mm	0 %	1.1.2007 - 31.12.2008
ex 5607 50 90	10	Twine, unsterilised, wholly of poly(glycollic acid), plaited or braided, with an inner core, for the manufacture of surgical sutures (1)	0 %	1.1.2007 - 31.12.2008
ex 5803 00 10	91	Gauze of cotton, of a width of less than 1 500 mm	0 %	1.1.2007 - 31.12.2008
ex 5903 10 90	10	Knitted or woven fabrics, coated or covered on one side with artificial plastic material in which are embedded microspheres	0 %	1.1.2007 - 31.12.2008
ex 5903 20 90	10			
ex 5903 90 99	20			

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 5903 20 90	20	Tape of polyester fabric laminated with a metallised polyurethane film containing glass beads, for use in the manufacture of marine life-saving equipment (1)	0 %	1.1.2007 - 31.12.2008
ex 5906 99 90	10	Rubberised textile fabric, consisting of warp yarns of polyamide-6,6 and weft yarns of polyamide-6,6, polyurethane and a copolymer of terephthalic acid, <i>p</i> -phenylenediamine and 3,4'-oxybis(phenyleneamine)	0 %	1.1.2007 - 31.12.2008
ex 5907 00 90	10	Textile fabrics, coated with adhesive in which are embedded spheres of a diameter not exceeding 75 µm	0 %	1.1.2007 - 31.12.2008
ex 5911 10 00	10	Needle-punched synthetic-fibre felts, not containing polyester, whether or not containing catalytic particles entrapped within the synthetic fibres, coated or covered on one side with polytetrafluoroethylene film, for the manufacture of filtration products (1)	0 %	1.1.2007 - 31.12.2008
ex 5911 90 90	10	Yarn and strip of impregnated polytetrafluoroethylene, whether or not oiled or graphited	0 %	1.1.2007 - 31.12.2008
ex 5911 90 90	30	Parts of equipment for the purification of water by reverse osmosis, consisting essentially of plastic-based membranes, supported internally by woven or non-woven textile materials which are wound round a perforated tube, and enclosed in a cylindrical plastic casing of a wall-thickness not exceeding 4 mm, whether or not housed in a cylinder of a wall-thickness of 5 mm or more	0 %	1.1.2007 - 31.12.2008
ex 8421 99 00	92			
6305 10 10		Sacks and bags, of a kind used for the packing of goods, used, of jute or of other textile bast fibres of heading No 5303	0 %	1.1.2007 - 31.12.2008
ex 6305 90 00	10	Sacks and bags, of a kind used for the packing of goods, used, of flax or of sisal	0 %	1.1.2007 - 31.12.2008
ex 6305 90 00	93			
ex 6305 90 00	95			
ex 6307 90 10	10	Sterile mesh-implant, consisting of a knitted fabric of polypropylene monofilaments, with rounded edges, in forms covered by a square of dimensions not exceeding 31 × 31 cm	0 %	1.1.2007 - 31.12.2008
ex 6805 10 00	10	Abrasive in the form of identically shaped particles on a support	0 %	1.1.2007 - 31.12.2008
ex 6805 20 00	10			
ex 6805 30 80	10			
ex 6813 89 00	10	Friction material, of a thickness of less than 20 mm, not mounted, for the manufacture of friction components of a kind used in automatic	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		transmissions and clutches (1)		
ex 6903 20 90	10	Yarn of continuous ceramic filaments, each filament containing by weight:	0 %	1.1.2007 - 31.12.2008
ex 6914 90 90	10	— 12 % or more of diboron trioxide, — 26 % or less of silicon dioxide and — 60 % or more of dialuminium trioxide		
ex 6903 90 90	10	Beryllium oxide, of a purity by weight of more than 99 %, in the form of blanks, bars, blocks or plates	0 %	1.1.2007 - 31.12.2008
ex 6909 19 00	40			
ex 6903 90 90	20	Silicon carbide reactor tubes and holders, of a kind used for insertion into diffusion and oxidation furnaces for production of semiconductor materials	0 %	1.1.2007 - 31.12.2008
ex 6909 12 00	20	Plate, of dialuminium trioxide and titanium carbide, of dimensions not exceeding 48 × 48 mm, or of a diameter not exceeding 125 mm, for the manufacture of magnetic heads (1)	0 %	1.1.2007 - 31.12.2008
ex 6909 19 00	30	Supports for catalysts, consisting of porous cordierite or mullite ceramic pieces, of an overall volume not exceeding 65 l, having, per cm ² of the cross-section, not less than one continuous channel which may be open at both ends or stopped at one end	0 %	1.1.2007 - 31.12.2008
ex 6909 19 00	50	Ceramic articles made of continuous filaments of ceramic oxides, containing by weight:	0 %	1.1.2007 - 31.12.2008
ex 6914 90 90	20	— 2 % or more of diboron trioxide, — 28 % or less of silicon dioxide and — 60 % or more of dialuminium trioxide		
ex 6909 19 00	60	Supports for catalysts, consisting of porous ceramic pieces, of a blend of silicon carbide and silicon, with a hardness of less than 9 on the Mohs scale, with a total volume not exceeding 65 liters, having per cm ² of the surface of the cross section one or more closed channels at the tail end	0 %	1.1.2007 - 31.12.2008
ex 6914 90 90	30	Ceramic microspheres, transparent, obtained from silicon dioxide and zirconium dioxide, of a diameter of more than 125 µm	0 %	1.1.2007 - 31.12.2008
ex 7002 10 00	10	Balls of E-glass, of a diameter of 20,3 mm or more but not exceeding 26 mm	0 %	1.1.2007 - 31.12.2008
ex 7006 00 90	10	Glass plate, coated on one side with chromium and/or with a mixture of diindium trioxide and tin dioxide, of dimensions of 260 × 320 mm or more but not exceeding 400 × 400 mm, of a thickness not exceeding	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		1,2 mm, for the manufacture of liquid crystal displays (1)		
ex 7006 00 90	20	Colour filter, consisting of a glass plate with red, blue and green pixels, having a total thickness of 1,1 mm ($\pm 0,1$ mm) and exterior dimensions of 320×352 mm or more but not exceeding 320×400 mm, for the manufacture of liquid crystal displays (1)	0 %	1.1.2007 - 31.12.2008
ex 7006 00 90	30	Glass plate, uncoated, of dimensions of 320×352 mm or more but not exceeding 320×400 mm, of a thickness of 0,6 mm or more but not exceeding 1,2 mm, for the manufacture of liquid crystal displays (1)	0 %	1.1.2007 - 31.12.2008
ex 7007 19 20	10	Glass plate of a diagonal size of 81,28cm ($\pm 1,5$ cm) or more, but not exceeding 185,42 cm ($\pm 1,5$ cm), consisting of tempered glass; provided either with a mesh film and a near-infrared absorbing film or a sputtered conductive layer, with optional additional anti-reflex layer on one or two sides, for use in the manufacture of PDP videomonitors or television sets (1)	0 %	1.1.2007 - 31.12.2008
ex 7007 29 00	10	Glass plate of a diagonal size of 81,28 cm (+/- 1,5cm) or more, but not exceeding 185,42 cm (+/- 1,5 cm), consisting of 2 sandwich plates laminated together; provided either with a mesh film and a near-infrared absorbing film or a sputtered conductive layer, with optional additional anti-reflex layer on one or two sides, for use in the manufacture of PDP videomonitors or television sets (1)	0 %	1.1.2007 - 31.12.2008
ex 7011 10 00	10	Glass lenses with a stippled front refractor or with a front refractor composed of prismatic elements, with an external diameter of more than 121 mm but not exceeding 125 mm	0 %	1.1.2007 - 31.12.2008
ex 7011 10 00	20	Parabolic glass cup, with an external diameter of more than 121 mm but not exceeding 125 mm	0 %	1.1.2007 - 31.12.2008
ex 7011 90 00	10			
ex 7011 20 00	25	Glass cone for cathode-ray tube, of a diagonal measurement of 912 mm (± 5 mm) and a distance from seal edge to the end of the neck of 454,3 mm (± 5 mm)	0 %	1.1.2007 - 31.12.2008
ex 7011 20 00	40	Glass face-plate: <ul style="list-style-type: none"> — with a diagonal measurement of 366,4 mm ($\pm 1,5$ mm) and of dimensions of $246,4 \times 315,4$ mm ($\pm 1,5$ mm), — with a diagonal measurement of 391 mm ($\pm 1,5$ mm) and of dimensions of $261,4 \times 326,8$ mm ($\pm 1,5$ mm), — with a diagonal measurement of 442 mm ($\pm 1,5$ mm) and of dimensions of $293,4 \times 369,2$ mm ($\pm 1,5$ mm), — with a diagonal measurement of 544,5 mm ($\pm 1,6$ mm) and of dimensions of 358×454 mm ($\pm 1,6$ mm), having a cylindrical curvature, — with a diagonal measurement of 570,5 mm ($\pm 1,6$ mm) and of dimensions of 360×486 mm ($\pm 1,6$ mm), — with a diagonal measurement of 629,8 mm (± 3 mm) and of dimensions of $406,5 \times 519$ mm (± 2 mm), having a cylindrical curvature, or — with a diagonal measurement of 753 mm ($\pm 1,6$ mm) and of 	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 7011 20 00	75	<p>dimensions of 471 × 640 mm (± 1,6 mm), and with a raised edge, for the manufacture of colour cathode-ray tubes (1)</p> <p>Glass face-plate:</p> <ul style="list-style-type: none"> — with a diagonal measurement of 604,5 mm (± 3 mm) and of dimensions of 340 × 541 mm (± 2 mm), — with a diagonal measurement of 639,3 mm (± 3 mm) and of dimensions of 413,6 × 527 mm (± 2 mm), — with a diagonal measurement of 708 mm (± 3 mm) and of dimensions of 404 × 633 mm (± 2 mm), — with a diagonal measurement of 723 mm (± 3 mm) and of dimensions of 477 × 602 mm (± 2 mm), or — with a diagonal measurement of 812,8 mm (± 3 mm) and of dimensions of 463,8 × 725,5 mm (± 2 mm), <p>having a cylindrical curvature, for the manufacture of colour cathode-ray tubes (1)</p>	0 %	1.1.2007 - 31.12.2008
ex 7011 20 00	80	Glass bulb for monochrome cathode-ray tube, of a diagonal measurement of 3,8 cm or more but not exceeding 51 cm and a nominal neck diameter of 13 mm, 20 mm, 29 mm or 37 mm	0 %	1.1.2007 - 31.12.2008
ex 7014 00 00	10	Optical elements of glass (other than those of heading No 7015), not optically worked, other than signalling glassware	0 %	1.1.2007 - 31.12.2008
ex 7019 12 00	10	Rovings, measuring 2 600 tex or more but not more than 3 300 tex and of a loss on ignition of 4 % or more but not exceeding 8 % by weight (as determined by the ASTM D 2584-94 method)	0 %	1.1.2007 - 31.12.2008
ex 7019 12 00	15	Rovings, measuring 650 tex or more but not more than 2 500 tex, coated with a layer of polyurethane whether or not mixed with other materials	0 %	1.1.2007 - 31.12.2008
ex 7019 12 00	30	Rovings, measuring 1 693 tex (± 10 %), coated with a layer of styrene-butadiene rubber (SBR)	0 %	1.1.2007 - 31.12.2008
ex 7019 12 00	40	Rovings, measuring 2 040 tex (± 10 %), coated with carbon	0 %	1.1.2007 - 31.12.2008
ex 7019 12 00	50	Rovings, measuring 392 tex or more but not more than 2 884 tex, coated with a layer of an acrylic copolymer	0 %	1.1.2007 - 31.12.2008
ex 7019 12 00	60	Rovings, measuring 517 tex or more but not more than 3 569 tex, coated with a layer of paraffin	0 %	1.1.2007 - 31.12.2008
ex 7019 12 00	70	Rovings, measuring 417 tex or more but not more than 3 180 tex, coated with a layer of poly(sodium acrylate) and poly(acrylic acid)	0 %	1.1.2007 - 31.12.2008
ex 7019 19 10	10	Yarn of 33 tex or a multiple thereof (± 7,5 %), obtained from continuous spun-glass filaments of a nominal diameter of 3,5 µm or of 4,5 µm, in	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		which filaments of a diameter of 3 µm or more but not exceeding 5,2 µm predominate, other than those treated so as to improve their adhesion to elastomers		
ex 7019 19 10	30	Yarn of 22 tex ($\pm 7,5\%$), obtained from continuous spun-glass filaments of a nominal diameter of 5 µm, in which filaments of a diameter of 4,2 µm or more but not exceeding 5,8 µm predominate	0 %	1.1.2007 - 31.12.2008
ex 7019 19 10	40	Yarn of 33, 34 or 51 tex or a multiple thereof ($\pm 7,5\%$), obtained from continuous spun-glass filaments of a nominal diameter of 6 µm, in which filaments of a diameter of 5,1 µm or more but not exceeding 6,9 µm predominate	0 %	1.1.2007 - 31.12.2008
ex 7019 19 10	50	Yarn of E-glass of 68 or 74 tex ($\pm 7\%$), obtained from continuous spun-glass filaments of a nominal diameter of 9 µm, in which filaments of a diameter of 8,1 µm or more but not exceeding 9,9 µm predominate, for the manufacture of woven fabrics for electrical laminates (prepregs) (1)	0 %	1.1.2007 - 31.12.2008
ex 7019 39 00	30	Sheet, consisting of a layer of glass fibres and polypropylene, containing by weight 40 % or more but not more than 60 % of glass fibres of a length of 12,7 mm ($\pm 0,2$ mm) and a diameter of 16 µm (± 1 µm), covered on one side with a plastic film and on the other side with a plastic layer, of a total thickness not exceeding 1 mm	0 %	1.1.2007 - 31.12.2008
ex 7019 39 00	40	Sheet, consisting of chopped glass fibres and thermoplastic polymer, containing by weight 30 % or more but not more than 70 % of glass fibres of a diameter of 16 µm (± 1 µm), whether or not covered on one or both sides with a protective plastic layer	0 %	1.1.2007 - 31.12.2008
ex 7019 39 00	50	Non-woven product of non-textile glass fibre, for the manufacture of air filters (1)	0 %	1.1.2007 - 31.12.2011
ex 7019 90 10	10	Non-textile glass fibres in which fibres of a diameter of less than 4,6 µm predominate	0 %	1.1.2007 - 31.12.2008
ex 7019 90 10	20	Non-textile E-glass fibres, of a length not exceeding 3 mm and a diameter of 5 µm, for the manufacture of catalysts for the purification of smokes (1)	0 %	1.1.2007 - 31.12.2008
ex 7019 90 99	10	Glass cord impregnated with rubber or plastic, obtained from twisted glass filament yarns, coated with a latex comprising at least a resorcinol-formaldehyde resin and chlorosulfonated polyethylene	0 %	1.1.2007 - 31.12.2008
ex 7019 90 99	20	Glass cord impregnated with rubber or plastic, obtained from twisted glass filament yarns, coated with a latex comprising at least a resorcinol-formaldehyde-vinylpyridine resin and an acrylonitrile-butadiene rubber (NBR)	0 %	1.1.2007 - 31.12.2008
ex 7019 90 99	30	High modulus glass cord (K) impregnated with rubber, obtained from twisted high modulus glass filament yarns, coated with a latex comprising a resorcinol-formaldehyde resin with or without	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		vinylpyridine and/or hydrogenated acrylonitrile-butadiene rubber (HNBR)		
ex 7116 20 90	10	Disc of silicon on sapphire	0 %	1.1.2007 - 31.12.2008
ex 7201 10 11	10	Pig iron ingots with a length of not more than 350 mm, a width of not more than 150 mm, a height of not more than 150 mm	0 %	1.1.2007 - 31.12.2011
ex 7201 10 30	10	Pig iron ingots with a length of not more than 350 mm, a width of not more than 150 mm, a height of not more than 150 mm, containing by weight not more than 1 % of silicon	0 %	1.1.2007 - 31.12.2011
7202 50 00		Ferro-silico-chromium	0 %	1.1.2007 - 31.12.2008
ex 7202 99 80	10	Ferro-silicon, nitrided, containing by weight 55 % or more of silicon and 25 % or more of nitrogen	0 %	1.1.2007 - 31.12.2008
ex 7326 20 80	20	Metal fleece, consisting of a mass of stainless steel wires of diameters ranging from 0.022 mm to 0.070 mm, compacted by sintering and rolling	0 %	1.1.2007 - 31.12.2011
ex 7409 19 00	10	Sheet or plate of polytetrafluoroethylene, with aluminium oxide or titanium dioxide as a filler or reinforced with glass-fibre fabric, laminated on both sides with copper foil	0 %	1.1.2007 - 31.12.2008
ex 7410 21 00	10	Sheet or plate of polytetrafluoroethylene, containing aluminium oxide or titanium dioxide as filler or reinforced with glass-fibre fabric, covered on both sides with copper foil	0 %	1.1.2007 - 31.12.2008
ex 7410 21 00	40	Sheet or plates <ul style="list-style-type: none"> — consisting of a central layer of paper, laminated on each side with glass-fibre fabric and impregnated with epoxide resin, or — consisting of multiple layers of paper, impregnated with phenolic resin, coated on one or both sides with a copper film with a maximum thickness of 0,15 mm	0 %	1.1.2007 - 31.12.2008
ex 7419 99 90	91	Disc (target) with deposition material, consisting of molybdenum silicide:	0 %	1.1.2007 - 31.12.2008
ex 7616 99 90	60	<ul style="list-style-type: none"> — containing 1 mg/kg or less of sodium and — mounted on a copper or aluminium support 		
ex 7419 99 90	92	Disc (target) with deposition material, of tungsten or an alloy containing by weight 90 % of tungsten and 10 % of titanium:	0 %	1.1.2007 - 31.12.2008
ex 7616 99 90	70	<ul style="list-style-type: none"> — containing 100 µg/kg or less of sodium and — mounted on a copper or aluminium support 		

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 7419 99 90	93	Disc (target) with deposition material, of titanium:	0 %	1.1.2007 - 31.12.2008
ex 7616 99 90	80	— containing 50 µg/kg or less of sodium and — mounted on a copper or aluminium support		
ex 7605 19 00	10	Not alloyed aluminium wire, of a diameter of 2 mm or more but not exceeding 6 mm, covered with a layer of copper of a thickness of 0,032 mm or more but not exceeding 0,117 mm	0 %	1.1.2007 - 31.12.2008
ex 7606 11 10	20	Tape of not alloyed aluminium, with a reflecting film, a transparent polyurethane topcoat, a netting and ceramic anti-skid particles	0 %	1.1.2007 - 31.12.2008
ex 7606 11 91	20	Strip with depth-etching, of band-anodic oxidation treated aluminium of a purity by weight of 99,9 % and a thickness of less than 3 mm, for incorporation in bodies for motor vehicles (1)	0 %	1.1.2007 - 31.12.2008
ex 7606 11 93	20			
ex 7607 11 90	10	Plain aluminium foil with the following parameters: — an aluminium content of 99.98 % or more — a thickness of 0.070 mm or more but not more than 0.115 mm — with a cubic texture of a kind used for high voltage etching (1)	0 %	1.1.2007 - 31.12.2011
ex 7613 00 00	20	Aluminium container, seamless, for compressed natural gas or compressed hydrogen, wholly embedded in an overwrap of epoxy-carbon fibres composite, of a capacity of 172 l (± 10 %) and an unfilled weight not exceeding 64 kg	0 %	1.1.2007 - 31.12.2008
ex 8708 99 97	10			
ex 7616 99 90	15	Honeycomb aluminium blocks of the type used in the manufacture of aircraft parts	0 %	1.1.2007 - 31.12.2008
ex 7616 99 90	50	Discs of aluminium alloy, of a thickness not exceeding 0,84 mm, for the manufacture of goods of subheading 8523 29 15 (1)	0 %	1.1.2007 - 31.12.2008
ex 7905 00 00	10	Plate of an alloy of zinc, ground and polished on one surface and coated with an epoxide resin on the other surface, of rectangular or square shape, of a length of 300 mm or more but not exceeding 2 000 mm and of a width of 300 mm or more but not exceeding 1 000 mm, and containing: — 10 mg/kg or less of iron, — 10 mg/kg or less of lead, — 700 mg/kg or more but not more than 900 mg/kg of aluminium and	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		— 500 mg/kg or more but not more than 900 mg/kg of magnesium, for the manufacture of sensitised printing plates (1)		
ex 8103 90 90	10	Welded tube solely of tantalum, or solely of an alloy of tantalum with tungsten containing by weight 3,5 % or less of tungsten	0 %	1.1.2007 - 31.12.2008
8104 11 00		Unwrought magnesium, containing at least 99,8 % by weight of magnesium	0 %	1.1.2007 - 31.12.2008
ex 8104 90 00	10	Ground and polished magnesium sheets, of dimensions not exceeding 1 500 × 2 000 mm, coated on one side with an epoxy resin insensitive to light	0 %	1.1.2007 - 31.12.2008
ex 8104 90 00	20	Sections, of extruded magnesium, of a length of 800 mm or more but not exceeding 2 900 mm and a width of 15 mm or more but not exceeding 70 mm	0 %	1.1.2007 - 31.12.2008
ex 8108 20 00	10	Titanium sponge	0 %	1.1.2007 - 31.12.2008
ex 8108 30 00	10	Waste and scrap of titanium and titanium alloys, except those containing by weight 1 % or more but not more than 2 % of aluminium	0 %	1.1.2007 - 31.12.2008
ex 8108 90 50	10	Alloy of titanium and aluminium, containing by weight 1 % or more but not more than 2 % of aluminium, in sheets or rolls, of a thickness of 0,49 mm or more but not exceeding 3,1 mm, of a width of 1 000 mm or more but not exceeding 1 254 mm, for the manufacture of goods of subheading 8714 19 00 (1)	0 %	1.1.2007 - 31.12.2008
ex 8108 90 50	20	Alloy of titanium, aluminium and vanadium, containing by weight 2,5 % or more but not more than 3,5 % of aluminium and 2,0 % or more but not more than 3,0 % of vanadium, in sheets or rolls, of a thickness of 0,6 mm or more but not exceeding 0,9 mm, of a width not exceeding 1 000 mm, for the manufacture of goods of subheading 8714 19 00 (1)	0 %	1.1.2007 - 31.12.2008
ex 8108 90 50	30	Alloy of titanium and silicon, containing by weight 0.15 % or more but not more than 0.60 % of silicon, in sheets or rolls, for use in the manufacture of exhaust systems for internal combustion engines (1)	0 %	1.1.2007 - 31.12.2011
ex 8109 20 00	10	Non-alloy zirconium, in the form of ingots, containing by weight more than 0,01 % of hafnium, for use in the manufacture of tubes for the chemical industry (1)	0 %	1.1.2007 - 31.12.2008
ex 8110 10 00	10	Antimony in the form of ingots	0 %	1.1.2007 - 31.12.2008
ex 8112 19 00	10	Beryllium, of a purity by weight of 94 % or more, in the form of bars, plates and sheets	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 8112 99 30	10	Alloy of niobium (columbium) and titanium, in the form of bars and rods	0 %	1.1.2007 - 31.12.2008
ex 8305 20 00	10	Staples of a width of 12 mm (\pm 1 mm) and a depth of 8 mm (\pm 1 mm) for use in copiers and printers (1)	0 %	1.1.2007 - 31.12.2008
ex 8309 90 90	10	Aluminium can ends with so-called "ring pull" full aperture with a diameter of 136,5 mm (\pm 1 mm)	0 %	1.1.2007 - 31.12.2008
ex 8401 30 00	20	Non-irradiated hexagonal fuel modules (elements) for use in nuclear reactors (1)	0 %	1.1.2007 - 31.12.2008
ex 8407 31 00	10	Two stroke internal combustion engine, of a cylinder capacity not exceeding 30 cm ³ for use in the manufacture of portable motorised scooters falling within subheading 8711 10 00 (1)	0 %	1.1.2007 - 31.12.2008
ex 8407 33 90	10	Spark-ignition reciprocating or rotary internal combustion piston engines, having a cylinder capacity of not less than 300 cc and a power of not less than 6 kW but not exceeding 15.5 kW, for the manufacture of:	0 %	1.1.2007 - 31.12.2011
ex 8407 90 80	10			
ex 8407 90 90	10	<ul style="list-style-type: none"> — self-propelled lawn mowers, with a seat of sub-heading 8433 11 51 — tractors of subheading 8701 90 11, whose main function is that of a lawn mower or — four stroke mowers with motor of a cylinder capacity of not less than 300 cc of subheading 8433 20 10 <p>(1)</p>		
ex 8407 90 10	10	Four-stroke petrol engines of a cylinder capacity not exceeding 250 cm ³ for use in the manufacture of lawnmowers of sub-heading 8433 11 or mowers with motor of subheading 8433 20 10 (1)	0 %	1.1.2007 - 31.12.2011
ex 8407 90 10	20	Two-stroke internal combustion engines, having a cylinder capacity not exceeding 125 cm ³ , for the manufacture of lawnmowers of sub-heading 8433 11 (1)	0 %	1.1.2007 - 31.12.2008
ex 8408 90 41	20	Diesel engines of a power not exceeding 15 kW, with 2 or 3 cylinders, for use in the manufacture of vehicle mounted temperature control systems (1)	0 %	1.1.2007 - 31.12.2008
ex 8408 90 43	20	Diesel engines of a power not exceeding 30 kW, with 4 cylinders, for use in the manufacture of vehicle mounted temperature control systems (1)	0 %	1.1.2007 - 31.12.2008
ex 8414 30 89	20	Vehicle air conditioning system part, consisting of an open shaft reciprocating compressor of a power exceeding 0.4 kW but not	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		exceeding 10 kW		
ex 8414 59 20	20	Axial fan of 170 mm (± 10 mm) diameter and 50 mm (± 0.10 mm) height, for use in the manufacture of products of CN 8525 (1)	0 %	1.1.2007 - 31.12.2008
ex 8414 90 00	20	Aluminium pistons, partially covered with polytetrafluoroethylene, for incorporation into compressors of air conditioning machines of motor vehicles (1)	0 %	1.1.2007 - 31.12.2008
ex 8414 90 00	30	Pressure-regulating system, for incorporation into compressors of air conditioning machines of motor vehicles (1)	0 %	1.1.2007 - 31.12.2008
ex 8414 90 00	40	Drive part, for compressors of air conditioning machines of motor vehicles (1)	0 %	1.1.2007 - 31.12.2008
ex 8414 90 00	50	Cross-flow fan, of 97.4 mm (± 0.2 mm) diameter and 645 mm (± 1 mm) or 873 mm ($+0.5/-1$ mm) height made from anti-static, anti-bacterial and heat-resistant, glass fiber reinforced plastic with a minimum temperature resistance of 70°C, for use in the manufacture of indoor air conditioning units (1)	0 %	1.1.2007 - 31.12.2011
ex 8415 90 00	20	Evaporator made of aluminium for use in the manufacture of air conditioning machines for automobiles (1)	0 %	1.1.2007 - 31.12.2011
ex 8418 99 90	91	Welded cooling micro-elements, of an alloy of aluminium, for the manufacture of condensers (1)	0 %	1.1.2007 - 31.12.2008
ex 8419 19 00	10	Heat accumulator for motor vehicles, of a coolant capacity of 4 l or more but not exceeding 10 l	0 %	1.1.2007 - 31.12.2008
ex 8419 89 98	10	Immersion-tube (coils) bundles, consisting of an assembly of plastic tubes terminating at each end in a honeycomb-structure (end-fitting) surrounded by a pipe-connector	0 %	1.1.2007 - 31.12.2008
ex 8421 99 00	91	Parts of equipment, for the purification of water by reverse osmosis, consisting of a bundle of hollow fibres of artificial plastic material with permeable walls, embedded in a block of artificial plastic material at one end and passing through a block of artificial plastic material at the other end, whether or not housed in a cylinder	0 %	1.1.2007 - 31.12.2008
ex 8421 99 00	93	Components of separators for the separation or purification of gases from gas mixtures, consisting of a bundle of permeable hollow fibres enclosed within a container, whether or not perforated, of an overall length of 300 mm or more but not exceeding 3 700 mm and a diameter not exceeding 500 mm	0 %	1.1.2007 - 31.12.2008
ex 8421 99 00	95	Parts of equipment for the filtration of magnetic dispersions, consisting essentially of nylon-6 fibres, enclosed in a plastic casing of a diameter of 70 mm (± 2 mm) and a length of 520 mm (± 5 mm)	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 8422 30 00	10	Machines and apparatus, other than injection moulding machines, for the manufacture of ink-jet printer cartridges (1)	0 %	1.1.2007 - 31.12.2008
ex 8479 89 97	30			
ex 8439 99 10	10	Suction-roll shells, not drilled, in the form of alloy-steel tubes, of a length of 5 207 mm or more and an external diameter of 754 mm or more, for use in machinery for making paper or paperboard (1)	0 %	1.1.2007 - 31.12.2008
ex 8439 99 90	10			
ex 8454 30 10	10	Casting machines for casting under pressure of metal alloys in thixotropic (semi-solid) form	0 %	1.1.2007 - 31.12.2008
ex 8455 90 00	10	Helical turn device for cold-rolling mill	0 %	1.1.2007 - 31.12.2008
ex 8456 10 00	10	Machine-tool operating by laser beam, for the cutting of slots on the surface of a cylindrical tube for use in the manufacture of endo-vascular prosthesis (so-called "stents") (1)	0 %	1.1.2007 - 31.12.2008
ex 8473 40 18	10	Thermal printer head	0 %	1.1.2007 - 31.12.2008
ex 8477 80 99	10	Machines for casting or for surface modification of plastic membranes of heading No 3921	0 %	1.1.2007 - 31.12.2008
ex 8479 89 97	20	Motor, whether or not mounted on a baseplate, for use in the manufacture of products falling within subheading 8517 12 00 or 8517 69 31 (1)	0 %	1.1.2007 - 31.12.2008
ex 8501 10 99	78			
ex 8481 80 59	10	Air control valve, consisting of a stepping motor and a valve pintle, for the regulation of idle air flow in fuel injection engines	0 %	1.1.2007 - 31.12.2008
ex 8481 80 99	50	Service valve, consisting a combination of a two way valve on the liquid line and a three way valve on the gas line with: <ul style="list-style-type: none"> — a minimum enclosing pressure of 30 kgf/cm², — a minimum withstanding pressure of 45 kgf/cm², for use in the manufacture of outdoor air conditioning units (1)	0 %	1.1.2007 - 31.12.2011
ex 8481 80 99	60	Four way valve, consisting of: <ul style="list-style-type: none"> — a core plunger, — a sealing plunger, — a 220 V-240 V AC 50/60 Hz solenoid coil, — a working pressure up to 4.3 Mpa, — a housing for directing the flow of the refrigerant, for use in the manufacture of	0 %	1.1.2007 - 31.12.2011

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		outdoor air conditioning units (1)		
ex 8483 10 95	20	Integrally forged and roughly shaped generator and turbine shafts of a weight exceeding 215 tonnes	0 %	1.1.2007 - 31.12.2008
ex 8483 40 51	20	Gear box, having a differential with wheel axle, for use in the manufacture of self-propelled lawnmowers with a seat of subheading 8433 11 51 (1)	0 %	1.1.2007 - 31.12.2008
ex 8483 40 59	20	Hydrostatic speed changer, having a hydro pump and a differential with wheel axle, for use in the manufacture of self-propelled lawnmowers with a seat of subheading 8433 11 51 (1)	0 %	1.1.2007 - 31.12.2008
ex 8483 40 90	20			
ex 8501 10 93	20	Single phased 50 Hz, AC motor driven by permanent single capacitor and having a power output of less than 37 W, for use in the manufacture of indoor split air conditioning units (1)	0 %	1.1.2007 - 31.12.2011
ex 8501 10 99	54	DC motor, brushless, with an external diameter not exceeding 25,4 mm, a rated speed of 2 260 (± 15 %) or 5 420 (± 15 %) rpm, a supply voltage of 1,5 V or 3 V	0 %	1.1.2007 - 31.12.2008
ex 8501 10 99	59	DC stepping motor, with an angle of step of 1,8° ($\pm 0,09^\circ$), a holding torque of 0,156 Nm or more, a coupling flange the exterior dimensions of which do not exceed 43 × 43 mm, a chuck of a diameter of 4 mm ($\pm 0,1$ mm), a two-phase winding and an output not exceeding 5 W	0 %	1.1.2007 - 31.12.2008
ex 8501 10 99	73	DC motor, whether or not mounted on a baseplate, for use in the manufacture of products falling within subheading 8471 70 50 (1)	0 %	1.1.2007 - 31.12.2008
ex 8501 10 99	77	DC motor, with brushes, with a typical running torque of 0,004 Nm ($\pm 0,001$ Nm), with a coupling flange of a diameter of 32 mm ($\pm 0,5$ mm) and a chuck of a diameter of 2 mm ($\pm 0,004$ mm), with an internal rotor, a three-phase winding, a rated speed of 2 800 (± 10 %) rpm and a supply voltage of 12 V (± 15 %)	0 %	1.1.2007 - 31.12.2008
ex 8501 10 99	79	DC motor with brushes and an internal rotor with a three-phase winding, of a specified temperature range covering at least - 20 °C to + 70 °C	0 %	1.1.2007 - 31.12.2008
ex 8501 10 99	81	DC stepping motor, with an angle of step of 18 ° or more, a holding torque of 0.5 mNm or more, a coupling bracket the exterior dimensions of which do not exceed 22 x 68 mm, a two phase winding and an output not exceeding 5 W	0 %	1.1.2007 - 31.12.2008
ex 8501 10 99	82	DC motor, brushless, with an external diameter not exceeding 29 mm, a rated speed of 1 500 (± 15 %) or 6 800 (± 15 %) rpm, a supply voltage of 2 V or 8 V	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 8501 10 99	83	Multiphase DC motor, brushless, of a continuous output of 31 W (± 5 W) calculated with 600 rpm, equipped with electronic circuit with sensor using Hall effect (electric power steering motor)	0 %	1.1.2007 - 31.12.2008
ex 8502 40 00	20	Rotary converter, with a ferrite core, having coils with 2 or 6 windings and a diameter of 0,1 mm, connected to a flexible printed circuit	0 %	1.1.2007 - 31.12.2008
ex 8503 00 91	31	Rotor, at the innerside provided with one or two magnetic rings whether or not incorporated in a steel ring	0 %	1.1.2007 - 31.12.2008
ex 8503 00 99	32			
ex 8503 00 99	31	Stamped collector of an electric motor, having an external diameter not exceeding 16 mm	0 %	1.1.2007 - 31.12.2008
ex 8504 40 90	20	Direct current to direct current converter	0 %	1.1.2007 - 31.12.2008
ex 8504 40 90	30	Static converter comprising a power switch with insulated-gate bipolar transistors (IGBTs), contained in a housing, for use in the manufacture of microwave ovens of subheading 8516 50 00 (1)	0 %	1.1.2007 - 31.12.2008
ex 8504 50 95	20	Inductor with an inductance not exceeding 62 mH	0 %	1.1.2007 - 31.12.2008
ex 8504 50 95	30	Multilayer monolithic inductors, contained in a housing of the SMD (surface mounted device) type the exterior dimensions of which do not exceed 1,8 x 3,4 mm, for use in the manufacture of products falling within subheading 8517 11 00, 8517 12 00 or 8517 69 31 (1)	0 %	1.1.2007 - 31.12.2008
ex 8504 90 11	10	Ferrite cores, other than for deflection yokes	0 %	1.1.2007 - 31.12.2008
ex 8504 90 18	32	Part of a rotary transformer, comprising a ferrite core provided with circular grooves with copper wire windings	0 %	1.1.2007 - 31.12.2008
ex 8504 90 18	40	Trans coil for boosting DC voltage and isolating high and low voltages for use in the manufacture of products falling within subheading 8504 31 80 (1)	0 %	1.1.2007 - 31.12.2011
ex 8505 11 00	31	Ferrite magnet having a remanence of 455 mT (± 15 mT)	0 %	1.1.2007 - 31.12.2008
ex 8505 11 00	33	Magnets consisting of an alloy of neodymium, iron and boron, either in the shape of a rounded rectangle with measurements not exceeding 15 x 10 x 2 mm, or in the shape of disc with a diameter not exceeding 90 mm, whether or not containing a hole in the centre	0 %	1.1.2007 - 31.12.2008
ex 8505 19 90	31	Neodymium-ferro ring with an external diameter not exceeding 13 mm, an internal diameter not exceeding 9 mm	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 8505 19 90	32	Magnet, for use in the manufacture of deflection yokes (1)	0 %	1.1.2007 - 31.12.2008
ex 8505 20 00	20	Electromagnetic wrap spring clutch with a diameter not exceeding 40 mm, for use in the manufacture of copiers and printers, including multi-functional copiers (1)	0 %	1.1.2007 - 31.12.2008
ex 8505 20 00	30	Electromagnetic clutch, for use in the manufacture of compressors of air conditioning machines of motor vehicles (1)	0 %	1.1.2007 - 31.12.2008
ex 8505 90 10	91	Solenoid with a plunger, operating at a nominal supply voltage of 24 V at a nominal DC of 0,08 A, for use in the manufacture of products falling within heading No 8517 (1)	0 %	1.1.2007 - 31.12.2008
ex 8505 90 10	92	Electro-mechanical throttle plate actuator for automotive engines	0 %	1.1.2007 - 31.12.2008
ex 8506 50 90	10	Lithium iodine single cell battery the dimensions of which do not exceed 9 x 23 x 45 mm and a voltage not exceeding 2,8 V	0 %	1.1.2007 - 31.12.2008
ex 8506 50 90	20	Unit consisting of not more than 2 lithium batteries embedded in a socket for integrated circuits (battery-buffered socket), with not more than 32 connections and incorporating a control circuit	0 %	1.1.2007 - 31.12.2008
ex 8506 50 90	30	Lithium-iodine or lithium-silver vanadium oxide single cell battery of dimensions not exceeding 28 x 45 x 15 mm and a capacity of not less than 1,05 Ah	0 %	1.1.2007 - 31.12.2008
ex 8507 30 20	20	Rectangular accumulator, with a length not exceeding 69 mm, a width not exceeding 36 mm and a thickness not exceeding 12 mm, for use in the manufacture of rechargeable batteries (1)	0 %	1.1.2007 - 31.12.2008
ex 8507 80 20	20			
ex 8507 80 30	20			
ex 8507 80 80	20			
ex 8507 30 20	30	Cylindrical nickel-cadmium accumulator, with a length of 65,3 mm ($\pm 1,5$ mm) and a diameter of 14,5 mm (± 1 mm), having a nominal capacity of 1 000 mAh or more, for use in the manufacture of rechargeable batteries (1)	0 %	1.1.2007 - 31.12.2008
ex 8507 80 20	30	Cylindrical nickel-hydride accumulator, of a diameter not exceeding 14,5 mm, for the manufacture of rechargeable batteries (1)	0 %	1.1.2007 - 31.12.2008
ex 8507 80 30	30	Cylindrical lithium-ion accumulator, with a length of 64,6 mm or more and a diameter of 18,1 mm or more, having a nominal capacity of 1 200 mAh or more, for use in the manufacture of rechargeable batteries (1)	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 8516 90 00	31	Dual diode, consisting of a power rectifying diode connected with a transformer protector diode through a wire, with a peak reverse power rate of 2 J or more, for use in the manufacture of products falling within subheading 8516 50 00 (1)	0 %	1.1.2007 - 31.12.2008
ex 8516 90 00	33	Stainless steel soleplate with heating wire, for use in the manufacture of electric irons (1)	0 %	1.1.2007 - 31.12.2008
ex 8518 29 95	20	Loudspeaker having a power of 5 W and an impedance of 4 ohms, with a diameter not exceeding 50 mm, for use in the manufacture of portable phones (1)	0 %	1.1.2007 - 31.12.2008
ex 8518 30 95	20	Headphone and earphone for hearing aids, contained in a housing the exterior dimensions of which, excluding connecting points, do not exceed 5 × 6 × 8 mm	0 %	1.1.2007 - 31.12.2008
ex 8518 40 81	20	Audio-frequency amplifier unit, comprising at least an audio-frequency amplifier, a static converter and a sound generator, for the manufacture of active loudspeaker boxes (1)	0 %	1.1.2007 - 31.12.2008
ex 8518 90 00	91	Integrally cold-upsetted steel coreplate, in the form of a disk on one side provided with a cylinder, for use in the manufacture of loudspeakers (1)	0 %	1.1.2007 - 31.12.2008
ex 8522 90 49	40	Optical unit consisting of a laser diode with one photodiode, emitting light of a nominal wavelength of 780 nm, contained in a housing with a diameter of not more than 10 mm and a height of not more than 9 mm, with not more than 10 connections	0 %	1.1.2007 - 31.12.2008
ex 8522 90 49	50	Electronic assembly for a laser read-head of a compact disc player, comprising: <ul style="list-style-type: none"> — a printed circuit, — a photo-detector, in the form of a monolithic integrated circuit, contained in a housing, — not more than 3 connectors, — not more than 1 transistor, — not more than 3 variable and 4 fixed resistors, — not more than 5 capacitors, the whole mounted on a support	0 %	1.1.2007 - 31.12.2008
ex 8522 90 49	60	Printed circuit board mounted with electronic circuits operating at a voltage of 12 V, for use in the manufacture of television sets combined with video units (1)	0 %	1.1.2007 - 31.12.2008
ex 8522 90 49	70	Assembly, comprising at least a flexible printed circuit, a laser driver integrated circuit and a signal converter integrated circuit	0 %	1.1.2007 - 31.12.2008
ex 8522 90 80	30	Thin-film recording and reproducing device, having at least 9 parallel channels for digital signals and at least 2 channels for analogue signals, to which a non-magnetic ceramic substrate is fixed, the whole rounded at one side, for use in the manufacture of magnetic heads for digital	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		sound recording and digital/analogue sound reproducing apparatus of the cassette-type (1)		
ex 8522 90 80	35	Cassette-deck sub-assembly for sound recording and reproducing apparatus, for use in the manufacture of telephone answering machines (1)	0 %	1.1.2007 - 31.12.2008
ex 8522 90 80	40	Sound reproducing assembly, comprising a tape deck mechanism of the cassette type, comprising a DC motor, for use in the manufacture of products falling within heading No 8519 (1)	0 %	1.1.2007 - 31.12.2008
ex 8522 90 80	45	Roll for magnetic tape guiding and winding, for use in the manufacture of products falling within heading No 8521 or 8522 (1)	0 %	1.1.2007 - 31.12.2008
ex 8522 90 80	50	Magnetic head for erasing video tapes, for use in the manufacture of products falling within heading No 8521 or 8522 (1)	0 %	1.1.2007 - 31.12.2008
ex 8522 90 80	55	Assembly consisting of a driver circuit, a tacho-sensor and a brushless DC motor	0 %	1.1.2007 - 31.12.2008
ex 8522 90 80	60	Analogue sound recording and reproducing assembly, comprising a record/playback head and a twin tape deck mechanism of the cassette type, not comprising circuits with amplification functions or power supply drive functions, for use in the manufacture of products falling within subheadings 8527<nbsp>91<nbsp>35 and 8527<nbsp>91<nbsp>99 (1)	0 %	1.1.2007 - 31.12.2008
ex 8522 90 80	65	Assembly for optical discs, comprising at least an optical unit and DC motors, capable or not of double layer recording	0 %	1.1.2007 - 31.12.2008
ex 8522 90 80	70	Video tape recording/reproducing assembly comprising at least a motor and a printed circuit board containing integrated circuits with driver or control functions, whether or not incorporating a transformer, for use in the manufacture of products falling within heading No 8521 (1)	0 %	1.1.2007 - 31.12.2008
ex 8522 90 80	75	Optical reading head for CD player, consisting of one laser diode, one photodetector integrated circuit and one beam splitter	0 %	1.1.2007 - 31.12.2008
ex 8522 90 80	80	Laser optical drive unit assembly (so called mecha units) for the recording and/or reproduction of digital video and/or audio signals, comprising at least a laser optical reading and/or writing unit, one or more DC motors and not containing a printed circuit board or containing a printed circuit board not capable of signal processing for sounds and images, for use in the manufacture of products falling within headings No 8519, 8521, 8526, 8527, 8528 or 8543 (1)	0 %	1.1.2007 - 31.12.2008
ex 8548 90 90	45			
ex 8522 90 80	81	Laser optical pick up unit for the reproduction of optical signals from CD or DVD and the recording of optical signal on DVD, comprising at	0 %	1.1.2007 - 31.12.2011

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		<p>least</p> <ul style="list-style-type: none"> — a laser diode, — a laser driver integrated circuit, — a photo detector integrated circuit, — a front monitor integrated circuit and an actuator, <p>for use in the manufacture of products falling within heading No 8521 (1)</p>		
ex 8522 90 80	85	Video head drum, with video heads or with video and audio heads and an electric motor, for use in the manufacture of products falling within heading No 8521 (1)	0 %	1.1.2007 - 31.12.2008
ex 8522 90 80	90	Magnetic head for playback of audio tapes, for use in the manufacture of products falling within heading 8519 (1)	0 %	1.1.2007 - 31.12.2008
ex 8522 90 80	95	Drive-unit capable of magneto-optical signal recording and optical signal reproducing, comprising at least an optical unit, DC motors and a printed circuit on which are mounted integrated circuits providing drive and signal processing functions for reading optical discs having an external diameter not exceeding 70 mm, not comprising circuits with amplification functions or power supply drive functions	0 %	1.1.2007 - 31.12.2008
ex 8525 80 19	20	Assembly for television cameras of dimensions not exceeding 10 × 15 × 18 mm, comprising an image sensor, an objective and a color processor, having an image resolution not exceeding 1024 × 1280 pixel, whether or not fitted with cable and/or housing, for the manufacture of goods of subheading 8517 12 00 (1)	0 %	1.1.2007 - 31.12.2008
ex 8525 80 19	30	Compact chassis-type closed circuit television (CCTV) cameras, of a weight of not more than 250 g, contained in a housing of dimensions not exceeding 50 × 60 × 89,5 mm, with a single sensor Charge-Coupled Device (CCD), with effective pixels not exceeding 440 000, for use in CCTV surveillance systems (1)	0 %	1.1.2007 - 31.12.2008
ex 8525 80 19	40	Assembly for cameras used in computer notebooks of dimensions not exceeding 15 x 25 x 25 mm, comprising an image sensor, an objective and a color processor, having an image resolution not exceeding 1600 x 1200 pixel, whether or not fitted with cable and/or housing, whether or not mounted on a base and containing a LED chip (1)	0 %	1.1.2007 - 31.12.2011
ex 8528 49 10	10	<p>Video monitor comprising:</p> <ul style="list-style-type: none"> — a flat screen monochrome cathode-ray tube with a diagonal measurement of the screen not exceeding 110 mm and equipped with a deflector yoke, and — a printed circuit on which are mounted a deflection unit, a video-amplifier and a transformer, <p>the whole mounted or not on a chassis, for the manufacture of video entry-phones, video telephones or surveillance apparatus (1)</p>	0 %	1.1.2007 - 31.12.2008
ex 8528 59 90	20	Liquid crystal display colour video monitor having a DC input voltage of 7 V or more but not exceeding 30 V, with a diagonal measurement of the screen of 33,2 cm or less, suitable for the incorporation into goods of	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		chapters 84 to 90 and 94		
ex 8529 10 80	20	Ceramic filter package comprising 2 ceramic filters and 1 ceramic resonator for a frequency of 10,7 MHz (± 30 kHz), contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8529 10 80	25	Ceramic filter for a centre frequency of 10,7 MHz, with a bandwidth not exceeding 330 kHz at 3 dB and not exceeding 950 kHz at 20 dB, contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8529 10 80	30	Ceramic filters for frequencies of 4,5 MHz or more but not exceeding 6,6 MHz contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8529 10 80	35	Ceramic filter for a centre frequency of 450 kHz or more but not exceeding 470 kHz, with a bandwidth not exceeding 13 kHz at 3 dB, contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8529 10 80	40	Ceramic filter for a frequency of 450 kHz, with a bandwidth not exceeding 18 kHz at 10 dB, contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8529 10 80	45	Ceramic filter for a centre frequency of 455 kHz ($\pm 1,5$ kHz), with a bandwidth not exceeding 25 kHz at 6 dB and not exceeding 60 kHz at 40 dB, contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8529 10 80	50	Ceramic filter for a centre frequency of 450 kHz ($\pm 1,5$ kHz) or 455 kHz ($\pm 1,5$ kHz), with a bandwidth not exceeding 30 kHz at 6 dB and not exceeding 70 kHz at 40 dB, contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8529 10 80	55	Radio frequency (RF) signal isolator for frequencies of 890 MHz or more but not exceeding 1 990 MHz, having an insertion loss not exceeding 0,7 dB, contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8529 10 80	60	Filters, excluding surface acoustic wave filters, for a center frequency of 485 MHz or more but not exceeding 1 990 MHz with an insertion loss not exceeding 3,5 dB, contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8529 10 80	65	Ceramic filter package, excluding surface acoustic wave filters, consisting of: <ul style="list-style-type: none"> — a transmit filter with a centre frequency of 1 747,5 MHz and an insertion loss not exceeding 2,3 dB at a bandwidth of 75 MHz and <ul style="list-style-type: none"> — a receive filter with a centre frequency of 1 842,5 MHz and an insertion loss not exceeding 3,3 dB at a bandwidth of 75 MHz, the whole contained in a housing	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 8529 10 80	70	Ceramic filter package, excluding surface acoustic wave filters, comprising 2 filters with one of the following combinations of characteristics: <ul style="list-style-type: none"> — a transmit centre frequency of 902,5 MHz, a receive centre frequency of 947,5 MHz and an insertion loss not exceeding 3,2 dB at a bandwidth of 25 MHz or <ul style="list-style-type: none"> — a transmit centre frequency of 1 747,5 MHz, a receive centre frequency of 1 842,5 MHz and an insertion loss not exceeding 3,5 dB at a bandwidth of 75 MHz, the whole contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8529 10 95	20	Antenna switch, comprising: <ul style="list-style-type: none"> — a transmit filter with a centre frequency of 942,5 MHz or more but not exceeding 1 990 MHz and — a receive filter with a centre frequency of 847,5 MHz or more but not exceeding 1 990 MHz, the whole contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8529 90 65	30	Parts of TV-apparatus, having micro-processor and video-processor functions, comprising at least a micro-controller and a video-processor, mounted on a leadframe and contained in a plastic housing	0 %	1.1.2007 - 31.12.2008
ex 8548 90 90	44			
ex 8529 90 65	40	Analogue sound recording and reproducing assembly, comprising a record/playback head, a single tape deck mechanism of the cassette type, a spindle electric motor, a rotation direction change mechanism and a chassis	0 %	1.1.2007 - 31.12.2008
ex 8529 90 65	50	Tuner transforming high-frequency signals into mid-frequency signals, for use in the manufacture of products falling under n° 8521 and n° 8528 (1)	0 %	1.1.2007 - 31.12.2011
ex 8529 90 65	60	Tuner transforming high frequency signals to mid frequency signals for use in the manufacture of satellite or terrestrial TV receivers for set-top boxes (1)	0 %	1.1.2007 - 31.12.2011
ex 8529 90 92	32	Optical unit for video projection, comprising a colour separation system, a positioning mechanism and lenses, for use in the manufacture of products falling within heading No 8528 (1)	0 %	1.1.2007 - 31.12.2008
ex 8529 90 92	34	Assembly consisting of a lens unit, having an adjustable focal length of 4 mm or more but not exceeding 69 mm and comprising a zoom encoder, a stepping motor unit, a zoom motor unit, an iris motor unit and a photo interrupter	0 %	1.1.2007 - 31.12.2008
ex 8529 90 92	35	Video recording and reproducing assembly, comprising a tape deck mechanism of the cassette type, comprising a DC motor, for use in the manufacture of products falling within heading No 8525 (1)	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 8529 90 92	36	Assembly consisting of a monochrome cathode-ray tube with a diagonal measurement of the screen of 143 mm or more but not exceeding 230 mm and a concave focus lens mounted on a liquid-filled cooling armature	0 %	1.1.2007 - 31.12.2008
ex 8529 90 92	37	Filter, consisting of 2 piezo-electric crystals each with a frequency of 21 MHz or more but not exceeding 30 MHz and separately mounted on a bracket, with not more than 7 connections	0 %	1.1.2007 - 31.12.2008
ex 8529 90 97	40			
ex 8529 90 92	40	Assembly comprising prisms, digital micromirror device (DMD) chips and electronic control circuits, for the manufacture of television projection equipments or video projectors (1)	0 %	1.1.2007 - 31.12.2008
ex 8529 90 92	41	Digital micromirror device (DMD)-chips, for use in the manufacture of video projectors (1)	0 %	1.1.2007 - 31.12.2008
ex 8529 90 92	42	Heat sinks and cooling fins of aluminium, for maintaining the operating temperature of transistors and integrated circuits in television sets (1)	0 %	1.1.2007 - 31.12.2008
ex 8529 90 92	43	Plasma display module incorporating only address and display electrodes, with or without driver and/or control electronics for pixel address only and with or without a power supply	0 %	1.1.2007 - 31.12.2008
ex 8529 90 92	44	LCD modules, solely consisting of one or more TFT glass or plastic cells, not combined with touch screen facilities, with or without backlight unit, with or without inverters and one or more printed circuit boards with control electronics for pixel addressing only	0 %	1.1.2007 - 31.12.2008
ex 8529 90 92	45	Integrated circuit package with TV reception functionality containing a channel decoder die, tuner die, power management die, GSM filters and discrete as well as embedded passive circuit elements for reception of digitally broadcasting videosegments of DVB-T and DVB-H formats	0 %	1.1.2007 - 31.12.2008
ex 8529 90 97	50	Video tape recording/reproducing assembly comprising at least a motor and a printed circuit board containing integrated circuits with driver or control functions, mounted on a printed circuit board containing at least integrated circuits for controlling the tape deck mechanism functions, video recording functions and TV-signal processing functions, for use in the manufacture of products falling within heading No 8528 (1)	0 %	1.1.2007 - 31.12.2008
ex 8531 80 95	20	Indicator lamp, consisting of 4 light-emitting diodes made from silicon-carbide (SiC) semiconductor material, operating at a nominal wavelength of 481, 560 or 630 nm, contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8531 80 95	30	Indicator lamp, consisting of 2 light-emitting diodes made from aluminium-gallium-arsenic (AlGaAs) or gallium-phosphor (GaP) semiconductor material, having a rectangular base, contained in a housing of the SMD (surface mounted device) type and having a lens	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 8531 80 95	40	Electro-acoustic transducer	0 %	1.1.2007 - 31.12.2008
ex 8531 80 95	50	An electromagnetic display, consisting of 7 electromagnetic coils which by means of the residual magnetism in the stators provide that the last indication remains available (set state), and 7 pivoting light-reflecting segments each of which is attached to a bar magnet; assembly comprising such displays	0 %	1.1.2007 - 31.12.2008
ex 8536 30 30	11	Thermo-electric switch with a cut-off current of 50 A or more, comprising a snap action switch, for direct mounting on an electric motor coil, contained in a hermetically sealed housing	0 %	1.1.2007 - 31.12.2008
ex 8536 30 90	31			
ex 8536 50 80	96			
ex 8536 41 10	91	Thermal relays contained in a hermetically sealed glass cartridge not exceeding 35 mm in length excluding wires, with a maximum leakage rate of 10^{-6} cm ³ He/sec at one bar in the temperature range 0 to 160 °C, to be incorporated into compressors for refrigerating equipment (1)	0 %	1.1.2007 - 31.12.2008
ex 8536 41 90	91			
ex 8536 49 00	91			
ex 8536 50 11	31	Switch of the printed circuit mount type, operating at a force of 4,9 N ($\pm 0,9$ N), contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8536 50 11	32	Mechanical tact switch for connecting electronic circuits, operating at a voltage not exceeding 60 V and at a current strength not exceeding 50 mA, for use in the manufacture of television sets (1)	0 %	1.1.2007 - 31.12.2008
ex 8536 50 15	32	Rotary switch in form of a wheel with a diameter of between 15 and 16 mm and contacts for closing the circuit, for a rated voltage of 12 V at 50 mA	0 %	1.1.2007 - 31.12.2008
ex 8536 50 19	91	Hall effect switch, comprising 1 magnet, 1 Hall effect sensor and 2 capacitors, contained in a housing with 3 connections	0 %	1.1.2007 - 31.12.2008
ex 8536 50 19	92	Hydraulic pressure switch, incorporating a pressure sensitive snap action disc, operating at a supply voltage of 6 V or more but not exceeding 18 V	0 %	1.1.2007 - 31.12.2008
ex 8536 50 19	93	Devices, having adjustable controller and switching functions, comprising one or more monolithic integrated circuits whether or not combined with semiconductor elements, mounted together on a leadframe and contained in a plastic housing	0 %	1.1.2007 - 31.12.2008
ex 8536 50 80	97			

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 8536 50 80	93	Switch unit for coaxial cable, comprising 3 electromagnetic switches, with a switching time not exceeding 50 ms and an actuating current not exceeding 500 mA at a voltage of 12 V	0 %	1.1.2007 - 31.12.2008
ex 8536 50 80	95	Reed switch having a switching power of 20 W or more within the range of 17 - 43 A.turn, in the form of a glass capsule, not containing mercury, the dimensions of which do not exceed 3 × 21 mm, for use in the manufacture of automotive airbag shock-sensors (1)	0 %	1.1.2007 - 31.12.2008
ex 8536 50 80	98	Mechanical push-button switch for connecting electronic circuits, operating at a voltage of 220 V or more but not exceeding 250 V and at a current strength not exceeding 5 A, for use in the manufacture of television sets (1)	0 %	1.1.2007 - 31.12.2008
ex 8536 90 85	92	Metallic stamped frame with connections	0 %	1.1.2007 - 31.12.2008
ex 8536 90 85	93	Contact element with a hold-force of more than 3 N, in the form of 2 rectangular plastic frames interconnected by electric conductors	0 %	1.1.2007 - 31.12.2008
ex 8536 90 85	94	Elastomeric connector, of rubber or silicone, consisting of one or more conductor elements	0 %	1.1.2007 - 31.12.2008
ex 8544 49 93	10			
ex 8537 10 99	92	Touch sensitive screen panel, consisting of a conductive grid between two glass or plastic plates or sheets, fitted with electric conductors and connectors	0 %	1.1.2007 - 31.12.2008
ex 8537 10 99	93	Electronic control units for a voltage of 12 V, for use in the manufacture of vehicle mounted temperature control systems (1)	0 %	1.1.2007 - 31.12.2008
ex 8537 10 99	94	Unit consisting of two junction field effect transistors contained in a dual lead frame housing	0 %	1.1.2007 - 31.12.2008
ex 8543 70 90	20			
ex 8537 10 99	95	Unit consisting of two metal oxide semiconductor field effect transistors contained in a dual lead frame housing	0 %	1.1.2007 - 31.12.2008
ex 8543 70 90	25			
ex 8538 90 99	92	Part of an electrothermal fuse, consisting of a tin coated copper wire attached to a cylindrical casing, the exterior dimensions of which do not exceed 5 × 48 mm	0 %	1.1.2007 - 31.12.2008
ex 8540 11 11	91	Colour cathode-ray tube with a slit or slot mask, equipped with electron guns placed side by side (in-line technology) and with a diagonal measurement of the screen of 12 cm or more but not exceeding 26 cm	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 8540 11 11	93	Colour cathode-ray tube, equipped with one gun with three rays and with a diagonal measurement of the screen of 19 cm or more but not exceeding 26 cm	0 %	1.1.2007 - 31.12.2008
ex 8540 11 13	91	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,42 mm and a diagonal measurement of the screen of 49 cm, for use in the manufacture of professional video monitors including security and medical monitor applications (1)	0 %	1.1.2007 - 31.12.2008
ex 8540 11 15	20	Full square curved screen colour cathode-ray tube, equipped with an electron gun and a deflection yoke and with a screen width/height ratio of 4/3 and a diagonal measurement of the screen of 68 cm (\pm 2 mm)	0 %	1.1.2007 - 31.12.2011
ex 8540 11 19	91	Colour cathode-ray tube equipped with electron guns placed side by side (in-line technology), with a diagonal measurement of the screen of 85 cm or more	0 %	1.1.2007 - 31.12.2008
ex 8540 11 91	31	Colour cathode-ray tube with a screen width/height ratio of 16/9 and a diagonal measurement of the screen of 39,8 cm (\pm 0,3 cm)	0 %	1.1.2007 - 31.12.2008
ex 8540 12 00	82	Monochrome cathode-ray tube with a diagonal measurement of the screen of 250 mm or more but not exceeding 320 mm and an anode voltage of 18 kV or more but not exceeding 22 kV	0 %	1.1.2007 - 31.12.2008
ex 8540 12 00	83	Monochrome cathode-ray tube, with a diagonal measurement of the screen of 150 mm or more but not exceeding 182 mm, a neck diameter of less than 30 mm and an anode voltage of 25 kV or more but not exceeding 32 kV	0 %	1.1.2007 - 31.12.2008
ex 8540 12 00	84	Flat screen monochrome cathode-ray tube, with a diagonal measurement of the screen not exceeding 102 mm	0 %	1.1.2007 - 31.12.2008
ex 8540 20 80	91	Photomultiplier consisting of a photocathode tube with 9 or 10 dyodes, for light of a wavelength of 160 nm or more but not exceeding 930 nm, of a diameter not exceeding 14 mm and a height not exceeding 94 mm	0 %	1.1.2007 - 31.12.2011
ex 8540 40 00	31	Colour cathode-ray tube with a dot mask, equipped with 3 electron guns placed side by side (in-line technology) or 1 gun with 3 rays, with a diagonal measurement of the screen of more than 72 cm and a distance of less than 0,5 mm between dots of the same colour	0 %	1.1.2007 - 31.12.2008
ex 8540 60 00	31			
ex 8540 40 00	32	Colour cathode-ray tube with a dot mask, equipped with 3 electron guns placed side by side (in-line technology) or 1 gun with 3 rays, having a diagonal measurement of the screen not exceeding 72 cm	0 %	1.1.2007 - 31.12.2008
ex 8540 60 00	32			

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 8540 40 00	33	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,35 mm and a diagonal measurement of the screen not exceeding 53 cm	0 %	1.1.2007 - 31.12.2008
ex 8540 40 00	34	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,39 mm and a diagonal measurement of the screen of 33 cm or more but not exceeding 38 cm	0 %	1.1.2007 - 31.12.2008
ex 8540 40 00	35	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,35 mm and a diagonal measurement of the screen not exceeding 72 cm, for use in the manufacture of monitors (1)	0 %	1.1.2007 - 31.12.2008
ex 8540 40 00	36	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,30 mm and a diagonal measurement of the screen not exceeding 58 cm	0 %	1.1.2007 - 31.12.2008
ex 8540 50 00	31	Flat screen monochrome cathode-ray tube, with a diagonal measurement of the screen of 142 mm or more but not exceeding 190 mm, a luminescence of 300 lumen or more but not exceeding 2 000 lumen, a resolution of 0,06 mm or more but not exceeding 0,1 mm, phosphor types P1 or P22 or P53 or P55 or P56, an anode voltage of more than 34 kV, a focus voltage of more than 7 kV and a cathode current of 3 mA or more	0 %	1.1.2007 - 31.12.2008
ex 8540 60 00	33			
ex 8540 50 00	32	Monochrome cathode-ray tube with a diagonal measurement of the screen of 176 mm or more but not exceeding 520 mm and a neck diameter not exceeding 21 mm	0 %	1.1.2007 - 31.12.2008
ex 8540 60 00	34			
ex 8540 71 00	20	Continuous wave magnetron with a fixed frequency of 2 460 MHz, packaged magnet, probe output, for use in the manufacture of products falling within subheading 8516 50 00 (1)	0 %	1.1.2007 - 31.12.2008
ex 8540 89 00	91	Displays in the form of a tube consisting of a glass housing mounted on a board the dimensions of which do not exceed 300 mm × 350 mm excluding leads. The tube contains one or more rows of characters or lines arranged in rows, each character or line consisting of fluorescent or phosphorescent elements. These elements are mounted on a metallised base which is covered with fluorescent substances or phosphorescent salts which give off light when bombarded with electrons	0 %	1.1.2007 - 31.12.2008
ex 8540 89 00	92	Vacuum fluorescent display tube	0 %	1.1.2007 - 31.12.2008
ex 8540 91 00	31	Electron gun, for use in the manufacture of colour cathode-ray tubes of subheading 8540 40 00 with a diagonal measurement of the screen of 34 cm or more but not exceeding 39 cm (1)	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 8540 91 00	32	Electron gun of colour cathode-ray tubes with an anode voltage of 27,5 kV or more but not exceeding 36 kV	0 %	1.1.2007 - 31.12.2008
ex 8540 91 00	36	Flat masks, with: <ul style="list-style-type: none"> — a width of 592,8 mm (+/- 0,5 mm) — a height of 463,1 mm (+/- 0,5 mm) — a thickness of 250 µm (+/- 10 µm) — a width of the apertures in the centre of 180 µm (+/- 8 µm) — a width of the apertures at the edge of 210 µm (+/- 8 µm) 	0 %	1.1.2007 - 31.12.2008
ex 8540 91 00	92	Slit or slot mask, excluding masks with continuously vertical slits, with a diagonal measurement of 69 cm or less	0 %	1.1.2007 - 31.12.2011
ex 8540 91 00	93	Electron gun for the production of monochrome cathode-ray tubes with a diagonal measurement of the screen of 7,6 cm or more but not exceeding 30,5 cm (1)	0 %	1.1.2007 - 31.12.2008
ex 8540 91 00	96	Assembly for cathode-ray tubes with 2 or more but not more than 6 coils, a plastic support and a metal fixing ring, for the adjustment of display sharpness and/or convergence	0 %	1.1.2007 - 31.12.2008
ex 8540 91 00	97	Slit mask, consisting of continuously vertical slits measuring more than 275 mm in the length	0 %	1.1.2007 - 31.12.2008
ex 8540 91 00	98	Frame of molybdenum chrome steel, for use in the manufacture of cathode-ray tubes (1)	0 %	1.1.2007 - 31.12.2008
ex 8540 99 00	91	Anode, cathode or output part, or an assembly comprising these components (magnetron core tube), for the manufacture of magnetrons of subheading 8540 71 00 (1)	0 %	1.1.2007 - 31.12.2008
ex 8543 10 00	10	Electron beam accelerator systems, with an operating voltage not exceeding 1,5 MV and a beam current not exceeding 70 mA	0 %	1.1.2007 - 31.12.2008
ex 8543 70 90	30	Amplifier, consisting of active and passive elements mounted on a printed circuit, contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8543 70 90	35	Radio frequency (RF) modulator, operating with a frequency range of 43 MHz or more but not exceeding 870 MHz, capable of switching VHF and UHF signals, consisting of active and passive elements mounted on a printed circuit, contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8543 70 90	40	Rectifier assembly of power barrier diodes, consisting of 2 diodes with an average forward current not exceeding 600 A and a repetitive reverse peak voltage not exceeding 40 V, each contained in a housing and connected by a common cathode	0 %	1.1.2007 - 31.12.2008
ex 8543 70 90	45	Piezo-electric crystal oscillator with a fixed frequency, within a	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
		frequency range of 1,8 MHz to 67 MHz, contained in a housing		
ex 8543 70 90	50	Mechanical vibratory gyroscope driven by a 25 or 26 kHz oscillator, comprising a differential amplifier and a detector circuit, contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8543 70 90	55	Opto-electronic circuit comprising one or more light-emitting diodes (LEDs), whether or not equipped with an integrated driving circuit, and one photodiode with amplifier circuit, whether or not with an integrated logic gate arrays circuit or one or more light-emitting diodes and at least 2 photodiodes with an amplifier circuit, whether or not with an integrated logic gate arrays circuit or other integrated circuits, contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8543 70 90	60	Oscillator, with a centre frequency of 20 GHz or more but not exceeding 42 GHz, consisting of active and passive elements not mounted on a substrate, contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8543 70 90	65	Audio recording and reproducing circuit, capable of stereo audio data storage and simultaneous record and playback, comprising 2 or 3 monolithic integrated circuits mounted on a printed circuit or a lead frame, contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8543 70 90	70	Overvoltage suppression assembly, comprising 8 diodes, having a reverse stand-off voltage not exceeding 4,5 V, a reverse leakage current not exceeding 10 µA, a peak pulse current not exceeding 30 A and a nominal capacitance of 50 pF, contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8543 70 90	75	Charged coupled device (CCD) scanner assembly, for a real-time film scanning system, having optical functions, illumination functions and signal processing functions	0 %	1.1.2007 - 31.12.2008
ex 8543 70 90	80	Temperature compensated oscillator, comprising a printed circuit on which are mounted at least a piezo-electric crystal and an adjustable capacitor, contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8543 70 90	85	Voltage controlled oscillator (VCO), other than temperature compensated oscillators, consisting of active and passive elements mounted on a printed circuit, contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8543 70 90	90	Fuel cell module consisting of: -polymer electrolyte membrane fuel cells in a housing with an integrated cooling system, -a voltage monitoring unit and connections, for use in the manufacture of car propulsion systems (1)	0 %	1.1.2007 - 31.12.2008
ex 8543 90 00	20	Stainless steel cathode in the form of a plate with a hanger bar, whether or not with plastic side strips	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 8543 90 00	30	Assembly of products falling within heading No 8541 or 8542 mounted on a printed circuit, contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8544 60 10	10	Anode cap cable, for use in the manufacture of fly back transformers (1)	0 %	1.1.2007 - 31.12.2008
ex 8545 19 90	20	Carbon electrodes, for use in the manufacture of zinc-carbon batteries (1)	0 %	1.1.2007 - 31.12.2008
ex 8545 90 90	01	Cell and battery carbon, in the form of rods, with a length of 34 mm or more but not exceeding 160 mm and a diameter not exceeding 12 mm	0 %	1.1.2007 - 31.12.2008
ex 8547 10 10	10	Insulated fitting of ceramics, containing by weight 90 % or more of aluminium oxide, metallized, in the form of a hollow cylindrical body of an external diameter of 20 mm or more but not exceeding 250 mm, for the manufacture of vacuum interrupters (1)	0 %	1.1.2007 - 31.12.2008
ex 8548 90 90	38	Parts, for use in the manufacture or the repair of products falling within subheading 8443 31 10 (1)	0 %	1.1.2007 - 31.12.2008
ex 8548 90 90	40	Infrared signal receiver unit, consisting of a photodiode and at least an amplifier in the form of a monolithic integrated circuit, contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8548 90 90	41	Unit, consisting of a resonator operating within a frequency range of 1,8 MHz or more but not exceeding 40 MHz and a capacitor, contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 8548 90 90	42	Clock/calendar circuit, consisting of a printed circuit on which are mounted at least a quartz oscillator and a monolithic integrated circuit, the whole contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 9110 90 00	94			
ex 8548 90 90	43	Contact image sensor	0 %	1.1.2007 - 31.12.2008
ex 8548 90 90	47	Unit consisting of two or more light emitting diode chips operating at a typical wavelength of 450 nm or more but not exceeding 660 nm, contained in a lead frame housing having a circular opening whose exterior dimensions without fittings – do not exceed 4 x 4 mm	0 %	1.1.2007 - 31.12.2008
ex 8548 90 90	48	Optical unit, consisting at least of a laserdiode and a photodiode operating at a typical wavelength of 635 nm or more but not exceeding 815 nm	0 %	1.1.2007 - 31.12.2008
ex 8548 90 90	49	LCD modules, solely consisting of one or more TFT glass or plastic cells, combined with touch screen facilities, with or without backlight unit, with or without inverters and one or more printed circuit boards with control electronics for pixel addressing only	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 8708 99 97	20	Metal housing caps for incorporation into balancing-arms or spherical bearings used in the suspension systems for the front wheels of motor vehicles (1)	0 %	1.1.2007 - 31.12.2011
ex 8711 10 00	10	Portable motorised scooter, presented unassembled or disassembled	0 %	1.1.2007 - 31.12.2008
ex 9001 10 90	10	Image reverser made up from an assembly of optical fibres	0 %	1.1.2007 - 31.12.2008
ex 9001 20 00	10	Material consisting of a polarising film, supported on one or both sides by transparent material	0 %	1.1.2007 - 31.12.2008
ex 9001 90 00	20	Rear projection screen, comprising a Fresnel lens of plastic and a polarising sheet of plastic, for use in the manufacture of products falling within heading No 8528 (1)	0 %	1.1.2007 - 31.12.2008
ex 9001 90 00	25	Lens of plastic, unmounted, having a focal length of 3,86 mm ($\pm 0,1$ mm) and with a diameter not exceeding 8 mm, for use in the manufacture of compact disc players (1)	0 %	1.1.2007 - 31.12.2008
ex 9001 90 00	30	Optical fibre plate, for use in the manufacture of screens and photocathodes for image intensifiers (1)	0 %	1.1.2007 - 31.12.2008
ex 9001 90 00	35	Rear projection screen, comprising a lenticular plastic plate	0 %	1.1.2007 - 31.12.2008
ex 9001 90 00	40	Prism for the splitting of light, unmounted, for use in the manufacture of charged-coupled image (CCD) cameras (1)	0 %	1.1.2007 - 31.12.2008
ex 9001 90 00	45	Rod of neodymium-doped yttrium-aluminium garnet (YAG) material, polished at both ends	0 %	1.1.2007 - 31.12.2008
ex 9001 90 00	50	Lens of plastic, unmounted, for use in the manufacture of products falling within subheading 9006 40 00 (1)	0 %	1.1.2007 - 31.12.2008
ex 9001 20 00 ex 9001 90 00	20 55	Diffuser sheets for use in the manufacture of LCD modules (1)	0 %	1.1.2007 - 31.12.2011
ex 9001 20 00 ex 9001 90 00	30 65	Prism sheets for use in the manufacture of LCD modules (1)	0 %	1.1.2007 - 31.12.2011
ex 9002 11 00	10	Adjustable lens unit, having a focal length of 90 mm or more but not exceeding 180 mm and comprising a combination of between 4 and 8 glass or methacrylic lenses with a diameter of 120 mm or more but not exceeding 180 mm, each lens coated on at least one side with a magnesium fluoride layer, for use in the manufacture of video projectors (1)	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 9002 11 00	50	Lens unit, having a focal length of 25 mm or more but not exceeding 150 mm, consisting of glass or plastic lenses, with a diameter of 60 mm or more but not exceeding 190 mm	0 %	1.1.2007 - 31.12.2008
ex 9002 11 00	60	Optical element, comprising one or more mounted lenses of plastic, for use in the manufacture of products falling within subheading 9006 40 00 (1)	0 %	1.1.2007 - 31.12.2008
ex 9002 19 00	10	Lens unit, having a focal length of 24,96 mm ($\pm 0,1$ mm), a diameter of 16 mm and a length of 16 mm, for use in the manufacture of products falling within subheading 8443 31 10 (1)	0 %	1.1.2007 - 31.12.2008
ex 9002 20 00	10	Filter, consisting of a plastic polarising membrane, a glass plate and a transparent protective film, mounted on a metal frame, for use in the manufacture of products falling within heading 8528 (1)	0 %	1.1.2007 - 31.12.2008
ex 9002 90 00	20	Lens, mounted, having a fixed focal length of 3,8 mm ($\pm 0,19$ mm) or 8 mm ($\pm 0,4$ mm), with a relative aperture of F2.0 and a diameter not exceeding 33 mm, for use in the manufacture of charged-coupled (CCD) cameras (1)	0 %	1.1.2007 - 31.12.2008
ex 9002 90 00	30	Optical unit, comprising 1 or 2 rows of optical glass fibres in the form of lenses and with a diameter of 0,85 mm or more but not exceeding 1,15 mm, embedded between 2 plastic plates	0 %	1.1.2007 - 31.12.2008
ex 9002 90 00	40	Lens and image gate assembly, for a real-time film scanning system, comprising a lens consisting of 9 or 11 elements and having an illumination function	0 %	1.1.2007 - 31.12.2008
ex 9002 90 00	50	Lenses, mounted, for use in the manufacture of projection TV (1)	0 %	1.1.2007 - 31.12.2008
ex 9006 91 00	10	Parts, for use in the manufacture of products falling within subheading 9006 40 00 (1)	0 %	1.1.2007 - 31.12.2008
ex 9013 80 90	10	Polarisation insensitive fibre-optic isolator, operating at a wavelength of 1 200 nm or more, contained in a cylindrical housing	0 %	1.1.2007 - 31.12.2008
ex 9013 80 90	20	Optical switch, comprising at least one optical input and two optical outputs and with electrical connectors	0 %	1.1.2007 - 31.12.2008
ex 9017 90 00	10	Thermal printer head, comprising at least 7 168 heater elements mounted on 2 or more ceramic supports, the whole contained in a housing the exterior dimensions of which exceed $21 \times 39 \times 639$ mm	0 %	1.1.2007 - 31.12.2008
ex 9022 30 00	10	X-ray tube with a target voltage of 4 kV or more but not exceeding 30 kV, a power not exceeding 9 W and a target current not exceeding 2 mA	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 9027 10 90	10	Sensor element for gas or smoke analysis in motor vehicles, essentially consisting of a zirconium-ceramic element in a metal housing	0 %	1.1.2007 - 31.12.2008
ex 9031 80 34	30	Apparatus for measuring the angle and direction of rotation of motor vehicles, consisting of at least one yaw rate sensor in the form of a monocrystalline quartz, whether or not combined with one or more measuring sensors, the whole contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 9031 80 38	30			
ex 9031 80 38	10	Acceleration measurement device for automotive applications, comprising one or more active and/or passive elements and one or more sensors, the whole contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 9031 80 38	20	Machines and apparatus for the automatic testing of the integrity of ink-jet cartridge housings (1)	0 %	1.1.2007 - 31.12.2008
ex 9031 90 85	20	Assembly for a laser align sensor, in the form of a printed circuit comprising optical filters and a charge-coupled image (CCD) sensor, the whole contained in a housing	0 %	1.1.2007 - 31.12.2008
ex 9032 10 81	20	Thermostat, comprising a snap-action switch, for direct mounting on an electric motor coil, contained in a hermetically sealed housing	0 %	1.1.2007 - 31.12.2008
ex 9032 89 00	20	Automotive airbag shock-sensor, comprising a contact capable of switching a current of 12 A at a voltage of 30 V, having a typical contact resistance of 80 mOhm	0 %	1.1.2007 - 31.12.2008
ex 9032 89 00	30	Electronic controller of electric power steering (EPS controller)	0 %	1.1.2007 - 31.12.2008
ex 9106 90 10	10	Timer assembly, for use in the manufacture of goods of subheading 8516 50 00 (1)	0 %	1.1.2007 - 31.12.2008
ex 9107 00 00	20	Mechanical timer for use in the manufacture of no-frost refrigerators (1)	0 %	1.1.2007 - 31.12.2011
ex 9110 12 00	91	Assembly consisting of a printed circuit on which are mounted one quartz oscillator, at least one watch circuit and, whether or not integrated, at least one capacitor, of a thickness not exceeding 5 mm	0 %	1.1.2007 - 31.12.2008
ex 9110 90 00	92	Assembly consisting of a printed circuit on which is mounted a watch circuit or a watch circuit and a quartz oscillator, of a thickness not exceeding 5 mm	0 %	1.1.2007 - 31.12.2008
ex 9114 90 00	91			
ex 9110 90 00	93	Assembly consisting of a printed circuit on which is mounted at least one watch circuit, a quartz oscillator and a piezo-electric sound element,	0 %	1.1.2007 - 31.12.2008

CN code	TARIC	Description	Rate of autonomous duty	Validity period
ex 9405 40 35	10	with a thickness exceeding 5 mm Electric light assembly of synthetic material containing 3 fluorescent tubes (RBG) of a diameter of 3,0 mm ($\pm 0,2$ mm), of a length of 420 mm (± 1 mm) or more, but not exceeding 600 mm (± 1 mm), for the manufacture of goods of heading 8528 (1)	0 %	1.1.2007 - 31.12.2008
ex 9608 91 00	10	Non-fibrous plastic pen-tips with an internal channel	0 %	1.1.2007 - 31.12.2008
ex 9608 91 00	20	Felt tips and other porous-tips for markers, without internal canal	0 %	1.1.2007 - 31.12.2008
ex 9612 10 10	10	Ribbons of plastic with segments of different colours, providing the penetration of dyes by heat into a support (so called dye-sublimation)	0 %	1.1.2007 - 31.12.2008
ex 9613 90 00	20	Piezo-electric ignition mechanism, whether or not with complementary elements	0 %	1.1.2007 - 31.12.2008

(1) Entry under this subheading is subject to conditions laid down in the relevant Community provisions (see Articles 291 to 300 of Commission Regulation (EEC) No. 2454/93 - OJ L 253 11.10.1993 p. 1 and subsequent amendments).

(2) The suspension shall apply to fish intended to undergo any operation unless they are intended to undergo exclusively one or more of the following operations:

- cleaning, gutting, tailing, heading,
- cutting (excluding filleting or cutting of frozen blocks, or splitting of frozen interleaved fillet blocks),
- sampling, sorting,
- labelling,
- packing,
- chilling,
- freezing,
- deep freezing,
- thawing, separation.

The suspension is not allowed for products intended, in addition, to undergo treatment (or operations) qualifying for suspension where such treatment (or operations) is (are) carried out at retail or catering level. The suspension of customs duties shall apply only to fish intended for human consumption.

(3) However, the suspension is not allowed where processing is carried out by retail or catering undertakings.

**LEGISLATIVE FINANCIAL STATEMENT FOR PROPOSALS HAVING A
BUDGETARY IMPACT EXCLUSIVELY LIMITED TO THE REVENUE SIDE**

1. NAME OF THE PROPOSAL:

Proposal for a Council Regulation amending Regulation (EC) No 1255/96 temporarily suspending the autonomous common customs tariff duties on certain industrial, agricultural and fishery products

2. BUDGET LINES:

Chapter and Article: Chap. 12 art. 120

The loss for the following years mentioned in the column "validity period" will be calculated separately by the following regulations.

Amount budgeted for the year 2007: **€15 287 900 000**

3. FINANCIAL IMPACT

Proposal has no financial implications

Proposal has no financial impact on expenditure but has a financial impact on revenue – the effect is as follows:

(€ million to one decimal place)

Budget line	Revenue ⁴	12 month period, starting dd/mm/aaaa	[Year 2007]
Article 120	<i>Impact on own resources</i>	01/01/2007	- 25.5

4. ANTI-FRAUD MEASURES

Checks on the end-use of some of the products covered by this Council Regulation will be carried out in accordance with Articles 291 to 300 of Commission Regulation (EEC) No 2454/93 laying down provisions for the implementation of the Community Customs Code.

⁴ Regarding traditional own resources (agricultural duties, sugar levies, customs duties) the amounts indicated must be net amounts, i.e. gross amounts after deduction of 25% of collection costs.

5. OTHER REMARKS

In order to reduce the economic problems an expiry date has been set out.

This proposal contains the existing unchanged products as well as the amendments which must be made to the annex to the existing Regulation in order to take account of the following:

1. new requests for suspension which have been presented and accepted;
2. technical product developments and economic trends on the market resulting in the lifting of certain existing suspensions.

Therefore a consolidated annex will be published.

Addition

This Annex, in addition to the amendments resulting from changes to CN codes, contains 71 new products. The uncollected duties corresponding to these suspensions, calculated on the basis of expected imports into the requesting Member State for 2007, total MEUR 19.8.

On the basis of the existing statistics for the preceding years, it would appear, however, that this amount must be increased by an average factor, estimated at 1.8, to take account of imports into other Member States using the same suspensions. This means **a loss of revenue of some MEUR 35.6/year.**

Withdrawal:

12 products have been withdrawn from this annex reflecting the reintroduction of customs duties. This represents **an increase of MEUR 1.6 in resources**, as calculated from requests for suspension or available statistics (2005).

Estimated cost of this operation

Taking available statistics (2005) as a basis, the impact on the loss of revenue resulting from this Regulation may therefore be estimated at **35.6 – 1.6 = MEUR 34.0** (gross amount, expenses incurred in collection included) **x 0.75 = EUR 25.5 MEUR for the period 1.1.2007-31.12.2007.**

The shortfall in traditional own resources will have to be made up by the Member States by topping up the GNP component.